TELEDYNE
WEBB RESEARCH
A Teledyne Technologies Company

Document #:	4095-GBPSH
Rev:	E
Date:	3/5/2013
ECO #:	730

Ballasting The Slocum Glider (Spreadsheet)

Reference Ballasting Procedure 4095-GBP

1- Fill in all fields that are shaded in blue
2- Adjust weight by amount in yellow box to go from neutrally buoyant in tank to neutrally buoyant in target water
3- If you want to change anything, the password to unprotect the sheet is "glider"

Glider Name:	Unit 461
Ballasted by:	Cliff Silva
Date:	5/29/2014
Glider Type:	G2 Deep (1000m)

Add-ons (check box for each)

G1 Shallow Science Bay	1st ☐	2nd ☐
G1 Deep/G2 Science Bay	1st ☑	2nd ☐
G2 Extended Science/ Energy Bay (14.85")	☐	
DVL Bay (5.75")	☐	
TAISR Science/Energy Bay (15.75")	☐	
Mark III Aft End Cap	☑	

Base Glider Displacement:	46.02	Liters
Total Glider Displacement:	56.73	Liters

	Tank Water		Target Water		Weight Change
Temperature and	20.4860	°C	20.4860	°C	0.0000 grams
(Density or	0.0000	g/L°C	0.0000	g/L°C	
Conductivity or	4.8310	s/m	4.8310	s/m	
Salinity)	0.0000	pss	0.0000	pss	
Calculated/given Salinity	34.9209	pss	34.9209	pss	
Calculated/given Density	1024.5736	g/L°C	1024.5736	g/L°C	0.0000 grams
			Total Weight Adjustment:		0.0000 grams

Drive Weight Material	Stainless Steel
Drive Weight (g)	0

Battery Type:	Lithium	weight (kg)
Pitch Configuration	Lithium Pitch Pack	9.3044
Science/Energy Bay Configuration	N/A	NA
Aft Configuration	Lithium Aft Pack	9.7778
Nose Configuration	Lithium Emergency Pack	0.208

NOTE: This spreadsheet to consist of 4 pages. **COMPLETE** 3 pages, 1, 2 & 9.

Select **one** Glider Option Page from pages 3 to 8 inclusive.