

clip-max-ignore-zeros-custom

July 29, 2020

```
[2]: # rank the obtained results using the *.log files
import os
import pandas as pd
import numpy as np
```

```
[7]: source = "3b"
targetdir = '../../data/' + source + "/"
filelist = sorted(os.listdir(targetdir))
```

```
[8]: filelist
```

```
[8]: ['1.data', '2.data', '3.data', '4.data', '5.data', '6.data', '7.data']
```

```
[9]: # Create dataframe from files
df = pd.DataFrame()

for file in filelist:
    filename = targetdir+file
    col_name = [file]
    temp_df = pd.read_csv(filename,names=col_name)
    df = pd.concat([df, temp_df], axis=1)

# Look at the data
df.head()
```

```
[9]:
```

	1.data	2.data	3.data	4.data	5.data	6.data	7.data
0	1.00	1.00	1.00	1.00	0.73	1.00	1.0
1	1.06	1.16	0.00	1.20	0.73	0.00	0.0
2	1.12	1.22	0.00	1.33	0.73	0.00	0.0
3	0.99	0.83	0.91	0.83	0.63	0.91	1.0
4	0.99	0.83	0.91	0.83	0.63	0.00	0.0

```
[10]: # Clip values > 1 with 1 and ignore 0s
df.mask(df > 1, 1, inplace=True)
df.mask(df == 0, np.NaN, inplace=True)
```

```
[11]: # Count NaN values
df.isna().sum()
```

```
[11]: 1.data      18
      2.data       0
      3.data    324
      4.data    288
      5.data       0
      6.data    261
      7.data    324
      dtype: int64
```

```
[12]: # Ignore invalid values by dropping them from the dataframe
df = df.dropna()
```

```
[13]: df
```

```
[13]:
```

	1.data	2.data	3.data	4.data	5.data	6.data	7.data
0	1.00	1.00	1.00	1.00	0.73	1.00	1.00
3	0.99	0.83	0.91	0.83	0.63	0.91	1.00
6	0.97	0.71	0.81	0.71	0.53	0.49	1.00
9	1.00	1.00	1.00	1.00	0.75	1.00	1.00
12	1.00	0.84	0.94	0.84	0.64	0.92	1.00
..
718	0.99	0.73	0.97	0.98	0.53	0.50	0.99
719	0.99	0.73	0.97	0.98	0.53	0.50	0.99
726	1.00	0.74	0.99	1.00	0.54	0.50	1.00
727	1.00	0.74	0.99	1.00	0.54	0.50	1.00
728	1.00	0.74	1.00	1.00	0.54	0.50	1.00

```
[324 rows x 7 columns]
```

```
[14]: # Creating ranked dataframe
ranked_df = pd.DataFrame()
stats_df = pd.DataFrame()
```

```
[15]: # Creating scenario quantity variable
tao = len(df)
tao
```

```
[15]: 324
```

```
[16]: for column in df:
      wwtp = column[0]

      # TODO: get original (pre-analysis) value
      # pending
```

```

# calculate mean
avg_eff = round(df[column].mean(),3)

# calculate max
max_eff = round(df[column].max(),3)

# calculate min
min_eff = round(df[column].min(),3)

# calculate amplitude
amplitude = round((max_eff - min_eff)*100,2)

amp_str = "Amplitude (max-min)(%)"

# print stats results
print("WWTP", wwtp, "Mean =", avg_eff, "Maximum =", max_eff, "Minimum",
↪=" ", min_eff, amp_str, "=", amplitude)
stats_df = stats_df.append({ 'WWTP': wwtp, "Mean": avg_eff, "Maximum" :
↪max_eff, "Minimum": min_eff, amp_str: amplitude}, ignore_index=True)

# TODO: Populate statistics dataframe using pd.df.append

# Calculating Sk sum of factors
Sk = round(df[column].sum(),3)

# Calculating ek sum of factors of 1 (or above if errors in calculation)
ek = df[column] >= 1
ek = ek.sum()

# Calculating R1k ek/tao
R1k = round(ek/tao,3)

# Calculate R2k
if tao != ek:
    R2k = (Sk - ek)/(tao - ek)
elif Rk1 == 1:
    R2k = 0

R2k = round(R2k,3)

# Printing results
print("WWTP", wwtp, "R1k =", R1k, " | Sk =", Sk, " | R2k =", R2k)

# Populate ranking dataframe using pd.df.append
# Using unicode to name columns with super and subscripts

```

```

R1k_col = 'R\u00B9\u2096\u2080'
R2k_col = 'R\u00B2\u2096\u2080'
ranked_df = ranked_df.append({ R2k_col:R2k, R1k_col: R1k, 'WWTP':\u2192wwtp},ignore_index=True)

```

```

WWTP 1 Mean = 0.988 Maximum = 1.0 Minimum = 0.95 Amplitude (max-min)(%) = 5.0
WWTP 1 R1k = 0.426 | Sk = 320.1 | R2k = 0.979
WWTP 2 Mean = 0.811 Maximum = 1.0 Minimum = 0.7 Amplitude (max-min)(%) = 30.0
WWTP 2 R1k = 0.111 | Sk = 262.62 | R2k = 0.787
WWTP 3 Mean = 0.929 Maximum = 1.0 Minimum = 0.76 Amplitude (max-min)(%) = 24.0
WWTP 3 R1k = 0.315 | Sk = 301.07 | R2k = 0.897
WWTP 4 Mean = 0.894 Maximum = 1.0 Minimum = 0.68 Amplitude (max-min)(%) = 32.0
WWTP 4 R1k = 0.333 | Sk = 289.74 | R2k = 0.841
WWTP 5 Mean = 0.601 Maximum = 0.76 Minimum = 0.51 Amplitude (max-min)(%) = 25.0
WWTP 5 R1k = 0.0 | Sk = 194.64 | R2k = 0.601
WWTP 6 Mean = 0.685 Maximum = 1.0 Minimum = 0.48 Amplitude (max-min)(%) = 52.0
WWTP 6 R1k = 0.111 | Sk = 221.86 | R2k = 0.645
WWTP 7 Mean = 0.994 Maximum = 1.0 Minimum = 0.97 Amplitude (max-min)(%) = 3.0
WWTP 7 R1k = 0.667 | Sk = 322.2 | R2k = 0.983

```

```

[17]: # Reorder columns to be usable as a results table
ranked_df = ranked_df.reindex(columns=['WWTP',R1k_col, R2k_col])

```

```

[18]: ranked_df

```

```

[18]:   WWTP   R1   R2
0     1  0.426  0.979
1     2  0.111  0.787
2     3  0.315  0.897
3     4  0.333  0.841
4     5  0.000  0.601
5     6  0.111  0.645
6     7  0.667  0.983

```

```

[24]: import os

# define the name of the directory to be created
path = "../results/" + source + "/"

try:
    os.mkdir(path)
except OSError:
    print ("Creation of the directory %s failed" % path)
else:
    print ("Successfully created the directory %s " % path)

```

Successfully created the directory ../results/3b/

```
[25]: # Save rankings dataframe as csv file
ranked_df.to_csv(path + "ranking.csv",index=False)
```

1 Calculate Descriptive Statistics

```
[26]: # Calculate the mean of every column
mean_mean = round(stats_df.Mean.mean(),3)
mean_max = round(stats_df.Maximum.mean(),3)
mean_min = round(stats_df.Minimum.mean(),3)
mean_amp = round(stats_df[amp_str].mean(),3)
```

```
[27]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "Mean", "Mean" : mean_mean, "Maximum" : ↵
↵mean_max,
                             "Minimum" : mean_min, amp_str : ↵
↵mean_amp},ignore_index=True)
```

```
[28]: # Calculate the standard deviation of every column
sd_mean = round(stats_df.Mean.std(),3)
sd_max = round(stats_df.Maximum.std(),3)
sd_min = round(stats_df.Minimum.std(),3)
sd_amp = round(stats_df[amp_str].std(),3)
```

```
[29]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "SD", "Mean" : sd_mean, "Maximum" : sd_max,
                             "Minimum" : sd_min, amp_str : ↵
↵sd_amp},ignore_index=True)
```

```
[30]: # Reorder columns
stats_df = stats_df.reindex(columns=["WWTP", "Mean", "Maximum", "Minimum", ↵
↵amp_str])
```

```
[31]: stats_df
```

```
[31]:
```

	WWTP	Mean	Maximum	Minimum	Amplitude (max-min)(%)
0	1	0.988	1.000	0.950	5.000
1	2	0.811	1.000	0.700	30.000
2	3	0.929	1.000	0.760	24.000
3	4	0.894	1.000	0.680	32.000
4	5	0.601	0.760	0.510	25.000
5	6	0.685	1.000	0.480	52.000
6	7	0.994	1.000	0.970	3.000
7	Mean	0.843	0.966	0.721	24.429
8	SD	0.141	0.084	0.178	15.518

```
[32]: # Save statistics dataframe as csv file
stats_df.to_csv(path + "statistics.csv",index=False)
```