

# clip-max-ignore-zeros-custom

August 10, 2020

```
[1]: # rank the obtained results using the *.log files
import os
import pandas as pd
import numpy as np
```

```
[2]: source = "8c"
targetdir = '../..data/' + source + "/"
filelist = sorted(os.listdir(targetdir))
```

```
[3]: filelist
```

```
[3]: ['1.data', '2.data', '3.data', '4.data', '5.data', '6.data', '7.data']
```

```
[4]: # Create dataframe from files
df = pd.DataFrame()

for file in filelist:
    filename = targetdir+file
    col_name = [file]
    temp_df = pd.read_csv(filename,names=col_name)
    df = pd.concat([df, temp_df], axis=1)

# Look at the data
df.head()
```

```
[4]:
```

	1.data	2.data	3.data	4.data	5.data	6.data	7.data
0	0.82	0.91	1.00	1.00	0.68	1.00	0.65
1	0.82	0.91	0.00	1.31	0.68	0.00	0.68
2	0.82	0.91	0.00	1.51	0.68	0.00	0.74
3	0.75	0.84	0.96	0.91	0.62	0.96	0.60
4	0.75	0.84	0.96	0.91	0.62	0.00	0.60

```
[5]: # Clip values > 1 with 1 and ignore 0s
df.mask(df > 1, 1, inplace=True)
df.mask(df <= 0, np.NaN, inplace=True)
```

```
[6]: # Count NaN values
df.isna().sum()
```

```
[6]: 1.data      0
     2.data      0
     3.data    324
     4.data    297
     5.data      0
     6.data    297
     7.data      0
     dtype: int64
```

```
[7]: # Ignore invalid values by dropping them from the dataframe
df = df.dropna()
```

```
[8]: df
```

```
[8]:      1.data  2.data  3.data  4.data  5.data  6.data  7.data
0      0.82   0.91   1.00   1.00   0.68   1.00   0.65
3      0.75   0.84   0.96   0.91   0.62   0.96   0.60
6      0.69   0.77   0.91   0.84   0.57   0.53   0.55
7      0.69   0.77   0.91   0.84   0.57   0.53   0.55
9      0.83   0.92   1.00   1.00   0.68   1.00   0.66
..      ...      ...      ...      ...      ...      ...
718    0.72   0.78   0.98   0.99   0.57   0.53   0.55
719    0.72   0.78   0.99   0.99   0.57   0.53   0.55
726    0.73   0.79   1.00   1.00   0.58   0.54   0.56
727    0.73   0.79   1.00   1.00   0.58   0.54   0.56
728    0.73   0.79   1.00   1.00   0.58   0.54   0.56
```

```
[360 rows x 7 columns]
```

```
[9]: # Save processed dataframe as csv file
df.to_csv("../data/processed/" + source + ".csv", index=False)
```

```
[10]: # Creating ranked dataframe
ranked_df = pd.DataFrame()
stats_df = pd.DataFrame()
```

```
[11]: # Creating scenario quantity variable
tao = len(df)
tao
```

```
[11]: 360
```

## 0.1 Ranking of WWTP

```
[12]: for column in df:
    wwtp = column[0]

    # TODO: get original (pre-analysis) value
    # pending

    # calculate mean
    avg_eff = round(df[column].mean(),3)

    # calculate max
    max_eff = round(df[column].max(),3)

    # calculate min
    min_eff = round(df[column].min(),3)

    # calculate amplitude
    amplitude = round((max_eff - min_eff)*100,2)

    amp_str = "Amplitude (max-min)(%)"

    # print stats results
    print("WWTP", wwtp, "Mean =", avg_eff, "Maximum =", max_eff, "Minimum",
    ↪="min_eff, amp_str, "=", amplitude)
    stats_df = stats_df.append({ 'WWTP': wwtp, "Mean": avg_eff, "Maximum" :
    ↪max_eff, "Minimum": min_eff, amp_str: amplitude},ignore_index=True)

    # TODO: Populate statistics dataframe using pd.df.append

    # Calculating Sk sum of factors
    Sk = round(df[column].sum(),3)

    # Calculating ek sum of factors of 1 (or above if errors in calculation)
    ek = df[column] >= 1
    ek = ek.sum()
    print("ek =",ek)

    # Calculating R1k ek/tao
    R1k = round(ek/tao,3)

    # Calculate R2k
    if tao != ek:
        R2k = (Sk - ek)/(tao - ek)
    elif R1k == 1:
        R2k = 0
```

```

R2k = round(R2k,3)

# Printing results
print("WWTP", wwtp,"| ek =",ek,"| R1k =",R1k, "| Sk =",Sk, "| R2k =",R2k)

# Populate ranking dataframe using pd.df.append
# Using unicode to name columns with super and subscripts
R1k_col = 'R\u00B9\u2096\u2080'
R2k_col = 'R\u00B2\u2096\u2080'
ranked_df = ranked_df.append({ R2k_col:R2k, R1k_col: R1k,'WWTP':\u2192wwtp},ignore_index=True)

```

```

WWTP 1 Mean = 0.74 Maximum = 0.83 Minimum = 0.68 Amplitude (max-min)(%) = 15.0
ek = 0
WWTP 1 | ek = 0 | R1k = 0.0 | Sk = 266.38 | R2k = 0.74
WWTP 2 Mean = 0.818 Maximum = 0.93 Minimum = 0.76 Amplitude (max-min)(%) = 17.0
ek = 0
WWTP 2 | ek = 0 | R1k = 0.0 | Sk = 294.62 | R2k = 0.818
WWTP 3 Mean = 0.963 Maximum = 1.0 Minimum = 0.88 Amplitude (max-min)(%) = 12.0
ek = 108
WWTP 3 | ek = 108 | R1k = 0.3 | Sk = 346.58 | R2k = 0.947
WWTP 4 Mean = 0.937 Maximum = 1.0 Minimum = 0.83 Amplitude (max-min)(%) = 17.0
ek = 108
WWTP 4 | ek = 108 | R1k = 0.3 | Sk = 337.4 | R2k = 0.91
WWTP 5 Mean = 0.604 Maximum = 0.69 Minimum = 0.56 Amplitude (max-min)(%) = 13.0
ek = 0
WWTP 5 | ek = 0 | R1k = 0.0 | Sk = 217.44 | R2k = 0.604
WWTP 6 Mean = 0.712 Maximum = 1.0 Minimum = 0.52 Amplitude (max-min)(%) = 48.0
ek = 36
WWTP 6 | ek = 36 | R1k = 0.1 | Sk = 256.26 | R2k = 0.68
WWTP 7 Mean = 0.581 Maximum = 0.66 Minimum = 0.54 Amplitude (max-min)(%) = 12.0
ek = 0
WWTP 7 | ek = 0 | R1k = 0.0 | Sk = 208.98 | R2k = 0.58

```

```

[13]: # Reorder columns to be usable as a results table
ranked_df = ranked_df.reindex(columns=['WWTP',R1k_col, R2k_col])

```

```

[14]: ranked_df

```

```

[14]:
  WWTP  R1  R2
0     1   0.0  0.740
1     2   0.0  0.818
2     3   0.3  0.947
3     4   0.3  0.910
4     5   0.0  0.604
5     6   0.1  0.680

```

```
6    7    0.0    0.580
```

```
[15]: import os

path = "../../results/" + source + "/"

# Save rankings dataframe as csv file

try:
    ranked_df.to_csv(path + "ranking.csv",index=False)
    print("Save succesful")
except:
    print("Creating folder and saving")
    os.mkdir(path)
    ranked_df.to_csv(path + "ranking.csv",index=False)
```

Save succesful

## 0.2 Calculate Descriptive Statistics

```
[16]: # Calculate the mean of every column
mean_mean = round(stats_df.Mean.mean(),3)
mean_max = round(stats_df.Maximum.mean(),3)
mean_min = round(stats_df.Minimum.mean(),3)
mean_amp = round(stats_df[amp_str].mean(),3)
```

```
[17]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "Mean", "Mean" : mean_mean, "Maximum" : ↵
    ↵mean_max,
                                "Minimum" : mean_min, amp_str : ↵
    ↵mean_amp},ignore_index=True)
```

```
[18]: # Calculate the standard deviation of every column
sd_mean = round(stats_df.Mean.std(),3)
sd_max = round(stats_df.Maximum.std(),3)
sd_min = round(stats_df.Minimum.std(),3)
sd_amp = round(stats_df[amp_str].std(),3)
```

```
[19]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "SD", "Mean" : sd_mean, "Maximum" : sd_max,
                                "Minimum" : sd_min, amp_str : ↵
    ↵sd_amp},ignore_index=True)
```

```
[20]: # Reorder columns
stats_df = stats_df.reindex(columns=["WWTP", "Mean", "Maximum", "Minimum", ↵
    ↵amp_str])
```

```
[21]: stats_df
```

```
[21]:
```

	WWTP	Mean	Maximum	Minimum	Amplitude (max-min)(%)
0	1	0.740	0.830	0.680	15.000
1	2	0.818	0.930	0.760	17.000
2	3	0.963	1.000	0.880	12.000
3	4	0.937	1.000	0.830	17.000
4	5	0.604	0.690	0.560	13.000
5	6	0.712	1.000	0.520	48.000
6	7	0.581	0.660	0.540	12.000
7	Mean	0.765	0.873	0.681	19.143
8	SD	0.139	0.137	0.135	11.945

```
[22]: # Save statistics dataframe as csv file
stats_df.to_csv(path + "statistics.csv",index=False)
```

```
[23]: # Convert Jupyter Notebook to PDF LaTeX file
!jupyter-nbconvert --to pdf "clip-max-ignore-zeros-custom.ipynb" --output-dir ".
↪ ../results/8c/"
```

```
[NbConvertApp] Converting notebook clip-max-ignore-zeros-custom.ipynb to pdf
[NbConvertApp] Writing 45170 bytes to ./notebook.tex
[NbConvertApp] Building PDF
[NbConvertApp] Running xelatex 3 times: ['xelatex', './notebook.tex', '-quiet']
[NbConvertApp] Running bibtex 1 time: ['bibtex', './notebook']
[NbConvertApp] WARNING | bibtex had problems, most likely because there were no
citations
[NbConvertApp] PDF successfully created
[NbConvertApp] Writing 47177 bytes to ../results/8c/clip-max-ignore-zeros-
custom.pdf
```

```
[ ]:
```