

ignore-zeros

July 23, 2020

```
[1]: # rank the obtained results using the *.log files
```

```
import os
import pandas as pd
import numpy as np
```

```
[2]: targetdir = '../..data/processed/'
filelist = sorted(os.listdir(targetdir))
```

```
[3]: filelist
```

```
[3]: ['1.data', '2.data', '3.data', '4.data', '5.data', '6.data', '7.data']
```

```
[4]: df = pd.DataFrame()
```

```
[5]: for file in filelist:
    filename = targetdir+file
    col_name = [file]
    temp_df = pd.read_csv(filename,names=col_name)
    df = pd.concat([df, temp_df], axis=1)
```

```
[6]: df
```

```
[6]:
```

	1.data	2.data	3.data	4.data	5.data	6.data	7.data
0	1.00	1.00	1.00	1.00	0.73	1.00	1.00
1	1.06	1.16	0.00	0.00	0.73	0.00	0.00
2	1.12	1.22	0.00	0.00	0.73	0.00	0.00
3	0.99	0.83	0.91	0.83	0.63	0.91	1.00
4	0.99	0.83	0.91	0.83	0.63	0.00	0.00
...
724	1.06	0.87	0.00	0.00	0.65	0.88	1.01
725	1.11	0.87	0.00	0.00	0.65	0.00	0.00
726	1.00	0.74	1.00	1.00	0.54	0.50	1.00
727	1.00	0.74	1.00	1.00	0.54	0.50	1.00
728	1.00	0.74	1.00	1.00	0.54	0.50	1.00

```
[729 rows x 7 columns]
```

```
[7]: # Replace values >1 with NaN
df.mask(df == 0, np.NaN, inplace=True)
```

```
[8]: # Count NaN values
df.isna().sum()
```

```
[8]: 1.data      18
     2.data       0
     3.data    324
     4.data    324
     5.data       0
     6.data    261
     7.data    324
     dtype: int64
```

Now we will drop all values marked with NA (previously 0)

```
[9]: # Ignore invalid values by dropping them from the dataframe
df = df.dropna()
```

```
[10]: df
```

```
[10]:
```

	1.data	2.data	3.data	4.data	5.data	6.data	7.data
0	1.00	1.00	1.00	1.00	0.73	1.00	1.00
3	0.99	0.83	0.91	0.83	0.63	0.91	1.00
6	0.97	0.71	0.81	0.71	0.53	0.49	1.00
9	1.01	1.01	1.03	1.02	0.75	1.01	1.01
12	1.00	0.84	0.94	0.84	0.64	0.92	1.01
..
718	0.99	0.73	0.97	0.98	0.53	0.50	0.99
719	0.99	0.73	0.97	0.98	0.53	0.50	0.99
726	1.00	0.74	1.00	1.00	0.54	0.50	1.00
727	1.00	0.74	1.00	1.00	0.54	0.50	1.00
728	1.00	0.74	1.00	1.00	0.54	0.50	1.00

[324 rows x 7 columns]

```
[11]: # Creating ranked dataframe
ranked_df = pd.DataFrame()
stats_df = pd.DataFrame()
```

```
[12]: # Creating scenario quantity variable
tao = len(df)
tao
```

```
[12]: 324
```

```

[13]: for column in df:
    wwtp = column[0]

    # TODO: get original (pre-analysis) value
    # pending

    # calculate mean
    avg_eff = round(df[column].mean(),3)

    # calculate max
    max_eff = round(df[column].max(),3)

    # calculate min
    min_eff = round(df[column].min(),3)

    # calculate amplitude
    amplitude = round((max_eff - min_eff)*100,2)

    amp_str = "Amplitude (max-min)(%)"

    # print stats results
    print("WWTP", wwtp, "Mean =", avg_eff, "Maximum =", max_eff, "Minimum",
    ↪="min_eff, amp_str, "=", amplitude)
    stats_df = stats_df.append({ 'WWTP': wwtp, "Mean": avg_eff, "Maximum" :
    ↪max_eff, "Minimum": min_eff, amp_str: amplitude},ignore_index=True)

    # TODO: Populate statistics dataframe using pd.df.append

    # Calculating Sk sum of factors
    Sk = round(df[column].sum(),3)

    # Calculating ek sum of factors of 1 (or above if errors in calculation)
    ek = df[column] >= 1
    ek = ek.sum()

    # Calculating R1k ek/tao
    R1k = round(ek/tao,3)

    # Calculate R2k
    if tao != ek:
        R2k = (Sk - ek)/(tao - ek)
    elif Rk1 == 1:
        R2k = 0

    R2k = round(R2k,3)

```

```

# Printing results
print("WWTP", wwtp, "R1k =", R1k, " | Sk =", Sk, " | R2k =", R2k)

# Populate ranking dataframe using pd.df.append
# Using unicode to name columns with super and subscripts
R1k_col = 'R\u00B9\u2096\u2080'
R2k_col = 'R\u00B2\u2096\u2080'
ranked_df = ranked_df.append({ R2k_col: R2k, R1k_col: R1k, 'WWTP': wwtp}, ignore_index=True)

```

```

WWTP 1 Mean = 0.991 Maximum = 1.02 Minimum = 0.95 Amplitude (max-min)(%) = 7.0
WWTP 1 R1k = 0.426 | Sk = 320.94 | R2k = 0.984
WWTP 2 Mean = 0.811 Maximum = 1.02 Minimum = 0.7 Amplitude (max-min)(%) = 32.0
WWTP 2 R1k = 0.111 | Sk = 262.86 | R2k = 0.788
WWTP 3 Mean = 0.936 Maximum = 1.06 Minimum = 0.76 Amplitude (max-min)(%) = 30.0
WWTP 3 R1k = 0.333 | Sk = 303.31 | R2k = 0.904
WWTP 4 Mean = 0.898 Maximum = 1.03 Minimum = 0.68 Amplitude (max-min)(%) = 35.0
WWTP 4 R1k = 0.333 | Sk = 291.0 | R2k = 0.847
WWTP 5 Mean = 0.601 Maximum = 0.76 Minimum = 0.51 Amplitude (max-min)(%) = 25.0
WWTP 5 R1k = 0.0 | Sk = 194.64 | R2k = 0.601
WWTP 6 Mean = 0.685 Maximum = 1.02 Minimum = 0.48 Amplitude (max-min)(%) = 54.0
WWTP 6 R1k = 0.111 | Sk = 222.1 | R2k = 0.646
WWTP 7 Mean = 1.0 Maximum = 1.03 Minimum = 0.97 Amplitude (max-min)(%) = 6.0
WWTP 7 R1k = 0.667 | Sk = 324.0 | R2k = 1.0

```

```

[14]: # Reorder columns to be usable as a results table
ranked_df = ranked_df.reindex(columns=['WWTP', R1k_col, R2k_col])

```

```

[15]: ranked_df

```

```

[15]:
   WWTP  R1  R2
0     1  0.426  0.984
1     2  0.111  0.788
2     3  0.333  0.904
3     4  0.333  0.847
4     5  0.000  0.601
5     6  0.111  0.646
6     7  0.667  1.000

```

```

[16]: # Save rankings dataframe as csv file
ranked_df.to_csv("../results/ignore-zeros/ranking.csv", index=False)

```

```

[17]: # Calculate the mean of every column
mean_mean = round(stats_df.Mean.mean(), 3)
mean_max = round(stats_df.Maximum.mean(), 3)
mean_min = round(stats_df.Minimum.mean(), 3)
mean_amp = round(stats_df[amp_str].mean(), 3)

```

```
[18]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "Mean", "Mean" : mean_mean, "Maximum" :
↪mean_max,
                                "Minimum" : mean_min, amp_str :
↪mean_amp},ignore_index=True)

[19]: # Calculate the standard deviation of every column
sd_mean = round(stats_df.Mean.std(),3)
sd_max = round(stats_df.Maximum.std(),3)
sd_min = round(stats_df.Minimum.std(),3)
sd_amp = round(stats_df[amp_str].std(),3)

[20]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "SD", "Mean" : sd_mean, "Maximum" : sd_max,
                                "Minimum" : sd_min, amp_str :
↪sd_amp},ignore_index=True)

[21]: # Reorder columns
stats_df = stats_df.reindex(columns=["WWTP", "Mean", "Maximum", "Minimum",
↪amp_str])

[22]: stats_df
```

	WWTP	Mean	Maximum	Minimum	Amplitude (max-min)(%)
0	1	0.991	1.020	0.950	7.000
1	2	0.811	1.020	0.700	32.000
2	3	0.936	1.060	0.760	30.000
3	4	0.898	1.030	0.680	35.000
4	5	0.601	0.760	0.510	25.000
5	6	0.685	1.020	0.480	54.000
6	7	1.000	1.030	0.970	6.000
7	Mean	0.846	0.991	0.721	27.000
8	SD	0.143	0.095	0.178	15.455

```
[23]: # Save statistics dataframe as csv file
stats_df.to_csv("../results/ignore-zeros/statistics.csv",index=False)
```