

clip-max-ignore-zeros-custom

August 2, 2020

```
[1]: # rank the obtained results using the *.log files
import os
import pandas as pd
import numpy as np
```

```
[2]: source = "6d"
targetdir = '../..data/' + source + "/"
filelist = sorted(os.listdir(targetdir))
```

```
[3]: filelist
```

```
[3]: ['1.data', '2.data', '3.data', '4.data', '5.data', '6.data', '7.data']
```

```
[4]: # Create dataframe from files
df = pd.DataFrame()

for file in filelist:
    filename = targetdir+file
    col_name = [file]
    temp_df = pd.read_csv(filename,names=col_name)
    df = pd.concat([df, temp_df], axis=1)

# Look at the data
df.head()
```

```
[4]:
```

| | 1.data | 2.data | 3.data | 4.data | 5.data | 6.data | 7.data |
|---|--------|--------|--------|--------|--------|--------|--------|
| 0 | 0.67 | 0.86 | 1.00 | 1.00 | 0.62 | 1.00 | 0.67 |
| 1 | 0.67 | 0.86 | -1.00 | -1.00 | 0.62 | -1.00 | 0.67 |
| 2 | 0.67 | 0.86 | -1.00 | -1.00 | 0.62 | -1.00 | 0.67 |
| 3 | 0.62 | 0.79 | 0.98 | 0.92 | 0.57 | 0.53 | 0.62 |
| 4 | 0.62 | 0.79 | 0.98 | 0.92 | 0.57 | 0.53 | 0.62 |

```
[5]: # Clip values > 1 with 1 and ignore non-positive values
df.mask(df > 1, 1, inplace=True)
df.mask(df < 0, np.NaN, inplace=True)
```

```
[6]: # Count NaN values
df.isna().sum()
```

```
[6]: 1.data      81
     2.data       0
     3.data    342
     4.data    324
     5.data       0
     6.data    297
     7.data       0
     dtype: int64
```

```
[7]: # Ignore invalid values by dropping them from the dataframe
df = df.dropna()
```

```
[8]: df
```

```
[8]:      1.data  2.data  3.data  4.data  5.data  6.data  7.data
0      0.67   0.86   1.00   1.00   0.62   1.00   0.67
3      0.62   0.79   0.98   0.92   0.57   0.53   0.62
4      0.62   0.79   0.98   0.92   0.57   0.53   0.62
6      0.57   0.73   0.95   0.85   0.53   0.49   0.57
7      0.57   0.73   0.95   0.85   0.53   0.49   0.57
..      ...      ...      ...      ...      ...      ...
718    0.85   0.85   0.99   1.00   0.62   1.00   0.58
719    0.85   0.85   0.99   1.00   0.62   1.00   0.58
726    0.85   0.85   0.99   1.00   0.63   0.85   0.58
727    0.86   0.85   1.00   1.00   0.63   1.00   0.58
728    0.86   0.85   1.00   1.00   0.63   1.00   0.58
```

```
[387 rows x 7 columns]
```

```
[9]: # Save processed dataframe as csv file
df.to_csv("../data/processed/" + source + ".csv", index=False)
```

```
[10]: # Creating ranked dataframe
ranked_df = pd.DataFrame()
stats_df = pd.DataFrame()
```

```
[11]: # Creating scenario quantity variable
tao = len(df)
tao
```

```
[11]: 387
```

1 Ranking of WWTP

```
[12]: for column in df:
    wwtp = column[0]

    # TODO: get original (pre-analysis) value
    # pending

    # calculate mean
    avg_eff = round(df[column].mean(),3)

    # calculate max
    max_eff = round(df[column].max(),3)

    # calculate min
    min_eff = round(df[column].min(),3)

    # calculate amplitude
    amplitude = round((max_eff - min_eff)*100,2)

    amp_str = "Amplitude (max-min)%"

    # print stats results
    print("WWTP", wwtp, "Mean =", avg_eff, "Maximum =", max_eff, "Minimum",
    ↪ "=", min_eff, amp_str, "=", amplitude)
    stats_df = stats_df.append({ 'WWTP': wwtp, "Mean": avg_eff, "Maximum" :
    ↪ max_eff, "Minimum": min_eff, amp_str: amplitude},ignore_index=True)

    # TODO: Populate statistics dataframe using pd.df.append

    # Calculating Sk sum of factors
    Sk = round(df[column].sum(),3)

    # Calculating ek sum of factors of 1 (or above if errors in calculation)
    ek = df[column] >= 1
    ek = ek.sum()
    print("ek =",ek)

    # Calculating R1k ek/tao
    R1k = round(ek/tao,3)

    # Calculate R2k
    if tao != ek:
        R2k = (Sk - ek)/(tao - ek)
    elif R1k == 1:
```

```

R2k = 0

R2k = round(R2k,3)

# Printing results
print("WWTP", wwtp,"| ek =",ek,"| R1k =",R1k, "| Sk =",Sk, "| R2k =",R2k)

# Populate ranking dataframe using pd.df.append
# Using unicode to name columns with super and subscripts
R1k_col = 'R\u00B9\u2096\u2080'
R2k_col = 'R\u00B2\u2096\u2080'
ranked_df = ranked_df.append({ R2k_col:R2k, R1k_col: R1k,'WWTP':\u2192wwtp},ignore_index=True)

```

```

WWTP 1 Mean = 0.644 Maximum = 0.86 Minimum = 0.57 Amplitude (max-min)(%) = 29.0
ek = 0
WWTP 1 | ek = 0 | R1k = 0.0 | Sk = 249.15 | R2k = 0.644
WWTP 2 Mean = 0.801 Maximum = 0.87 Minimum = 0.71 Amplitude (max-min)(%) = 16.0
ek = 0
WWTP 2 | ek = 0 | R1k = 0.0 | Sk = 309.87 | R2k = 0.801
WWTP 3 Mean = 0.979 Maximum = 1.0 Minimum = 0.93 Amplitude (max-min)(%) = 7.0
ek = 107
WWTP 3 | ek = 107 | R1k = 0.276 | Sk = 378.72 | R2k = 0.97
WWTP 4 Mean = 0.94 Maximum = 1.0 Minimum = 0.84 Amplitude (max-min)(%) = 16.0
ek = 126
WWTP 4 | ek = 126 | R1k = 0.326 | Sk = 363.79 | R2k = 0.911
WWTP 5 Mean = 0.587 Maximum = 0.64 Minimum = 0.52 Amplitude (max-min)(%) = 12.0
ek = 0
WWTP 5 | ek = 0 | R1k = 0.0 | Sk = 227.08 | R2k = 0.587
WWTP 6 Mean = 0.689 Maximum = 1.0 Minimum = 0.48 Amplitude (max-min)(%) = 52.0
ek = 84
WWTP 6 | ek = 84 | R1k = 0.217 | Sk = 266.75 | R2k = 0.603
WWTP 7 Mean = 0.606 Maximum = 0.68 Minimum = 0.57 Amplitude (max-min)(%) = 11.0
ek = 0
WWTP 7 | ek = 0 | R1k = 0.0 | Sk = 234.45 | R2k = 0.606

```

```

[13]: # Reorder columns to be usable as a results table
ranked_df = ranked_df.reindex(columns=['WWTP',R1k_col, R2k_col])

```

```

[14]: ranked_df

```

```

[14]:
  WWTP  R1  R2
0     1  0.000  0.644
1     2  0.000  0.801
2     3  0.276  0.970
3     4  0.326  0.911
4     5  0.000  0.587

```

```

5    6    0.217    0.603
6    7    0.000    0.606

```

```

[15]: import os

path = "../../results/" + source + "/"

# Save rankings dataframe as csv file
try:
    ranked_df.to_csv(path + "ranking.csv", index=False)
    print("Save succesful")
except:
    print("Creating folder and saving")
    os.mkdir(path)
    ranked_df.to_csv(path + "ranking.csv", index=False)

```

Creating folder and saving

2 Calculate Descriptive Statistics

```

[16]: # Calculate the mean of every column
mean_mean = round(stats_df.Mean.mean(),3)
mean_max = round(stats_df.Maximum.mean(),3)
mean_min = round(stats_df.Minimum.mean(),3)
mean_amp = round(stats_df[amp_str].mean(),3)

```

```

[17]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "Mean", "Mean" : mean_mean, "Maximum" : ↵
    ↪mean_max,
                                "Minimum" : mean_min, amp_str : ↵
    ↪mean_amp}, ignore_index=True)

```

```

[18]: # Calculate the standard deviation of every column
sd_mean = round(stats_df.Mean.std(),3)
sd_max = round(stats_df.Maximum.std(),3)
sd_min = round(stats_df.Minimum.std(),3)
sd_amp = round(stats_df[amp_str].std(),3)

```

```

[19]: # Add means to stats dataframe
stats_df = stats_df.append({ 'WWTP': "SD", "Mean" : sd_mean, "Maximum" : sd_max,
                                "Minimum" : sd_min, amp_str : ↵
    ↪sd_amp}, ignore_index=True)

```

```
[20]: # Reorder columns
stats_df = stats_df.reindex(columns=["WWTP", "Mean", "Maximum", "Minimum", "Amplitude (max-min) (%)"])
```

```
[21]: stats_df
```

```
[21]:
```

| | WWTP | Mean | Maximum | Minimum | Amplitude (max-min) (%) |
|---|------|-------|---------|---------|-------------------------|
| 0 | 1 | 0.644 | 0.860 | 0.570 | 29.000 |
| 1 | 2 | 0.801 | 0.870 | 0.710 | 16.000 |
| 2 | 3 | 0.979 | 1.000 | 0.930 | 7.000 |
| 3 | 4 | 0.940 | 1.000 | 0.840 | 16.000 |
| 4 | 5 | 0.587 | 0.640 | 0.520 | 12.000 |
| 5 | 6 | 0.689 | 1.000 | 0.480 | 52.000 |
| 6 | 7 | 0.606 | 0.680 | 0.570 | 11.000 |
| 7 | Mean | 0.749 | 0.864 | 0.660 | 20.429 |
| 8 | SD | 0.148 | 0.141 | 0.159 | 14.391 |

```
[22]: # Save statistics dataframe as csv file
stats_df.to_csv(path + "statistics.csv", index=False)
```

```
[23]: # Convert Jupyter Notebook to PDF LaTeX file
!jupyter-nbconvert --to pdf "clip-max-ignore-zeros-custom.ipynb" --output-dir ".\
    \>./../results/6d/"
```

```
[NbConvertApp] Converting notebook clip-max-ignore-zeros-custom.ipynb to pdf
[NbConvertApp] Writing 44947 bytes to ./notebook.tex
[NbConvertApp] Building PDF
[NbConvertApp] Running xelatex 3 times: ['xelatex', './notebook.tex', '-quiet']
[NbConvertApp] Running bibtex 1 time: ['bibtex', './notebook']
[NbConvertApp] WARNING | bibtex had problems, most likely because there were no
citations
[NbConvertApp] PDF successfully created
[NbConvertApp] Writing 46789 bytes to ../results/6c/clip-max-ignore-zeros-
custom.pdf
```