

## LATERAL PILE ANALYSIS

Project: Sample Project      Number: LP-2026-002  
Prepared By: S. OConnell, PE      Date: 2026-02-17  
Company: Geotech Associates

### 1. INPUT PARAMETERS

---

| Parameter            | Symbol | Value     | Unit              |
|----------------------|--------|-----------|-------------------|
| Pile length          | $L$    | 15.00     | m                 |
| Pile diameter        | $D$    | 0.610     | m                 |
| Young's modulus      | $E$    | 200000000 | kPa               |
| Wall thickness       | $t$    | 0.0127    | m                 |
| Flexural rigidity    | $EI$   | 212651    | kN-m <sup>2</sup> |
| Lateral load at head | $V_t$  | 100.0     | kN                |
| Moment at head       | $M_t$  | 0.0       | kN-m              |
| Axial load           | $Q$    | 0.0       | kN                |

### 1. SOIL PROFILE

---

#### Soil Layer Definition

| # | Top (m) | Bottom (m) | Description | p-y Model       | Key Parameters  |
|---|---------|------------|-------------|-----------------|---|
| 1 | 0.0     | 15.0       | Soft clay   | SoftClayMatlock | $c=50 \text{ kPa}, \gamma=17.0 \text{ kN/m}^3, \epsilon_{50}=0.02, J=0.5$ |

### 1. PILE SECTION PROPERTIES

---

#### Moment of Inertia (hollow pipe)

$$I = \pi/64 \times (D^4 - d^4)$$

$$I = \pi/64 \times (0.610^4 - 0.584^4)$$

$$I = 1.063255e - 03 \text{ m}^4$$

## Flexural Rigidity

$$EI = E \times I$$

$$EI = 200000000 \times 1.063255e - 03$$

$$EI = \textcolor{blue}{212,651} \text{ kN-m}^2$$

## 1. SOLVER PERFORMANCE

---

### Finite Difference Solution

$$\text{Iterative } p-y \text{ method : } EI \times d^4y/dz^4 + Q \times d^2y/dz^2 - p(y, z) = 0$$

Converged = Yes

COM624P finite difference formulation

Iterations: 43

## 1. KEY RESULTS

---

### Pile Head Response

| Quantity                 | Value   | Unit |
|--------------------------|---------|------|
| Head deflection          | 7.98    | mm   |
| Head rotation            | -2.7260 | mrad |
| Maximum moment           | 145.6   | kN-m |
| Depth of max moment      | 2.85    | m    |
| Maximum shear            | 100.0   | kN   |
| Maximum deflection       | 7.98    | mm   |
| Depth of zero deflection | 4.90    | m    |

## 1. FIGURES

---




Figure 1: \*

Figure 1: Deflection, bending moment, shear force, and soil reaction profiles along the pile ( $V_t = 100$  kN,  $M_t = 0$  kN-m,  $Q = 0$  kN).




Figure 2: \*  
Figure 2: Detailed deflection profile. Head deflection = 7.98 mm.

## 1. REFERENCES

---

1. Wang, S.T. & Reese, L.C. (1993). COM624P — Laterally Loaded Pile Analysis Program for the Microcomputer. FHWA-SA-91-048.
  2. Reese, L.C. & Matlock, H. (1956). Non-dimensional Solutions for Laterally Loaded Piles with Soil Modulus Assumed Proportional to Depth.
  3. Matlock, H. (1970). Correlations for Design of Laterally Loaded Piles in Soft Clay. OTC-1204.
  4. Reese, L.C. et al. (1974). Analysis of Laterally Loaded Piles in Sand. OTC-2080.
  5. API RP 2GEO (2014). Geotechnical and Foundation Design Considerations.
  6. Jeanjean, P. (2009). Re-Assessment of p-y Curves for Soft Clays from Centrifuge Testing and Finite Element Modeling. OTC-20158.
  7. FHWA GEC-13 (FHWA-HIF-18-031): Ground Modification Methods.
-