

linux CheatSheet

Top-level Directories

- / : root
 - /etc : Program Configuration Files
 - /var : Frequently changing content (ex. logs)
 - /home : User account files
 - /sbin : System binary files
 - /bin : User binary files
 - /lib : Shared libraries
 - /usr : Third-party libraries

Basic Commands

ls

- lists content of a directory

```
ls [/aDirectoryName]
```
- lists content with the long flag `-l` and human-readable flag `h` displays file permissions and size information

```
$ ls -lh /users/max/documents
```
- lists with the recursive flag `-R` everything in and under a directory

```
$ ls -R /users/max/documents
```
- lists hidden files as well

```
$ ls -a /users/max/documents
```

```
$ ls -all (2 hyphens)
```

pwd (present working directory)

- print name of current/working directory
- using flag Logical `-L` to include symlinks

cd (change directory)

- ex. : moving to root directory :

```
$ cd \
```
- back to Home to directory from where-ever

```
$ cd
```

rm (remove)

- removing a file :

```
$ rm myFile
```
- removing an empty directory:

```
$ rmdir myEmptyDirectory
```
- removing a non-empty directory and its contents recursively :

```
rm -r myDirectory
```

cp (copy)

- copy a file to a specified directory

```
$ cp myFile /home/max/anotherDirectory
```

mv (move)

- move a file to a specified directory

```
$ mv myFile /home/max/anotherDirectory
```

Other Commands

cat (concatenate)

- prints file content to output

less

- quickly display less than a complete file contents
- scroll document's content with arrows
- quit by typing 'q'

man

- brings up a one-page interface to reference manuals about a linux command

```
ex. : $ man ls
```
- type `\` (backslash) followed by keywords to search into document

```
move forward to next keyword by typing 'n'
```
- quit by typing 'q'

touch

- updates file timestamps
- if file doesn't exist it will create it

stat (status)

- displays file or file system status

```
displays file's inode (metadata) information
```

| (pipe)

- creates a unidirectional data channel
- takes the output of a command to feed it as the input of another

```
$ journalctl | grep myFile.php
```
- you can chain as many pipes as you wish

```
$ journalctl | grep myFile.php | grep error
```

info

- reading documentation in Info format
- useful, when you don't know the name of a command you want to use
- click Enter on underlined text to follow links

```
'u' will bring you back one level
```

```
'q' to exit
```

journalctl

- tool to query the contents of the systemd journal

```
ideally do filter query with grep
```

```
$ journalctl | grep myPage.php
```

kernel & architecture

- print your system architecture (ex: x86_64)

```
$ arch
```
- print your kernel's version

```
$ uname -r
```

Keyboard Shortcuts

TAB (completion)

- press TAB to complete a command

```
$ touch myNewFile
```

```
$ rm my<TAB>
```

Special Characters

* (gobbling)

- wildcard used to designate all files in a directory

```
$ mv * /home/max/archive
```
- wildcard used to designate any characters

```
$ git add linux*.tex, linux*.pdf
```

? (question mark)

- represents or matches a single occurrence of any character

```
there are files named 'file1', 'file2', 'file3'
```

```
$ rm file? /home/max/documents
```

\ (backslash)

- The backslash character can be used to conveniently break a long command into multiple lines on the command line.

```
# yum install lxc lxc-templates \libcaps-devel libcgrouper busybox
```

System Administration

networking

- display machine's ip addresses
\$ ip addr

bash

- bashrc : file containing shell settings from non-logged in shell
\$ less .bashrc
- .profile : file containing shell settings from logged-in shell (ex.: ssh sessions)
\$ less .profile
\$ less /etc/profile
- apps user information and default shell
\$ cat /etc/passwd
- list of 1000 most recent commands typed
\$ cat .bash_history

systemd

- first process to run on a system
- show all services and processes running
\$ systemctl list-units -type service -state running
or
\$ systemctl -no-pager | grep service | grep running | column -t
- show all installed unit-files
\$ systemctl list-units -type service
or
\$ systemctl list-units -type service -state running -no-legend

- show processes that executed then exited
\$ systemctl list-units -type service -state exited
- show processes that have failed
\$ systemctl list-units -type service -state failed
- *In order to pass the output to *stdout* instead of a pager
add argument '--no-pager'
- enabling and starting a service (without rebooting)
\$ systemctl enable -now httpd
- show boot time
\$ systemd-analyze
- identify which process slow down boot
\$ systemd-analyze blame

SELinux

- show SELinux status
\$ sestatus
- disable error enforcing and logging them instead
\$ sudo setenforce 0

Docker

- show Docker version
\$ docker version
- starting Docker daemon manually
\$ sudo docker daemon
- add user to Docker group (i.e. running Docker as root)
on Ubuntu
\$ sudo usermod -aG docker
- restarting Docker
\$ sudo service docker restart

Utils

- display environmental variables
\$ echo \$PATH
- locate an executable file
\$ which python3
- show regional settings
\$ locale
\$ localectl
- display information about the nature of a command
\$ type {command}
\$ type bash
- display information about time and timezones
\$ timedatectl
- display all block devices connected and their size
df -ht ext4
- display interactions with the kernel
\$ dmesg
- list all hardware connected
\$ sudo lshw | less
- show grub configuration
\$ less /etc/default/grub

python

- create a new virtual environment
\$ python3 -m venv myVenvName

Last compilation : July 25, 2020