

# Ocelloids Network Specification

The Zone Council, SO/DA

January 11, 2024

This document is a **work in progress**.

## Abstract

This document outlines the functional specifications of the Ocelloids network, a system for secure and transparent leasing of software agents that observe, correlate, and respond to blockchain activity. The network comprises provider nodes hosting agents under negotiated leases with consumers. A continuous service attestation process ensures reliable agent operation, while the network registry controls the admission, suspension and termination processes for service providers and auditors within a trust zone. The document details network roles, leasing processes, and attestation methods, providing a comprehensive understanding of the Ocelloids network's functionalities.

# 1 Introduction

The Ocelloids network operates as a real-time reactive layer with software agents that observe, correlate, and respond to blockchain activity. These program instances, hosted by provider nodes in a leasing model, naturally connect offchain data with onchain activity. Providers undergo an admission process within a trust zone and operate within defined geographical boundaries, subject to applicable laws. The **Service Attestation** process ensures the reliable functioning of the agents, enabling providers to earn leasing fees for hosting them.

## 2 Network

An Ocelloids network is a collection of nodes under a common trust zone with vetted access for participation.

The network is governed through an onchain registry in the **reference chain**, known as the **Network Registry**, containing participant information and their **Network Roles**.

Network participants have well-known identities tied to specific organizations, geolocations, and publicly accessible endpoints.

### 2.1 Network Registry

The network registry exists in the **reference chain** and delineates a trust zone characterized by designated sovereign and administrative accounts. These accounts are endowed with privileges related to the admission, suspension and termination of service providers and auditors in the network. These procedures play a critical role as they establish connections with entities subject to liabilities and potentially involve the establishment of legally binding contractual agreements.

Each participant of the network has an associated **Party Record**, which includes essential information for locating service providers and verifying the authenticity of digital signatures.

Table 1: Party Record

Property	Description
Subject	Distinguished name[1].
Accounts	Operator and treasurer account addresses.

Property	Description
Endpoints	URLs[2] of the public endpoints.
Location	Geographic point location[3].
Role	The node role (section 2.2).

## 2.2 Network Roles

The network encompasses two node roles.

### *Provider Node*

Negotiates service agreements, hosts **agents** in accordance with active leases and receives leasing fees.

### *Auditor Node*

Verifies the execution of the **agents** involved in active leases and provides attestations to authorize the payment of leasing fees.

## 2.3 Program Catalog

The Ocelloids network maintains a curated catalog on the **reference chain** of programs eligible for hosting. These programs are organized into packages identified by content-addressable identifiers and stored in a content-addressable storage network. Each package contains source code and/or binary files, along with a manifest describing the program and its required hosting capabilities. An instance of a program is referred to as an **agent** and possesses a unique **agent identifier**.

Reference Ocelloids Node spec. when written.

## 3 Service Leasing

The service leasing process involves consumers requesting service offers, depositing funds to pay for **agent** hosting, undergoing continuous service attestations, managing periodic payment claims, and facilitating automatic lease renewals.

### 3.1 Service Agreement

The service agreement process mandates that the **consumer** deposit funds to cover at least one period before the **provider** provisions the **agent**. The **consumer** queries the **Program Catalog** to determine the identifier of the program it wishes to execute. The **providers** are discovered through the **Network Registry**. The high-level steps are as follows.

1. *Request Quote.* The **consumer** initiates the leasing process by submitting a quote request to the **provider**, specifying the desired **program identifier** for execution.
2. *Service Offer.* The **provider** responds with a service offer, providing details such as the **program identifier** to be executed, the leasing period duration in number of blocks, leasing fee, and minimum deposit required.
3. *Place Deposit.* The **consumer** submits a deposit to the **reference chain**, specifying the offer and the transfer amount. The funds for one leasing period are locked, with any remaining funds available for withdrawal by the consumer at any time.
4. *Confirm Deposit.* The **reference chain** issues a deposit receipt for the offer to the **consumer**, confirming the deposit. The **consumer** then sends this receipt to the **provider**.
5. *Provision Agent.* The **provider** verifies the deposit and provisions the **agent** based on the accepted offer.
6. *Confirm Lease.* The **provider** submits the deposit receipt to the **reference chain** to formalize the lease, receiving a lease receipt in response.
7. *Activate Lease.* The **provider** acknowledges the lease activation to the **consumer** upon receiving the lease receipt.

### 3.2 Service Attestation

The service attestation process<sup>1</sup> involves **auditors** continuously verifying the accurate operation and fulfillment of the agents hosted by a **providers** under the leasing duration. The attestation process operates within the timeframe of a leasing period. The hosted **agent** observes the activity of **monitored**

---

<sup>1</sup>For non-deterministic sources affecting the program output, a snapshot mechanism must be provided for reproducibility.

chain/s, processing each block, which constitutes the primary input of on-chain data. The **provider** commits a verifiable proof of the processing of each block to a locally maintained verifiable map. Since blocks could be processed out of order, the **provider** maintains a local verifiable key-value map independent of the insertion order, such as a sparse Merkle tree[4]. The commitment to the map adds a pair  $(k, v)$ , where  $k = Block_{hash}$  and  $v = \text{digest}(Program_{output})$ . The **provider** must anchor the top hash of the verifiable map to the **reference chain** at the end of the period. The attestation process for each period works as follows.

1. *Request Service Proofs.* The **auditor** requests service proofs for a random sample<sup>2</sup> of block hashes from **monitored chain** within the most recent anchored period.  $B_{samp} = \{Block_{hash}^0, \dots, Block_{hash}^n\}$ .
2. *Present Service Proofs.* The **provider** presents the requested inclusion proofs for the given **monitored chain** block hashes.  $P_{samp} = \{Proof(b) : b \in B_{samp}\}$ , where *Proof* produces an inclusion proof for the committed value  $v$  on the key  $b$ .
3. *Verify Service Proofs.* The **auditor** verifies the inclusion proofs  $P_{samp}$ .
  - (a) Confirms the inclusion proof using the anchored top hash for the period retrieved from **reference chain**.
  - (b) Independently processes the selected blocks, retrieving them from **monitored chain**<sup>3</sup>, to verify that the digest of the resulting log output matches the value  $v$  of the requested block in the proof.
4. (i) **On successful verification**  
*Record Attestation.* The **auditor** submits a signed attestation of the verified period. The attestation authorizes<sup>4</sup> the payment of leasing fees<sup>5</sup> by the **provider**.
  - (ii) **Otherwise**  
*Record Dispute.* The **auditor** submits a signed dispute with details

---

<sup>2</sup>A simple approach would be to use Yamane's method ( $n = \frac{N}{1+Ne^2}$ ) for  $N$  blocks in the period, where  $n \approx 400$  for a 1-month period with 95% confidence.

<sup>3</sup>We assume that the historical blocks of monitored chain/s for a leasing period are retrievable at the end of the period.

<sup>4</sup>Variations could require signatures from multiple auditors.

<sup>5</sup>The authorized payment should be captured by the **provider** and could entail the deduction of a management fee accrued to the **auditor/s**.

for further resolution<sup>6</sup>.

This continuous attestation process ensures the maintenance of verified operational records, serving as a prerequisite for claiming leasing fees.

### 3.3 Payment & Lease Renewal

At the end of each leasing period, the **provider** must claim the leasing fees and an automatic renewal process is initiated.

1. *Claim Fees.* **Provider** claims the payment of the fees for the leasing period by submitting a transaction to the **reference chain**; e.g., *Claim-PaymentForPeriod*.
2. *Verify & Transfer.* **Reference chain** verifies the latest **agent** operational attestation and transfers the funds to the **provider**.
3. *Renewal Check.* **Provider** checks renewal conditions.
  - (a) The lease is active.
  - (b) Sufficient funds for next period in the **consumer** account.
4. (i) **On successful check**  
*Renew Lease.* **Reference chain** initiates the renewal process, locking funds for the next period.
  - (ii) **Otherwise**  
*Cancel Lease.* **Reference chain** cancels the lease, and the **provider** takes appropriate actions to decommission the **agent**.

This process ensures a smooth transition between leasing periods, with automatic renewals and the flexibility to cancel if necessary. Consumers are responsible for maintaining sufficient deposit funds to cover renewals.

---

<sup>6</sup>While operating in a vetted governance model (i.e., without funds at stake), the resolution falls under the discretion of the trust zone sovereign entities, who are responsible for suspending or terminating the misbehaving party and transferring funds to the rightful party.

# Glossary

agent

A program instance running on a provider node. 2–4, 6, 7

agent identifier

A unique identifier for a program instance running in a specific host. 3

auditor

Node responsible for verifying the execution of agents involved in active leases and providing attestations to authorize the payment of leasing fees. 3–5

consumer

Party that leases the hosting of an agent on a provider within the network. 4, 6

monitored chain

Blockchain that serves as onchain data source for an agent. 4, 5

program

Package containing executable bytecode or source code published through vetted catalogues. 2

program identifier

A unique content-bound identifier pointing to a program package stored in a content-addressable storage network. 4

provider

Node responsible for negotiating service agreements, hosting agents according to active leases, and receiving leasing fees. 2–7

reference chain

Blockchain that provides the governance, discovery, leasing, anchoring and settlement functions for an Ocelloids network. 2–6

# References

- [1] The directory: Selected attribute types. X.520, October 2019. URL <https://handle.itu.int/11.1002/1000/14037>.

- [2] Tim Berners-Lee, Roy T. Fielding, and Larry M Masinter. Uniform Resource Identifier (URI): Generic Syntax. RFC 3986, January 2005. URL <https://www.rfc-editor.org/info/rfc3986>.
- [3] Standard representation of geographic point location by coordinates. ISO 6709:2022, September 2022. URL <https://www.iso.org/standard/75147.html>.
- [4] Rasmus Dahlberg, Tobias Pulls, and Roel Peeters. Efficient sparse merkle trees: Caching strategies and secure (non-)membership proofs. Cryptology ePrint Archive, Paper 2016/683, 2016. URL <https://eprint.iacr.org/2016/683>. <https://eprint.iacr.org/2016/683>.