CYG WAYON
Let's make electronics safer!

WS05MF

Order Code: WS05MF

Transient Voltage Suppressor

Features

- Solid-state silicon-avalanche technology
- 100 Watts Peak Pulse Power per Line (t_p=8/20μs)
- Low operating and clamping voltages
- Up to Four (4) Lines of Protection
- Working Voltages: 5 V
- Low Leakage Current



SOT-353

IEC COMPATIBILITY (EN61000-4)

- **IEC 61000-4-2 (ESD) ±15kV (air), ±8kV (contact)**
- **IEC 61000-4-4 (EFT) 40A (5/50ns)**
- **IEC 61000-4-5 (Lightning) 5.5A (8/20μs)**

Mechanical Characteristics

- SOT-353 package
- Molding compound flammability rating: UL 94V-0
- Marking: Marking Code
- Packaging: Tape and Reel
- RoHS Compliant

Applications

- Cellular Handsets & Accessories
- Personal Digital Assistants (PDAs)
- Notebooks & Handhelds
- Portable Instrumentation
- Digital Cameras
- MP3 Player

Circuit Diagram



Schematic & PIN Configuration



SOT-353 (Top View)

Absolute Maximum Rating			
Rating	**Symbol**	**Value**	**Units**
Peak Pulse Power（t_p =8/20μs）	P_{PP}	100	W
Peak Forward Voltage (I_F = 1A, t_p=8/20μs)	V_{FP}	1.5	V
Operating Temperature	T_J	-55 to + 125	℃
Storage Temperature	T_{STG}	-55 to +150	℃

Electrical Parameters (T=25℃)

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_F	Forward Current
V_F	Forward Voltage @ I_F



Electrical Characteristics

WS05MF						
Parameter	**Symbol**	**Conditions**	**Minimum**	**Typical**	**Maximum**	**Units**
Reverse Stand-Off Voltage	V_{RWM}				5.0	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	6.0			V
Reverse Leakage Current	I_R	V_{RWM}=5V,T=25℃			1	μA
Peak Pulse Current	I_{PP}	t_p =8/20μs			5.5	A
Clamping Voltage	V_C	I_{PP}=1A, t_p=8/20μs			9.6	V
Clamping Voltage	V_C	I_{PP}=5.5A, t_p=8/20μs		15	18	V
Junction Capacitance	C_j	Between I/O pins and Ground V_R = 0V, f = 1MHz		22	25	pF

Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time



Figure 2: Power Derating Curve



Figure 3: Clamping Voltage vs. Peak Pulse Current



Figure 4: WS05MF Insertion Loss



Figure 5: Normalized Junction Capacitance vs. Reverse Voltage



Figure 6: ESD Pulse Waveform (Per IEC 61000-4-2)



Outline Drawing – SOT-353

PACKAGE OUTLINE





SOT-353

DIMENSIONS				
SYMBOL	INCHES		MILLIMETER	
	MIN	MAX	MIN	MAX
A	0.035	0.043	0.900	1.100
A1	0.000	0.004	0.000	0.100
A2	0.035	0.039	0.900	1.000
D	0.079	0.087	2.000	2.200
E1	0.045	0.053	1.150	1.350
E	0.085	0.096	2.150	2.450
e	0.020 TYP		0.650 TYP	
e1	0.047	0.055	1.200	1.400
L	0.022 REF		0.525 REF	
L1	0.010	0.018	0.260	0.460
θ	0°		8°	0° 8°



DIMENSIONS		
DIM	INCHES	MILLIMETERS
Z	0.090	2.30
G	0.073	1.85
P	0.020 TYP	0.65 TYP
X	0.008	0.20
Y	0.033	0.085

Notes

1. Dimensioning and tolerances per ANSI Y14.5M, 1985.
2. Controlling Dimension: Inches
3. Pin 3 is the cathode (Unidirectional Only).
4. Dimensions are exclusive of mold flash and metal burrs.

Marking Codes

Part Number	WS05MF
Marking Code	05F

Package Information

Qty：3k/Reel

CONTACT INFORMATION

CYG WAYON CIRCUIT PROTECTION CO., LTD.
No.1001, Shiwan (7) Road, Pudong District, Shanghai, P.R.China.201202
Tel: 86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: **http://www.way-on.com**

For additional information, please contact your local Sales Representative.

CYG WAYON ® is registered trademark of Wayon Corporation.