
Manages all the communication between the backendserver and the frontend-application

Index

Constructors

constructor

Properties

singleBackendServerCommunicator

Methods

- login
 - [pullConfigFileWithConfigFileNameWithWorkflowInstanceName](#)
 - [pullGraphForTemporaryTemplate](#)
 - [pullServers](#)
 - [pullTemplateWithName](#)
 - [pullTemplatesName](#)
 - [pullUsers](#)
 - [pullVersionsWithWorkflowInstanceName](#)
 - [pullWorkflowInstancesNameAndConfigFilesName](#)
 - [pushConfigFileWithConfigFilesNameWithWorkflowInstanceName](#)
 - [pushCreateTemplate](#)
 - [pushDeleteUser](#)
 - [pushReplaceActiveVersionOfWorkflowInstance](#)
 - [pushServer](#)
 - [pushUser](#)
 - [pushWorkflowInstanceFromTemplate](#)
 - [register](#)
 - [returnBackendServerCommunicator](#)
-

Constructors

Private **constructor**

```
new BackendServerCommunicator(): BackendServerCommunicator
```

Defined in classes/BackendServerCommunicator.ts:8

Returns *BackendServerCommunicator*

Properties

Private **singleBackendServerCommunicator**

```
singleBackendServerCommunicator: BackendServerCommunicator
```

Defined in classes/BackendServerCommunicator.ts:6

Methods

login

```
login(userName: string, userPassword: string): void
```

Defined in classes/BackendServerCommunicator.ts:20

A person signs in to his account

Parameters

- **userName:** *string*
the persons userName
- **userPassword:** *string*
the persons userPassword

Returns *void*

pullConfigFileWithConfigFileNameWithWorkflowInstanceName

```
pullConfigFileWithConfigFileNameWithWorkflowInstanceName(configFileName: string, workflowInstanceName: string): ConfigFile
```

Defined in classes/BackendServerCommunicator.ts:67

Pulls a configFile-object from backendserver

Parameters

- **configFileName:** *string*
The name of the configFile
- **workflowInstanceName:** *string*
The name of the workflowInstance

Returns *ConfigFile*

The configFile-object

pullGraphForTemporaryTemplate

pullGraphForTemporaryTemplate(tempTemplate: *Template*): *File*

Defined in classes/BackendServerCommunicator.ts:32

Pulls a graph-image of the temporary tempalte from the backendserver

Parameters

- **tempTemplate:** *Template*
The temporary template

Returns *File*

The image of the graph

pullServers

pullServers(): *Server*[]

Defined in classes/BackendServerCommunicator.ts:105

Pulls all the server-objects from the backendserver

Returns *Server*[]

The server-objects

pullTemplateWithName

pullTemplateWithName(templateName: *string*): *Template*

Defined in classes/BackendServerCommunicator.ts:55

Pulls a template object from the backendserver

Parameters

- **templateName:** *string*

The template name

Returns *Template*

The template-object

pullTemplatesName

```
pullTemplatesName(): string[]
```

Defined in classes/BackendServerCommunicator.ts:49

Pulls all the template names from the backendserver

Returns *string*[]

List of template names

pullUsers

```
pullUsers(): User[]
```

Defined in classes/BackendServerCommunicator.ts:90

Pulls all user-objects from the backendserver

Returns *User*[]

The user-objects

pullVersionsWithWorkflowInstanceName

```
pullVersionsWithWorkflowInstanceName(workflowInstanceName: string):  
WorkflowInstance
```

Defined in classes/BackendServerCommunicator.ts:79

Pulls a workflowInstance from the server

Parameters

- **workflowInstanceName:** *string*

The name of the workflowInstance

Returns *WorkflowInstance*

the workflowInstance-object

pullWorkflowInstancesNameAndConfigFileName

```
pullWorkflowInstancesNameAndConfigFileName(): string[][]
```

Defined in classes/BackendServerCommunicator.ts:60

Pulls all workflowInstances names the according configFiles names from the backendServer

Returns *string[][]*

WorkflowInstances names and configFiles names

pushConfigFileWithConfigFileNameWithWorkflowInstanceName

```
pushConfigFileWithConfigFileNameWithWorkflowInstanceName(configFiles: ConfigFile[], workflowInstanceName: string): void
```

Defined in classes/BackendServerCommunicator.ts:73

Pushes the configFile-objects of a specificWorkflowInstance to the backendserver

Parameters

- **configFiles:** *ConfigFile[]*
The configFile-objects
- **workflowInstanceName:** *string*
The name of the workflowInstance

Returns *void*

pushCreateTemplate

```
pushCreateTemplate(template: Template): void
```

Defined in classes/BackendServerCommunicator.ts:37

pushes the new template to the backendserver

Parameters

- **template:** *Template*

The new template-object

Returns *void*

pushDeleteUser

```
pushDeleteUser(user: User): void
```

Defined in classes/BackendServerCommunicator.ts:100

Pushes a delete-request to the backendserver

Parameters

- **user:** *User*
The user-object

Returns *void*

pushReplaceActiveVersionOfWorkflowInstance

```
pushReplaceActiveVersionOfWorkflowInstance(workflowInstanceName: string,  
versionNumber: string): void
```

Defined in classes/BackendServerCommunicator.ts:85

Parameters

- **workflowInstanceName:** *string*
The name of the workflowInstance
- **versionNumber:** *string*
The name of the versionNumber

Returns *void*

pushServer

```
pushServer(server: Server): void
```

Defined in classes/BackendServerCommunicator.ts:110

Pushes a server-object to the backend

Parameters

- **server:** *Server*

The server-object

Returns *void*

pushUser

```
pushUser(user: User): void
```

Defined in classes/BackendServerCommunicator.ts:95

Pushes a user-object to the backendServer

Parameters

- **user:** *User*
The user-object

Returns *void*

pushWorkflowInstanceFromTemplate

```
pushWorkflowInstanceFromTemplate(templateName: string, workflowInstanceName:  
  string, configFolder: File): void
```

Defined in classes/BackendServerCommunicator.ts:44

pushes a new workflowInstance to the backendserver

Parameters

- **templateName:** *string*
The name of the choosen template
- **workflowInstanceName:** *string*
The name for the new workflowInstance
- **configFolder:** *File*
The configFolder encoded as zip-file

Returns *void*

register

```
register(userName: string, userPassword: string): void
```

Defined in classes/BackendServerCommunicator.ts:26

A person registers a new account

Parameters

- **userName:** *string*
The choosen userName of the person
- **userPassword:** *string*
The choosen userPassword of the person

Returns *void*

returnBackendServerCommunicator

```
returnBackendServerCommunicator(): BackendServerCommunicator
```

Defined in classes/BackendServerCommunicator.ts:14

Returns the only instance of BackendServerCommunicator (Singelton-Pattern)

Returns *BackendServerCommunicator*

singleBackendServerCommunicator
