


SOFA: a modular yet efficient physical simulation architecture

Francois.Faure@imag.fr



Outline

A complex physical simulation




Material, internal forces, constraints, contact detection and modeling, ODE solution, visualization, interaction, etc.

Simulation platforms

- ▶ Current platforms (ODE, Havok, Novodex, etc.) provide :
 - ▶ limited number of material types
 - ▶ limited number of geometry types
 - ▶ no control on collision detection algorithms
 - ▶ no control on interaction modeling
 - ▶ few (if any) control of the numerical models and methods.
 - ▶ no control on the main loop
 - ▶ few (if any) parallelism
- ▶ We need much more !
 - ▶ models, algorithms, scheduling, visualization, etc.

Animation of a simple body

► a liver





- inside : soft material
- surface : stiffer material

A specialized program :

```
f = M*g
f += F1(x,v)
f += F2(x,v)
a = f/M
a = C(a)
v += a * dt
x += v * dt
display(x)
```

A generic approach

- ▶ Behavior model : all internal laws
- ▶ Others : interaction with the world
- ▶ Mappings : relations between the models (uni- or bi-directional)





Outline

Components

Data :



- ▶ sample points and associated values :
 x, v, a, f
- ▶ constraints : fixed points
other : oscillator, collision plane, etc.



Components

Data :



- ▶ sample points and associated values :
 x, v, a, f
- ▶ constraints : fixed points
- ▶ force field : tetrahedron FEM
other : triangle FEM, springs, Lennard-Jones, SPH, etc.



Components

Data :



- ▶ sample points and associated values :
 x, v, a, f
- ▶ constraints : fixed points
- ▶ force field : tetrahedron FEM
- ▶ force field : triangle FEM



Components

Data :


- ▶ sample points and associated values :
 x, v, a, f
- ▶ constraints : fixed points
- ▶ force field : tetrahedron FEM
- ▶ force field : triangle FEM
- ▶ mass : uniform
other : diagonal, sparse symmetric matrix



Components


Data :

- ▶ sample points and associated values :
 x, v, a, f
- ▶ constraints : fixed points
- ▶ force field : tetrahedron FEM
- ▶ force field : triangle FEM
- ▶ mass : uniform
- ▶ ODE solver : explicit Euler
other : Runge-Kutta, implicate Euler, static solution, etc.





Layered body

- independent DOFs (blue)





Layered body

- ▶ independent DOFs (blue)
- ▶ visual samples (salmon)





Layered body

- ▶ independent DOFs (blue)
- ▶ visual samples (salmon)
- ▶ visual mapping



Layered body


- ▶ independent DOFs (blue)
- ▶ visual samples (salmon)
- ▶ visual mapping
- ▶ collision samples (green)
- ▶ collision mapping



Layered body


- ▶ independent DOFs (blue)
- ▶ visual samples (salmon)
- ▶ visual mapping
- ▶ collision samples (green)
- ▶ collision mapping
- ▶ apply displacements

1. $\mathbf{v}_{visual} = \mathbf{J}_{visual} \mathbf{v}$
2. $\mathbf{v}_{collision} = \mathbf{J}_{collision} \mathbf{v}_{visual}$





Layered body

- ▶ independent DOFs (blue)
- ▶ visual samples (salmon)
- ▶ visual mapping
- ▶ collision samples (green)
- ▶ collision mapping
- ▶ apply displacements
 1. $v_{visual} = J_{visual} v$
 2. $v_{collision} = J_{collision} v_{visual}$
- ▶ apply forces
 1. $f_{visual} = J_{collision}^T f_{collision}$
 2. $f = J_{visual}^T f_{visual}$




Two bodies in contact

Use extended trees (Directed Acyclic Graphs) to model trees with loops.




ODE solution of interacting bodies

- Soft interactions : independent processing, no synchronization required




ODE solution of interacting bodies

- ▶ Soft interactions : independent processing, no synchronization required
- ▶ Stiff interactions : unified implicit solution, synchronized objects




ODE solution of interacting bodies

- ▶ Soft interactions : independent processing, no synchronization required
- ▶ Stiff interactions : unified implicit solution, synchronized objects
- ▶ Hard interaction constraints : work in progress (*Christian Duriez, ALCOVE*)



Outline


Actions



- ▶ No global state vector
- ▶ Action = graph traversal + global vector ids + call of abstract top-down and bottom up methods


Example : clearing a global vector

- ▶ The solver triggers an action starting from its parent system and carrying the necessary symbolic information
- ▶ the action is propagated through the graph and calls the appropriate methods at each DOF node



Example : accumulating the forces

- ▶ The solver triggers the appropriate action
- ▶ the action is propagated through the graph and calls the appropriate (bottom-up) methods at each Force and Mapping node



Efficient implicit integration

- ▶ Large time steps for stiff internal forces and interactions
- ▶ solve $(\alpha M + \beta h^2 K) \Delta v = h(f + hKv)$ Iteratively using a conjugate gradient solution

Actions :

- ▶ propagateDx
- ▶ computeDf
- ▶ vector operations
- ▶ dot product (only global value directly accessed by the solver)


Ongoing work : building global vectors and matrices also

Efficiency

- ▶ No global state vector
 - ▶ they are scattered over the DOF components
 - ▶ each DOF component can be based on its own types (e.g. Vec3, Frame, etc.)
 - ▶ symbolic values are used to represent global state vectors
- ▶ Action = graph traversal + global vector ids + call of abstract top-down and bottom up methods
 - ▶ Displacements are propagated top-down
 - ▶ Interactions forces are evaluated after displacement propagation
 - ▶ Forces are accumulated bottom-up
 - ▶ Branches can be processed in parallel
 - ▶ virtual functions applied to components

Outline

Current stage



Efficient coupling

High modularity :

- ▶ Abstract components : DOF, Force, Constraint, Solver, Topology, Mass, CollisionModel, VisualModel, etc.
- ▶ Arbitrary DOF types can coexist in the same scene

Efficiency :

- ▶ global vectors and matrices are avoided
- ▶ parallel processing is allowed

Implementation :

- ▶ currently 20000 C++ lines
- ▶ Windows, Linux
- ▶ Qt or FLTK user interfaces
- ▶ XML file format

Ongoing work

- ▶ More people : ETHZ, ...
- ▶ More algorithms : cutting (*Hervé Delingette, ASCLEPIOS*), interfaces (*François Faure, EVASION*),...
- ▶ More schedulers : asynchronous simulation/rendering/haptic feedback (*Jeremie Allard, Cimit*)
- ▶ More brute force : parallelization on PC cluster (*Everton Hermann, LIG/LJK*)
- ▶ More visual performance : coupling to a good render engine (*Pierre-Jean Bensoussan, ALCOVE*)
- ▶ More documentation (*everybody...*)

www.sofa-framework.org