NeuroScan API - Frontend Endpoint Guide

Frontend integration reference | October 23, 2026

Base URL: https://neuroscan-api-pcka.onrender.com **API prefix:** /api/v1 except service utilities. JSON requests. Protected routes require Authorization: Bearer <access_token>.

Endpoints

Method	Endpoint	Auth	Request body	Success
POST	/api/v1/auth/register	No	email; password (10-128 chars)	202 - sends verification code
POST	/api/v1/auth/verify-email	No	email; six-digit code	200 - access + refresh tokens
POST	/api/v1/auth/resend-code	No	email	202 - resend; 60-second cooldown
POST	/api/v1/auth/login	No	email; password	200 - access + refresh tokens
POST	/api/v1/auth/refresh	No	refresh_token	200 - rotated token pair
POST	/api/v1/auth/logout	Bearer	refresh_token	204 - no response body
GET	/api/v1/auth/me	Bearer	None	200 - signed-in user profile
POST	/api/v1/auth/forgot-password	No	email	202 - generic response; reset email if eligible
POST	/api/v1/auth/verify-reset-code	No	email; six-digit code	200 - reset_token; expires_in seconds
POST	/api/v1/auth/reset-password	No	reset_token; new_password (10-128 chars)	200 - password reset confirmation
POST	/api/v1/chat	Bearer	message; optional conversation_id, image_urls, image_data	200 - conversation_id; reply
GET	/api/v1/chat/conversations	Bearer	None	200 - signed-in user conversations
GET	/api/v1/chat/conversations/{conversation_id}/messages	Bearer	None	200 - conversation messages
GET	/health	No	None	200 - liveness status
GET	/ready	No	None	200 ready; 503 if DB unavailable
GET	/	No	None	200 - service information
GET	/playground	No	None	200 - browser demo
GET	/docs	No	None	Interactive OpenAPI docs

Integration notes

Forgot password: POST /auth/forgot-password; submit the emailed six-digit code to /auth/verify-reset-code; then use the returned single-use reset_token at /auth/reset-password. The request endpoint gives the same response whether or not an eligible account exists. Reset authorization expires after 10 minutes by default; successful resets revoke refresh tokens.

Chat/images: message is required (1-12,000 characters). Omit conversation_id or set null to start, then reuse the returned ID. image_urls accepts up to four public HTTPS URLs. image_data accepts one JPEG, PNG, or WebP base64 data URL (max 3 MB before encoding).

Browser/security: CORS allows all origins, methods, and headers; cookies are disabled. Do not use credentials: include. Errors generally return {"detail":"..."}. Never put tokens in URLs or logs. Render free instances may sleep while idle. Docs: https://neuroscan-api-pcka.onrender.com/docs | Demo: https://neuroscan-api-pcka.onrender.com/playground