Ipv4 and Ipv 6

This table presents an IPv4 and IPv6 addressing plan using Variable Length Subnet Masking (VLSM) for IPv4. It includes the required number of hosts, network addresses, usable host ranges, broadcast addresses, subnet masks, and IPv6 network prefixes.

NUMBER OF HOSTS	IPv6 NETWORK ADDRESS	NETWORK ADDRESS	USABLE RANGE		BROADCAST	SUBNET MASK
170	2001:B:B:1::/64	172.16.1.0	172.16.1.1	172.16.1.254	172.16.1.255	255.255.255.0
95	2001:B:B:2::/64	172.16.2.0	172.16.2.1	172.16.2.126	172.16.2.127	255.255.255.128
50	2001:B:B:3::/64	172.16.2.128	172.16.2.129	172.16.2.190	172.16.2.191	255.255.255.192
20	2001:B:B:4::/64	172.16.2.192	172.16.2.193	172.16.2.222	172.16.2.223	255.255.255.224
2	2001:B:B:5::/64	172.16.2.224	172.16.2.225	172.16.2.226	172.16.2.227	255.255.255.252
2	2001:B:B:6::/64	172.16.2.228	172.16.2.229	172.16.2.230	172.16.2.231	255.255.255.252
2	2001:B:B:7::/64	172.16.2.232	172.16.2.233	172.16.2.234	172.16.2.235	255.255.255.252
2	2001:B:B:8::/64	172.16.2.236	172.16.2.237	172.16.2.238	172.16.2.239	255.255.255.252