

En algo	En Python	Exemple
Lo ← long (Ch)	Lo = len(Ch)	Lo = len("Salut") → 5 Lo = len("L'élève") → 7 Lo = len("") → 0
Po ← pos (Ch1, Ch2)	Po = Ch2.find(Ch1)	ch1 = "A" ch2 = "enaAdmis" Po = ch2.find(ch1) Po2 = ch2.find("T") En algo ch1 ← "A" ch2 ← "enaAdmis" Po ← pos(ch1,ch2) Po2 ← pos("T",ch2) Po → 3 Po2 → -1
Ch2 ← sous_chaine (Ch1, Début, Fin)	Ch2 = Ch1[Début:Fin]	Ch1 = "informatique" Ch2 = Ch1[4:7] En algo Ch2 ← sous_chaine (Ch1, 4, 7) Ch2 → "rma"
Ch2 ← effacer (Ch1, d, f)	Ch2 = Ch1[:d] + Ch1[f:]	Ch1 = "INFORMATIQUE" Ch2 = Ch1[:6] + Ch1[10:] En algo Ch2 ← effacer (Ch1, 6, 10) Ch2 → "INFORMUE"

ChM ← majus (Ch)	ChM = Ch.upper()	Ch = "Jour" ChM = Ch.upper() → "JOUR" ChM ← majus (Ch) → "JOUR"
Test ← estnum (Ch)	Pas de correspondance directe	Ch = "489" Ch.isnumeric() → True Ch = "abc" Ch.isnumeric() → False En algo Ch ← "489" Test ← estnum (Ch) → True
N ← valeur(Ch)	N = int(Ch) ou bien N = float(Ch)	Ch = "489" N = int(Ch) → 489 Ch = "489" N = float(Ch) → 489.0 En algo Ch ← "489" N ← valeur(Ch) → 489

Algo	Python	Role	Exemple	Résultat
ord(caractere)	ord(caractere)	Retourne le code ASCII du caractere	ord('A') ord('a')	65 97
chr(x)	chr(x)	Retourne le caractère dont le code ASCII x	chr(65) chr(97)	'A' 'a'