

```
1.<script type="text/javascript">
x=4+"4";
document.write(x);
</script>
```

What is the output?

- (a) 44
- (b) 8
- (c) 4
- (d) Error output

Correct answer (a)

```
2.<script type="text/javascript" language="javascript">
var qpt = "Quality Point Technologies";
var result = qpt.split(" ");
document.write(result);
</script>
```

- (a) Quality
- (b) Q,u,a,l,i,t,y,P,o,i,n,t,T,e,c,h,n,o,l,o,g,i,e,s
- (c) Quality,Point,Technologies
- (d) QualityPointTechnologies

Correct answer (c)

3.Is it possible to nest functions in JavaScript?

- (a) True
- (b) False
- (c)
- (d)

Correct answer (a)

```
4.<script>
document.write(navigator.appCodeName);
</script>
```

What is the output?

- (a) Get code name of the browser of a visitor
- (b) set code name of the browser of a visitor
- (c) None of the above
- (d)

Correct answer (a)

5. Which of the following is true?

- (a) If onKeyDown returns false, the key-press event is cancelled.
- (b) If onKeyPress returns false, the key-down event is cancelled.
- (c) If onKeyDown returns false, the key-up event is cancelled.
- (d) If onKeyPress returns false, the key-up event is canceled.

Correct answer (a)

6. Scripting language are?

- (a) High Level Programming language
- (b) Assembly Level programming language
- (c) Machine level programming language
- (d) None of the above

Correct answer (a)

7. Which best explains getSelection()?

- (a) Returns the VALUE of a selected OPTION.
- (b) Returns document URL of the window in focus.
- (c) Returns the value of cursor-selected text
- (d) Returns the VALUE of a checked radio input.

Correct answer (c)

8. `<script language="javascript">`
`function x()`
`{`
`var s= "Good 100%";`
`var pattern = /\D/g;`
`var output= s.match(pattern);`
`document.write(output);`
`}`
`</script>`
What is the output?

- (a) Good %
- (b) 1,0,0
- (c) G,o,o,d, ,%
- (d) Error

Correct answer (c)

```
9.<script language="javascript">
var qpt="QUALITY POINT TECHNOLOGIES";
alert(qpt.charAt(qpt.length-1));
</script>
```

What is the output?

- (a) P
- (b) E
- (c) S
- (d) Error

Correct answer (c)

10.Choose the client-side JavaScript object:

- (a) Database
- (b) Cursor
- (c) Client
- (d) FileUpLoad

Correct answer (d)

11.Are java and javascript the same?

- (a) No
- (b) Yes
- (c)
- (d)

Correct answer (a)

12.Syntax for creating a RegExp object:

- (a). var txt=new RegExp(pattern,attributes);
- (b). var txt=/pattern/attributes;

- (a) (a) only
- (b) (b) only
- (c) Both (a) and (b)
- (d) None of the above

Correct answer (c)

```
13.<script language="javascript">
function x(z,t)
{
alert(x.length);
}
</script>
```

What is the output?

- (a) Error
- (b) 2
- (c) 1
- (d) 3

Correct answer (b)

14.What is mean by "this" keyword in javascript?

- (a) It refers current object
- (b) It refers previous object
- (c) It is variable which contains value
- (d) None of the above

Correct answer (a)

15.In JavaScript, Window.prompt() method return true or false value ?

- (a) False
- (b) True
- (c) None of the above
- (d)

Correct answer (a)

16.Math.round(-20.51)=?

- (a) 20

- (b) -21
- (c) 19
- (d) None

Correct answer (b)

```
17.<script language="javascript">
function x()
{
var s = "Quality 100%![!!";
var pattern = /\w/g;
var output = s.match(pattern);
document.write(output);
}
</script>
What is the output?
```

- (a) %,!,{,[,!,!
- (b) Q,u,a,l,i,t,y,1,0,0
- (c) Quality 100
- (d) Error

Correct answer (b)

```
18.<script type="text/javascript" language="javascript">
var qpt= new Array();
qpt[0] = "WebDevelopment";
qpt[1]="ApplicationDevelopment"
qpt[2]="Testing"
qpt[3] = "QualityPointTechnologies";
document.write(qpt[0,1,2,3]);
</script>
What is the output?
```

- (a) Error
- (b) QualityPointTechnologies
- (c) WebDevelopment
- (d) WebDevelopmnet,ApplicationDevelopment,Testing,QualityPointTechnologies

Correct answer (b)

19.Choose the server-side JavaScript object:

- (a) FileUpLoad
- (b) Function
- (c) File

(d) Date

Correct answer (c)

20. `parseFloat(9+10)=?`

(a) 19

(b) 910

(c) None

(d) Error

Correct answer (a)

```
21.<script language="javascript">
function x()
{
document.write(2+5+"8");
}
</script>
```

(a) 258

(b) Error

(c) 7

(d) 78

Correct answer (d)

22. _____ keyword is used to declare variables in javascript.

(a) Var

(b) Dim

(c) String

(d) None of the above

Correct answer (a)

23. In Javascript, Which of the following method is used to evaluate the regular expression?

(a) `eval(2*(3+5))`

(b) `evaluate(2*(3+5))`

(c) `evalu(2*(3+5))`

(d) None of the above

Correct answer (a)

```
24.<script language="javascript">
function x()
{
var s= "quality 100%";
var pattern = /\d/g;
var output= s.match(pattern);
document.write(output);
}
</script>
```

- (a) 100
- (b) 1,0,0
- (c) q,u,a,l,i,t,y,%
- (d) Error

Correct answer (b)

```
25.<script type="text/javascript" language="javascript">

qpt=((45%2)==0)? "hello" : "bye";
document.write(qpt);

</script>
```

What is the output?

- (a) hello
- (b) bye
- (c) Error in string handling
- (d) None of the above

Correct answer (b)

```
26.<script language="javascript">
function x()
{
var qpt = "QualityPointTechnologies";
var pattern = new RegExp("POiINT","i");
document.write(qpt.match(pattern));
}
</script>
```

What is the output?

- (a) Error
- (b) POiNT

- (c) Point
- (d) Null

Correct answer (d)

27. How do you create a new object in JavaScript?

- (a) `var obj = {};`
- (b) `var obj = Object();`
- (c) `var obj = new {};`
- (d) None of the above

Correct answer (a)

28. In Javascript, What does `isNaN` function do?

- (a) Return true if the argument is not a number.
- (b) Return false if the argument is not a number.
- (c) Return true if the argument is a number.
- (d) None of the above

Correct answer (a)

29. If `x=103` & `y=9` then `x%=y`, what is the value of `x` after executing `x%=y`?

- (a) 4
- (b) 3
- (c) 2
- (d) 5

Correct answer (a)

30. Choose the external object:

- (a) Date
- (b) Option
- (c) Layer
- (d) Check box

Correct answer (d)

31. Choose the four symbol pairs that represent RegExp properties `lastMatch`,

lastParent, leftContext, and rightContext, respectively:

- (a) \$&, \$+, \$`, \$'
- (b) \$+, \$&, \$', \$`
- (c) \$&, \$~, \$`, \$'
- (d) \$+, \$&, \$`, \$'

Correct answer (a)

32.parseInt("15",10)=?

- (a) 15
- (b) 10
- (c) 151
- (d) 150

Correct answer (a)

33.Which JavaScript feature uses JAR files?

- (a) Object signing
- (b) Style sheets
- (c) Netcaster channels
- (d) Image rollovers

Correct answer (a)

34.How to assign a function to a variable with the JavaScript Function constructor ?

- (a) var f=Function("x","y","return x+y");
- (b) var f=Function(x,y){ return x+y;}
- (c) var f= new Function("x", "y", "return x + y");
- (d) None of the aboce

Correct answer (c)

35.In JavaScript, Window.alert() is used to allow user to enter something

- (a) True
- (b) False
- (c) None of above

(d)

Correct answer (b)

```
36.<script language="javascript">
function x()
{
var qpt = "We are fast growing Software Company located in Chennai, India.";
var pattern = new RegExp("in","gi");

document.write(pattern.exec(qpt) + " ");
document.write(pattern.exec(qpt) + " ");
document.write(pattern.exec(qpt) + " ");
}

</script>
```

(a) in in In

(b) in in in

(c) in in null

(d) in null null

Correct answer (a)

37.Is Javascript has any date data type?

(a) Yes

(b) No

(c) None of the above

(d)

Correct answer (b)

38.Math.round(-20.5)=?

(a) -21

(b) 20

(c) -20

(d) 21

Correct answer (c)

39.?_name is it valid javascript identifier?

- (a) Yes
- (b) No
- (c) None of the above
- (d)

Correct answer (b)

```
40.<script language="javascript">
function x()
{
var qpt = "First come, first served";
var pattern = /first/gi;
document.write(qpt.match(pattern) [1]);
}
</script>
```

What is the output?

- (a) first
- (b) undefined
- (c) First
- (d) Error

Correct answer (a)

```
41. (a) . // , /* ..... **/
(b) . / , /** ...../ , /*
(c) . /*.....*/ , //
(d) . \*.....*\ , //
```

In javascript, Which of the above Comments lines are used ?

- (a) Only (d)
- (b) Only (c)
- (c) Either (c) or (d)
- (d) Only (b)

Correct answer (b)

```
42.<script language="javascript">
function x()
{
var s = "Give 100%![!!!";
var pattern = /\W/g;
var output = s.match(pattern);
document.write(output);
}
</script>
```

- (a) ,%,!,{,[,!,!
- (b) G,i,v,e,1,0,0
- (c) Give 100
- (d) Error

Correct answer (a)

43. Which best describes void?

- (a) A method
- (b) A function
- (c) A statement
- (d) An operator

Correct answer (d)

```
44. <script type="text/javascript" language="javascript">
var qpt="QualityPointTechnologies";
var result =qpt.lastIndexOf("l");
document.write(result);
</script>
```

What is the output?

- (a) 3
- (b) 18
- (c) 17
- (d) 19

Correct answer (b)

```
45.) <script language="javascript">
function x()
{
var qpt = "First come, first served";
var pattern = /first/g;
document.write(qpt.match(pattern) [1]);
}
</script>
```

What is the output

- (a) first
- (b) First
- (c) undefined

(d) None of the above

Correct answer (c)

```
46.<script language="javascript">
function sum(x)
{
    function add(y)
    {
        return x+y;
    }
return add;
}

function callme()
{ result=sum(5) (5);
  alert(result);
}
</script>
```

If you call the function callme(), what will happen ?

(a) 10

(b) Error in calling Function

(c) 5

(d) None of the above

Correct answer (a)

47.) Who invented the javascript programming language?

(a) Tennis Ritchie

(b) James Gosling

(c) Brendan Eich

(d) None of the above

Correct answer (c)

```
48.<script type="text/javascript">
document.write("<h1>This is a heading</h1>");
document.write("<p>This is a paragraph.</p>");
document.write("<p>This is another paragraph.</p>");
</script>
```

Can you write HTML tag inside the javascript?

(a) No

(b) Yes

- (c) Impossible
- (d) None of the above

Correct answer (b)

49. Which feature is supported in MSIE 3.x?

- (a) split()
- (b) document.clear()
- (c) join()
- (d) charAt()

Correct answer (d)

50. How to specify the color of the hypertext links with JavaScript ?

- (a) document.linkColor="#00FF00";
- (b) document.LColor="#00FF00";
- (c) document.LinkC="#00FF00";
- (d) document.hyperTextLink="#00FF00";

Correct answer (a)

```
51. script language="javascript">
function x()
{
var qpt = "QualityPointTechnologies";
var pattern = /point/;

var output= qpt.search(pattern);

document.write("Position: " + output);
}
</script>
```

What is the output?

- (a) Position-7
- (b) Position-1
- (c) Null
- (d) Error

Correct answer (b)

52.----- method returns the number of milliseconds in a date string?

- (a) setHours()
- (b) setMinutes()
- (c) parse()
- (d) None of the above

Correct answer (d)

53.----- converts a string to floating point numbers.

- (a) eval
- (b) parseInt
- (c) parseFloat
- (d) None

Correct answer (c)

54.----- attempts to evaluate a string representing any javascript literals or variables, converting it to a number.

- (a) eval
- (b) parseFloat
- (c) parseInt
- (d) None

Correct answer (a)

55.Which is not an attribute of the cookie property?

- (a) path
- (b) host
- (c) secure
- (d) domain

Correct answer (b)

56.How do substring() and substr() differ?

- (a) One is not a method of the String object.
- (b) substr() takes three arguments, substring() only two.
- (c) Only one accepts a desired string length as an argument.
- (d) Besides the spelling, nothing.

Correct answer (c)

57.Which is not a reserved word?

- (a) interface
- (b) short
- (c) program
- (d) throws

Correct answer (c)

58.In Javascript, Which of the following method is used to find out the character at a position in a string?

- (a) charAt()
- (b) CharacterAt()
- (c) CharPos()
- (d) characAt()

Correct answer (a)

60.How do you delete an element from an options array?

- (a) Set it to false.
- (b) Set it to null.
- (c) Set it to undefined.
- (d) Set it to -1

Correct answer (b)

61.Is javascript case sensitive ?

- (a) Yes
- (b) No
- (c) None of the above
- (d)

Correct answer (a)

62. JavaScript RegExp Object has modifier 'i' to _____ ?

- (a) Perform case-sensitive matching
- (b) Perform case-insensitive matching
- (c) Perform both case-sensitive&case-insensitive matching
- (d) None of the above

Correct answer (b)

63. What are the following looping structures available in javascripts?

a) for, foreach

- (a) for, foreach
- (b) foreach, while loop
- (c) do-while loop, foreach
- (d) for, while loop

Correct answer (d)

64. Which of these is not a method of the Math object?

- (a) atan()
- (b) atan2()
- (c) eval()
- (d) acos()

Correct answer (c)

```
65.<script type="text/javascript">
var s = "9123456 or 80000?";
var pattern = /\d{4}/;
var output = s.match(pattern);
document.write(output);
</script>
```

What is the output?

- (a) 9123
- (b) 91234
- (c) 80000
- (d) None of the above

Correct answer (a)

66. In javascript, RegExp Object Method test() is used to search a string and returns _____?

- (a) true or false
- (b) found value
- (c) index
- (d) None of the above

Correct answer (a)

67. What property would you use to redirect a visitor to another page?

- (a) document.URL
- (b) window.location.href
- (c) document.location.href
- (d) link.href

Correct answer (b)

68. a.) `var qpt="Quality Point Technologies";`

b.) `var qpt=new String("Quality Point Technologies");`

Question:

In javascript, which of the above statement can be used for string declaration?

- (a)) Either (a) or (b)
- (b) Only (a)
- (c) Neither (a) nor (b)
- (d) Only (b)

Correct answer (a)

```
69.<script type="text/javascript" language="javascript">
var qpt = "QualityPointTechnologies";
var result =qpt.indexOf("Tech");
document.write(result);
</script>
```

What is the output?

- (a) 11
- (b) 12
- (c) 15
- (d) 13

Correct answer (b)

```
70. script language="javascript">
function x()
{
var s = "Eat to live, but do not live to eat";
var pattern = new RegExp("eat$");
document.write(pattern.exec(s));
}
</script>
```

What is the output?

- (a) Eat
- (b) eat
- (c) undefined
- (d) Eat eat

Correct answer (b)

```
71. <script language="javascript">
function x()
{
var qpt = "We are fast growing Software Company located in Chennai, India.";
var pattern = new RegExp("in", "g");

document.write(pattern.exec(qpt) + " ");
document.write(pattern.exec(qpt) + " ");
document.write(pattern.exec(qpt) + " ");
}

</script>
```

What is the output?

- (a) in in In
- (b) in in in
- (c) in in null
- (d) in null null

Correct answer (c)

72.----- method is used to remove focus from the specified object.

- (a) blur()
- (b) focus()
- (c) None
- (d)

Correct answer (a)

73.parseInt("FF2")=?

- (a) 152
- (b) FF2
- (c) NaN
- (d) None

Correct answer (c)

74.eval((20*4))=?

- (a) Nan
- (b) 204
- (c) 24
- (d) 80

Correct answer (d)

```
75.)<script language="javascript">
function x()
{
var qpt = "QualityPointTechnologies";
var pattern = new RegExp("TECHNOLOGIES","i");
document.write(qpt.match(pattern));
}
</script>
```

What is the output?

- (a) null
- (b) Technologies
- (c) TECHNOLOGIES
- (d) Error

Correct answer (b)

76.How do you create a function?

- (a) function myFunction()
- (b) function:myFunction()
- (c) function=myFunction()
- (d) None of the above

Correct answer (a)

77.How do you call a function named "myFunction"?

- (a) call function myFunction
- (b) call myFunction()
- (c) myFunction()
- (d) None of the above

Correct answer (c)

78.How do you write a conditional statement for executing some code if "i" is equal to 5?

- (a) if i=5 then
- (b) if (i==5)
- (c) i==5 then
- (d) i=5

Correct answer (b)

79.How do you write a conditional statement for executing some code if "i" is NOT equal to 5?

- (a) if (i <> 5)
- (b) if != 5 then
- (c) if (i != 5)
- (d) if <>5

Correct answer (c)

80.How does a "while" loop start?

- (a) while i=1 to 10

- (b) `while (i<=10)`
- (c) `while (i;<=10;i++)`
- (d) None of the above

Correct answer (b)

81.How does a "for" loop start?

- (a) `for (i = 0; i <= 5; i++)`
- (b) `for i = 1 to 5`
- (c) `for (i = 0; i <= 5)`
- (d) `for (i <= 5; i++)`

Correct answer (a)

82.How can you add a comment in a JavaScript?

- (a) `"This is a comment`
- (b) `//This is a comment`
- (c)
- (d) None of the above

Correct answer (c)

83.What is the correct JavaScript syntax to insert a comment that has more than one line?

- (a) `/*This comment has more than one line*/`
- (b)
- (c) `/This comment has more than one line//`
- (d) None of the above

Correct answer (a)

84.What is the correct way to write a JavaScript array?

- (a) `var txt = new Array("tim","kim","jim")`
- (b) `var txt = new Array(1:"tim",2:"kim",3:"jim")`
- (c) `var txt = new Array:1=("tim")2=("kim")3=("jim")`
- (d) `var txt = new Array="tim","kim","jim"`

Correct answer (a)

85.How do you round the number 7.25, to the nearest integer?

- (a) round(7.25)
- (b) math.rnd(7.25)
- (c) rnd(7.25)
- (d) math.round(7.25)

Correct answer (d)

86.How do you find the number with the highest value of x and y?

- (a) ceil(x,y)
- (b) math.max(x,y)
- (c) top(x,y)
- (d) math.ceil(x,y)

Correct answer (b)

87.Output of the following code :

```
<script>
var temp=1, a=2,c;
do{
c=ab;
a=b;
}
while (c<20);
document.write(c);
</script>
```

- (a) 20
- (b) 21
- (c) 13
- (d) None of the above

Correct answer (c)

88.Which of following are important characteristics of an array?

- (a) Each element has same data type.
- (b) The entire array is stored contiguously in memory
- (c) Every array has to be declared before it is used
- (d) None of the above

Correct answer (a)

89. When an array is initialized during the declaration stage, known as ----- array.

- (a) Single dimension
- (b) Multi dimension
- (c) Dense
- (d) None of the above

Correct answer (c)

90. We can create an array containing -----?

- (a) String
- (b) Boolean values
- (c) Other array
- (d) Null

Correct answer (a)

91. `var Myarray=new array(1,"s2","s5", true, new array(1,2,3))`
What is the length of the array?

- (a) 4
- (b) 5
- (c) 6
- (d) 7

Correct answer (b)

92. Which of the methods declares an array of infinite length and allows you to add elements at run time?

- (a) `array name=new Array (array length)`
- (b) `array name=new Array ()`
- (c) `array name=new Array (5)`
- (d) None of the above

Correct answer (b)

93. `var myarray =new Array (1,4,3,6,10,0,22)`
`document.write(myarray.sort())`

What will be the output?

- (a) 22,10,6,4,3,1,0
- (b) 1,4,3,6,10,0,22
- (c) 6,10,22,4,3,2,1
- (d) 0,1,10,22,3,4,6

Correct answer (d)

94.Which of the following standard functions convert an array to a string?

- (a) toString()
- (b) join()
- (c) sort()
- (d) revers()

Correct answer (a)

```
95.myarray=array("Aptech","Computer","Education")
document.write(myarray[1]);
```

what will be the output?

- (a) Aptech
- (b) Computer
- (c) Education
- (d) Null

Correct answer (b)

96.Choose which are reserved words?

- (a) typeof, viod
- (b) abstract, with
- (c) debbegger
- (d) all of the above

Correct answer (d)

```
97.<script>
var temp=10;
document.write(temp++);
document.write(++temp);
</script>
```

What is the output?

- (a) 1012
- (b) 1011
- (c) 1112
- (d) None of the above

Correct answer (a)

98.JavaScript is a object based scripting language.

- (a) true
- (b) false
- (c)
- (d)

Correct answer (a)

```
99.<script>
var num=20;
var nuM=30;
document.write(num+nuM);
</script>
```

What will be the output?

- (a) 20
- (b) 30
- (c) 50
- (d) None of the above

Correct answer (c)

100.Escape sequence always begin with a bacsalash and used in document.write.

- (a) true
- (b) False
- (c)
- (d)

Correct answer (b)

101.Which of the following is incorrect declarations of variables in JavaScript.

- (a) var i,j=0;
- (b) var 8ip;
- (c) var _rahim
- (d) var i,j=0;

Correct answer (b)

102.Which of the following is not a good user for javaScript?

- (a) Implement small, simple programs.
- (b) large application development.
- (c) provided limited user interaction.
- (d) Quick development of programs.

Correct answer (a)

103.-----are those whose scope to limited within the block in which they are declared and can not be accessed from out side that particular block.

- (a) Local variable
- (b) Global variable
- (c) None
- (d)

Correct answer (a)

104.Statment1:

JavaScript is loosely typed language, does not require to specify the type of the data contained in a variable while declaring.

Statement2:

In JavaScript same variable can be used to store an integer,string or float.

- (a) Only statement 1 is true
- (b) Only statement 2 is true
- (c) both are false
- (d) both are true

Correct answer (d)

105.The statement `while(3==3)` is an example of-----?

- (a) A typographical error
- (b) an infinite loop
- (c) an illegal JavaScript statement
- (d) None of the above

Correct answer (b)

106.Which of the following object cannot be used with the `new` keyword?

- (a) Date
- (b) Math
- (c) String
- (d) None of the above

Correct answer (b)

107.What does the `prototype` keyword allow you to do in a script?

- (a) Change the syntax or JavaScript commands
- (b) Modify the dimension of built-in objects
- (c) Modify the user's browser so only your script will work
- (d) None of the above

Correct answer (b)

108.JavaScript was originally developed by---?

- (a) Netscape
- (b) Microsoft
- (c) IBM
- (d) Sun Micro System

Correct answer (c)

109.Which of the following are conditional statements?

- (a) `if else` statement
- (b) `while` statement

- (c) for statement
- (d) Break and continue statement

Correct answer (a)

110.Which of the following are looping statements?

- (a) While statement
- (b) for statement
- (c) if ... else statement
- (d) Break and continue statement

Correct answer (a&b)

111.In the do ... while statement the condition may be checked

- (a) at the beginning of a statement
- (b) at the end of a statement
- (c) at the middle of a statement
- (d) both a and b are true

Correct answer (b)

112.the substring method returns the.....?

- (a) Character of a string
- (b) The numeric value of specified string
- (c) whole string
- (d) None of the above

Correct answer (a)

113.typeof operator returns which of the following values?

- (a) Boolean
- (b) Function
- (c) Undefined
- (d) null

Correct answer (a,b)

114.'===' operator is used for which purpose?

- (a) Equality of value
- (b) Equality of type
- (c) Both a and b are true
- (d) None of the above

Correct answer (c)

```
115.var i=1, j=10;
do{
  if(i++>--j)
  {
    continue;
  }
  while(i<5);
}
document.write("i="+i+"and j="+j);
```

What is the result?

- (a) i=6 and j=5
- (b) i=5 and j=5
- (c) i=6 and j=6
- (d) i=5 and j=6

Correct answer (d)

```
116.<script>
var a=2;
switch(a)
{
  case 1: document.write("jan");
  break;
  case 2: document.write("feb");
  default:
  case 1: document.write("out of range");
}

</script>
```

Wha will be the output?

- (a) jan
- (b) feb
- (c) feb, out of range
- (d) error

Correct answer (c)

117.The process of dealing errors in a script or program is known as.....?

- (a) Error detection
- (b) frustration
- (c) debugging
- (d) None of the above

Correct answer (c)

118.The code execute in response to an event is called an or?

- (a) Event handler, Message handler
- (b) Array, Function
- (c) Calling a function called function
- (d) None of the above

Correct answer (c)

119.Which of the following are advantages of function?

- (a) Code can be altered without affecting other parts of the program.
- (b) Ease of understand
- (c) Save memory space
- (d) All

Correct answer (d)

120.Function parameter are also referred as-----?

- (a) Index
- (b) Argument
- (c) String
- (d) None of the above

Correct answer (b)

121.When does the onLoad event handler execute?

- (a) When an image is finished loading
- (b) When the page and all of its images are finished.
- (c) When user attempt to load another page.

(d) None of the above

Correct answer (a)

122. Which of the following objects can be used to load a new URL into the browser window?

(a) document.url

(b) document.write

(c) window.url

(d) window.location

Correct answer (d)

123. Which of the following methods opens a dialog box with OK and Cancel buttons and waits for a response?

(a) window.alert

(b) window.confirm

(c) window.prompt

(d) None of the above

Correct answer (b)

124. When creating rollovers which HTML should include the onMouseOver event handler?

(a)

(b)

(c)

(d) None of the above

Correct answer (c)

125. What can javascript do with forms that CGI script can't?

(a) Cause all sorts of problem

(b) Submit the data to a browser

(c) Gives the user instant feedback about errors.

(d) All

Correct answer (b)

126.To go to the next page, which of the following is right syntax

- (a) window.history.forward()
- (b) window.history.back()
- (c) window.history.go(1)
- (d) window.history.go(-1)

Correct answer (a,c)

127.To open an additional window which is the possible syntax?

- (a) window.open
- (b) self.open
- (c) window.open()
- (d) addition.open

Correct answer (c)

128.Which of the following is executed first by a browser?

- (a) Script in the head section
- (b) Script in the body section
- (c) An even handler for a button
- (d) None of the above

Correct answer (a)

129.Which of the following object can not be used with the new key word?

- (a) date
- (b) math
- (c) string
- (d) None of the above

Correct answer (b)

131.What dose the <noscript> tag to do?

- (a) Enclose text to be displayed by non-javascript browser.
- (b) Prevents script on the page from executing.
- (c) Describes certain low-budget movies.
- (d) None of the above.

Correct answer (a)

132.Which feature of new browsers allows you to use javascript?

- (a) HTML 4.0
- (b) HTML 0.4
- (c) CSS2 .0
- (d) The DOM

Correct answer (a)

133.Which of the following DOM objects never has a parent node?

- (a) body
- (b) div
- (c) document
- (d) None of the above

Correct answer (c)

134.Javascript can access database?

- (a) true
- (b) false
- (c)
- (d)

Correct answer (a)

135.What dose the break statement do?

- (a) exit from form
- (b) starts the loop over
- (c) escape the loop entirely
- (d) None of the above

Correct answer (c)

136.Which is the static object?

- (a) date
- (b) string
- (c) math

(d) None

Correct answer (b)

137.How do you put a message in the browsers status bar?

(a) status ("put you message")

(b) window.status ="put you message here";

(c) statusbur="put you message"

(d) status ="put you message"

Correct answer (b)

138.How do you find the clients browsers name?

(a) client.navName

(b) navigator.appName

(c) browser.name

(d) None of the above

Correct answer (b)

139.After evaluating the element

```
var x="25"+250;
```

x will have the value....?

(a) "25250"

(b) 25250

(c) "275"

(d) 275

Correct answer (b)

140.<script language "javascript">

```
var i=5;
```

```
while(true)
```

```
{
```

```
document.write("dhaka");
```

```
break;
```

```
}
```

```
</script>
```

What is the result?

- (a) Error
- (b) infinitive loop
- (c) print dhaka only once
- (d) None of the above

Correct answer (c)

141.To load a new URL?

- (a) document.url
- (b) window.location
- (c) window.history
- (d) b and c

Correct answer (b)

142.Which of the following is correct event handler to detect mouse click

- (a) onCommand
- (b) onLink
- (c) onMouseup
- (d) onClick

Correct answer (d)

```
143.var x=3;
var y=1;
if(x=y)
{
    document.write("x="+x);
}
```

What is the result?

- (a) x=1
- (b) x=3
- (c) The code runs with no output
- (d) error

Correct answer (a)

```
144.<script>
var i=0;
```

```
for(i;i<4;i+=2)
{
    document.write(i+"");
}
document.write(i);
</script>
```

what will be the output?

- (a) 0 2 4
- (b) 0 2 4 5
- (c) 0 1 2 3 4
- (d) Error

Correct answer (a)

```
145.<script>
for(i=0;i<3;i++)
{
    switch(i)
    {
        Case 0: break;
        Case 1: document.write("one");
        Case 2: document.write("two");
        Case 3: document.write("three");
    }
}
```

```
document.write("done");
What is the result?
```

```
</script>
```

- (a) done
- (b) one two done
- (c) one two three two three done
- (d) compilation fails

Correct answer (c)

```
146.public void test (int x)
{
    int odd=x%2;
    if(odd)
    {
        document.write("even");
    }
}
```

Which statement is true?

- (a) Error
- (b) "odd" will always be output
- (c) "even" will always be output
- (d) b and c

Correct answer (a)

```
147. var i=0;
while(true)
{
    if(i==4)
    {
        break;
    }
    --i;
}
document.write("i="+i);
```

- (a) 3
- (b) 4
- (c) 5
- (d) error /infinite loop

Correct answer (d)

148. <script language="javascript">

```
var a='TCL';
var b=a.toLowerCase();
b.concat('dhaka');
document.write(b);
```

</script>

What will be the output?

- (a) tcl
- (b) dhaka
- (c) tcldhaka
- (d) TCL

Correct answer (a)

149. Which is a valid identifier?

- (a) false
- (b) default
- (c) object
- (d) a class

Correct answer (c)

150.The syntax of the charAt()method is.....?

- (a) charAt(string index position ending index position)
- (b) charAt(string index position e)
- (c) charAt(ending index position)
- (d) All of the above

Correct answer (b)

151.Which of the following are not true?

- (a) When a function is called from within a program, the control(flow at the program) is transferred to the function.
- (b) a function can not be used another function.
- (c) standard function van be used user define function.
- (d) after the last statement of the function is executed, the control is transferred back to the calling program,to the statement of the function call.

Correct answer (b)

152.-----is a popular data-encryption package

- (a) mhash
- (b) md5
- (c) MCrypt
- (d) All of the above

Correct answer (c)