


Table of contents

- Introduction
- TOPIC 1: Electrostatic Discharge Tools
- TOPIC 2: Hand Tools
- TOPIC 3: Cleaning Tools
- TOPIC 4: Diagnostic Tools

Introduction



Most tools used in computer system servicing are hand tools. These can be part of a computer repair toolkit as well. In this lesson, you will learn about the common hand tools and equipment that you will be using especially in handling computer equipment such as disassembly/assembly of a computer, as well as repair and maintenance.

TOPIC 1: Electrostatic Discharge Tools

*When working with electronic equipment, it is important to make sure that there is **no static electricity** to avoid damage of computer parts.*

Static electricity can be easily generated by friction on carpets, clothing, hair, fabric, flooring, etc.

Thus, these tools should be utilized:

Anti-static wrist wrap

Worn to prevent ESD damage to computer hardware



Anti-static mat

Used to stand on or place tools to prevent buildup of static electricity.



Photo Courtesy of [ndcillano](#)

TOPIC 2: Hand Tools

TOPIC 3: Cleaning Tools

Lint-free cloth

For cleaning computer parts without leaving marks or scratches.



Compressed air

For clearing or blowing away dust from computer parts.



Cable Ties

Used to organize and bundle cable together.



Parts organizer


For holding and organizing screws and other small computer parts.



TOPIC 4: Diagnostic Tools


Digital Multimeter

A tool that can be used to measure amps, volts, and ohms. It can test the integrity of circuits and the quality of electricity in computer components. Information is flashed on the screen.



Loopback Adapter

Also called as loopback plug. This tool tests the basic functionality of computer ports. The adapter is specific to the port that you want to test.



Toner Probe

A two-part tool that generates a tone that travels the length of the cable. The toner part is attached to a cable at one end using specific adapters, such as RJ-45, coaxial, or metal clips. When the probe is near to the cable where the toner is attached, a tone can be heard from the speaker.

