

Software Engineering in Industrial Practice (SEIP)

Dr. Ralf S. Engelschall

ENGINEERING FUNDAMENTALS

Modern Software Specification

TECHNISCHE UNIVERSITÄT MÜNCHEN

SpecBook

Hierarchical Object Model
Versatile Object to Markdown Mapping
Wiki-Style Object Linking

Strict Validation with Custom Schema
Object Model Diagram Visualisation
CLI, MCP, and API Interface

AST Exports for AI/LLMs
HTML Export for Developers
PDF Export for Customers

SpecBook **SCHEMA Model** (YAML)

```yaml
- kind: META
  name: Title
  file: sample.md
  props:
    - name: TITLE
      desc: The title of the specification.
    - name: SUBTITLE
      desc: The subtitle of the specification.
      optional: true
- kind: SPEC
  name: Data Model
  file: sample.md
  id: DM
  desc: >
    The structure of named entities, with named attributes and directed relationships,
    of the data the solution manages, defining how information is organized and connected.
  diagram:
    type: graph
    nodes: "[[SPEC:DM.ENTITY:*]]"
    edges: "[[SPEC:DM.ENTITY:*.RELATION:*]]"
    config:
      size-node-height-scale:  8
      size-edge-port-gap:      60
      graph-node-degree-max:   4
      graph-channel-width-max: 300
      graph-channel-width-min: 300
  childs:
    - kind: ENTITY
      name: "[A-Z][a-zA-Z0-9]*"
      desc: >
        A named entity of the data model, carrying a Pascal-cased, 1-3 word long,
        per-artifact unique name, and described by a 1-sentence description ("what")
        plus a 1-sentence rationale ("why").
      diagram:
        type: hub
        center: self
        nodes: "[[SPEC:DM.ENTITY:*]]"
        edges: "[[SPEC:DM.ENTITY:*.RELATION:*]]"
        config:
          size-node-width-max: 440
      childs:
        - kind: ATTRIBUTE
          name: "[a-z][a-zA-Z0-9]*"
          desc: >
            A named attribute of the entity, carrying a camel-cased, 1-3 word long,
            per-entity unique identifier, and described by a 1-sentence description
            ("what") plus a 1-sentence rationale ("why").
          props:
            - name: TYPE
              desc: >
                The type of the entity attribute, one of `boolean`, `string`,
                `integer`, `float`, `uuid`, `bytes`, `date`, `time`, `datetime`, or
                `enum(XXX,YYY[,...])`, optionally prefixed with the qualifier
                `unique` to indicate inclusion into the primary key of the entity,
                and optionally suffixed with `?` to indicate an optional (nullable)
                value.
              value: /^(?:unique\s+)?(?:boolean|string|integer|float|uuid|datetime|enum)$/
            - name: DEFAULT
              desc: The default value of the entity attribute.
              value: /.*/
              optional: true
        - kind: RELATION
          name: "[a-z][a-zA-Z0-9]*"
          desc: >
            A named directed relation of the entity, carrying a camel-cased, 1-3 word
            long, per-entity unique identifier and targeting another entity, and
            described by a 1-sentence description ("what") plus a 1-sentence rationale
            ("why").
          optional: true
          props:
            - name: TYPE
              desc: Reference to the DATA-MODEL entity the directed relation targets.
              value: "[[SPEC:DM.ENTITY:*]]"
            - name: ARITY
              desc: >
                The arity (cardinality) of the relation at the target entity: `0..1`
                or `?` for zero or one ("optional"), `1` for exactly one
                ("mandatory"), `0..n` or `*` for zero or more, `1..n` or `+` for one
                or more, or `{n}`/`{n,m}` for an exact number or range.
              value: /^(?:\?|\*|\+|\{\d+(?:,\d+)?\}|1|0\.\.1|0\.\.n|1\.\.n)$/
              optional: true
```

SpecBook **SPEC Model** (Markdown)

```
---
Created:  2026-08-23 00:15
Modified: 2026-08-23 13:03
---

META: Title
==========

-   TITLE:____Sample
-   SUBTITLE: Sample Specification

SPEC: Data Model (DM)
=====================

ENTITY: Unit
------------

An organizational unit of the enterprise, BECAUSE the organization is
structured into nested units which group the people working in them.

-   ATTRIBUTE: id; TYPE: `unique uuid`; DEFAULT: `uuid()`;
    Unique identifier of the unit, BECAUSE every unit needs a stable
    handle independent of its name.

-   ATTRIBUTE: name; TYPE: `string`;
    Full name of the unit, BECAUSE the unit is addressed by a
    human-readable label.

-   ATTRIBUTE: abbreviation; TYPE: `string`;
    Short form of the unit name, BECAUSE compact renderings like org
    charts have no room for the full name.

-   RELATION: parentUnit; TYPE: [[ENTITY:Unit]]; ARITY: `0..1`;
    The unit this unit is nested in, BECAUSE the units form a hierarchy
    whose top-most unit has no parent.

-   RELATION: members; TYPE: [[ENTITY:Person]]; ARITY: `0..n`;
    The people assigned to this unit, BECAUSE a unit is staffed by an
    arbitrary number of people.

-   RELATION: director; TYPE: [[ENTITY:Person]]; ARITY: `0..1`;
    The person heading this unit, BECAUSE a unit has at most one
    accountable lead.

ENTITY: Person
--------------

An individual person working in the organization, BECAUSE the
organization is staffed by people who are assigned to its units.

-   ATTRIBUTE: id; TYPE: `unique uuid`; DEFAULT: `uuid()`;
    Unique identifier of the person, BECAUSE names are neither stable
    nor unique across the organization.

-   ATTRIBUTE: name; TYPE: `string`;
    Full name of the person, BECAUSE people are addressed by their
    human-readable name.


-   ATTRIBUTE: initials; TYPE: `string`;
    Short form of the person name, BECAUSE compact renderings like org
    charts have no room for the full name.

-   ATTRIBUTE: role; TYPE: `string`;
    Job role of the person, BECAUSE the responsibility of a person has
    to be visible beside their unit assignment.

-   RELATION: belongsTo; TYPE: [[ENTITY:Unit]]; ARITY: `0..1`;
    The unit this person is assigned to, BECAUSE a person works in at
    most one unit at a time.

-   RELATION: supervisor; TYPE: [[ENTITY:Person]]; ARITY: `0..1`;
    The person this person reports to, BECAUSE the reporting lines form
    a hierarchy whose top-most person has no supervisor.
```

SpecBook **SPEC Export** (AST, HTML, PDF)



01 ● **SPEC: Data Model** (DM)

01.01 ● **ENTITY: Unit**

An organizational unit of the enterprise — **BECAUSE** the organization is structured into nested units which group the people working in them.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
id	unique uuid	uuid()	Unique identifier of the unit — **BECAUSE** every unit needs a stable handle independent of its name
name	string		Full name of the unit — **BECAUSE** the unit is addressed by a human-readable label
abbreviation	string		Short form of the unit name — **BECAUSE** compact renderings like org charts have no room for the full name

● RELATION	○ TYPE	○ ARITY	Description
parentUnit	● ENTITY: Unit	0..1	The unit this unit is nested in — **BECAUSE** the units form a hierarchy whose top-most unit has no parent
members	● ENTITY: Person	0..n	The people assigned to this unit — **BECAUSE** a unit is staffed by an arbitrary number of people
director	● ENTITY: Person	0..1	The person heading this unit — **BECAUSE** a unit has at most one accountable lead

01.02 ● **ENTITY: Person**

An individual person working in the organization — **BECAUSE** the organization is staffed by people who are assigned to its units.

● ATTRIBUTE	○ TYPE	○ DEFAULT	Description
id	unique uuid	uuid()	Unique identifier of the person — **BECAUSE** names are neither stable nor unique across the organization
name	string		Full name of the person — **BECAUSE** people are addressed by their human-readable name
initials	string		Short form of the person name — **BECAUSE** compact renderings like org charts have no room for the full name
role	string		Job role of the person — **BECAUSE** the responsibility of a person has to be visible beside their unit assignment

● RELATION	○ TYPE	○ ARITY	Description
belongsTo	● ENTITY: Unit	0..1	The unit this person is assigned to — **BECAUSE** a person works in at most one unit at a time
supervisor	● ENTITY: Person	0..1	The person this person reports to — **BECAUSE** the reporting lines form a hierarchy whose top-most person has no supervisor

EF 02.6

Intellectual Content: Version 1.0.0 (2026-10-28), Authored 2026 by Dr. Ralf S. Engelschall
Graphical Illustration: Version 1.0.0 (2026-10-28), Copyright © 2026 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved.
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.


artifacts & modeling

ENGINEERING FUNDAMENTALS

Software Engineering Efforts

TECHNISCHE UNIVERSITÄT MÜNCHEN

Software **products** follow a **life-cycle** of seven temporal, non-equally sized **phases**. Software Engineering **disciplines** individually focus their **efforts** on those phases and their efforts either bottom-up depend on the domain-specific **scope** or top-down do not depend on it. The amount of required **human resources** differs between those phases, too. Effort **estimations** have to take disciplines, their phase focus, their domain-specific scope dependency, and the human resource **staffing curve** into account.




EF 03.1

Intellectual Content: Version 1.0.4 (2022-08-11) Authored 2021-2022 by Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Graphical Illustration: Version 1.0.1 (2021-09-11) Copyright © 2021 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

phases & efforts

Uncertainty & Elaboration

Cone of Uncertainty



The ***Cone of Uncertainty*** (*Steve McConnell*, 2006) tells how the variability of the project scope (measured in Effort, Cost or Features) in Software Development changes over time. Initially, it usually is within the range of +/- 400% of the final scope.

The early development phases Inception and Elaboration especially have to ensure that within the first 20% of the project, the variability is reduced noticeably to just +/- 50%. During the initial iterations of the Construction phase within the first 30% of the project, the variability usually can be further reduced to about +/- 25%.

For iterative/agile approaches, experience showed that during the Construction phase inherently the final scope further shifts by about + 40% due to the just step-by-step learned required details of the required solution. This especially has to be taken into account for estimations.


Essential Elaboration Phase

Walking Skeleton:

The ***Walking Skeleton*** (or *Technical Breakthrough*) is the design and implementation of the bare technical foundation of an application, still *without* any domain-specific functionalities. It is made during the Elaboration phase with the primary purpose to establish a stable integration of all technical aspects (libraries, frameworks, build procedures, etc) onto which the domain-specific functionalities later can be successively put onto.



Agile Fixed-Price Contracts:



The ***Agile Fixed-Price*** is an agile variant of a fixed-price contract, *not* a fixed-price project with an agile development process.



There are two important inherent aspects:

First, the contract contains two types of conditions: one (usually *Time & Material* but fixed duration based) for the Inception and Elaboration phases in order to make experiences and to gather necessary figures, and one (usually Fixed-User-Story and/or Fixed-Price based) for the Construction and Transition phases based on deferred estimated figures, gathered in the Elaboration phase.

Second, the Fixed-Price aspect of the contract is actually based on an amount of User-Stories (resulting in costs by multiplying them with either an average hourly rate of an engineer or individual rates based on engineer job levels), which the customer can 1:1 *exchange* during the project for different deliverables.

The crux of an Agile Fixed-Price contract is: first, during the Inception and Elaboration phases the supplier can shrink the *Cone of Uncertainty* and this way its risks dramatically, and second, during the Construction and Transition phases the customer still remains flexible in scope.

Intellectual Content: Version 1.0.2 (2022-10-10), Authored 2021-2020 by Dr. Ralf S. Engelschall based on concepts from Steve McConnell
Graphical Illustration: Version 1.0.1 (2023-10-10), Copyright © 2021-2020 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

ENGINEERING FUNDAMENTALS

Effort Estimations

TECHNISCHE UNIVERSITÄT MÜNCHEN

Estimation & Variability

Three-Point Estimation and Estimation Variability Classes:

$e = (b + 4 \times m + w) / 6$	expected effort (weighted average)
$s = (w - b) / 6$	standard deviation (effort variation)

b: best-case (optimistic)
m: most-likely (realistic)
w: worst-case (pessimistic)

Insane Variability: +/- 10%
Very Good Variability: +/- 15%
Good Variability: +/- 20%
Acceptable Variability: +/- 25%




Conversion & Normalization

1. Ask Estimater:
"How many Person-Days do you need when you can focus on this task?"

2. Convert from Estimator to Performer:
(see also CAP model, http://cap-model.com)

Estimator \ Performer	Novice (Non-Linear Effort Reduction 0%)	Practitioner (10%)	Master (25%)	Expert (45%)	Guru (80%)
Novice	1,00	0,90	0,75	0,55	0,20
Practitioner	1,11	1,00	0,83	0,61	0,22
Master	1,33	1,20	1,00	0,73	0,27
Expert	1,82	1,64	1,36	1,00	0,36
Guru	5,00	4,50	3,75	2,75	1,00




Sizes & Variability

Estimation Sizes and Estimation Variability:

T-Shirt-Size (Logically)	XXS	XS	S	M	L	XL	XXL	XXXL
Fibonacci-Size (PD or SP)	**0,50**	**1**	**2**	**3**	**5**	**8**	**13**	**21**
Size Variability (-)	0,25	0,25	0,50	0,50	1,00	1,50	2,50	4,00
Size Variability (+)	0,25	0,50	0,50	1,00	1,50	2,50	4,00	8,00

Notice: Estimations can be done in *Person-Days (PD)* or *Story-Points (SP)*. In both cases, keep in mind to use something like the *Fibonacci* numbers which increase in a non-linear fashion and express the increasing variability with the increasing total amount of estimated effort.



Risk Mitigation & Upscaling

3. Adjust for Reality:
Estimator Optimism: **+30%**
Performer Meetings: **+20%**

4. Adjust for Uncertainty:

Domain	Inception	Elaboration	Construction
unknown	30%	40%	20%
partially known	15%	20%	10%
fully known	0%	0%	0%

Technology	Inception	Elaboration	Construction
unknown	20%	60%	10%
partially known	10%	30%	5%
fully known	0%	0%	0%

Process	Inception	Elaboration	Construction
unknown	60%	40%	10%
partially known	30%	20%	5%
fully known	0%	0%	0%

People	Inception	Elaboration	Construction
unknown	60%	40%	0%
partially known	30%	20%	0%
fully known	0%	0%	0%



Intellectual Content: Version 1.0.1 (2022-10-10), Authored 2021-2022 by Dr. Ralf S. Engelschall based on concepts from Steve McDonnell
Graphical Illustration: Version 1.0.1 (2022-10-10), Copyright © 2021-2022 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

ENGINEERING FUNDAMENTALS

Agentic Software Engineering

TECHNISCHE UNIVERSITÄT MÜNCHEN

EF 05.1

SW Software 1

The collection of programs (instructions) and their associated data that make a computer perform tasks. In contrast to hardware, it is intangible and can be changed, copied, and distributed without altering the physical machine.

SA Software Agent 2

Software that acts autonomously on behalf of a user or another program to achieve delegated goals. Exhibits reactivity (responds to environment), proactivity (goal-directed initiative), and social ability (interacts with other agents/users). Perceives its environment via sensors/inputs (APIs, files, messages, events) and acts via actuators/outputs (commands, calls, messages).

EN Engineering 3

The systematic application of scientific and technological knowledge, principles, approaches, practices, methods, and experiences to design, build, operate, and maintain solutions, up to complex production-grade ones, through a traceable process.

SE Software Engineering 4

The application of **Engineering** to the development, operation, and maintenance of **Software**.

AI Artificial Intelligence 5

The field of Computer Science focusing on building systems that perform tasks normally requiring human intelligence: perception, reasoning, learning, planning, decision-making, and language understanding. It spans Symbolic AI (rules, logic, search) and Machine Learning (including Deep Learning and Generative AI such as LLMs and diffusion models), ranging from narrow, task-specific AI to Artificial General Intelligence (AGI).

AH Agent Harness 6

The **Software** that surrounds an AI model and turns it from a passive, predicting model into an acting **Software Agent**. It implements a control loop (e.g. ReAct or Plan-and-Execute) that sends context to the model, executes the requested actions, and feeds results back, and it supplies the tools (sensors and actuators), context management, and guardrails. The model decides what to do; the harness determines what it can do and how.

AG AI Agent 7

A **Software Agent** formed by an AI model (typically an Large Language Model, LLM) as its reasoning core, operated by an **Agent Harness**.

AA Agentic AI 8

The paradigm of building AI systems out of one or more **AI Agents** that perceive, plan, decide, act, and adapt to pursue high-level, long-horizon goals with a high degree of autonomy, typically coordinated through task decomposition, orchestration, and shared context. Unlike purely generative (prompt-response) AI, its systems take actions in the world (call APIs, run code, edit files, browse the web).

AS Agentic Software Engineering 9

Software Engineering following the **Agentic AI** paradigm, in which **AI Agents** perform multi-step tasks across the software development lifecycle, within a traceable process. Goes beyond inline code completion and chat assistants. Engineers shift toward goal specification, oversight, review, and governance, with human-in-the-loop gates.

concepts & relationships

Intellectual Content: Version 1.0.0 (2026-10-28), Authored 2026 by Dr. Ralf S. Engelschall
Graphical Illustration: Version 1.0.0 (2026-10-28), Copyright © 2026 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

ENGINEERING FUNDAMENTALS

Agentic Modus Operandi

TECHNISCHE UNIVERSITÄT MÜNCHEN

Intellectual Content: Version 1.0.0 (2026-10-28), Authored 2026 by Dr. Ralf S. Engelschall
Graphical Illustration: Version 1.0.0 (2026-10-28), Copyright © 2026 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

Actor	HUMAN ⟶ AI AGENT				
Modus Operandi	⟵ - - - ⟵ ■■■ ⟶				
Level	0 manually	1 assisted	2 supervised	3 delegated	4 autonomous
View	white	grey / light	grey	grey / dark	black
Objective	none	step	task	workflow	lifecycle
Think	self	assistant	co-worker	offshoring	3rd-party
Solution	life-critical	safety-related	mission-critical	business-supporting	non-critical
Productivity	costs ⟶ efficiency				
Knowledge	do-it-yourself ⟶ reviewing				
Traceability	do-it-yourself ⟶ evidence				
Briefing	do-it-yourself ⟶ specification				

Agentic Briefing

Intellectual Content: Version 1.0.0 (2026-10-28), Authored 2026 by Dr. Ralf S. Engelschall
Graphical Illustration: Version 1.0.0 (2026-10-28), Copyright © 2026 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved.
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

● ⧉ **ASE:** GRILLING: *Relentless Interviewing Until Clarity*

QUESTION	ANSWERS
1 ▶ DOM ▷ Purpose: Shall `ase hello` be a permanent, user-facing command of the CLI, or only a hidden demo/smoke-test command?	**A ▶ Public ⚑:** listed in `ase --help` like all others **B ▶ Hidden:** works, but omitted from help output
2 ▶ IFC ▷ Color Detection: Shall red be emitted only if stdout is a terminal (honoring `NO_COLOR`/`FORCE_COLOR`), or always as ANSI sequences?	**A ▶ Auto-detect:** chalk default, plain text on pipes **B ▶ Forced:** always ANSI red, like `ase statusline`
3 ▶ IFC ▷ Arguments: Shall `ase hello` take no options/arguments at all, or an optional `name` replacing `World`?	**A ▶ None ⚑:** fixed text `Hello World!` **B ▶ Name:** `ase hello [name]`, default `World`
4 ▶ IFC ▷ Documentation: Shall the command get a man page `tool/man/ase-hello.md` plus entries in `tool/man/ase.md`, `AGENTS.md`, and `CHANGELOG.md`?	**A ▶ Full:** man page plus all listings **B ▶ Partial:** man page and `CHANGELOG.md` o… **C ▶ Minimal:** `CHANGELOG.md` entry only
5 ▶ IFC ▷ Style: Shall the text be plain red, or bold red like the `error` log tag?	**A ▶ Plain red ⚑:** `chalk.red` **B ▶ Bold red:** `chalk.red.bold`, as for err…
6 ▶ ARC ▷ Placement: Should the command live in a new module `tool/src/ase-hello.ts` (class `HelloCommand`), lazily registered in `commands` of `tool/src/ase.ts`?	**A ▶ New module:** mirrors `ase-man.ts`, lazy **B ▶ Inline:** registered directly in `ase.t…`
7 ▶ IMP ▷ Coloring: May the coloring use the existing `chalk` dependency instead of raw ANSI escape sequences?	**A ▶ chalk:** existing dependency, TTY dete… **B ▶ Raw ANSI:** `\x1b[31m...\x1b[0m`, no imp…
8 ▶ IMP ▷ Output: May the greeting be written via `writeStdout` of `ase-lib-stdio.ts`, so `process.exit` cannot truncate it?	**A ▶ writeStdout:** flushed before exit, co… **B ▶ console.log:** simpler, may truncate o…

Legend: **DOM:** Domain (MUST) **IFC:** Interface (MUST) **n:** round-local question number
ARC: Architecture (SHOULD) **IMP:** Implementation (MAY) **X:** question-local answer letter
REG: Regression (SHOULD) **CON:** Confirmation (SHOULD) **⚑:** current decision state

(⧉ ASE: DIALOG: GRILLING)

What is your (combined) answer to all (or a subset) of the above questions?
(keywords or nX short responses are sufficient)

❶ ▶ SKIP GRILLING: skip all remaining grilling and continue with the implementation
❷ ▶ STOP SKILL: stop the entire skill immediately

Please choose *one* option by typing **❶/❷/CANCEL**, or any other free-text instruction.

(⧉ ASE: DIALOG: GRILLING)

✻ Worked for 1m 23s · done 19:04

new task? /clear to s…

❯ 1A 2A 3B 4B 5A

※ user: rse ⚑ project: tool ◉ task: default ⏻ session: fafc0070-32be-41db-b9e7-99373ae8fe7e
⚙ model: Opus 5.5 ⚒ effort: high ✳ thinking: yes ◔ context: ▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓▓ 12%
⏲ 5h-usage: – ⏱ 5h-resets: – ⏲ 7d-usage: 20.0% ⏱ 7d-resets: 2d 14hr 49m
▶ cwd: /Users/rse/Work/ase/master/tool ⎇ branch: master ± changed: +7/-2 ?! untracked: 4
☯ persona: engineer ≡ style: ase:ase-terse ▶ guidance: minimal ▢ boxing: grey
▸▸ auto mode on (shift+tab to cycle)

⏸ claudeX ※ rse ⚑ ase-master

Brief Engineering: The systematic specification of a delegated assignment for an AI agent: goals, scope, constraints, acceptance criteria, and safety boundaries. It defines *what* must be achieved and how success is verified, so an agent can work autonomously across long-horizon tasks and deliver traceable evidence.

≡ color-output Colorize CLI Output on Terminals 5 - Done ▷ INTEGRATED

predecessors: ≡ hello3 successors: —

0 ▸ plan 1

Id: color-output
Created: 2026-08-03 00:21
Modified: 2026-09-13 19:49
After: hello3
Status: INTEGRATED
Kind: CRAFTING
Tags: grilled:true

TASK: Colorize CLI Output on Terminals

SPECIFICATION (WHAT)

- ☐ DOM: **Hello Command**: Add a new top-level CLI command `ase hello` which prints exactly `Hello World` (no punctuation, no version suffix) to the terminal in *red* color, plus a companion `ase_hello` MCP tool.
- ☐ DOM: **Smoke Test**: Provides a minimal, self-contained *smoke-test* command for verifying that the `ase` binary is installed, executable, and able to emit colored terminal output, and that the MCP bridge is reachable from a skill without a Bash tool.
- ☐ IFC: **CLI Surface**: `ase hello` takes *no* arguments and *no* options beyond the standard `--help`, prints `Hello World` followed by a trailing newline, colored *red* on a TTY and *plain* when piped into a file.
- ☐ IFC: **MCP Surface**: The `ase_hello` MCP tool is *argument-less* and returns the plain, un-colored text `Hello World` as its `text` content.
- ☐ IFC: **Documentation**: Add an `ase hello` bullet point to the `COMMANDS` section of `docs/usage-tool.md`, in the style of the existing `ase compat` entry and introduced by its own lead-in sentence.
- ☐ IFC: **ChangeLog**: Add a `FEATURE [code]` bullet point announcing the new `ase hello` command and `ase_hello` MCP tool to the topmost section of `CHANGELOG.md`, matching its existing style and category conventions.

DESIGN (HOW)

- ☐ ARC: **Single Module**: Create `tool/src/ase-hello.ts` as the *sole* new module, carrying both the CLI and the MCP surface, so the greeting text lives in *one* shared constant `GREETING = "Hello World"` and cannot drift between the two surfaces.
- ☐ ARC: **Command Class**: Export a default `HelloCommand` class with a `register (program: Command): void` method mirroring `CompatCommand` in `tool/src/ase-compat.ts`: it registers `program.command("hello")` with a short description and an async action, and takes *no* `Log` dependency.
- ☐ ARC: **MCP Class**: Export a named `HelloMCP` class with a `register (mcp: McpServer): void` method mirroring `CompatMCP`, registering the tool `ase_hello` via `mcp.registerTool(...)` with an *empty* `inputSchema`, a title, and a description.

← / → / ⇤ / ⇥ switches tab · ↑ / ↓ / ⇞ / ⇟ scrolls · e edits · E edits by prompt · R requests by prompt · T transitions · A assigns · D deletes · ↵ / ESC closes


Prompt Engineering: The craft of formulating individual inputs (prompts) to an AI model so that a single request reliably produces the desired output. It focuses on phrasing, structure, examples, and instructions within one prompt–response exchange.

Context Engineering: The systematic design and management of everything an AI model sees while it works: instructions, retrieved knowledge, tool definitions and results, memory, and conversation history. It decides what goes into the limited context window at each step of an agent's control loop, usually handled by the Agent Harness.

Agentic Workflow

The usual workflow in Agentic Software Engineering is built around three primary artifacts: **Tasks** (aka user stories), which brief both humans and AI agents about individual changes; the **Specification**, a binding and coherent description of the WHAT and HOW that serves as the Single Source of Truth; and the **Code**, which implements the WHAT and HOW.

The dominant paradigm is usually **Spec-Driven Development (SDD)**, but it comes in two approaches with different points of view: on the one hand, the set of Tasks incrementally forms the Specification and drives the implementation; on the other hand, the Specification artifact is crafted incrementally and drives the Code implementation itself. In practice, both SDD approaches are combined: Tasks specify how both the Specification and the Code are incrementally extended.




	Ad-Hoc Mode (Standard)	Direct Mode	Plan Mode (Standard)	Task Mode	Sync Mode
Direct Instruction	X	X			
Intention Grilling		X		X	
Tenet-Driven		X	X	X	X
Deferred Execution			X	X	X
Plan Refinement			X	X	X
Parallel Plans				X	
Cross-Session Plans				X	X
Use-Case Steering		X		X	
Solution Approach Choices		X		X	


Intellectual Content: Version 1.0.0 (2026-10-28), Authored 2026 by Dr. Ralf S. Engelschall
Graphical Illustration: Version 1.0.0 (2026-10-28), Copyright © 2026 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.


ENGINEERING FUNDAMENTALS


Agentic Development Pipeline


TECHNISCHE UNIVERSITÄT MÜNCHEN











EF 05.5

Intellectual Content: Version 1.0.0 (2026-10-28), Authored 2026 by Dr. Ralf S. Engelschall
Graphical Illustration: Version 1.0.0 (2026-10-28), Copyright © 2026 Dr. Ralf S. Engelschall <http://engelschall.com> All Rights Reserved
Unauthorized Reproduction Prohibited. Licensed to Technische Universität München (TUM) for reproduction in Computer Science lecture contexts only.

tasks & states