Note and Formula of DDA4210

softstar

February 17, 2026

1 Lec1: introduction

There are no formulas in Lecture 1. Good luck with the rest!

2 Lec2: Advanced Ensemble Learning

2.1 Gradient Boosting:

Boosting is an ensemble technique that combines multiple weak learners to create a strong learner. The main idea is to train models sequentially, with each model focusing on the errors made by the previous ones. (用人话说，就是一波接一波地训练模型，每一波都专注于纠正前一波的错误，从而逐步提升整体的预测能力。)

- **Final Model:**

$$H_T(\mathbf{x}) = \sum_{t=1}^{T} \alpha_t h_t(\mathbf{x})$$

    - The weighted sum of all weak learners(加权和).
    - $H_T(\mathbf{x})$ is the final model after T rounds.
    - $h_t(\mathbf{x})$ is the t-th weak learner.
    - α_t is the weight of the t-th weak learner.

- **Loss Function:**

$$\mathcal{L}(H) := \frac{1}{n} \sum_{i=1}^{n} \ell(H(\mathbf{x}_i), y_i)$$

    - **Each Step:** We want to add a function h to minimize the loss as fast as possible. Using first-order Taylor expansion(一阶泰勒展开):

    $$\mathcal{L}(H + \alpha h) \approx \mathcal{L}(H) + \alpha \langle \nabla \mathcal{L}(H), h \rangle$$

    - **Find h:** Minimize $\langle \nabla \mathcal{L}(H), h \rangle$, i.e.:

    $$h = \arg\min_{h \in \mathbb{H}} \sum_{i=1}^{n} \frac{\partial \mathcal{L}}{\partial [H(\mathbf{x}_i)]} h(\mathbf{x}_i)$$

        * Here $\frac{\partial \mathcal{L}}{\partial [H(\mathbf{x}_i)]}$ is the gradient of the loss function w.r.t. the current model's output on the i-th sample.

∗ We train h to fit these **negative gradients(负梯度)**.

- **GBR with squared error loss:** For regression tasks with squared error loss:

$$\ell(H(\mathbf{x}_i), y_i) = \sum_{i=1}^{n} (y_i - H(\mathbf{x}_i))^2$$

  – Solve $h_{t+1} = \arg\min_{h \in \mathbb{H}} \sum_{i=1}^{n} q_i h(\mathbf{x}_i)$, where $q_i = \frac{\partial \mathcal{L}}{\partial [H(\mathbf{x}_i)]}$

  – Let $\sum_{i=1}^{n} h^2(\mathbf{x}_i) = $ constant (we can always normalize the predictions(对结果归一化处理)) and replace q_i with $-2r_i$. We have

$$\begin{aligned}
h_{t+1} &= \arg\min_{h \in \mathbb{H}} \sum_{i=1}^{n} q_i h(\mathbf{x}_i) \\
&= \arg\min_{h \in \mathbb{H}} -2 \sum_{i=1}^{n} r_i h(\mathbf{x}_i) \\
&= \arg\min_{h \in \mathbb{H}} \sum_{i=1}^{n} \left(r_i^2 - 2r_i h(\mathbf{x}_i) + (h(\mathbf{x}_i))^2 \right) \\
&= \arg\min_{h \in \mathbb{H}} \sum_{i=1}^{n} (h(\mathbf{x}_i) - r_i)^2
\end{aligned} \tag{1}$$

  – We train h_{t+1} to predict r_i, which are from the old model H_t.

  – The gradient is:

$$\frac{\partial \mathcal{L}}{\partial [H(\mathbf{x}_i)]} = -2(y_i - H(\mathbf{x}_i))$$

  – So we fit h to the residuals:

$$r_i = y_i - H(\mathbf{x}_i)$$

  – Update the model:

$$H_t(\mathbf{x}) = H_{t-1}(\mathbf{x}) + \alpha_t h_t(\mathbf{x})$$

- **GBR with Absolute loss (更鲁棒):** For regression tasks with absolute loss:

  – Square loss is easy to deal with mathematically but not robust to outliers.

  – Absolute loss (more robust to outliers):

$$\ell(y, \hat{y}) = |y - \hat{y}|$$

  – The gradient is $q_i = \frac{\partial \mathcal{L}}{\partial H(\mathbf{x}_i)} = -\text{sign}(y_i - H(\mathbf{x}_i))$.

  – Then fit h on $-q_i$, $i = 1, 2, \ldots, n$. (no longer the residuals, different from using the squared loss)

- **GBR with Huber loss(更更鲁棒):**

  – Huber loss (more robust to outliers):

$$\ell(y, \hat{y}) = \begin{cases} \frac{1}{2}(y - \hat{y})^2 & |y - \hat{y}| \leq \delta \\ \delta(|y - \hat{y}| - \delta/2) & |y - \hat{y}| > \delta \end{cases}$$

– The gradient is:

$$\frac{\partial \mathcal{L}}{\partial H(\mathbf{x}_i)} = \begin{cases} -(y_i - H(\mathbf{x}_i)) & |y_i - H(\mathbf{x}_i)| \leq \delta \\ -\delta \operatorname{sign}(y_i - H(\mathbf{x}_i)) & |y_i - H(\mathbf{x}_i)| > \delta \end{cases}$$

- **GBM for classification:**

  – Predict probability of K classes:

$$p_k(\mathbf{x}) = \frac{\exp(h^{(k)}(\mathbf{x}))}{\sum_{c=1}^{K} \exp(h^{(c)}(\mathbf{x}))} \triangleq \hat{y}^{(k)}, \quad k = 1, 2, \ldots, K$$

  – Loss: $\mathcal{L}(H) = \sum_{i=1}^{n} \ell(\mathbf{y}_i, \hat{\mathbf{y}}_i)$ (e.g. cross-entropy or KL divergence)

  – Initialize $H^{(1)}, H^{(2)}, \ldots, H^{(K)}$, iterate until converge or reach max T:

  1. Calculate negative gradients for every class:

$$-g_k(\mathbf{x}_i) = -\frac{\partial \mathcal{L}}{\partial [H^{(k)}(\mathbf{x}_i)]}, \quad i = 1, \ldots, n, \ k = 1, \ldots, K$$

  2. Fit $h^{(k)}$ to $-g_k(\mathbf{x}_i)$ (负梯度), $k = 1, 2, \ldots, K$.
  3. Update: $H^{(k)} \leftarrow H^{(k)} + \alpha h^{(k)}$, $k = 1, 2, \ldots, K$.

2.2 AdaBoost

A special case of gradient boosting with exponential loss.

- Exponential loss (learns α adaptively):

$$\mathcal{L}(H) = \sum_{i=1}^{n} e^{-y_i H(\mathbf{x}_i)}$$

- Gradient: $q_i = \frac{\partial \mathcal{L}}{\partial H(\mathbf{x}_i)} = -y_i e^{-y_i H(\mathbf{x}_i)}$

- Let $w_i = \frac{1}{Z} e^{-y_i H(\mathbf{x}_i)}$, where $Z = \sum_{i=1}^{n} e^{-y_i H(\mathbf{x}_i)}$ (constant w.r.t h), so $\sum_{i=1}^{n} w_i = 1$.
  w_i is the relative contribution of $(\mathbf{x}_i, y_i)$ to the overall loss.

- Binary classification: $y \in \{-1, +1\}$, $h(\mathbf{x}) \in \{-1, +1\}$.

- Derivation:

$$\begin{aligned} h &= \arg\min_{h \in \mathbb{H}} \sum_{i=1}^{n} q_i h(\mathbf{x}_i) \\ &= \arg\min_{h \in \mathbb{H}} -\sum_{i=1}^{n} w_i y_i h(\mathbf{x}_i) \\ &= \arg\min_{h \in \mathbb{H}} \sum_{i:h(\mathbf{x}_i) \neq y_i} w_i - \sum_{i:h(\mathbf{x}_i) = y_i} w_i \\ &= \arg\min_{h \in \mathbb{H}} \sum_{i:h(\mathbf{x}_i) \neq y_i} w_i \end{aligned}$$

* Last equality holds because $\sum_{i=1}^{n} w_i = 1$.

- Result:

$$h = \arg\min_{h \in \mathbb{H}} \sum_{i:h(\mathbf{x}_i) \neq y_i} w_i$$

$$\epsilon := \sum_{i:h(\mathbf{x}_i) \neq y_i} w_i$$

is the weighted classification error(加权错误率).

Note: misclassified points by H get larger weights(分类错误的点会得到更大的权重).

- Given h, find α via:

$$\alpha = \arg\min_\alpha \mathcal{L}(H + \alpha h) = \arg\min_\alpha \sum_{i=1}^n e^{-y_i(H(\mathbf{x}_i) + \alpha h(\mathbf{x}_i))}$$

- Differentiate w.r.t α and set to zero:

$$\sum_{i=1}^n y_i h(\mathbf{x}_i) e^{-(y_i H(\mathbf{x}_i) + \alpha y_i h(\mathbf{x}_i))} = 0$$

It follows that:

$$\sum_{i:h(\mathbf{x}_i)y_i=1} e^{-(y_i H(\mathbf{x}_i) + \alpha y_i h(\mathbf{x}_i))} - \sum_{i:h(\mathbf{x}_i)y_i=-1} e^{-(y_i H(\mathbf{x}_i) + \alpha y_i h(\mathbf{x}_i))} = 0$$

$$\sum_{i:h(\mathbf{x}_i)y_i=1} w_i e^{-\alpha} - \sum_{i:h(\mathbf{x}_i)y_i=-1} w_i e^{\alpha} = 0$$

We have $(1-\epsilon)e^{-\alpha} - \epsilon e^{\alpha} = 0$, $e^{2\alpha} = \frac{1-\epsilon}{\epsilon}$, and get:

$$\boxed{\alpha = \frac{1}{2}\ln\frac{1-\epsilon}{\epsilon}}$$

2.3 Mixture of Experts(MoE)

A machine learning technique where multiple expert learners (e.g. neural networks) are used to divide a problem space into homogeneous regions (distinct subtasks). (用人话 (AI) 说就是，把一个复杂的问题拆分成多个子任务，每个子任务由一个专家模型来处理，从而提升整体的学习效果。)
(骗你的人话也没看懂。。)

2.3.1 The First Attempt

- Error function:

$$E = \left\| y - \sum_{j=1}^k g_j O_j \right\|^2$$

- y: target vector; O_j: output of expert j; g_j: proportional contribution of expert j.

- *This error function does not ensure localisation of experts.(人话：专家没有明确的分工).

2.3.2 The Second Attempt

- Error function:
$$E = \sum_{j=1}^{k} g_j \|y - O_j\|^2$$

- The system tends to devote a single expert to each training case.

- *This may not work well in practice.(人话：实际效果可能不佳)

2.3.3 The Third Attempt [Jacobs et al. 1991]

- Error function (mixture of Gaussians):
$$E_{ME} = -\log \sum_{j=1}^{k} g_j \exp\left(-\frac{1}{2}(y - O_j)^T \Sigma^{-1}(y - O_j)\right)$$

- Assume $\Sigma = I$ (Σ: Covariance matrix, 协方差矩阵), derivative w.r.t the i-th expert:
$$\frac{\partial E_{ME}}{\partial O_i} = -\left[\frac{g_i \exp\left(-\frac{1}{2}(y - O_i)^T(y - O_i)\right)}{\sum_j g_j \exp\left(-\frac{1}{2}(y - O_j)^T(y - O_j)\right)}\right](y - O_i)$$

- Compare with derivative of second attempt:
$$\frac{\partial E}{\partial O_i} = -2g_i(y - O_i)$$

- The former considers how well expert i performs relative to others, adapting the best-fitting expert faster.

  E.g., $g_1 = 0.8$, $g_2 = 0.2$, then $\frac{0.8 \times 0.9}{0.8 \times 0.9 + 0.2 \times 0.1} \approx 0.97 > 0.8$.
  (人话：表现好的专家会得到更快的提升)

(这 nm 都是什么玩意?)

2.4 Stacking(堆叠法)

Multiple base learners' outputs $(\hat{y}_1, \hat{y}_2, \ldots, \hat{y}_N)$ are combined by a meta-learner (stacker) to produce the final prediction $\hat{Y}$. (用人话说就是，把多个模型的预测结果再拿去训练一个新的模型，从而提升整体的预测效果。)

- Multi-level stacking: stacking can be repeated.

- Popular stackers: linear models (fast), gradient boosting (accurate).

- Base models should be diverse, expert at different data parts.

- Trade-off: accurate but slow to predict.

(为什么一讲能有这么多神秘小知识点和神秘公式？)

3 Lec3: Advanced Applications

3.1 Recommendation Systems

3.1.1 Collaborative Filtering(协同过滤)

Core idea: Use behavioral data from many users (e.g., ratings, clicks) to predict what the current user might like. (人话：大数据推荐你喜欢的东西)

- **User-Item Interaction:**

  - Explicit Feedback(显式反馈): ratings, purchases.

  - Implicit Feedback(隐式反馈): clicks, browsing time.

- **User-Item Rating Matrix:** Rows = users, columns = items, values = ratings. Typically large and sparse.

- **Distance/Similarity Measurement(相似度度量):**

  - Euclidean distance: $\text{sim}(user_i, user_j) = \frac{1}{1+\|\mathbf{x}_i - \mathbf{x}_j\|_2}$
  - Cosine similarity: $\text{sim}(user_i, user_j) = \frac{\mathbf{x}_i \cdot \mathbf{x}_j}{\|\mathbf{x}_i\|\|\mathbf{x}_j\|}$
  - Pearson correlation: $\rho_{X,Y} = \frac{\text{cov}(X,Y)}{\sigma_X \sigma_Y}$

- **Nearest-Neighbor Collaborative Filtering(最近邻协同过滤):**

  Predict utility of item i based on similar users who rated that item.

  - $\mathcal{N}$: neighborhood set (most similar users to u who rated item i)(人话：给你推荐东西的那些"邻居"用户)

  - $w_{uv} \in [0,1]$: similarity weight between users u and v(人话：你和邻居用户的相似度)

  - Prediction:
  $$\hat{x}_{ui} = \bar{x}_u + \sum_{v \in \mathcal{N}} \left((x_{vi} - \bar{x}_v) \times \frac{w_{uv}}{\sum_{v' \in \mathcal{N}} w_{uv'}} \right)$$

  - $\bar{x}_u = \frac{1}{|I_u|} \sum_{i \in I_u} x_{ui}$ (average rating of user u, where I_u is the set of items rated by u)
  - $\bar{x}_v = \frac{1}{|I_v|} \sum_{i \in I_v} x_{vi}$ (average rating of user v, where I_v is the set of items rated by v)

- **Matrix Factorization Collaborative Filtering(矩阵分解协同过滤):**

  - Notations:

    * $R = [r_{ui}] \in \mathbb{R}^{m \times n}$: incomplete user-item rating matrix

    * Ω: set of observed entries (known ratings)

    * $P = [p_1, \ldots, p_u, \ldots, p_m] \in \mathbb{R}^{f \times m}, \quad Q = [q_1, \ldots, q_i, \ldots, q_n] \in \mathbb{R}^{f \times n}$

  - Basic SVD ($R \approx P^T Q$):
  $$\min_{P,Q} \sum_{(u,i) \in \Omega} \left\{ (r_{ui} - p_u^T q_i)^2 + \lambda(\|p_u\|^2 + \|q_i\|^2) \right\}$$

  - SVD with bias ($b_{ui} = \mu + b_u + b_i$):
  $$\min_{P,Q,B} \sum_{(u,i) \in \Omega} \left\{ (r_{ui} - \mu - b_u - b_i - p_u^T q_i)^2 + \lambda(\|p_u\|^2 + \|q_i\|^2 + b_u^2 + b_i^2) \right\}$$

- μ: global mean; b_u: user bias; b_i: item bias;

- $\lambda(\cdot)$: regularization term (prevents overfitting).

- Optimization: GD/SGD or Alternating Least Squares(交替最小二乘法).

- **Pros & Cons of Collaborative Filtering:**

  - Pros: No domain knowledge needed; captures diverse user preferences(人话：不需要领域知识，能捕捉多样的用户偏好).

  - Cons: Cold-start problem (new users/items); data sparsity(人话：新来的用户和物品数据较少，导致推荐效果差).

3.1.2 Content-Based Methods

- **Content analysis:** item → feature vector v (e.g. TF-IDF, image features).

- **Profile learning:** user → feature vector z (e.g. age, sex, education).

- **Filtering module:** train classification/regression model to predict user's utility for an item.

- **Recommendation for user:**

  - n: # of items;

  - $z_u \in \mathbb{R}^d$:

  - user u's feature vector;

  - $h : \mathbb{R}^d \to \mathbb{R}^n$ (e.g. neural network);

  - h_i: i-th output of h.

  - ℓ: loss function (e.g. squared loss).

$$\min_h \sum_{(u,i) \in \Omega} \ell(r_{ui}, h_i(z_u))$$

- **Recommendation for item:**

  - m: # of users;

  - $v_i \in \mathbb{R}^{d'}$: item

  - i's feature vector;

  - $g : \mathbb{R}^{d'} \to \mathbb{R}^m$ (e.g. neural network);

  - g_u: u-th output of g.

  - ℓ: loss function (e.g. squared loss).

$$\min_g \sum_{(u,i) \in \Omega} \ell(r_{ui}, g_u(v_i))$$

- **Pros & Cons of Content-Based Methods:**

  - Pros: User-independent; explainable; handles new items/users well.

  - Cons: Needs domain knowledge; narrow recommendations (similar items).

3.1.3 Hybrid Methods(看起来是不重要的知识点)

Most modern systems are hybrid recommenders.

- Combine separate recommenders (CF + CB): ensemble techniques (linear weighting, stacking, etc.)

- Add content-based aspects to CF: e.g. matrix factorization with side information.

3.1.4 Evaluation Metrics for RS

3.1.4.1 Prediction Metrics(评分预测指标)

- **Mean Absolute Error (MAE):**

$$\text{MAE} = \frac{1}{|\mathcal{T}|} \sum_{(u,i)\in\mathcal{T}} |r_{ui} - \hat{r}_{ui}|$$

- **Root Mean Squared Error (RMSE):**

$$\text{RMSE} = \sqrt{\frac{1}{|\mathcal{T}|} \sum_{(u,i)\in\mathcal{T}} (r_{ui} - \hat{r}_{ui})^2}$$

Here $\mathcal{T}$ denotes the set of user–item pairs used for evaluation (e.g., the test set).(人话：测试集中所有用户和物品的组合)

3.1.4.2 Ranking-based Metrics(基于排序的指标)

- **Precision@K:** fraction of top-K recommended items that are relevant(人话：前 K 个推荐中有多少是相关的).

$$\text{Prec}(R)_k = \frac{|\{r \in R : \ r \le k\}|}{k}$$

- **Recall@K:** fraction of relevant items covered in top-K(人话：前 K 个推荐覆盖了多少相关的物品).

$$\text{Recall}(R)_k = \frac{|\{r \in R : \ r \le k\}|}{|R|}$$

  - (Precision = TP/(TP+FP); Recall = TP/(TP+FN)).
  - r = rank position of a recommended item;
  - k = cut-off (top-k);
  - R = set of relevant items for the user.

- **Average Precision (AP@N):** average of precision values at ranks of relevant items.(前 N 个推荐中相关物品的精确率)

$$\text{AP@}N = \frac{1}{m} \sum_{k=1}^{N} P(k) \cdot \text{rel}(k)$$

where $P(k)$ is precision@k, m number of relevant items, and rel(k) is indicator if item at rank k is relevant.

- **Mean Average Precision (MAP):** mean of AP over Q users:

$$\text{MAP} = \frac{1}{Q} \sum_{q=1}^{Q} \text{AP}(q)$$

- **Normalized Discounted Cumulative Gain (NDCG):** evaluates ranked relevance with position discounting.

$$\text{NDCG}_p = \frac{\text{DCG}_p}{\text{IDCG}_p}, \quad \text{DCG}_p = \sum_{i=1}^{p} \frac{2^{\text{rel}_i} - 1}{\log_2(i+1)}$$

where rel_i is relevance of item at rank i, and IDCG_p is the ideal DCG (sorted by relevance). Range: $[0, 1]$. (NDCG 越接近 1 越好)

  - **Example:** 5 recommended items with relevances $[3, 2, 1, 0, 2]$ (in rank order).

$$\text{DCG}_5 = \frac{2^3 - 1}{\log_2(1+1)} + \frac{2^2 - 1}{\log_2(2+1)} + \frac{2^1 - 1}{\log_2(3+1)} + \frac{2^0 - 1}{\log_2(4+1)} + \frac{2^2 - 1}{\log_2(5+1)} \approx 10.5538,$$

$$\text{IDCG}_5 = \text{DCG}_5(\text{sorted rel} = [3, 2, 2, 1, 0]) \approx 10.8235,$$

$$\text{NDCG}_5 = \frac{\text{DCG}_5}{\text{IDCG}_5} \approx 0.975.$$

(这一坨又是什么玩意？)

3.2 Learning to Rank(L2R) (排序学习)

Learning to Rank (L2R) trains models to order items by relevance, optimizing ranking-specific objectives such as pairwise or listwise losses. (你说得对，但是这里好像也没有什么公式啊 (雾))

- L2R is a supervised learning problem for ranking.

- Training data consists of:

  - A set of queries $Q = \{q_1, \ldots, q_m\}$
  - A set of documents D
  - For each query i, relevant documents $D_i = \{d_{i,1}, \ldots, d_{i,n_i}\} \subseteq D$
  - Relevance scores $\mathbf{y}_i = (y_{i,1}, \ldots, y_{i,n_i})$ for each $d_{i,j}$

- Goal: Given a new query q, output a sorted list of relevant documents.

- **Point-wise Modeling:** Predicts each (query, document) pair independently.
  Pro: Simple, can use regression/classification.
  Con: Ignores relative order between documents.
  (一句话：点对点建模简单但忽略了文档间的相对顺序。)

- **Pair-wise Modeling:** Predicts preference between document pairs for a query.
  Pro: Models relative order.
  Con: Cannot distinguish excellent-bad from fair-bad pairs.
  (一句话：成对建模能捕捉相对顺序，但无法区分优秀-差和一般-差的对比。)

- **List-wise Modeling:** Predicts for the whole ranked list of documents.
  Pro: Considers position in ranking, aligns with ranking metrics.
  Con: High training complexity.
  (一句话：列表建模考虑排名位置，但训练复杂度高。)

- **Evaluation for L2R:** Use benchmark datasets and ranking metrics (e.g., MAP, NDCG).

- **Algorithms for L2R:**

  - **Example: Ranking SVM (pairwise):**

    * **Goal:** Learn a scoring function $h(x) = w^\top x$ such that for any pair with labels $y_i > y_j$ we have $h(x_i) > h(x_j)$. (人话：让相关性更高的文档得分更高)

    * **Training pairs:** Construct pair set $\mathcal{P} = \{(i,j) : y_i > y_j\}$; $m = |\mathcal{P}|$ denotes number of pairs.

    * **Optimization (primal):**

    $$\min_{w,\,\xi_{ij} \geq 0} \ \frac{1}{2}\|w\|^2 + \frac{C}{m}\sum_{(i,j)\in\mathcal{P}} \xi_{ij}$$

    $$\text{s.t.} \qquad w^\top x_i \geq w^\top x_j + 1 - \xi_{ij}, \quad \forall (i,j) \in \mathcal{P}.$$

    * **Notes:** ξ_{ij} are hinge-loss slacks; C controls margin vs. training error. The objective is equivalent to minimizing the average pairwise hinge loss.

    * **Prediction:** Score each document by $h(x) = w^\top x$ and sort descending to produce a ranking.

    * **Remarks:** Works well for pairwise preferences; training can be expensive due to $O(n^2)$ pairs, so sampling or stochastic methods are often used. Kernel SVMs and regularization extend naturally.

    * (人话总结：Ranking SVM 通过学习一个线性评分函数来排序文档，优化目标是最大化正确排序对的间隔 + 最小化排序错误的惩罚。训练时需要处理大量文档对，复杂度高。)

(叽里咕噜说什么在)

4　Lec4-1: Graph Cut and Spectral Clustering(谱聚类)

4.1　Graph Parition

A similarity graph G=(V,E,W) represents data points as vertices V, with an edge in E when the pairwise similarity is positive and weights W storing those affinities. The affinity matrix records these pairwise similarities. Graph partitioning (clustering) aims to split the graph so that edges inside a group have large weights while edges across groups have small weights. (人话：图划分就是把图分成若干部分，使得每个部分内的节点之间联系紧密 (组内权重大)，而不同部分之间的联系较弱 (组间权重小)。)

Given data points, a similarity graph can be constructed using methods such as **k-nearest neighbor or ϵ-neighborhood**. The edge weights are often defined by a **Gaussian kernel**:

$$k(x_i, x_j) = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

4.2　Minimum Cut

- Minimum cut: partition the graph into two sets A and B minimizing $\text{cut}(A,B) := \sum_{i\in A,\,j\in B} w_{ij}$.

- Solvable efficiently (e.g. via max-flow/min-cut algorithms, typical cost O(|V||E|)), but the minimum cut often yields unbalanced solutions (it may isolate vertices). (人话：最小割可以高效求解，但结果往往不平衡，可能会把一些节点孤立出来。)

- Not satisfactory partition? Often isolates vertices

图 1: Minimum Cut Example

(画的不错的一张图)

- To address this, we can use **Normalized Cut (Ncut)**:

4.3 Normalized Cut

Normalized Cut balances cut weight with cluster sizes. For a partition (A,B), define

$$\text{vol}(A) = \sum_{i \in A} d_i, \quad d_i = \sum_j w_{ij},$$

and

$$\text{Ncut}(A, B) := \text{cut}(A, B) \left(\frac{1}{\text{vol}(A)} + \frac{1}{\text{vol}(B)} \right).$$

- Minimizing Ncut favors balanced partitions but is **NP-hard**;

- **spectral clustering** (谱聚类) provides an efficient relaxation.

4.3.1 Degree Matrix and Graph Laplacian

$$W = \begin{bmatrix} w_{11} & w_{12} & \cdots & w_{1N} \\ w_{21} & w_{22} & \cdots & w_{2N} \\ \vdots & \vdots & \ddots & \vdots \\ w_{N1} & w_{N2} & \cdots & w_{NN} \end{bmatrix}$$

$$D = \begin{bmatrix} d_1 & 0 & \cdots & 0 \\ 0 & d_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & d_N \end{bmatrix}, \quad d_j = \sum_{i=1}^{N} w_{ij}.$$

- D is the **degree matrix**. And the **graph Laplacian matrix** is defined as

$$L := D - W.$$

- Properties: L is symmetric positive semi-definite, $\mathbf{1}^\top L = 0$, and its eigenvectors are used in spectral clustering (relaxation of Ncut).

4.3.2 Normalized Cut and Graph Laplacian

Mathematical derivation (optional)

Recall $L = D - W$ and $D = \text{diag}(d_1, \ldots, d_N)$.

Let $u = [u_1, u_2, \ldots, u_N]^\top$ with

$$u_i = \begin{cases} \dfrac{1}{\text{vol}(A)}, & \text{if } i \in A, \\ -\dfrac{1}{\text{vol}(B)}, & \text{if } i \in B. \end{cases}$$

Then

$$u^\top L u = \tfrac{1}{2} \sum_{i,j} w_{ij}(u_i - u_j)^2 = \sum_{i \in A, j \in B} w_{ij}\left(\frac{1}{\text{vol}(A)} + \frac{1}{\text{vol}(B)}\right)$$

and

$$u^\top D u = \sum_i d_i u_i^2 = \sum_{i \in A} \frac{d_i}{\text{vol}(A)^2} + \sum_{j \in B} \frac{d_j}{\text{vol}(B)^2} = \frac{1}{\text{vol}(A)} + \frac{1}{\text{vol}(B)}.$$

Therefore

$$\frac{u^\top L u}{u^\top D u} = \sum_{i \in A, j \in B} w_{ij}\left(\frac{1}{\text{vol}(A)} + \frac{1}{\text{vol}(B)}\right) = \text{Ncut}(A, B).$$

(这几把都是什么玩意？好像是上面的推导吧)

(不管了，反正是 optional，摆在这图个吉利)

Conclusion

- Ncut is equivalent to minimizing the Rayleigh quotient $\dfrac{u^\top L u}{u^\top D u}$, i.e.,

$$\min_{A,B} \text{Ncut}(A, B) \iff \min_u \frac{u^\top L u}{u^\top D u}, \quad u \in \mathbb{R}^N, \quad u_i = \begin{cases} \dfrac{1}{\text{vol}(A)}, & i \in A, \\ -\dfrac{1}{\text{vol}(B)}, & i \in B. \end{cases}$$

- Equivalent formulation: minimize the quotient subject to $u^\top D \mathbf{1} = 0$ and binary constraints $u_i \in \{1, -b\}$ (for some $b > 0$).

- Relaxation:

$$Lu = \lambda D u,$$

taking the eigenvector corresponding to the **second smallest eigenvalue** as the relaxed solution.

- Equivalently, use the normalized Laplacian $\widetilde{L} = D^{-1}L = I - D^{-1}W$.
  Obtain a binary partition by thresholding u at 0: $i \in A$ if $u_i \geq 0$, else $i \in B$.

- Extend to k clusters by using the first k nontrivial eigenvectors and applying k-means (spectral clustering).

- (人话：2 类划分找第二小特征值对应的特征向量，k 类划分用前 k 个非平凡特征向量，然后 k-means 聚类。)

(事实上还是没看懂，插个眼以后复习的时候看看有没有什么需要补的)

4.4 Spectral Clustering Algorithm

- Input: data $X = \{x_1, x_2, \ldots, x_N\}$ and number K of clusters.

- **Step 1**: Construct a similarity (affinity) matrix W (e.g. Gaussian kernel)

$$w_{ij} = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

  and build either a k-nearest neighbor or ϵ-neighborhood graph.

- **Step 2**: Compute Laplacian L (or normalized variants):

$$L = D - W, \qquad \widetilde{L} = D^{-1}L = I - D^{-1}W, \qquad \hat{L}_{sym} = I - D^{-1/2}WD^{-1/2}.$$

- **Step 3**: Eigen-decompose (normalized) Laplacian and take first K nontrivial eigenvectors to form $Z = [v_1, \ldots, v_K]^\top \in \mathbb{R}^{K \times N}$.(对 L 做特征值分解)

- **Step 4**: Normalize the columns (row-wise embedding) to unit ℓ_2 norm(归一化):

$$z_i \leftarrow z_i/\|z_i\|, \quad i = 1, \ldots, N.$$

- **Step 5**: Run K-means on $\{z_1, \ldots, z_N\}$ and output K clusters (assignments on Z or map back to X).

- Notes: use $\widetilde{L}_{sym}$ (symmetric normalized) for best numerical stability; thresholding the second eigenvector recovers a binary partition.

- **Properties of L:**
  For $L = D - W$ or $\hat{L} = I - D^{-1/2}WD^{-1/2}$

  - L (and $\hat{L}$) are symmetric and positive semi-definite.(对称 + 半正定)
  - Eigenvalues satisfy $0 = \lambda_1 \leq \lambda_2 \leq \cdots \leq \lambda_N$.
  - The multiplicity K of eigenvalue 0 equals the number of connected components of the graph (hence K clusters). (0 特征值的数量等于图的连通分量数，也就是聚类数)

5 Lec4-2: Semi-Supervised Learning (SSL, 半监督学习)

5.1 Notations

- Input (or feature) $\mathbf{x} \in \mathcal{X}$, output (or label) $\mathbf{y} \in \mathcal{Y}$

- Learner $f : \mathcal{X} \to \mathcal{Y}$

- Labeled data $(X_l, Y_l) = \{(\mathbf{x}_1, \mathbf{y}_1), \ldots, (\mathbf{x}_l, \mathbf{y}_l)\}$

- Unlabeled data $X_u = \{\mathbf{x}_{l+1}, \ldots, \mathbf{x}_N\}$, available during training

- Loss function $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}$

- Usually, $l \ll N$

- Test data $X_{\text{test}} = \{\mathbf{x}_{N+1}, \ldots\}$, not available during training

Why Semi-Supervised Learning?

Labeled data is often **scarce, expensive**, and requires expert annotation or specialized equipment. In contrast, unlabeled data is **abundant and cost-effective**. By leveraging both, we can build more robust and high-performing machine learning models.

5.2 Self-Training Algorithm

Assumption: One's own high confidence predictions are correct.(人话：自己高置信度的预测是正确的)

5.2.1 Algorithm Procedure:

1. Train model f from labeled data (X_l, Y_l).

2. Predict labels for unlabeled data $x \in X_u$. (用有标签数据训练模型，然后对无标签数据进行预测)

3. Add the pseudo-labeled pairs $(x, f(x))$ to the labeled training set. (把预测结果当作新的标签加入训练集)

4. Repeat the process until a stopping criterion is met.

5.2.2 Variations of Self-Training

Depending on how pseudo-labeled data is incorporated, there are several variations:

- **Most Confident:** Add only a few samples $(x, f(x))$ with the highest prediction confidence to the labeled data. (人话：只添加那些模型最有信心的预测结果)

- **All Samples:** Add all predicted $(x, f(x))$ directly to the labeled data.(直接把所有预测结果都加入训练集)

- **Weighted Approach:** Add all $(x, f(x))$ to the labeled data, but assign different weights to each sample according to its prediction confidence. (根据预测置信度给每个样本分配不同的权重)

5.2.3 Self-Training Algorithm: Propagating 1-NN (传播 1-NN)

This is a specific instance of self-training using the 1-Nearest Neighbor (1-NN) approach:

1. Classify an unlabeled sample x using the 1-NN rule (assigning the label of its nearest labeled neighbor).(用 1-NN 方法对无标签样本进行分类，分配最近的有标签邻居的标签)

2. Add the newly labeled pair $(x, f(x))$ to the labeled dataset and repeat the process.

Advantages and Disadvantages

- **Pros:** It is the simplest semi-supervised approach, serves as a versatile wrapper method, and is widely utilized in Natural Language Processing (NLP).

- **Cons:** The method is sensitive to outliers, and early classification errors can lead to self-reinforcing mistakes. (对异常值敏感)

5.3 Graph based SSL methods

Assumption: A graph is given on the labeled and unlabeled data. Instances connected by heavy edge tend to have the same label(由重边连接的实例往往具有相同的标签)

人话就是边的权重反应了两个节点 (数据点)，之间的相似程度，边权越大，数据点越相似

5.3.1 Graph Construction

- **Nodes:** The set of nodes is the union of labeled and unlabeled data, $X_l \cup X_u$.

- **Edges:** Constructed via a k-Nearest Neighbor graph (unweighted) or a fully connected graph where weights decay with distance (全连接图, 权重随距离衰减):

$$w_{ij} = \exp\left(-\frac{\|x_i - x_j\|^2}{2\sigma^2}\right)$$

- w_{ij} 是高斯核的那个函数，反映了数据点之间的相似度

Regularized Classifier　A standard classifier learns by minimizing a loss term combined with regularization (e.g., LASSO or Regularized Least Squares). We can extend this to semi-supervised learning by using unlabeled data for regularization.

Graph-Based Regularization　The core principle is that if two instances x_i and x_j are similar (indicated by a large edge weight w_{ij}), their predicted labels $f(x_i)$ and $f(x_j)$ should also be similar. This leads to the following optimization problem:

其实就是学习一个学习器来使得损失函数 + 正则化项最小

$$\min_f \sum_{i=1}^{l} \ell(y_i, f(x_i)) + \lambda \sum_{i=1}^{N} \sum_{j=1}^{N} w_{ij} \|f(x_i) - f(x_j)\|^2$$

第一项：有标签数据的损失。第二项：图正则化项，强制相似点有相似预测。λ：正则化参数。

Algorithm Objectives　The graph-based algorithm operates with two primary goals:

- **Label Constraint:** It enforces the correct labels on the existing labeled data.

- **Manifold Consistency:** It maximizes the consistency of unlabeled examples relative to the underlying graph topology.

5.3.2 Label Propagation Algorithm (标签传播算法)

1. Compute affinity matrix W (亲和矩阵).

2. Compute degree matrix D, where $D_{ii} = \sum_j W_{ij}$.

3. Initialize $\hat{Y}^{(0)} \leftarrow (y_1, \ldots, y_l, 0, 0, \ldots, 0)$.

4. Iterate: $\hat{Y}^{(t+1)} = D^{-1}W\hat{Y}^{(t)}$, fix labels of labeled data.

5. Repeat until convergence.

6. Assign labels based on the sign of $\hat{y}_i^{(\infty)}$.

- The algorithm forces the labels on the labeled data (强制在标记数据上保留标签)

- The algorithm tries to maximizes the consistency of the unlabeled examples with the topology of the graph (试图使未标记示例与图的拓扑结构保持最大程度的一致性)

其实到最后也不知道这一讲到底细讲了什么，并没有什么公式 (雾)

6 Lec5: GNN

to be continued... Happy new year!