

ST: Lab Assignment 2

Elias El Khaldi Ahanach, Dylan Bartels, Wojciech Czabanski, Quinten Heijn

September 17, 2017

1 Random floating point numbers

2 Recognizing triangles

3 Testing properties strength

4 Recognizing Permutations

There are two properties we want to check for *isPermutation*.

1. All permutations of a list should evaluate **True**.
2. All other list should evaluate **False**.

The first property is easily tested by generating all the properties of a list. This can be done with the Haskell function *permutations*. The second property we can test by generating all possible combinations of a list and removing the possible permutations. The combination can be generated by taking all the permutations of all the *subsequences*. However, because the amount of combinations grows really quickly, you can only test for small input lists. This is why we created a third test function that just takes a list and a second list of random list that shouldn't be permutations of the first list. This is ensured by removing all permutations of the first list from the second list. This way, testing can also be automated.

5 Recognizing and generating derangements

These are the properties we could use to test *isDerangement* (from weak to strong):

1. It should only return **True** when the lists are equal in size.
2. It should only return **True** when the lists are permutations of each other.
3. It should only return **True** when the second list is a derangement of the first list and only **False** when this is not the case.

We can automate the testing process because we can easily create lists that are derangements and list that are not derangements based on an input list. To do this we should use random number generation, making the implementation somewhat cumbersome (because of the mixing of pure and unpure functions).

6 Implementing and testing ROT13 encoding

ROT13 is a simple Caesar cipher that shifts every letter in the input by 13. The special thing about this cipher is that because of the 13-step shift, it is symmetric ($\text{rot13}(\text{rot13}(a)) == a$).

The implementation can be found in the `.hs` file.

The obvious way of testing the ROT13 function would be checking whether all letters have actually shifted 13 steps, but since that would be similar to implementing the method again, we formulated some properties that should hold for the function:

1. The input (if non-empty) should be different than the output ($\text{ROT13}(a) \neq a$).
2. The function is symmetric, meaning it returns itself after applying ROT13 twice ($\text{ROT13}(\text{ROT13}(a)) == a$).
3. The interval between each letter of the input should be the same for the output (e.g. for "ab" the interval is 1).
4. The frequencies should remain the same. Even though the letters change, the frequency array should stay the same (e.g. "aab" \rightarrow "nno", the frequency array for both the input and output is [2,1]).

7 Implementing and testing IBAN validation

There are two properties used to check if string is a valid IBAN number:

1. The length of the IBAN number is the correct length for its country listed in the appropriate ISO document.¹
2. The sum of the digits of the IBAN number, with letters being converted to numbers according to the following scheme: A \rightarrow 10, B \rightarrow 11, ..., Z \rightarrow 35, modulo 97 is equal to 1.

The first property checks if the number is not missing any digits or contains superfluous digits. The second property validates that the single digits have not been modified. Both properties need to yield **True** for the string to be a valid IBAN number.

7.1 Testing

Testing of the properties can be achieved as follows:

1. Preparing a test list of IBAN numbers with correct country codes and adding a few incorrect country codes and numbers with correct country codes but incorrect lengths.
2. Preparing a test list of 97 identical IBAN numbers with a different check digit (ranging from 02 to 98). The checksum property should discard 96 incorrect IBAN numbers and yield **True** for the IBAN number containing the correct check number.

Automating the test process is difficult because the numbers of valid alphanumeric combinations is relatively small so it cannot be entirely randomized and the check digits cannot be calculated by the test generator, because that would mean using the same logic that is being tested.

What can be done however is pro

¹IBAN Registry