



## Hands-on Lab: Stored Procedures

**Estimated time needed:** 10 minutes

In this lab, you will create and execute stored procedures on IBM Db2 using SQL. A stored procedure is a set of SQL statements that are stored and executed on the database server. So instead of sending multiple SQL statements from the client to the server, you encapsulate them in a stored procedure on the server and send one statement from the client to execute them. Also, stored procedures can be useful if you have an SQL query that you write over and over again. You can save it as a stored procedure, and then just call it to execute it. In stored procedures, you can also pass parameters so that a stored procedure can act based on the passed parameter values.

## Software Used in this Lab

In this lab, you will use an [IBM Db2 Database](#). Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow the lab below first:

- [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

## Data Used in this Lab

The data used in this lab is internal data. You will be working on the **PETSALE** table.

ID ▲	ANIMAL	SALEPRICE
1	Cat	450.09
2	Dog	666.66
3	Parrot	50.00
4	Hamster	60.60
5	Goldfish	48.48

This lab requires you to have the PETSALE table populated with sample data on Db2. You might have created and populated a PETSALE table in a previous lab. But for this lab, it is recommended you download the PETSALE-CREATE-v2.sql script below, upload it to Db2 console and run it. The script will create a new PETSALE table dropping any previous PETSALE table if exists, and will populate it with the required sample data.

- [PETSALE-CREATE-v2.sql](#)

Please go through the lab below to learn how to upload and run a script on Db2 console (for this case, you need don't need to know anything else other than how to upload and run a script):

- [Hands-on Lab : Create tables using SQL scripts and Load data into tables](#)

## Objectives

After completing this lab, you will be able to:

- Create stored procedures
- Execute stored procedures

## Instructions

When you approach the exercises in this lab, follow the instructions to run the queries on Db2:

- Go to the [Resource List](#) of IBM Cloud by logging in where you can find the Db2 service instance that you created in a previous lab under **Services** section. Click on the **Db2-xx service**. Next, open the Db2 Console by clicking on **Open Console** button. Click on the 3-bar menu icon in the top left corner and go to the **Run SQL** page. The Run SQL tool enables you to run SQL statements.
  - If needed, follow [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

### Exercise 1

In this exercise, you will create and execute a stored procedure to read data from a table on Db2 using SQL.

1. Make sure you have created and populated the **PETSALE** table following the steps in the “**Data Used in this Lab**” section of this lab.

ID ▲	ANIMAL	SALEPRICE
1	Cat	450.09
2	Dog	666.66
3	Parrot	50.00
4	Hamster	60.60
5	Goldfish	48.48

2.

- You will create a stored procedure routine named **RETRIEVE\_ALL**.
- This **RETRIEVE\_ALL** routine will contain an SQL query to retrieve all the records from the PETSALE table, so you don't need to write the same query over and over again. You just call the stored procedure routine to execute the query everytime.
- To create the stored procedure routine, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12
13. 13
14. 14
15. 15
16. 16
17. 17
18. 18
19. 19
```


```
1.  --#SET TERMINATOR @
2.  CREATE PROCEDURE RETRIEVE_ALL      -- Name of this stored procedure routine
3.
4.  LANGUAGE SQL                      -- Language used in this routine
5.  READS SQL DATA                  -- This routine will only read data from the table
6.
7.  DYNAMIC RESULT SETS 1            -- Maximum possible number of result-sets to be returned to the caller query
8.
9.  BEGIN
10.
```

```

11.      DECLARE C1 CURSOR          -- CURSOR C1 will handle the result-set by retrieving records row by row from the table
12.      WITH RETURN FOR          -- This routine will return retrieved records as a result-set to the caller query
13.
14.      SELECT * FROM PETSALe;      -- Query to retrieve all the records from the table
15.
16.      OPEN C1;                  -- Keeping the CURSOR C1 open so that result-set can be returned to the caller query
17.
18.      END
19.      @                        -- Routine termination character

```

Copied!



☒ Syntax assistant

```

1  --#SET TERMINATOR @
2  CREATE PROCEDURE RETRIEVE_All
3
4  LANGUAGE SQL
5  READS SQL DATA
6
7  DYNAMIC RESULT SETS 1
8
9  BEGIN
10
11     DECLARE C1 CURSOR
12     WITH RETURN FOR
13
14     SELECT * FROM PETSALe;
15
16     OPEN C1;
17
18  END
19  @
20

```

3. To call the RETRIEVE\_ALL routine, copy the code below in a **new blank script** and paste it to the textbox of the **Run SQL** page. Click **Run all**. You will have all the records retrieved from the PETSALe table.

```

1. 1
1. CALL RETRIEVE_ALL;      -- Caller query

```

Copied!

```
1 CALL RETRIEVE_ALL;  
2  
3
```

4. You can view the created stored procedure routine RETRIEVE\_ALL. Click on the 3-bar menu icon in the top left corner and click **EXPLORE > APPLICATION OBJECTS > Stored Procedures**. Find the procedure routine RETRIEVE\_ALL from Procedures by clicking **Select All**. Click on the procedure routine **RETRIEVE\_ALL**.



IBM Db2 on Cloud



Storage: 22%

## STORED PROCEDURES

Filter by schema name or procedure name



## Schemas

☒ Select All New implicit schema☒ AUDIT *2 procedures*☒ ZJH17769 *2 procedures*☒ DB2INST1 *1 procedure*☒ ERRORSHEMA *0 procedure*☒ SQL74605 *0 procedure*☒ ST\_INFORMTN\_SCHEMA *0 procedure*


## Procedures

<input checked="" type="checkbox"/> NAME ▼	SCHEMA
<input type="checkbox"/> CONNECT_CHE...	DB2INST1
<input type="checkbox"/> LOAD	AUDIT
<input checked="" type="checkbox"/> RETRIEVE_ALL	ZJH17769
<input type="checkbox"/> UPDATE	AUDIT
<input type="checkbox"/> UPDATE_SALEP...	ZJH17769

5. If you wish to drop the stored procedure routine RETRIEVE\_ALL, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
1. 1
2. 2
3. 3
1. DROP PROCEDURE RETRIEVE_ALL;
2.
3. CALL RETRIEVE_ALL;
```

Copied!



The screenshot shows a code editor with a toolbar at the top. The toolbar includes icons for saving, undo, redo, toggling code view, font size adjustment, search, and deleting. On the right side of the toolbar, there is a toggle switch for 'Syntax assistant' which is currently turned on. The code area contains two lines of SQL: 'DROP PROCEDURE RETRIEVE\_All;' on line 1 and 'CALL RETRIEVE\_ALL;' on line 3. Line 4 is highlighted in light blue.

```
1 DROP PROCEDURE RETRIEVE_All;  
2  
3 CALL RETRIEVE_ALL;  
4
```

## Exercise 2

In this exercise, you will create and execute a stored procedure to write/modify data in a table on Db2 using SQL.

1. Make sure you have created and populated the **PETSALE** table following the steps in the “**Data Used in this Lab**” section of this lab.



ID ▲	ANIMAL	SALEPRICE
1	Cat	450.09
2	Dog	666.66
3	Parrot	50.00
4	Hamster	60.60
5	Goldfish	48.48

2.

- You will create a stored procedure routine named **UPDATE\_SALEPRICE** with parameters **Animal\_ID** and **Animal\_Health**.
- This **UPDATE\_SALEPRICE** routine will contain SQL queries to update the sale price of the animals in the PETSALE table depending on their health conditions, **BAD** or **WORSE**.
- This procedure routine will take animal ID and health condition as parameters which will be used to update the sale price of animal in the PETSALE table by an amount depending on their health condition. Suppose -
- For animal with ID XX having BAD health condition, the sale price will be reduced further by 25%.
- For animal with ID YY having WORSE health condition, the sale price will be reduced further by 50%.
- For animal with ID ZZ having other health condition, the sale price won't change.
- To create the stored procedure routine, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

1. 1  
2. 2  
3. 3  
4. 4  
5. 5  
6. 6  
7. 7  
8. 8  
9. 9  
10. 10  
11. 11  
12. 12  
13. 13  
14. 14  
15. 15  
16. 16  
17. 17  
18. 18  
19. 19  
20. 20  
21. 21  
22. 22  
23. 23  
24. 24

25. 25  
26. 26  
27. 27  
28. 28

```
1.  --#SET TERMINATOR @
2.  CREATE PROCEDURE UPDATE_SALEPRICE (
3.      IN Animal_ID INTEGER, IN Animal_Health VARCHAR(5) ) -- ( { IN/OUT type } { parameter-name } { data-type }, ... )
4.
5.  LANGUAGE SQL -- Language used in this routine
6.  MODIFIES SQL DATA -- This routine will only write/modify data in the table
7.
8.  BEGIN
9.
10.     IF Animal_Health = 'BAD' THEN -- Start of conditional statement
11.         UPDATE PETSale
12.         SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.25)
13.         WHERE ID = Animal_ID;
14.
15.     ELSEIF Animal_Health = 'WORSE' THEN
16.         UPDATE PETSale
17.         SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.5)
18.         WHERE ID = Animal_ID;
19.
20.     ELSE
21.         UPDATE PETSale
22.         SET SALEPRICE = SALEPRICE
23.         WHERE ID = Animal_ID;
24.
25.     END IF; -- End of conditional statement
26.
27. END
28. @ -- Routine termination character
```

Copied!

☒ Syntax assistant 

```
1  --#SET TERMINATOR @
2  CREATE PROCEDURE UPDATE_SALEPRICE (
3      IN Animal_ID INTEGER, IN Animal_Health VARCHAR(5) )
4
5  LANGUAGE SQL
6  MODIFIES SQL DATA
7
8  BEGIN
9
10     IF Animal_Health = 'BAD' THEN
11         UPDATE PETSale
12         SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.25)
13         WHERE ID = Animal_ID;
14
15     ELSEIF Animal_Health = 'WORSE' THEN
16         UPDATE PETSale
17         SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.5)
18         WHERE ID = Animal_ID;
19
20     ELSE
21         UPDATE PETSale
22         SET SALEPRICE = SALEPRICE
23         WHERE ID = Animal_ID;
24
25     END IF;
26
27 END
28 @
29
```

3. Let's call the UPDATE\_SALEPRICE routine. We want to update the sale price of animal with ID **1** having **BAD** health condition in the PETSALE table. Copy the code below in a **new blank script** and paste it to the textbox of the **Run SQL** page. Click **Run all**. You will have all the records retrieved from the PETSALE table.

```
1. 1
2. 2
3. 3
4. 4
5. 5
1. CALL RETRIEVE_ALL;
2.
3. CALL UPDATE_SALEPRICE(1, 'BAD');      -- Caller query
4.
5. CALL RETRIEVE_ALL;
```

Copied!



Syntax assistant

```
1 CALL RETRIEVE_ALL;  
2  
3 CALL UPDATE_SALEPRICE(1, 'BAD');  
4  
5 CALL RETRIEVE_ALL;  
6
```

**Run all**

Remember my last behavior

4. Let's call the UPDATE\_SALEPRICE routine once again. We want to update the sale price of animal with ID **3** having **WORSE** health condition in the PETSale table. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**. You will have all the records retrieved from the PETSale table.

```
1. 1
2. 2
3. 3
4. 4
5. 5
1. CALL RETRIEVE_ALL;
2.
3. CALL UPDATE_SALEPRICE(3, 'WORSE');    -- Caller query
4.
5. CALL RETRIEVE_ALL;
```

Copied!



Syntax assistant

```
1 CALL RETRIEVE_ALL;  
2  
3 CALL UPDATE_SALEPRICE(3, 'WORSE');  
4  
5 CALL RETRIEVE_ALL;  
6
```

**Run all****Remember my last behavior**

5. You can view the created stored procedure routine UPDATE\_SALEPRICE. Click on the 3-bar menu icon in the top left corner and click **EXPLORE > APPLICATION OBJECTS > Stored Procedures**. Find the procedure routine UPDATE\_SALEPRICE from Procedures by clicking **Select All**. Click on the procedure routine **UPDATE\_SALEPRICE**.





IBM Db2 on Cloud



Storage: 22%

## STORED PROCEDURES

Filter by schema name or procedure name



## Schemas

☒ Select All New implicit schema☒ AUDIT 2 procedures☒ ZJH17769 2 procedures☒ DB2INST1 1 procedure☒ ERRORSHEMA 0 procedure☒ SQL74605 0 procedure☒ ST\_INFORMTN\_SCHEMA 0 procedure

## Procedures

☒ NAME ▼

SCHEMA

☐ CONNECT\_CHE... DB2INST1☐ LOAD AUDIT☐ RETRIEVE\_ALL ZJH17769☐ UPDATE AUDIT☒ UPDATE\_SALEP... ZJH17769



6. If you wish to drop the stored procedure routine UPDATE\_SALEPRICE, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
1. 1
1. DROP PROCEDURE UPDATE_SALEPRICE;
```

Copied!



Syntax assistant

```
1 DROP PROCEDURE UPDATE_SALEPRICE;
```

```
2
```

```
3 CALL UPDATE_SALEPRICE(5, 'BAD');
```

```
4
```

**Congratulations! You have completed this lab, and you are ready for the next topic.**

**Author(s)**

- [Sandip Saha Joy](#)

**Other Contributor(s)**

-

**Changelog**

Date	Version	Changed by	Change Description
2023-05-10	1.2	Eric Hao & Vladislav Boyko	Updated Page Frames
2020-12-25	1.1	Steve Ryan	ID Reviewed
2020-12-14	1.0	Sandip Saha Joy	Created initial version

**© IBM Corporation 2023. All rights reserved.**