




VARISCITE LTD.

VCAM-AR1335B Datasheet

i.MX8 Camera Extension Board V 1.x



VARISCITE LTD.

VCAM-AR1335B Datasheet

© 2021 Variscite Ltd.

All Rights Reserved. No part of this document may be photocopied, reproduced, stored in a retrieval system, or transmitted, in any form or by any means whether, electronic, mechanical, or otherwise without the prior written permission of Variscite Ltd.

No warranty of accuracy is given concerning the contents of the information contained in this publication. To the extent permitted by law no liability (including liability to any person by reason of negligence) will be accepted by Variscite Ltd., its subsidiaries or employees for any direct or indirect loss or damage caused by omissions from or inaccuracies in this document.

Variscite Ltd. reserves the right to change details in this publication without notice. Product and company names herein may be the trademarks of their respective owners.

Variscite Ltd.
4, Hamelacha Street
Lod
P.O.B 1121
Airport City, 70100
ISRAEL

Tel: +972 (9) 9562910
Fax: +972 (9) 9589477

Revision History

Revision	Date	Notes
1.00	Feb 2020	Initial Release
1.01	Mar 2021	Added DART-MX8M-PLUS and VAR-SOM-MX8M-PLUS info
1.02	Jun 2021	Removed VCAM-AR1335B-SYM

Compatible Products

PN	Compatible products
VCAM-AR1335B	DART-MX8M, DART-MX8M-MINI, DART-MX8M-PLUS

VCAM-AR1335B – Embedded Vision Kits

Development kit with a Basler dart BCON for MIPI camera module and Linux support for NXP's i.MX8M, i.MX8M Mini and i.MX8M Plus SoC on a Variscite SoM.

This Basler dart BCON for MIPI Development Kit is a kit for integrating a Basler dart camera with a BCON for MIPI interface. It contains a dart camera module, a Variscite SoM with Linux drivers as well as additional accessories and thus offers a complete plug and play design-in package for dart BCON for MIPI camera modules.



General Information

Design-In Sample: January 2020

Components Included	Camera model: daA4200-30mci (S-Mount) Boards: DART-MX8M / DART-MX8M-MINI Basler BCON for MIPI to VAR M / M Mini/ M Plus Lens: Evetar Lens M13B0618W F1.8 f6mm 1/3" Cables: FFC cable, 0.2m
---------------------	---

daA4200-30mci (S-Mount)

Sensor Vendor	ON Semiconductor
Sensor	AR1335
Shutter	Rolling Shutter
Max. Image Circle	1/3"
Sensor Type	CMOS
Sensor Size	4.63 mm x 3.43 mm
Resolution (HxV)	4208 px x 3120 px
Resolution	13 MP
Pixel Size (H x V)	1.1 µm x 1.1 µm
Frame Rate	30 fps
Mono/Color	Color
Interface	BCON for MIPI
Pixel Bit Depth	10 bits
Synchronization	free-run software trigger
Exposure Control	programmable via the camera API automatic

daA4200-30mci (S-Mount)

	manual
Digital Input	2
Digital Output	2
Power Requirements	5V DC (via BCON for MIPI interface)
Power Consumption (typical)	0.6 W
Housing Type	Board Level
Housing Size (L x W x H)	29 mm x 29 mm x 17.5 mm
Lens Mount	S-mount
Weight (typical)	5g
Conformity	RoHS CE FCC GenICam MIPI CSI-2 UL KC

DART-MX8M-MINI

Accessory Type	Board
Board type	Processing Board
Size (L x W)	151 mm x 90 mm x 18 mm
Processor Manufacturer	NXP
SoC (system on chip)	NXP i.MX 8M, i.MX 8M Mini, i.MX 8M Plus
Camera Interface	BCON for MIPI
Ethernet Interface	10/100/1000 Ethernet
Other Interfaces	Wi-Fi, Bluetooth, CSI-2, USB 2.0, USB 3.0, Mini PCIe
SD Card Slot	µSD card
Memory	2 GB
Flash Memory	16 GB
Power Requirements	5V DC
Operating System	Linux

Basler BCON for MIPI to VAR M / M Mini

Accessory Type	Board
Size (L x W)	55 mm x 31 mm x 12 mm
Camera Interface	BCON for MIPI
Additional Information	Single or dual camera support, depending on SoC

Evetar Lens M13B0618W F1.8 f6mm 1/3"

Order Number	2000035178
Accessory Type	Lenses

Evetar Lens M13B0618W F1.8 f6mm 1/3"

Accessory Developer	Evetar
Focal Length	6.0 mm
Lens Mount	S-mount
Iris	F1.8
Iris Type	fixed
IR Cut Filter	yes
Max. Image Circle	1/3"
Working Distance	200 mm

FFC cable, 0.2m

Accessory Type	Data Cables
Accessory Developer	AXON' CABLE S.A.S.
Cable Length	0.2 m
Connector Camera Side	28 pin Hirose ZIF connector
Connector Host Side	28 pin Hirose ZIF connector
Interface	BCON for MIPI

daA4200-30mci (S-Mount) - Basler dart

The Basler daA4200-30mci (S-Mount) BCON for MIPI camera module with the ON Semiconductor AR1335 CMOS sensor delivers 30 frames per second at 13 MP resolution.

This model comes with a S-mount.



General Information

Design-In Sample:	now																						
Series Production:	February 2020																						
Sensor	<table> <tr> <td>Sensor Vendor</td><td>ON Semiconductor</td></tr> <tr> <td>Sensor</td><td>AR1335</td></tr> <tr> <td>Shutter</td><td>Rolling Shutter</td></tr> <tr> <td>Max. Image Circle</td><td>1/3"</td></tr> <tr> <td>Sensor Type</td><td>CMOS</td></tr> <tr> <td>Sensor Size</td><td>4.6 mm x 3.4 mm</td></tr> <tr> <td>Resolution (HxV)</td><td>4208 px x 3120 px</td></tr> <tr> <td>Resolution</td><td>13 MP</td></tr> <tr> <td>Pixel Size (H x V)</td><td>1.1 μm x 1.1 μm</td></tr> <tr> <td>Frame Rate</td><td>30 fps</td></tr> <tr> <td>Mono/Color</td><td>Color</td></tr> </table>	Sensor Vendor	ON Semiconductor	Sensor	AR1335	Shutter	Rolling Shutter	Max. Image Circle	1/3"	Sensor Type	CMOS	Sensor Size	4.6 mm x 3.4 mm	Resolution (HxV)	4208 px x 3120 px	Resolution	13 MP	Pixel Size (H x V)	1.1 μ m x 1.1 μ m	Frame Rate	30 fps	Mono/Color	Color
Sensor Vendor	ON Semiconductor																						
Sensor	AR1335																						
Shutter	Rolling Shutter																						
Max. Image Circle	1/3"																						
Sensor Type	CMOS																						
Sensor Size	4.6 mm x 3.4 mm																						
Resolution (HxV)	4208 px x 3120 px																						
Resolution	13 MP																						
Pixel Size (H x V)	1.1 μ m x 1.1 μ m																						
Frame Rate	30 fps																						
Mono/Color	Color																						
Camera Data	<table> <tr> <td>Interface</td><td>BCON for MIPI</td></tr> <tr> <td>Pixel Bit Depth</td><td>10 bits</td></tr> <tr> <td>Synchronization</td><td>free-run software trigger</td></tr> <tr> <td>Image Processing</td><td>In-Camera Processing</td></tr> <tr> <td>Exposure Control</td><td>programmable via the camera API automatic manual</td></tr> <tr> <td>Digital Input</td><td>2</td></tr> <tr> <td>Digital Output</td><td>2</td></tr> <tr> <td>Power Requirements</td><td>5V DC (via BCON for MIPI interface)</td></tr> <tr> <td>Power Consumption (typical)</td><td>0.6 W</td></tr> </table>	Interface	BCON for MIPI	Pixel Bit Depth	10 bits	Synchronization	free-run software trigger	Image Processing	In-Camera Processing	Exposure Control	programmable via the camera API automatic manual	Digital Input	2	Digital Output	2	Power Requirements	5V DC (via BCON for MIPI interface)	Power Consumption (typical)	0.6 W				
Interface	BCON for MIPI																						
Pixel Bit Depth	10 bits																						
Synchronization	free-run software trigger																						
Image Processing	In-Camera Processing																						
Exposure Control	programmable via the camera API automatic manual																						
Digital Input	2																						
Digital Output	2																						
Power Requirements	5V DC (via BCON for MIPI interface)																						
Power Consumption (typical)	0.6 W																						
Housing	<table> <tr> <td>Housing Type</td><td>Board Level</td></tr> <tr> <td>Housing Size (L x W x H)</td><td>29 mm x 29 mm x 17.5 mm</td></tr> <tr> <td>Lens Mount</td><td>S-mount</td></tr> <tr> <td>Weight (typical)</td><td>5g</td></tr> </table>	Housing Type	Board Level	Housing Size (L x W x H)	29 mm x 29 mm x 17.5 mm	Lens Mount	S-mount	Weight (typical)	5g														
Housing Type	Board Level																						
Housing Size (L x W x H)	29 mm x 29 mm x 17.5 mm																						
Lens Mount	S-mount																						
Weight (typical)	5g																						
Conformity	<table> <tr> <td>Conformity</td><td>RoHS CE FCC GenICam MIPI CSI-2 UL KC</td></tr> </table>	Conformity	RoHS CE FCC GenICam MIPI CSI-2 UL KC																				
Conformity	RoHS CE FCC GenICam MIPI CSI-2 UL KC																						

Legal Notice

Variscite LTD (“Variscite”) products and services are sold subject to Variscite’s terms and conditions of sale, delivery and payment supplied at the time of order acknowledgement.

Variscite warrants performance of its products to the specifications in effect at the date of shipment. Variscite reserves the right to make changes to its products and specifications or to discontinue any product or service without notice. Customers should therefore obtain the latest version of relevant information from Variscite to verify that the information is current.

Testing and other quality control techniques are utilized to the extent Variscite deems necessary to support its warranty.

Specific testing of all parameters of each device is not necessarily performed unless required by law or regulation.

In order to minimize risks associated with customer applications, the customer must use adequate design and operating safeguards to minimize inherent or procedural hazards. Variscite is not liable for applications assistance or customer product design. The customer is solely responsible for its selection and use of Variscite products. Variscite is not liable for such selection or use nor for use of any circuitry other than circuitry entirely embodied in a Variscite product.

Variscite products are not intended for use in life support systems, appliances, nuclear systems or systems where malfunction can reasonably be expected to result in personal injury, death or severe property or environmental damage. Any use of products by the customer for such purposes is at the customer’s own risk.

Variscite does not grant any license (express or implied) under any patent right, copyright, mask work right or other intellectual property right of Variscite covering or relating to any combination, machine, or process in which its products or services might be or are used. Any provision or publication of any third party’s products or services does not constitute Variscite’s approval, license, warranty or endorsement thereof. Any third-party trademarks contained in this document belong to the respective third-party owner.

Reproduction of information from Variscite datasheets is permissible only if reproduction is without alteration and is accompanied by all associated copyright, proprietary and other notices (including this notice) and conditions. Variscite is not liable for any un-authorized alteration of such information or for any reliance placed thereon.

Any representations made, warranties given, and/or liabilities accepted by any person which differ from those contained in this datasheet or in Variscite’s standard terms and conditions of sale, delivery and payment are made, given and/or accepted at that person’s own risk. Variscite is not liable for any such representations, warranties or liabilities or for any reliance placed thereon by any person.

Warranty Terms

Variscite guarantees hardware products against defects in workmanship and material for a period of one (1) year from the date of shipment. Your sole remedy and Variscite's sole liability shall be for Variscite, at its sole discretion, to either repair or replace the defective hardware product at no charge or to refund the purchase price. Shipment costs in both directions are the responsibility of the customer. This warranty is void if the hardware product has been altered or damaged by accident, misuse or abuse.

Disclaimer of Warranty

THIS WARRANTY IS MADE IN LIEU OF ANY OTHER WARRANTY, WHETHER EXPRESSED, OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A SPECIFIC PURPOSE, NON-INFRINGEMENT OR THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION, EXCEPT THE WARRANTY EXPRESSLY STATED HEREIN. THE REMEDIES SET FORTH HEREIN SHALL BE THE SOLE AND EXCLUSIVE REMEDIES OF ANY PURCHASER WITH RESPECT TO ANY DEFECTIVE PRODUCT.

Limitation on Liability

UNDER NO CIRCUMSTANCES SHALL VARISCITE BE LIABLE FOR ANY LOSS, DAMAGE OR EXPENSE SUFFERED OR INCURRED WITH RESPECT TO ANY DEFECTIVE PRODUCT. IN NO EVENT SHALL VARISCITE BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES THAT YOU MAY SUFFER DIRECTLY OR INDIRECTLY FROM USE OF ANY PRODUCT.

Contact Information

Headquarters:

Variscite LTD

4, Hamelacha street

Lod.

P.O.B 1121

Airport City, 70100

ISRAEL

Tel: +972 (9) 9562910

Fax: +972 (9) 9589477

Sales: sales@variscite.com

Technical Support: support@variscite.com

Corporate Website: www.variscite.com

