

POWER & BIAS




VA = filtered supply for the VCA/output

VB = 4.5V bias (U1B buffer)

LFO (U1C Schmitt + U1D integrator)




DEPTH (U1A)




U1A converts the LFO into the VCA tail current

INPUT PREAMP (Q1)




VCA & OUTPUT (discrete LM3086: Q2, Q3 + Q4)



Q2 = matched pair (LM3086 Q1/Q2), Q3 = LM3086 Q3/Q4

RV4 pin 1 intentionally open (rheostat)

OFF-BOARD WIRING



NOTES

1. SMD passives 0805 unless noted (C3 8x10.5mm electrolytic). LCSC field = JLCPCB part number.
2. Hand-soldered on the BACK side: RV1–RV3 (Omeg 16mm), SW1 (SQ/TRI toggle), D2 (3mm LED). J1–J8 are wire pads.
3. Changes from Trem-22-01: Q1/Q4(was Q6) SOT-23 pinout corrected; D5+R38 shunt replaced by series SS14 (D1); LM3086 -> 2x MBT3904DW1; C1/C5 10uF electrolytics -> 0805 MLCC; 470n and 100k parts swapped to in-stock basic parts.

Super-Freq.com
Converted from Eagle Trem-22-01 for JLCPCB SMD assembly

Sheet: /
File: Trem_23.kicad_sch

Title: Trem 23 – SMD

Size: A3	Date: 2026-09-24	**Rev: 1.0**
KiCad E.D.A. 10.0.4		Id: 1/1