


POWER & BIAS




LFO (U1C Schmitt + U1D integrator)




DEPTH (U1A)




INPUT PREAMP (Q1)




VCA & OUTPUT (discrete LM3086: Q2, Q3 + Q4)



OFF-BOARD WIRING



RANGE (U2 CD4053)



NOTES

1. SMD passives 0805 unless noted (C3 8x10.5mm electrolytic). LCSC field = JLCPCB part number.
2. Hand-soldered on the BACK side: RV1–RV3 (Omeg 16mm), SW1 (SQ/TRI toggle), D2 (3mm LED). J1–J8 are wire pads.
3. Changes from Trem-22-01: Q1/Q4(was Q6) SOT-23 pinout corrected; D5+R38 shunt replaced by series SS14 (D1); LM3086 -> 2x MBT3904DW1:
   C1/C5 10uF electrolytics -> 0805 MLCC; 470n and 100k parts swapped to in-stock basic parts.

Super-Freq.com
Converted from Eagle Trem-22-01 for JLCPCB SMD assembly

Sheet: /		
File: Trem_23.kicad_sch		
Title: Trem 23 – SMD		
Size: A3	Date: 2026-09-24	**Rev: 1.0**
KiCad E.D.A. 10.0.4		Id: 1/1