

## Stanford CME 241 (Winter 2021) - Assignment 11

### Assignments:

1. We have written the function `mc_prediction` in [rl/monte\\_carlo.py](#) as an implementation of Monte-Carlo Prediction with function approximation. You have also learnt that since Tabular MC Prediction is a special case of MC Prediction with Function Approximation and so, writing a separate function for Tabular MC Prediction is not necessary. But for a learning experience, it's a great idea to write a function for Tabular MC Prediction **from scratch**. Think about what the input and output types must be. Be sure to reduce the learning rate appropriately as a function of number of updates (or as a function of number of episodes).
2. We have written the function `td_prediction` in [rl/td.py](#) as an implementation of Temporal-Difference Prediction with function approximation. You have also learnt that since Tabular TD Prediction is a special case of TD Prediction with Function Approximation and so, writing a separate function for Tabular TD Prediction is not necessary. But for a learning experience, it's a great idea to write a function for Tabular TD Prediction **from scratch**. Think about what the input and output types must be. Be sure to reduce the learning rate appropriately as a function of number of updates.
3. Test your above implementations of Tabular MC Prediction and Tabular TD Prediction on `SimpleInventoryMRPFinite` (from [rl/chapter2/simple\\_inventory\\_mrp.py](#)) by ensuring that your Value Function output matches that produced by the function approximation versions of MC Prediction and TD Prediction.
4. Extend `RandomWalkMRP` (in [rl/chapter10/random\\_walk\\_mrp.py](#)) to `RandomWalkMRP2D` which is a random walk in 2-D with states  $\{i, j\} | 0 \leq i \leq B_1, 0 \leq j \leq B_2\}$  with terminal states as  $(0, j)$  and  $(B_1, j)$  for all  $j$ ,  $(i, 0)$  and  $(i, B_2)$  for all  $i$ , and with reward of 0 for all  $(0, j)$  and for all  $(i, 0)$ , reward of 1 for all  $(B_1, j)$  and for all  $(i, B_2)$ , and with discrete probabilities of 4 movements - UP, DOWN, LEFT, RIGHT from any non-terminal state. Analyze the convergence of MC and TD on this `RandomWalkMRP2D` much like how we analyzed it for `RandomWalkMRP`, along with plots of similar graphs.