Epileptic Seizure Detection Using Machine Learning: A Comparative Study of Class Imbalance Handling Techniques

Soha Chand
Dept. of Artificial Intelligence Engineering
Mukesh Patel School of Technology Management & Engineering,
SVKM's NMIMS
soha.chand36@nmims.in

Atharv Dixit
Dept. of Artificial Intelligence Engineering
Mukesh Patel School of Technology Management & Engineering,
SVKM's NMIMS
atharv.dixit69@nmims.in

Hima Deepthi Vankayalapati
Dept. of Artificial Intelligence Engineering
Mukesh Patel School of Technology Management & Engineering,
SVKM's NMIMS
himadeepthi.vankayalapati@nmims.edu

Abstract*—Epilepsy affects over fifty million people worldwide, and automatic seizure detection from electroencephalogram (EEG) signals is hampered by severe class imbalance: seizure windows make up only 0.65% of the windows used here (about 153:1). This study compares class imbalance techniques on the CHB-MIT Scalp EEG Database with leave-one-patient-out validation over 22 patients (809,187 two-second windows), using eleven features per channel, PCA fitted on the training patients only, and paired significance tests. The techniques are a Baseline Random Forest (RF), SMOTE+RF, Balanced RF and XGBoost; SMOTETomek, which equalled SMOTE, was evaluated only in a preliminary two-patient study. No resampling or cost-sensitive technique improved AUC-ROC (0.802–0.810) or F1 (0.095–0.107) over the plain RF; they moved the operating point instead. Per-patient feature normalisation, the context of neighbouring windows and temporal smoothing, with parameters chosen on training patients only, raised the mean AUC-ROC to 0.891 (better in all 22 patients; Wilcoxon $p < 0.001$) and the mean F1 from 0.098 to 0.283, but only 27% of the seizures (45 of 164) were detected, at 0.41 false alarms per hour, and none in nine patients. In an exploratory cross-dataset test on 8 subjects of the Siena Scalp EEG Database, the AUC-ROC rose from 0.585 with the raw features to 0.771, but only 2 of 14 seizures were detected.*

Keywords— *EEG, epileptic seizure detection, class imbalance, SMOTE, SMOTE-TOMEK, Random Forest, XGBoost, PCA, CHB-MIT, Siena, AUC-ROC, false detection rate, cross-dataset validation, temporal smoothing, leave-one-patient-out*

I. Introduction

Epilepsy is one of the most frequent chronic neurological disorders, affecting more than 50 million people of all ages [1]. Besides the risk of injury and Sudden Unexpected Death in Epilepsy (SUDEP), the unpredictability of seizures restricts driving, employment and independent living [2].

EEG remains the clinical gold standard for identifying epileptic activity, but reviewing days of continuous multi-channel recordings by hand is slow and subjective [3].

A central difficulty is the extreme class imbalance of continuous EEG: seizures are rare, and in the data used here they make up only 0.65% of the windows (a ratio of non-seizure to seizure windows of about 153:1). Standard classifiers favour the majority class, reaching high accuracy while missing seizures. Threshold-dependent metrics such as F1 are also insufficient on their own, because clinical use needs the number of false detections per hour.

The contributions of this paper are: (i) a comparison of class imbalance methods (SMOTE, SMOTETomek, Balanced Random Forest and cost-sensitive XGBoost) against a plain Random Forest, with AUC-ROC and FDR/hour as the main clinical metrics, by leave-one-patient-out validation over 22 CHB-MIT patients with paired Wilcoxon and t-tests; (ii) per-patient feature normalisation, temporal context features and a temporal smoothing step whose parameters are chosen on training patients only, with window-level and event-level results; (iii) a preliminary two-patient study with five random seeds, threshold tuning and a PCA ablation; (iv) an exploratory cross-dataset test of the models trained on 22 patients on 8 Siena subjects, with an oracle threshold analysis; and (v) 1D-CNN and MLP baselines and a real-time feasibility check (about 0.01 ms per window). The central finding is that, across patients, no resampling or cost-sensitive technique improved AUC-ROC or F1 over a plain Random Forest, whereas handling patient variability and temporal context did, although the resulting seizure detection is still far from clinical requirements.

II. Related Work

Shoeb and Guttag [4] released the CHB-MIT Scalp EEG Database together with a patient-specific SVM detector, which became a standard benchmark. Subasi and Gursoy [5] reported that PCA-reduced statistical EEG features work well with an SVM, and Acharya et al. [7] concluded that combining time- and frequency-domain features is more effective than either alone.

SMOTE was proposed by Chawla et al. [8] to oversample the minority class, but its default 1:1 target breaks down at extreme imbalance. Batista et al. [9] combined SMOTE with Tomek-link cleaning (SMOTETomek). Chen et al. [10] introduced Balanced Random Forest, which undersamples the majority class in every bootstrap sample, and Chen and Guestrin [12] XGBoost, whose scale_pos_weight parameter re-weights the minority class.

III. Methodology



Fig. 1. Overview of the proposed EEG seizure detection pipeline.

Fig. 1 summarises the pipeline.

A. Datasets

CHB-MIT [4] holds long-term scalp EEG from paediatric patients at Children's Hospital Boston, recorded at 256 Hz and annotated by experts with seizure onsets and offsets. The main evaluation uses 22 cases (chb01–chb20, chb22 and chb23). Case chb21 is a later recording of the same subject as chb01 and was excluded, so that no subject appears in both training and test data, and chb24 was not used. For each patient, all usable files that contain a seizure and up to eight evenly spaced seizure-free files were used (files lacking the common channels were skipped). This gives 809,187 two-second windows (about 450 hours), of which 5,250 (0.65%) are seizure windows. A preliminary two-patient study was run first, with chb01 and chb03 as training set (21,588 windows, 185 seizure windows, ratio 115.7:1) and chb05 as test patient (3,598 windows, 113 seizure windows, 3.1%).

Siena [14] contains recordings from 14 adult patients at the University of Siena, sampled at 512 Hz and resampled here to 256 Hz. Only subjects whose annotation list and recording files could be retrieved were used, with at most two seizure recordings per subject, giving a subset of 8 subjects with 79,860 two-second windows (464 seizure windows, 0.58%). Because Siena uses a monopolar montage, the same 18 bipolar channels as in CHB-MIT were computed by subtracting electrodes. Models trained on all 22 CHB-MIT patients are applied to this subset without retraining, as an exploratory cross-dataset test.

B. Feature Extraction

Each recording is split into consecutive, non-overlapping 2-second windows. For every channel we compute eleven features (TABLE I): seven time-domain statistics and the power in four frequency bands (delta, theta, alpha, beta), obtained with the NumPy FFT. The 22-patient evaluation uses the 18 bipolar channels present in every file (198 features per window); the preliminary two-patient study used all 23 channels (253 features).

TABLE I
EXTRACTED STATISTICAL FEATURES PER EEG CHANNEL

Feature	Description
Mean	Mean signal amplitude in the window
Variance	Variability of the amplitude
RMS	Root mean square, a measure of signal power
Skewness	Asymmetry of the amplitude distribution
Kurtosis	Heavy-tailedness; increases during seizures
Maximum	Largest positive amplitude
Minimum	Largest negative amplitude
Delta power	Band power, 0.5–4 Hz
Theta power	Band power, 4–8 Hz
Alpha power	Band power, 8–13 Hz
Beta power	Band power, 13–30 Hz

C. Dimensionality Reduction

PCA projects the features onto orthogonal directions of maximal variance. A StandardScaler and a 120-component PCA are fitted on the training windows only (on the 21 training patients in the leave-one-patient-out evaluation, and on chb01 and chb03 in the two-patient study) and applied unchanged to the held-out patient, so no test-set statistics shape the projection. In the two-patient study the 120 components explain 98.2% of the variance (Section IV-D). For Siena, the CHB-MIT PCA projection is reused, after standardising the Siena features with a StandardScaler fitted on them (raw-feature pipeline) or after the per-subject normalisation of Section III-G (improved pipeline).

D. Classification Techniques

Three tree-based learners are used. Random Forest (RF) averages many decision trees trained on bootstrap samples with random feature subsets, which reduces overfitting on noisy EEG. Balanced Random Forest (BRF) undersamples the majority class in the bootstrap sample of every tree while keeping all seizure windows, so each tree sees a balanced sample without external resampling. XGBoost builds trees sequentially, each correcting the errors of the previous ones, and its scale_pos_weight parameter increases the weight of seizure windows. They were chosen for their robustness, their ability to model nonlinear relations and their strong results on tabular EEG features.

E. Class Imbalance Handling

SMOTE counters imbalance by creating synthetic seizure windows through linear interpolation between neighbouring minority samples. Rather than the usual 1:1 balance we set the sampling strategy to 0.05, so the minority class reaches 5% of the majority class. This avoids flooding the feature space with synthetic points, which caused a collapse in precision at the original 115.7:1 ratio.

SMOTETomek combines over- and undersampling: SMOTE first creates synthetic minority samples (sampling_strategy 0.05), and Tomek links, pairs of opposite-class nearest neighbours, are then removed to clean the class boundary.

Five strategies address the imbalance: (1) Baseline RF (maximum depth 10) without correction, as the reference; (2)

SMOTE+RF with sampling_strategy=0.05; (3) Balanced RF; (4) SMOTETomek+RF, i.e. SMOTE followed by Tomek-link removal; and (5) XGBoost with scale_pos_weight set to the training imbalance ratio. The forests have 100 trees in the two-patient study and 50 in the leave-one-patient-out evaluation, and XGBoost uses 150 and 100 boosting rounds, to fit the computing budget. The imbalance ratio is 115.7:1 in the two-patient study and 40:1 in the leave-one-patient-out evaluation (after the common undersampling of Section III-H). SMOTETomek+RF removed no samples in the two-patient study and was therefore not rerun in the 22-patient evaluation. SMOTE, SMOTETomek and Balanced RF come from imbalanced-learn [11].

F. Temporal Smoothing

A seizure lasts longer than one two-second window, so isolated window-level alarms are unlikely to be seizures. We therefore average the Baseline RF probabilities of consecutive windows within a recording with a moving average of k windows and then apply a threshold τ. The pair (k, τ), with $k \in \{1, 3, 5, 7, 9, 15\}$ windows (2–30 s) and $\tau \in \{0.05, 0.10, 0.15, 0.20, 0.30, 0.40, 0.50, 0.60\}$, is chosen to maximise the mean F1 over four inner leave-one-training-patient-out folds (20-tree forests), so the held-out patient is never used for the choice. This configuration is called Baseline RF + smoothing.

G. Patient Normalisation and Temporal Context

Patient variability is a main obstacle for patient-independent detection, so we added two label-free steps. First, each feature is transformed with $\text{sign}(x)\cdot\log(1+|x|)$ and then centred and scaled for each patient with the median and interquartile range of that patient, so that the features of every patient have a comparable scale. Second, the 120 PCA scores of a window are concatenated with their moving average over five windows (10 s) within the same recording, giving 240 inputs. The 40:1 undersampling, the 50-tree Random Forest and the smoothing selection (now on the 240 inputs) are unchanged. The imbalance techniques were not rerun on these inputs. For Siena, each subject is normalised in the same way, and the smoothing parameters are the most frequent k and the median τ selected in the 22 leave-one-patient-out runs.

H. Evaluation Protocol

We report precision, recall, F1-score, AUC-ROC and FDR/hour (false-positive windows per hour of test recording, computed on the windows of the selected files). In the main evaluation each of the 22 patients is held out in turn: the scaler, PCA and all classifiers are fitted on the other 21 patients, and the held-out patient is neither subsampled nor used for any choice. To limit computation, the training negatives are randomly undersampled to 40 per seizure window (the same subset for all techniques) before the scaler and PCA are fitted. Results are given as mean±std (population standard deviation) over the 22 held-out patients at threshold 0.5 and compared with the Baseline RF by the Wilcoxon signed-rank test and the paired t-test across patients. The preliminary two-patient study instead uses five random seeds (42, 123, 456, 789, 999) on the fixed split and a paired t-test over the seeds. For event-level results, a seizure counts as detected if at least one alarm (a run of consecutive positive windows) falls inside it, and a false alarm is an alarm without any seizure window. Inference time was measured per 2-second window.

IV. Results and Discussion

A. Leave-One-Patient-Out over 22 CHB-MIT Patients

TABLE II gives the mean±std over the 22 held-out patients and TABLE III the paired tests against the Baseline RF. The AUC-ROC of the four classifiers is almost identical (0.802 to 0.810) and no difference is significant (Wilcoxon $p \geq 0.77$). The F1-score is low for all of them (0.095–0.107), also without significant differences from the Baseline RF ($p > 0.10$), and varies strongly between patients (std 0.19 for the Baseline RF). The techniques differ in their operating point at threshold 0.5. The Baseline RF and SMOTE+RF are conservative: they detect no seizure window in 15 and 13 of the 22 patients (mean recall 0.069 and 0.088, mean FDR 2.1 and 3.2/hour). Balanced RF and XGBoost detect part of the seizures in every patient (mean recall 0.521 and 0.487) but raise 184 and 174 false alarms per hour on average, more than the Baseline RF in all 22 patients ($p < 0.001$), which is not usable in practice. SMOTE+RF raises the false-alarm rate slightly (Wilcoxon $p = 0.015$, higher in 13 and lower in 3 patients; t-test $p = 0.076$) without improving F1 or AUC-ROC. After Bonferroni correction for the 21 Wilcoxon tests in TABLE III ($\alpha = 0.0024$), the significant results are the FDR differences of Balanced RF and XGBoost, the AUC-ROC gains of temporal smoothing and of the three normalised variants, and the F1 gain of the full pipeline ($p = 0.0019$); the F1 gain with context only ($p = 0.0029$) narrowly misses it.

TABLE II
LEAVE-ONE-PATIENT-OUT OVER 22 CHB-MIT PATIENTS (MEAN±STD OVER PATIENTS). BOLD = BEST MEAN.

Technique	Prec.	Recall	F1	AUC	FDR/hr
Baseline RF	0.24±0.38	0.07±0.14	0.10±0.19	0.80±0.19	2.1±7.7
SMOTE+RF	0.22±0.34	0.09±0.17	0.11±0.19	0.80±0.18	3.2±9.1
BalancedRF	0.06±0.08	**0.52±0.34**	0.10±0.12	0.81±0.16	184±180
XGBoost	0.06±0.07	0.49±0.31	0.10±0.11	0.81±0.14	174±174
Baseline RF + smoothing	0.29±0.40	0.24±0.31	0.17±0.24	0.83±0.20	20.8±60.2
RF + patient norm	0.38±0.44	0.10±0.17	0.14±0.21	0.86±0.15	**1.9±6.0**
RF + norm + context	**0.44±0.44**	0.18±0.24	0.22±0.27	0.88±0.14	3.3±9.6
RF + norm + ctx + smoothing	0.43±0.44	0.28±0.33	**0.28±0.34**	**0.89±0.15**	5.9±14.2

TABLE III
PAIRED TESTS AGAINST BASELINE RF (RAW), 22 PATIENTS: WILCOXON P / T-TEST P. BOLD = SIGNIFICANT AFTER BONFERRONI.

Technique	F1	AUC	FDR/hr
SMOTE+RF	0.110 / 0.350	0.924 / 0.633	0.015 / 0.076
BalancedRF	0.198 / 0.950	0.775 / 0.370	**<0.001 / <0.001**
XGBoost	0.222 / 0.948	0.899 / 0.727	**<0.001 / <0.001**
+ smoothing	0.075 / 0.084	**<0.001 / 0.006**	0.069 / 0.161
+ patient norm	0.041 / 0.036	**<0.001 / <0.001**	0.795 / 0.689
+ norm + context	0.003 / 0.005	**<0.001 / <0.001**	0.054 / 0.042
+ ctx + smoothing	**0.002 / 0.005**	**<0.001 / <0.001**	0.005 / 0.138

Temporal smoothing of the raw-feature Baseline RF, with the length and threshold chosen on the training patients (k = 15 windows in 11 patients, 9 in seven and 7 in four; thresholds 0.05–0.4), raises the mean AUC-ROC from 0.802 to 0.829 (median 0.883 to 0.954; better in 19 of 22 patients; Wilcoxon $p < 0.001$, t-test $p = 0.006$) and the mean F1 from 0.098 to 0.170 ($p = 0.075$ and 0.084, not significant). In chb01, for example, the Baseline RF has an AUC-ROC of 0.963 but detects nothing at 0.5, whereas smoothing reaches F1 0.658 (precision 0.728, recall 0.601, 3.7 false alarms per hour). Smoothing does not help every patient: the false-alarm rate is higher in 8 of 22 patients (mean 20.8, median 0.0 per hour) and very high in chb04 (287/hour). Fig. 2 shows that performance is patient-dependent: the AUC-ROC of the raw Baseline RF is 0.90 or higher in 11 patients but below 0.5 in three (chb06, chb12 and chb13), and it stays below 0.65 for every raw-feature technique in these three.

Patient normalisation and temporal context are the changes that help most. Normalising the features of each patient raised the mean AUC-ROC from 0.802 to 0.856 (better in 21 of 22 patients), adding the context of neighbouring windows to 0.882 (better in all 22) and smoothing to 0.891 (better in all 22; Wilcoxon $p < 0.001$ in each case). The mean F1 rose from 0.098 to 0.138, 0.217 and 0.283 (Wilcoxon $p = 0.041$, 0.003 and 0.002), and the mean recall from 0.069 to 0.281 at a mean precision of 0.43. The false-alarm rate also rose, from 2.1 to 5.9 per hour (lower than the Baseline RF in only 5 of 22 patients). The normalisation uses the label-free statistics of all selected recordings of a patient, which include its seizure files; in clinical use these statistics would have to come from a baseline period of that patient, which we did not test.

At event level, the full pipeline detected 45 of 164 seizures (27.4%), against 36 (22.0%) after normalisation alone and 40 (24.4%) with context, at a mean of 0.41 false alarms per hour (median 0.13; 0.97 and 0.82 for the two simpler variants). At least one seizure was detected in 13 of the 22 patients and none in nine (chb02, chb06, chb12, chb14–chb18 and chb20); chb12 alone has 27 seizures, none of them detected. Event-level values exist only for the new models, because the earlier runs did not store the window probabilities, and, like FDR/hour, they refer to the selected recordings, not to continuous monitoring.




Fig. 2. Per-patient AUC-ROC in leave-one-patient-out validation for the Baseline RF and the Baseline RF with temporal smoothing, both on the raw features (a line joins the two values of one patient).

B. Two-Patient Study: Statistical Robustness

In the preliminary two-patient study (training on chb01 and chb03, test on chb05), TABLE IV reports the mean±std over five seeds. On this patient the Baseline RF has the highest AUC-ROC (0.984±0.001) and F1-score (0.575±0.034) and the lowest FDR/hour (26.0±3.5), with paired t-tests $p < 0.001$ against every other technique (with five seeds the Wilcoxon p-value cannot go below 0.0625). Balanced RF reaches a recall of 1.000 but at 501.8 false alarms/hour (seed 42), and SMOTETomek+RF equals SMOTE+RF because no Tomek links were removed. The seeds change only the model randomness on a fixed split, and this ranking does not carry over to the 22-patient evaluation (TABLE II); chb05 is a patient on which the baseline does well (AUC-ROC 0.94 and F1 0.54 in that evaluation).

TABLE IV
TWO-PATIENT STUDY (CHB-MIT, TEST ON CHB05): MEAN±STD OVER 5 SEEDS

Technique	F1	AUC	FDR/hr
Baseline RF	**0.575±0.034**	**0.984±0.001**	**26.0±3.5**
SMOTE+RF	0.223±0.043	0.943±0.006	70.0±3.8
BalancedRF	0.186±0.008	0.895±0.009	496.4±25.5
SMOTETomek+RF	0.223±0.043	0.943±0.006	70.0±3.8
XGBoost	0.281±0.013	0.925±0.007	218.6±8.2

C. Threshold Tuning

Tuning the Baseline RF threshold on chb05 in the two-patient study improved the F1-score from 0.549 at the default threshold of 0.50 to 0.628 at 0.40 (recall 0.920), but the FDR rose from 28.02 to 57.03 alerts/hour; at 0.10 the recall reaches 1.000 at 409.7 alerts/hour. The alert burden must therefore be considered together with classification effectiveness. A window whose probability equals the threshold counts as a seizure, so 0.549 differs slightly from the seed-42 F1 of 0.543.

D. PCA Ablation Study

With 40, 60, 90 and 120 PCA components (explaining 85.3%, 91.2%, 95.9% and 98.2% of the variance), the Baseline

RF on chb05 (seed 42) reaches an F1-score of 0.417, 0.478, 0.576 and 0.543 and an AUC-ROC of 0.957, 0.970, 0.978 and 0.983. The F1 difference between 90 and 120 components is about one seed standard deviation (0.034 in TABLE IV), so we do not claim that either is better and use 120 throughout. Without PCA (all 253 standardised features) the RF obtains F1 0.279, AUC-ROC 0.954 and FDR 60.5/hour, and XGBoost F1 0.350, AUC-ROC 0.946 and FDR 120.6/hour, compared with 0.292, 0.925 and 224.6 for XGBoost with PCA.

E. Cross-Dataset Validation on Siena

TABLE V shows the result of training on all 22 CHB-MIT patients and testing on the 8 Siena subjects. With the raw features the transfer largely failed: the AUC-ROC of the four classifiers lies between 0.468 and 0.585, and that of XGBoost (0.468) is below chance. At threshold 0.5 the Baseline RF, SMOTE+RF and SMOTETomek+RF detect no seizure window, whereas Balanced RF and XGBoost detect 22.2% and 12.3% of the seizure windows at 178 and 214 false detections per hour. Smoothing the Baseline RF ($k = 15$, $\tau = 0.05$, chosen on CHB-MIT) gave an AUC-ROC of 0.642 and an F1 of 0.069. Normalising each Siena subject (Section III-G) raised the AUC-ROC to 0.749, to 0.759 with temporal context and to 0.771 with smoothing ($k = 15$, $\tau = 0.4$, taken from the CHB-MIT runs). The F1 of the best configuration is only 0.096 (precision 0.159, recall 0.069), and it detects 2 of the 14 seizures at 0.36 false alarms per hour (1 and 2 of 14 for the two simpler variants), so the ranking is clearly better but the detector is not usable. The SMOTETomek+RF row equals the SMOTE+RF row, as on CHB-MIT.

TABLE V
CROSS-DATASET: 22 CHB-MIT PATIENTS → SIENA (8 SUBJECTS). BOLD = BEST (FDR NOT MARKED).

Technique	Prec.	Recall	F1	AUC	FDR/hr
Baseline RF	0.000	0.000	0.000	0.585	0.05
SMOTE+RF	0.000	0.000	0.000	0.578	0.18
BalancedRF	0.013	**0.222**	0.024	0.584	178.29
SMOTETomek+RF	0.000	0.000	0.000	0.578	0.18
XGBoost	0.006	0.123	0.011	0.468	213.56
Baseline RF + smoothing	0.043	0.179	0.069	0.642	41.90
RF + subject norm	0.048	0.002	0.004	0.749	0.45
RF + norm + context	0.048	0.011	0.018	0.759	2.25
RF + norm + ctx + smoothing	**0.159**	0.069	**0.096**	**0.771**	3.81

F. Deep-Learning Baselines

In the two-patient setting, a 1D-CNN and an MLP with positive-class weighting (pos_weight = 115.7) were trained on the same 120 PCA features (five seeds). On chb05 they reached F1 0.148±0.014 (AUC-ROC 0.937±0.091, FDR 613±71/hour) and 0.239±0.064 (AUC-ROC 0.924±0.016, FDR 353±101/hour), below the Baseline RF (F1 0.575, FDR 26.0/hour). These networks are small, untuned and not evaluated on 22 patients, so they are not a limit of deep learning.

G. Discussion

There are five main results. First, across 22 held-out patients no resampling or cost-sensitive technique improved on a plain Random Forest in AUC-ROC (0.802–0.810) or F1 (0.095–0.107), and the differences are far smaller than the spread between patients (std of AUC-ROC 0.14–0.19). Second, what the techniques change is the operating point. At threshold 0.5 the Baseline RF and SMOTE+RF are silent in most patients, whereas Balanced RF and XGBoost find about half of the seizure windows at roughly 180 false alarms per hour; neither extreme is clinically useful, and the advantage of the Baseline RF seen on chb05 did not generalise. Third, handling the patient variability and the temporal context was more effective than rebalancing the training data: per-patient normalisation, neighbouring-window context and smoothing together raised the mean AUC-ROC from 0.802 to 0.891 (better in all 22 patients) and the mean F1 from 0.098 to 0.283, at the price of a higher false-alarm rate (2.1 to 5.9 per hour). Fourth, this is still not clinically sufficient: the full pipeline detected 27% of the seizures (45 of 164) and none in nine patients. Fifth, performance varies strongly between patients: with the raw features the Baseline RF reaches an AUC-ROC of 0.90 or higher in 11 of 22 patients but below 0.5 in three, so whether the features generalise to the patient matters more than the choice of imbalance technique.

AUC-ROC evaluates how well windows are ranked across all thresholds, whereas F1 is computed at one operating point, and with seizure windows at 0.65% of the data even a small false-positive rate produces many false alarms. The threshold study on chb05 shows that the operating point matters: F1 rose from 0.549 to 0.628 when the threshold was lowered from 0.50 to 0.40, and in chb01 the Baseline RF has an AUC-ROC of 0.963 but detects no seizure at 0.5. Resampling and class weighting mainly shift the predicted probabilities, which is consistent with AUC-ROC staying unchanged, whereas smoothing and context add information from neighbouring windows. The validation design also matters: the leave-one-patient-out F1 (0.10–0.28) is far below the F1 of 0.575 on chb05, which shows how optimistic a single favourable split can be.

On Siena the raw-feature models did not transfer (AUC-ROC 0.47–0.59, 0.64 with smoothing). An oracle threshold, chosen with the Siena labels and therefore only an upper bound, gave the raw Baseline RF an F1 of at most 0.082 (precision 0.058, recall 0.136, 22.9 false detections per hour), and XGBoost reaches a recall of 0.989 at 0.02 only with a precision of 0.006 and 1,764 false detections per hour, so it flags nearly every window. Normalising each Siena subject was the most effective step (AUC-ROC 0.585 to 0.749), and context and smoothing added up to 0.771, but only 2 of 14 seizures are detected. Likely causes of the remaining gap are the difference in population (adults instead of children), recording equipment and montage, the small number of Siena subjects and the limited number of training patients; we did not isolate their effects.

Limitations. Only a subset of each CHB-MIT recording was used (the seizure files and at most eight seizure-free files per patient), so FDR/hour and the event-level false alarms are not rates for continuous monitoring. To keep the run time manageable, the training negatives were undersampled to 40 per seizure window, the models were smaller than in the two-patient study, the smoothing parameters were chosen with four inner folds and 20-tree forests, SMOTETomek was not rerun and no hyper-parameters were tuned. The patient normalisation uses unlabelled statistics of the selected recordings of each patient, which include its seizure files, so its gain is probably optimistic compared with statistics from a baseline period; the imbalance techniques were not rerun on the normalised inputs; and event-level values exist only for the new models. Smoothing was applied to the Random Forest only, and its chosen length often lies at the edge of the search grid. Three patients (chb06, chb12 and chb13) have an AUC-ROC at or below chance for the raw Baseline RF, which we did not investigate. The Siena evaluation uses only the subjects whose annotation lists and files could be retrieved (annotation lists for three subjects and file names for two others could not be downloaded) and at most two seizure recordings per subject, so it is a single, noisy test of one dataset pair, and its threshold sweep uses the Siena labels. The deep-learning baselines are small and untuned, and the seed analysis of the two-patient study varies only the random seed.

V. Conclusion

This paper compared class imbalance handling techniques for EEG-based seizure detection on CHB-MIT with leave-one-patient-out validation over 22 patients, a preliminary two-patient study and an exploratory cross-dataset test on 8 Siena subjects. Across the 22 held-out patients, SMOTE, Balanced RF and cost-sensitive XGBoost did not improve AUC-ROC (0.802–0.810) or F1 (0.095–0.107) over a plain Random Forest. They only moved the operating point, from no detection in 15 and 13 patients (Baseline RF and SMOTE+RF) to about 180 false alarms per hour (Balanced RF and XGBoost). Per-patient normalisation, the context of neighbouring windows and temporal smoothing raised the mean AUC-ROC to 0.891 (better in all 22 patients) and the mean F1 to 0.283, but at event level only 45 of 164 seizures were detected, at 0.41 false alarms per hour. In the cross-dataset test the AUC-ROC rose from 0.585 to 0.771 with per-subject normalisation, context and smoothing, but only 2 of 14 seizures were detected.

In conclusion: first, the benefit of the Baseline RF seen for a single patient did not hold across patients, so imbalance techniques should be judged with patient-independent validation before conclusions are drawn. Second, patient variability and temporal context mattered more than resampling: normalising the features of each patient, adding neighbouring windows and smoothing the probabilities of a plain Random Forest improved AUC-ROC in every patient. Third, the operating point must be set with FDR/hour as a clinical constraint, and detection remains insufficient (27% of the seizures in the patient-independent setting, 2 of 14 on Siena). Future work will use baseline-period normalisation that needs no seizure data, event-level evaluation on the full recordings, retraining of the imbalance techniques on the new inputs, tuned deep models, patient-specific calibration, and an analysis of the patients for whom every technique fails.

Data and code availability: CHB-MIT and Siena are public datasets hosted on PhysioNet [4], [14]; the analysis code can be obtained from the authors on request.

Acknowledgment

We thank Children's Hospital Boston, MIT and the University of Siena for making the CHB-MIT and Siena Scalp EEG databases available on PhysioNet, and the scikit-learn, imbalanced-learn, XGBoost and SHAP communities.

References

[1] World Health Organization, "Epilepsy: Key facts," WHO Fact Sheet, Feb. 2023.

[2] P. Kwan and M. J. Brodie, "Early identification of refractory epilepsy," New England Journal of Medicine, vol. 342, no. 5, pp. 314–319, 2000.

[3] S. Ramgopal et al., "Seizure detection, seizure prediction, and closed-loop warning systems in epilepsy," Epilepsy & Behavior, vol. 37, pp. 291–307, 2014.

[4] A. H. Shoeb and J. V. Guttag, "Application of machine learning to epileptic seizure detection," in Proc. 27th ICML, 2010, pp. 975–982.

[5] A. Subasi and M. I. Gursoy, "EEG signal classification using PCA, ICA, LDA and support vector machines," Expert Syst. Appl., vol. 37, pp. 8659–8666, 2010.

[6] L. Guo, D. Rivero, and A. Pazos, "Epileptic seizure detection using multiwavelet transform," J. Neurosci. Methods, vol. 193, pp. 156–163, 2010.

[7] U. R. Acharya et al., "Automated EEG analysis of epilepsy: A review," Knowl.-Based Syst., vol. 45, pp. 147–165, 2013.

[8] N. V. Chawla et al., "SMOTE: Synthetic minority over-sampling technique," J. Artif. Intell. Res., vol. 16, pp. 321–357, 2002.

[9] G. E. A. P. A. Batista et al., "A study of methods for balancing machine learning training data," ACM SIGKDD Explor. Newsl., vol. 6, pp. 20–29, 2004.

[10] C. Chen, A. Liaw, and L. Breiman, "Using random forest to learn imbalanced data," Univ. California Berkeley, Tech. Rep. 666, 2004.

[11] G. Lemaître et al., "Imbalanced-learn: A Python toolbox," J. Mach. Learn. Res., vol. 18, no. 17, pp. 1–5, 2017.

[12] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in Proc. 22nd ACM SIGKDD, 2016, pp. 785–794.

[13] H. He and E. A. Garcia, "Learning from imbalanced data," IEEE Trans. Knowl. Data Eng., vol. 21, pp. 1263–1284, 2009.

[14] P. Detti, "Siena Scalp EEG Database (version 1.0.0)," PhysioNet, 2020. [Online]. Available: https://doi.org/10.13026/5d4a-j060