

Open Adv Message Queuing Platform - Detail Design in Google Drive, open the NonProd QM – Queues worksheet.




In the upper right select filters → Only Approved Filters




Check the Queue Names in rows Z, AA, AB, and AC to make sure everything is named OK and nothing has repeated .., example AMQP.QA2.ESGV.AVDB..RECV. Also, be sure none of the Queue Names ends with a period AMQP.QA2.ESGV.AVDB.RECV. ←

Fix any issues before moving forward.


Save worksheet as Tab delimited.



In Notepad++ change all TABS to | (pipes)



After



Save file (no need to rename)

SCP file: Adv Message Queuing Platform - Detail Design - NonProd QM - Queues.tsv From your local machine to your home directory on a1eg1vln001.ebiz.verizon.com.

Log into a1eg1vln001.ebiz.verizon.com

From your home directory run:

chmod 666 'Adv Message Queuing Platform - Detail Design - NonProd QM - Queues.tsv'

cp 'Adv Message Queuing Platform - Detail Design - NonProd QM - Queues.tsv' /home/mqm

su - mqm

cp AMQPO001A.MQSC AMQPO001A.MQSC.{Todays Date}.bak

Run the following script from /home/mgm

./Create_AMQP_MQSC_QUEUE_DEFINITIONS.ksh

Spot check AMQPO001A.MQSC to make sure new queues are defined correctly.

Check for Syntax error (Note: this checks syntax and will not pick up in incorrectly defined queues), run runmgsc -v < /home/mgm/AMQPO001A.MQSC

Good result:

Example with error – correct all error before proceeding.

```
818 : DEFINE QALIAS ('AMQP.QA.F4GV.WFLV.REQ.WD.DEV') -
                defpsist(YES) -
                targq('AMQP.QL.F4GV.WFLV.REQ.WD.DEV') -
                replace
  819 : DEFINE QALIAS('AMQP.QA2.F4GV.WFLV.REQ.WD.DEV') -
                defpsist(YES) -
                targq('AMQP.QL.F4GV.WFLV.REQ.WD.DEV') -
                replace
  820 : DEFINE QALIAS('WHS/DEV/SSL.CL.F4GV.WFLV.REQ.WD.DEV') -
                cluster(WHS/DEV/SSL) -
                put (ENABLED) -
                descr('') -
                defpsist(YES) -
                targq('AMQP.QL.F4GV.WFLV.REQ.WD.DEV') -
                replace
820 MQSC commands read.
One command has a syntax error.
[mqm@63-21-64-238 ~]$
```

```
cp AMQPO001A.MQSC /apps/etc/SSI
```

Apply SSI (be sure you are user mqm)

runmqsc AMQPO001A < AMQPO001A.MQSC

Verify there are no errors:

```
AMQ8006: WebSphere MQ queue created.
   819 : DEFINE QALIAS ('AMQP.QA2.F4GV.WFLV.REQ.WD.DEV') -
                defpsist(YES) -
                targq('AMQP.QL.F4GV.WFLV.REQ.WD.DEV') -
                replace
AMQ8006: WebSphere MQ queue created.
   820 : DEFINE QALIAS('WHS/DEV/SSL.CL.F4GV.WFLV.REQ.WD.DEV') -
                cluster(WHS/DEV/SSL) -
                put (ENABLED) -
               descr('') -
                defpsist(YES) -
                targq('AMQP.QL.F4GV.WFLV.REQ.WD.DEV') -
                replace
AMQ8006: WebSphere MQ queue created.
820 MQSC commands read.
No commands have a syntax error.
All valid MQSC commands were processed.
[mqm@63-21-64-238 SSI]$
```

All done.