```
cqlsh:students> DELETE Last_Exam_Percent FROM Students_Info WHERE Roll_No = 2;
cqlsh:students> DELETE FROM Students_Info WHERE Roll_No = 2;
cqlsh:students> ALTER TABLE Students_Info ADD hobbies SET<text>;
cqlsh:students> ALTER TABLE Students_Info ADD languages LIST<text>;
cqlsh:students> UPDATE Students_Info
            ... SET hobbies = hobbies + {'Chess', 'Table Tennis'}
            ... WHERE Roll_No = 1;
cqlsh:students> CREATE TABLE library_book (
            ...     counter_value counter,
            ...     book_name text,
            ...     stud_name text,
            ...     PRIMARY KEY(book_name, stud_name)
            ... );
cqlsh:students> UPDATE library_book
            ... SET counter_value = counter_value + 1
            ... WHERE book_name = 'Big Data Analytics' AND stud_name = 'Jeet';
cqlsh:students> CREATE TABLE userlogin (
            ...     userid int PRIMARY KEY,
            ...     password text
            ... );
cqlsh:students> INSERT INTO userlogin (userid, password)
            ... VALUES (1, 'infy') USING TTL 30;
cqlsh:students> SELECT TTL(password) FROM userlogin WHERE userid = 1;

 ttl(password)
---------------
            20

(1 rows)
cqlsh:students> COPY Students_Info TO '/home/bmscecse/Desktop/Student_Info.csv';
Using 16 child processes

Starting copy of students.students_info with columns [roll_no, dateofjoining, hobbies, languages, last_exam_percent, studname].
Processed: 4 rows; Rate:      38 rows/s; Avg. rate:      38 rows/s
4 rows exported to 1 files in 0.124 seconds.
cqlsh:students> COPY Students_Info FROM '/home/bmscecse/Desktop/Student_Info.csv';
Using 16 child processes

Starting copy of students.students_info with columns [roll_no, dateofjoining, hobbies, languages, last_exam_percent, studname].
Processed: 4 rows; Rate:       7 rows/s; Avg. rate:      11 rows/s
4 rows imported from 1 files in 0.377 seconds (0 skipped).
cqlsh:students> COPY person (id, fname, lname) FROM STDIN;
Column family person not found
cqlsh:students> COPY Students_Info TO STDOUT;
5,2012-03-11 18:30:00.000+0000,,,56.9,Rohan
1,2012-03-11 18:30:00.000+0000,"{'Chess', 'Table Tennis'}",,79.9,Asha
4,2012-03-11 18:30:00.000+0000,,,67.9,Smith
3,2012-03-11 18:30:00.000+0000,,,90.9,Shanthi
cqlsh:students>
```

```
cqlsh:employee> CREATE KEYSPACE IF NOT EXISTS Library
            ... WITH replication = {'class': 'SimpleStrategy', 'replication_factor': 1};
cqlsh:employee> USE Library;
cqlsh:library> CREATE TABLE IF NOT EXISTS Library_Info (
           ...   Stud_Id INT PRIMARY KEY,
           ...   Stud_Name TEXT,
           ...   Book_Name TEXT,
           ...   Book_Id TEXT,
           ...   Date_of_issue DATE
           ... );
cqlsh:library> CREATE TABLE IF NOT EXISTS Book_Counter (
           ...   Stud_Id INT,
           ...   Book_Name TEXT,
           ...   Counter_value COUNTER,
           ...   PRIMARY KEY ((Stud_Id), Book_Name)
           ... );
cqlsh:library> BEGIN BATCH
           ... INSERT INTO Library_Info (Stud_Id, Stud_Name, Book_Name, Book_Id, Date_of_issue)
           ... VALUES (112, 'Anjali Rao', 'BDA', 'B101', '2024-10-01');
           ...
           ... INSERT INTO Library_Info (Stud_Id, Stud_Name, Book_Name, Book_Id, Date_of_issue)
           ... VALUES (113, 'Karthik N', 'AI', 'B102', '2024-11-11');
           ... APPLY BATCH;
cqlsh:library> UPDATE Book_Counter SET Counter_value = Counter_value + 1 WHERE Stud_Id = 112 AND Book_Name = 'BDA';
cqlsh:library> UPDATE Book_Counter SET Counter_value = Counter_value + 1 WHERE Stud_Id = 112 AND Book_Name = 'BDA';
cqlsh:library> SELECT * FROM Book_Counter WHERE Stud_Id = 112 AND Book_Name = 'BDA';

 stud_id | book_name | counter_value
---------+-----------+---------------
     112 |       BDA |             4

(1 rows)
```

```
cqlsh:students> DESCRIBE TABLE Students_Info;

CREATE TABLE students.students_info (
    roll_no int PRIMARY KEY,
    dateofjoining timestamp,
    last_exam_percent double,
    studname text
) WITH additional_write_policy = '99p'
    AND bloom_filter_fp_chance = 0.01
    AND caching = {'keys': 'ALL', 'rows_per_partition': 'NONE'}
    AND cdc = false
    AND comment = ''
    AND compaction = {'class': 'org.apache.cassandra.db.compaction.SizeTieredCompactionStrategy', 'max_threshold': '32', 'min_threshold': '4'}
    AND compression = {'chunk_length_in_kb': '16', 'class': 'org.apache.cassandra.io.compress.LZ4Compressor'}
    AND memtable = 'default'
    AND crc_check_chance = 1.0
    AND default_time_to_live = 0
    AND extensions = {}
    AND gc_grace_seconds = 864000
    AND max_index_interval = 2048
    AND memtable_flush_period_in_ms = 0
    AND min_index_interval = 128
    AND read_repair = 'BLOCKING'
    AND speculative_retry = '99p';
cqlsh:students> BEGIN BATCH
            ... INSERT INTO Students_Info (Roll_No, StudName, DateOfJoining, Last_Exam_Percent)
            ... VALUES (1, 'Asha', '2012-03-12', 79.9);
            ... INSERT INTO Students_Info (Roll_No, StudName, DateOfJoining, Last_Exam_Percent)
            ... VALUES (2, 'Kiran', '2012-03-12', 89.9);
            ... INSERT INTO Students_Info (Roll_No, StudName, DateOfJoining, Last_Exam_Percent)
            ... VALUES (3, 'Shanthi', '2012-03-12', 90.9);
            ... INSERT INTO Students_Info (Roll_No, StudName, DateOfJoining, Last_Exam_Percent)
            ... VALUES (4, 'Smith', '2012-03-12', 67.9);
            ... INSERT INTO Students_Info (Roll_No, StudName, DateOfJoining, Last_Exam_Percent)
            ... VALUES (5, 'Rohan', '2012-03-12', 56.9);
            ... APPLY BATCH;
cqlsh:students> SELECT * FROM Students_Info;

 roll_no | dateofjoining                   | last_exam_percent | studname
---------+---------------------------------+-------------------+----------
       5 | 2012-03-11 18:30:00.000000+0000 |              56.9 |    Rohan
       1 | 2012-03-11 18:30:00.000000+0000 |              79.9 |     Asha
       2 | 2012-03-11 18:30:00.000000+0000 |              89.9 |    Kiran
       4 | 2012-03-11 18:30:00.000000+0000 |              67.9 |    Smith
       3 | 2012-03-11 18:30:00.000000+0000 |              90.9 |  Shanthi
```

```
cqlsh:students> SELECT * FROM Students_Info WHERE Roll_No IN (1,2,3);

 roll_no | dateofjoining                     | last_exam_percent | studname
---------+-----------------------------------+-------------------+----------
       1 | 2012-03-11 18:30:00.000000+0000 |              79.9 |     Asha
       2 | 2012-03-11 18:30:00.000000+0000 |              89.9 |    Kiran
       3 | 2012-03-11 18:30:00.000000+0000 |              90.9 |  Shanthi

(3 rows)
cqlsh:students> CREATE INDEX ON Students_Info (StudName);
cqlsh:students> SELECT * FROM Students_Info WHERE StudName = 'Asha';

 roll_no | dateofjoining                     | last_exam_percent | studname
---------+-----------------------------------+-------------------+----------
       1 | 2012-03-11 18:30:00.000000+0000 |              79.9 |     Asha

(1 rows)
cqlsh:students> SELECT Roll_No, StudName FROM Students_Info LIMIT 2;

 roll_no | studname
---------+----------
       5 |    Rohan
       1 |     Asha

(2 rows)
cqlsh:students> SELECT Roll_No AS USN FROM Students_Info;

 usn
-----
   5
   1
   2
   4
   3

(5 rows)
```