J-FALL 2026

Context Is a Budget

Eight levers and three workflow patterns for spending tokens well with coding agents.

Soham Dasgupta
DEPLOYED ENGINEER
LangChain

github.com/sohamda/ai-token-management

ONE FEATURE, TWO WAYS

Same feature. Same repo. Very different bill.

When an order total exceeds $100, the confirmation email adds "VIP customer — free shipping on your next order".

The default way

- Opus at max effort, one long session
- "Add a VIP line to the order emails"
- Raw `mvn test` output, every run

$?.??

MEASURED ON THIS REPO

The way this talk ends

- Sonnet session, Opus only to plan and review
- Scoped asks, fresh context per role
- Test output trimmed to the failures

$?.??

MEASURED ON THIS REPO

Every step between those two numbers is one of eight levers or three patterns.

SET THE STAGE

The budget is real now

Copilot · since June 1

AI Credits bill every input, output and cached token at the model's API rate. Premium requests are gone.

Claude Code

Per token on the API. On a subscription: an allowance that resets every **5 hours** and every **week**.

~$13

PER DEVELOPER PER ACTIVE DAY

Anthropic's enterprise average; 90% of users stay under $30.



Cost

An invoice, or the agent stopping for the afternoon.



Speed

Every token in the window is processed on every turn.



Quality

Recall and reasoning **degrade** as the window fills.

KNOW YOUR ENEMY

Anatomy of a request

LAYER	WHAT MAKES IT GROW
System prompt + tools	MCP servers, plugins. Small now that tools load on demand
Project instructions	`AGENTS.md`, `CLAUDE.md`, unscoped rules
Files and tool output	Broad exploration, whole-file reads, **build and test logs**
Conversation history	Every turn you don't clear or compact
Output and thinking	Narration, recaps, high effort on easy tasks: **5× the input price**

All of it is re-sent on **every turn**. Caching makes that cheap, not free.

ONE YEAR LATER

The tool does the mechanics. You own the decisions.

A YEAR AGO, YOU HAD TO…	NOW THE TOOL DOES IT	STILL YOUR CALL
Order prompts so they cache	Cache breakpoints placed for you	**Not breaking** the cache
Prune MCP tool schemas	Tools load on demand	What tools **return**
Summarise chats by hand	Auto-compaction	**When** to clear or compact
Guess, because tokens were invisible	`/context`, `/usage`, status line	**Looking**, and setting a cap
Dodge Copilot's "Opus = 10×"	Per-token billing	Model **and effort** per task

ROADMAP

Eight levers, three patterns

A
Scope the ask

B
Don't break the cache

C
Make tool output cheap

D
Codify once, load on demand

E
Right-size model and effort

F
Output discipline

G
Make the repo cheap to read

H
Read the meter, set a budget

1
Loop with state on disk
many small tasks

2
Checkpoint & reset
one long task

3
Plan → Build → Review
one feature, several roles

LEVER A · DEMO 01

Scope the ask

The agent can't ask what you meant until it has explored. Exploration is what you pay for.

Vague

```
Refactor the order confirmation email
to use the new template engine.
```

Finds the Java **and** a dead JavaScript copy, reads both, then asks which one you meant.

Scoped

```
In @…/OrderConfirmationService.java,
call render("order_confirmation_v2", …)
instead of renderLegacy.
Keep behaviour identical.
```

Two files read. One small diff.

LEVER B · DEMO 02

Don't break the cache

Every turn re-sends the whole conversation. Cached, it costs **10%** of input on Sonnet, **5%** on Opus.

Breaks it

- **Switching model** mid-session
- Coming back after it expires: **1 h** on a subscription, **5 min** on an API key
- Compaction, by design

Cache-safe

- Editing files, skills, plan mode, subagents
- `/effort` on the 5.5 models
- Editing `AGENTS.md`, but it applies only after `/clear`

LEVER C · DEMO 03

Make tool output cheap

Tool definitions load on demand now. The tax moved to what tools **return**.

Filter before the model sees it

```
# .claude/hooks/filter-test-output.sh
mvn test  →  mvn test > $log 2>&1
             awk …  # totals, BUILD, failures
             exit $rc
```

50+ lines → **3** lines. Red still reads as red.

Other ways

- **Subagents** for noisy work: only the summary comes back
- **CLIs over MCP**: `gh pr view 42`
- **Your own tools**: `{id, summary}` by default

LEVER D

Codify once, load on demand

LOADS	CLAUDE CODE	COPILOT
Every session	`CLAUDE.md` or `AGENTS.md`	`copilot-instructions.md`
Matching file touched	`.claude/rules/` + `paths:`	`*.instructions.md` + `applyTo:`
When invoked	Skills, subagents	Prompt files, skills

Keep the always-on layer short

Under 200 lines. This repo's `AGENTS.md` is 30.

Two gotchas

- Test rules scoped to `src/**` load on every production edit.
- A `CLAUDE.md` hides `AGENTS.md` unless it imports `@AGENTS.md`.

LEVER E

Right-size the model *and* the effort

MODEL	IN / OUT PER MTOK
Haiku 5.5	$0.10 / $0.50
Sonnet 5.5	$2 / $10
Opus 5.5	$4 / $20

Opus is 2× Sonnet now. Sonnet is 20× Haiku.

Effort is the cheaper knob

- The 5.5 models always think; **thinking bills as output**
- Changing effort keeps the cache. Changing model doesn't.
- Default: Sonnet · medium. Haiku for subagents.

LEVER F

Output discipline

Output costs **5× input**, then gets re-read on every later turn.

Paragraphs and a tour

```
Explain TemplateEngine.java.
```

Three lines

```
In three bullets: what does
TemplateEngine.java do, and which
method should new emails call?
```

Make it the default, in AGENTS.md

```
- Be concise. No preamble.
- Return diffs, not full files.
- Ask one targeted question instead of guessing.
```

LEVER G

Make the repo cheap to read

Claude Code greps; Copilot searches an index. Either way, dead code gets found.

This repo's trap

An old JavaScript copy of the email code. Every search for "order confirmation" finds it, and the agent reads it.

Fix it

- **Delete dead code.** Git keeps it.
- Deny what you can't delete: `Read(./target/**)`
- Three-line summary at the top of each class

LEVER H · DEMO 14

Read the meter, set a budget

```
Sonnet 5.5 · medium  |  ctx 23%  |  cache 91%  |  $0.46  |  5h 12%
```

Look

- Status line, always on
- `/context`: what's in the window
- `/usage`: cost, cache, what used it

Cap

- `--max-budget-usd` on every headless run
- Team spend limits
- `npm run lint:context` in CI

FOR COPILOT USERS


Same levers, your tool

	CLAUDE CODE	COPILOT
A	`@path`, plan mode	`#file`, `#selection`
B	cache line in `/usage`	Auto switches only at session boundaries
C	hooks, subagents, `/mcp`	tool search; filter what commands print
D	`AGENTS.md`, `.claude/rules/`, skills	`copilot-instructions.md`, `applyTo`, prompt files
E	`/model`, `/effort`, per-subagent model	model picker, reasoning level, Auto
G	deny rules, `.gitignore`	index follows `.gitignore`, content exclusions
H	status line, `/context`, `/usage`	context indicator, usage page, AI-credit budgets
1–3	`claude -p` loop, `/clear`, subagents	cloud agent per issue, new chat, prompt files

Copilot column from GitHub and VS Code docs. Check what your IDE's plugin supports.

PATTERN 1 · DEMO 08

Loop with state on disk (Ralph)



Not this

"Repeat until TODO.md is done" **inside one chat**. Item five carries items one to four.

This: `tools/ralph.sh`

```
while grep -q '^- \[ \]' TODO.md; do
  claude -p "$(cat tools/ralph-prompt.md)" \
    --model sonnet --max-budget-usd 0.50
done
```

PATTERN 2

Checkpoint & reset

Compaction is automatic. **When** you reset is your call, and the options cost very different amounts.

ACTION	COST	USE IT WHEN
`/clear`	**Free**	Switching to an unrelated task
`/rewind`	Small: reuses the cache	The last turns went the wrong way
`/compact <focus>`	Reads the whole conversation	Mid-task, continuing with less
Auto-compaction	Same, at a moment you didn't choose	You forgot the other three

PATTERN 3 · DEMO 10

Plan → Build → Review

planner
opus · high · writes plan.md

→

implementer
sonnet · medium · commit per task

→

reviewer
opus · high · verdict

Why it's cheaper

- Each subagent **starts fresh**
- Only summaries come back
- Your session **keeps its model and cache**

Fan-out isn't free

- Each subagent pays for its own context
- Agent teams: **~7× the tokens**
- Pass artifacts, never chat history

FOR A JAVA AUDIENCE

Java's token sinks

Java's build tools are chatty, and every line they print becomes context.

SINK	FIX
Maven / Gradle output	`mvn -B -ntp -q` · `gradle -q --console=plain` · or a hook
Spring Boot startup logs	`spring.main.banner-mode=off`, `logging.level.root=warn` in a dev profile
Deep stack traces	Keep frames from your own packages; drop proxy and reflection frames
Generated sources	Deny `target/generated-sources/**` (Lombok, MapStruct, OpenAPI)
Multi-module builds	`mvn -pl <module> -am test`, `-Dtest=<Class>Test`

BACK TO THE FEATURE

Where the difference came from

	DEFAULT WAY	DISCIPLINED WAY	LEVER
The ask	"Add a VIP line"	planner writes plan.md first	A · 3
Model	Opus · max, throughout	Sonnet session, Opus only to plan and review	E · B
Test output	full Maven log, every run	summary and failures	C
Context	one session, growing	fresh context per role	2 · 3
Cost	**$?.??**	**$?.??**	**H**

TAKE-HOME

If you only do three things

1

`/clear` between tasks, and name the file

Free, and it works tomorrow morning.

2

Trim what your build prints

One flag or one hook pays off on every test run.

3

Turn on the meter

A status line with context %, cache % and cost.

Full Monday checklist in the repo and the appendix.

IN ONE SENTENCE

The tool handles the mechanics. You own the decisions.



github.com/sohamda/ai-token-management

slides · demos · blog · .claude config

Questions?



APPENDIX

For questions

Calculator · anti-patterns · scaling up · Monday checklist · references

APPENDIX · CALCULATOR

What does this actually cost?

Model

Claude Sonnet 5.5 ($2 / $10)

Input tokens / request

60000

Output + thinking tokens / request

1500

Requests / day / dev

200

Developers

50

Prompt cache hit rate

0% | 50% | 90% | 95%

Per request	$0.038
Per dev / day	$7.560
Per dev / month (22d)	$166.32
Team / month	$8,316

At 90% cache hit rate you save $21,384/mo (72%) vs no caching. For scale: Anthropic reports ~$13 per developer per active day for Claude Code.

Claude API list prices (Oct 2026). Cache reads: 10% of input (Haiku, Sonnet), 5% (Opus 5.5), 2.5% (Fable 5.1); cache writes ignored. Copilot bills these same API rates since June 1.

CALL THESE OUT IN REVIEW

Anti-patterns to stamp out

What goes in

- One session for the whole day's unrelated tasks.
- Vague asks in a repo full of dead code.
- Raw `mvn test` logs and full stack traces in context.
- A new `CLAUDE.md` that silently hides `AGENTS.md`.
- `**` globs on scoped rules.

How it runs

- `/model` mid-task "just to check".
- Opus at max effort for a rename.
- A "loop" that lives inside one chat; `/loop` for batch work.
- Five subagents where one would do.
- Headless runs without `--max-budget-usd`.

APPENDIX · SCALING UP (DEMOS 11–13)

From one repo to a fleet of agents

Adapted from a production repo running ~40 specialised skills. Each layer is portable on its own.

#	LAYER	WHAT IT GIVES YOU	IN CLAUDE CODE
1	**Budget at design time**	Know the fixed cost before writing the agent	`/context` in a fresh session
2	**Progressive disclosure**	AGENTS.md → rules → skills → references	`.claude/rules/`, skills
3	**Context shredding**	Full / digest / minimal variants of each skill	pick by `ctx %`
4	**Compaction phases**	Agents summarise at 60–80% instead of drowning	`# Compact instructions`
5	**Subagent extraction**	Heavy phases run in a fresh context, return a result	`.claude/agents/`
6	**Glob targeting**	No rule loads everywhere by accident	`paths:` + `lint:glob-audit`
7	**Observability**	Measure, then lint for regressions in CI	`/usage`, OpenTelemetry, `lint:context`

APPENDIX · TAKE-HOME

The Monday checklist

This week

- [ ] One always-on instructions file under 200 lines: commands, conventions, output style.
- [ ] Both `AGENTS.md` and `CLAUDE.md`? Import with `@AGENTS.md`.
- [ ] A status line with context %, cache % and cost.
- [ ] A hook that trims test and build output.
- [ ] Delete dead code. Deny generated folders.
- [ ] Model at session start; `/clear` between tasks.

This month

- [ ] Scoped rules with narrow globs; workflows into skills and subagents.
- [ ] Haiku subagents for search and summaries.
- [ ] A headless Ralph loop over a backlog of chores.
- [ ] Planner → implementer → reviewer on one real feature.
- [ ] `--max-budget-usd` on every headless run; spend limits for the team.
- [ ] `npm run lint:context` in CI.

APPENDIX · FURTHER READING

References

Context and cost

- Anthropic — Effective context engineering for AI agents
- Claude Code — Manage costs effectively
- Claude Code — How Claude Code uses prompt caching
- Chroma — Context Rot
- Claude — Pricing
- VS Code — Improving token efficiency in GitHub Copilot

Patterns and tools

- Geoffrey Huntley — Ralph Wiggum as a "software engineer"
- Claude Code — Subagents · Hooks · Memory & AGENTS.md
- Cognition — Don't build multi-agents
- GitHub — Copilot is moving to usage-based billing
- GitHub — Getting more from each token