

A growing manufacturer of polymer compounds

Tel No:-+91-11-49901800, Website: www.peecopolytech.com

Date:- 16-08-2025

Product Test Certificate				
Grade Name		PPBPRAOE-03		
Material Description		ELV PP Parts Recycle		
Batch No.		B0225G013		
Property	Unit	Test Method	Certified Specification	PPPL Results
Physical Properties				
Density	gm/cc	ASTM D792	0.93 ~ 1.04	0.98
Melt Flow Rate @ 230°C/ 2.16 kg	gm/10 min.	ASTM D1238	16 ~ 23	19.2
Mechanical Properties				
Tensile Strength @ Yield	Kg/cm ²	ASTM D638	170 ~ 198	191.2
Elongation @ Yield	%	ASTM D638	6 ~ 8	6.4
Flexural strength	Kg/cm ²	ASTM D790	240 ~ 424	369
Flexural modulus	Mpa	ASTM D790	870 ~ 2050	1557.8
Izod Impact (Notched @ 23°C)	Kg/cm ²	ASTM D256	20 ~ 27	25.6
Thermal Properties				
Filler content (@650°C)	%	PPPL Method	10 ~ 16	14.2
Heat Deflection Temperature @ 455 Kpa	°C	ASTM D648	80 ~ 110	89.6
Chemical Substances				
Cd	PPM	XRF Screening	1000	Nd
Pb			100	38
Cr-VI			1000	Nd
Hg			1000	Nd
Br			1000	10

This is a computer- generated sheet which does not require any signature.

UNIT 1: A-88, DSIIDC NARELA INDUSTRIAL AREA, DELHI- 110040, INDIA

UNIT 2: 304, HSIIDC INDUSTRIAL AREA, REFINERY ROAD, PANIPAT, HARYANA- 132140, INDIA

UNIT 3: 537, BARHI INDUSTRIAL AREA, SONIPAT, HARYANA- 131101, INDIA