

A growing manufacturer of polymer compounds

Tel No:-+91-11-49901800, Website: www.peecopolytech.com

Date:-11-09-2025

Product Test Certificate				
Grade Name		PPUPPAOE-05		
Material Description		ELV PP Parts Recycle		
Batch No.		B0225I006		
Property	Unit	Test Method	Certified Specification	PPPL Results
Physical Properties				
Density	gm/cc	ASTM D792	0.93 ~ 1.03	0.99
Melt Flow Rate @ 230°C/ 2.16 kg	gm/10 min.	ASTM D1238	16 ~ 25	20.91
Mechanical Properties				
Tensile Strength @ Yield	Kg/cm ²	ASTM D638	198 ~ 228	203.8
Elongation @ Yield	%	ASTM D638	5 ~ 8	6.64
Flexural strength	Kg/cm ²	ASTM D790	298 ~ 455	356.4
Flexural modulus	Mpa	ASTM D790	1160 ~ 2170	1405.4
Izod Impact (Notched @ 23°C)	Kg/cm ²	ASTM D256	10 ~ 27	15.8
Thermal Properties				
Filler content (@650°C)	%	PPPL Method	10 ~ 17	16.0
Heat Deflection Temperature @ 455 Kpa	°C	ASTM D648	85 ~ 114	112
Chemical Substances				
Cd	PPM	XRF Screening	1000	Nd
Pb			100	Nd
Cr-VI			1000	Nd
Hg			1000	Nd
Br			1000	9

This is a computer- generated sheet which does not require any signature.

UNIT 1: A-88, DSIIDC NARELA INDUSTRIAL AREA, DELHI- 110040, INDIA

UNIT 2: 304, HSIIDC INDUSTRIAL AREA, REFINERY ROAD, PANIPAT, HARYANA- 132140, INDIA

UNIT 3: 537, BARHI INDUSTRIAL AREA, SONIPAT, HARYANA- 131101, INDIA