

A growing manufacturer of polymer compounds

Tel No:-+91-11-49901800, Website: www.peecopolytech.com

Date:-16-08-2025

Product Test Certificate				
Grade Name		PPUPPAOE-03		
Material Description		ELV PP Parts Recycle		
Batch No.		B0225G012		
Property	Unit	Test Method	Certified Specification	PPPL Results
Physical Properties				
Density	gm/cc	ASTM D792	0.93 ~ 1.03	0.99
Melt Flow Rate @ 230°C/ 2.16 kg	gm/10 min.	ASTM D1238	16 ~ 25	21.4
Mechanical Properties				
Tensile Strength @ Yield	Kg/cm ²	ASTM D638	198 ~ 228	217.4
Elongation @ Yield	%	ASTM D638	5 ~ 8	6.9
Flexural strength	Kg/cm ²	ASTM D790	298 ~ 455	410.2
Flexural modulus	Mpa	ASTM D790	1160 ~ 2170	1815.8
Izod Impact (Notched @ 23°C)	Kg/cm ²	ASTM D256	10 ~ 27	13.6
Thermal Properties				
Filler content (@650°C)	%	PPPL Method	10 ~ 17	14.6
Heat Deflection Temperature @ 455 Kpa	°C	ASTM D648	85 ~ 114	95.2
Chemical Substances				
Cd	PPM	XRF Screening	1000	102
Pb			100	24
Cr-VI			1000	Nd
Hg			1000	Nd
Br			1000	14

This is a computer- generated sheet which does not require any signature.

UNIT 1: A-88, DSIIDC NARELA INDUSTRIAL AREA, DELHI- 110040, INDIA

UNIT 2: 304, HSIIDC INDUSTRIAL AREA, REFINERY ROAD, PANIPAT, HARYANA- 132140, INDIA

UNIT 3: 537, BARHI INDUSTRIAL AREA, SONIPAT, HARYANA- 131101, INDIA