Langchain: Memory

Friday, February 27, 2026 5:59 PM

Recap:

Chat prompt Template →

Few Shot Chat Messages Prompt Template

Few Shot prompting

sys_temp

hum_temp

ai_temp: '{ response }'

Messages - system, Human, AI — Message prompt Templates.

. from_template(sys, hum, AI

Chat prompt Template . from_messages(

[hum_msg, sys_msg, ai_msg])

Import Few Shot Chat Messages prompt Temp

few_shot = FSCMPT(examples, example_prompt, input var)

examples = [

{ 'inp': , 'res': }

{ }

{ }

]

prompt_Temp = Chat prompt Temp. from_messages(

[few shot, human msg.]

)

prompt = promp_temp. invoke({ ✓ })

LCEL

Chain = promp_temp | LLM | parser

Chain. invoke ({ })

response = llm. invoke(prompt)

response. Content

Case Study → An application - Created - Chat prompt Temp. ✓

Memory ✓ → How to create a history ✓.

↑ How to add conv history. { add manager }

limit # conv in history.

App - Based on user description

↳ Create a web page using LLM

↓

All the code necessary to create webpage

Create a portfolio webpage using the following info (resume content)

↓

Code → creating web page

HTML ✓
CSS ✓
JS. ✓

we can

↓

parse code

↓

html

Run webpage

↓

elaborate sys prompt

↓

Code gen with demarcation

Preliminary.

↓

Sys prompt: Role - LLM

↳ Senior Front end dev good exp HTML, CSS, JS.

↳ prodn Ready.

↓

Clear instruction to LLM

Split the Code

Seperate

html
- - - - - -
CSS
- - - - - - -
JS

Code.html

Code CSS

Code. JS.

.html

↓

webpage

webpage is displayed

Code. JS.

Memory:

Why? ⇒ Create a Conv Chat → Must rember. Sem Conv.

↓ Memory

↓ Memory ⇒ Save Info

✗ langchain.memory ✗

② langchain_core ✓ → Runnables

① lang chain_community → Chat Message history

Save conv → to history.

history obj ✓ ← Save conversation

Save Items

Container

Create a history

↓

Student name & Marks

↓

Container { Key : Value } Marks