Window Memory and Adding a tool to LLM

Tuesday, March 3, 2026 6:00 PM

Recap:

Memory

1) Create memory using lang chain

↓

Chat-Message History. → memory.

In Memory Chat Message History

Container

↓

Save conver

↓

memory.add_user_message(Human)

memory.add_ai_message(AIMessage)

↓

Access this memory ⇒ memory.messages.

↓

After creating Memory

Build a Conv with LLM

↓

wont be stored in the memory.

↓

To make the Conv store in the memory.

↓

Messages Place Holder = (var_name = 'history').

↓ CPT'

element in Chat Prompt Template

↓

Save Conv → memory.

Sys. hum. ai.

Store Conv Memory

Chain = PT | LLM | parser → AIMessage

Prompt PT|str Resp

Save → [Human AI messages. ✓

Chain = PT | LLM | parser | memory]

Prompt → PT → Temp. → .invoke

PT|str → LLM → response → .invoke

Resp → parser → clean res → .invoke

Save → memory → X → X.invoke

[Human) → AI messages. ✓

part of chat prompt temp

Should be a runnable

On every runnable → allows usage of method .invoke( ).

Sth → Takes i/p → Trans → Return o/p

Runnable with Manage History

→ add the o/p from parser to Memory

✓Chain = PT | LLM | parser →

✓get_session_history → function → [ ] ← store all the user msg com

Input → history_messages_key = 'history' { } ← store

Can all → Manage place holder → Key value

all the respective user messages.

'user1' : [ ] ← add memory

'user2' : [ ] memory

Truncate messages ✓

input_message_key = ' '