Add tools to LLM and Agent

Thursday, March 5, 2026 5:58 PM

Recap.

window memory.

→ Create memory - Langchain

→ chat message history

→ Memory

→ list

Runnable with memory

Store Conv.

→ Messages placeholder

→ LLM → prev Conv Context

1) How to store single session Conv

Multi session Conv.

→ Runnable with message lambda session_id : memory.

→ Dictionary.

Keys → session ids

Value → memory

[list]

Problem.

→ LLM → Respond go thru all the Conv available in the memory. thru msg place

→ Response

Memory

→ 100 Conv.

→ Query to LLM.

→ 100 msg + query → i/p to LLM → response

→ i/p Tokens Consumed → large

To avoid large # i/p tokens

↓

window Memory.

time window

ex: past 3 conv

5 conv

10 conv

How to make window memory available to LLM.

↓

Runnable pass through

↓

Identity function

↓

Runnable

↓

add Chain.

LCEL

Chain = PT | LLM | parser

Topic → PT → prompt → LLM → resp → parser → clean response

Chain.invoke({'topic' : 'query'})

(topic) prompt → PT → prompt → LLM → resp → parser → clean string

Chain 2 : PT | Runnable PassThrough() | LLM | parser

Topic → PT → prompt → Runnable PassThrough() → Prompt → LLM → resp → parser → cleaned response

$f(x) = x$ ✓

In → x, out → x

$f(2) = 2$

i/p → 2, o/p → 2