Customizing LLMs

Tuesday, February 17, 2026 6:00 PM

Recap:

Functionality → Chat

→ Chat bot → Memory } Content Understand.

client = genai.Client()

✓ Chat = client.chats.create(
model: 'gemini-2.5-flash'.
) } chat_obj

Chat.

Chat.send_message(' ')

→ Interact with LLM

→ Stored in memory.

Chat.get_history()

user input:
LLM resp:
user inp
LLM resp
⋮

Conv stored

→ Interaction → Content aware Interaction

→ Req for Multi turn Conv Chat bots

Creating Front end → Streamlit

→ Chatbot → QA application

client = - - - - - ✓

user-promp = - - - -

Run-1

~~Hello~~

Run-2

Memory (session)

✓ I am Sreeram

user-promp = ____

chat object

res = chat_obj.send_message(user prompt)

print(resp)

Run-3.

Context

Saved

Stores session

St. session_state.

Hello

Chat obj

Hello

LLM resp.

history X

I am Sreeram

New Chat obj

Memory

No new

No new hist

I am Sreeram

LLM → memory

as it is a

history

Save

old history.

Customizing LLMs.

→ Control Beh of LLM

1) prompt-engg. — System, User

2) Controlling param of LLM.

Temp

top-p

top-k

3) Prompt chaining.

Adv prompt engg.

prompt elaborate way

seq of steps.

4) Fine Tuning of LLMs.

New data

Model

retrain LLM

New data

RAG

Costly

Computation