
PA Amplifier NT - 60APA







PA Amplifier (NT-60APA)

The NT-60APA is a professional power amplifier designed for public address (PA) and background music systems, with higher-power variants available for larger installations. It features 3 microphone inputs, 2 auxiliary inputs, and 1 AUX output, making it suitable for announcements, live speaking, and audio playback. The amplifier supports both 70V/100V constant voltage and $4-16\Omega$ outputs, ensuring compatibility with various speaker configurations. Advanced functions include 4-zone independent volume control, USB playback for stored audio files, and an emergency broadcast override for priority announcements. Built-in protection mechanisms like short-circuit and overheat alarms safeguard the system, while a limiter prevents audio distortion. With timed power control and a 5-LED display for easy monitoring, this amplifier is ideal for commercial spaces, schools, and emergency broadcast systems.

TECHNICAL DATA SPECIFICATION

Model	NT-60APA
Line Voltage:	70-100 v
Impedance:	4-16 Ω
Rated Power:	60 W
Zone:	4
Dimension (mm):	485x360x90
Weight (kg):	7.48 KG
Gross Weight (kg):	8.48 KG
Panel Color:	Silver/Black

KEY FEATURES

The LPA-60A power amplifier offers professional audio performance with multiple connectivity options including 3 microphone inputs, 2 AUX inputs and 1 AUX output, supporting both 70V/100V constant voltage and 4- 16Ω outputs for flexible system integration.

QUICK GUIDE

Simply connect your microphones or audio devices, adjust the 4-zone independent volume controls, and use the USB port for playback. Enable the emergency broadcast override when needed, and rely on the built-in short-circuit and overheat protection for safe operation.

