

Professional Speaker

NT-(168 APS+168 BPS+168 CPS)



Professional Speaker (NT-168 APS+168 BPS+168 CPS)

This high-performance two-way speaker features a dual-driver full-range design with 90°×55° wide dispersion for superior coverage. Engineered with computer-optimized acoustics, it delivers high sound pressure, excellent frequency response, and clear audio for bars, clubs, and live events. Compatible with 350W–1000W amplifiers and subwoofers, it works as a main PA, monitor, or fill speaker in both fixed installations and mobile setups. Ideal for DJs, live sound, and large venues requiring powerful, distortion-free sound.

TECHNICAL DATA SPECIFICATION

Model	NT-168 APS	NT-168 BPS	NT-168 CPS
System:	2-WAY FULL RANGE	2-WAY FULL RANGE	2-WAY FULL RANGE
Frequency response:	55Hz-18KHz	50Hz-18KHz	45Hz-18KHz
Driver:	LF : 10" x 1 HF:1"x1	LF : 12" x 1 HF:1"x1	LF : 15" x 1 HF:1.5"x1
Nominal impedance:	8Ω	8Ω	8Ω
Sensitivity:	97dB	97dB	98dB
Rated Power:	250W	350W	500W
Maximum:	123dB	123dB	125dB
Size (mm):	300x303x503	368x400x605	410x463x685
Package size (mm):	360x362x575	460x455x710	522x495x800
Net weight (kg):	16.5	23.5	35
Gross weight (kg):	17.5	26	38.1

Key Features

This professional two-way PA speaker system delivers powerful, high-fidelity sound through its dual-driver full-range design, featuring 90°×55° wide dispersion for optimal coverage and computer-optimized acoustics for crystal-clear audio reproduction. With high sound pressure levels and excellent frequency response, it's versatile enough for use as main PA, monitor, or fill speaker in bars, clubs, and live events. The system pairs seamlessly with subwoofers and works with 350W-1000W amplifiers, offering flexible deployment options for both permanent installations and mobile setups. Its road-ready construction ensures reliable performance for DJs, bands, and sound engineers needing professional-grade sound reinforcement in demanding environments.

