SOTA



- Resolving P ² NP has proven extremely difficult
- In the past 50 years:
 - Not a single correct proof either way has been found
 - Many types of proofs have been shown to be insufficiently powerful to determine whether $P \stackrel{?}{=} NP$
- Most(?) computer scientists believe P ≠ NP

Korea Institute of Energy Technology 2022-05-10


37



Sub-Classes in NP



- Problems in NP vary widely in their difficulty, even if P = NP
- How can we rank the relative difficulties of problems?




Korea Institute of Energy Technology 2022-05-10

39

Maximum Matching Problem




- Given an undirected graph G, a matching in G is a set of edges such that no two edges share an endpoint
- A maximum matching is a matching with the largest number of edges.




Korea Institute of Energy Technology 2022-05-10

40








Korea Institute of Energy Technology 2022-05-10

41

Domino Tiling Problem



ullet Given an $n \times m$ board with blocks, tile as many 2 imes 1 dominos as possible




Korea Institute of Energy Technology 2022-05-10

42

Domino Tiling





the more dontino passible

Is this optimal?

NO


Korea Institute of Energy Technology 2022-05-10

43

43

Domino Tiling





Optimal


Relation between maximum matching and domino tiling?

Korea Institute of Energy Technology 2022-05-10

44

Domino Tiling





Transformation

think each block = node

Leonneuted by link

Represent an empty square as a node Connect adjacent empty squares with an

Suppose you place a horizontal domino on right bottom corner Then you can not place dominos as shown

→ Maximum matching problem


Korea Institute of Energy Technology 2022-05-10

45

45


Domino Tiling





Korea Institute of Energy Technology 2022-05-10

46



Relative Difficulty



```
bool canPlaceDominos (Grid G, int k) {

return hasMatching (GridToGraph(G), k);

Among Domino tiling & MM problems,
which one is easier (or more difficult)?
```

Domino tiling can't be "harder" than maximum matching, because if we can solve maximum matching efficiently, we can solve domino tiling efficiently


Korea Institute of Energy Technology 2022-05-10 48

Another Example: Reachability



• Reachability problem:

Given a directed graph G and nodes s and t in G, is there a path from s to t?



- It's known that this problem can be solved in polynomial time (use DFS or BFS)
- Given that we can solve the reachability problem in polynomial time, what other problems can we solve in polynomial time?

Korea Institute of Energy Technology 2022-05-10

49

Converter Conundrums



- Suppose that you want to plug your laptop into a projector
- Your laptop only has a VGA output, but the projector needs HDMI input
- You have a box of connectors that convert various types of input into various types of output (for example, VGA to DVI, DVI to DisplayPort, etc.)
- Question: Can you plug your laptop into the projector?
 - Use as many converters as necessary
 - Minimum number of converters


Korea Institute of Energy Technology 2022-05-10 50

Converter Conundrums



Converters

- RGB to USB node
- VGA to DisplayPort
- DB13W3 to CATV
- · DisplayPort to RGB
- DB13W3 to HDMI
- DVI to DB13W3
- S-Video to DVI
- FireWire to SDI
- VGA to RGB
- DVI to DisplayPort
- · USB to S-Video
- · SDI to HDM




Korea Institute of Energy Technology 2022-05-10

51

51

Converter Conundrums





52

Relative Difficulty



```
bool canPlugIn (List<Plug> plugs) {
   return is Reachable (plugs To Graph (plugs), VGA, HDMI;
}
```

Among PlugIn & Reachability problems, which one is easier (or more difficult)?

PlugIn can't be "harder" than the reachability problem, because if we can solve reachability efficiently, we can solve PlugIn efficiently

Korea Institute of Energy Technology 2022-05-10

53

53



Polynomial-Time Reduction



bool problemA (input) { $A \rightarrow B$ return problemB(transform (input)); }

Problem A can't be "harder" than problem B, because solving problem B lets us solve problem A

• If A and B are problems where it's possible to solve A by transforming it into B (in polynomial time) and solve B, we write


$$A \leq_p B$$
 \rightarrow A con't be harder than B.

- **O**A is polynomial-time reducible to B
- The \leq_p relation ranks the relative difficulties of problems


Korea Institute of Energy Technology 2022-05-10 55

Polynomial-Time Reduction





56





57

NP-Hardness




- If $A \leq_p B$, then problem B is at least as hard as problem A
- To show that some problem is hard, show that lots of other problems reduce to it
 - To show that B is hard, find other problems that can be reduced to B

Korea Institute of Energy Technology 2022-05-10

NP-Hardness



• A language L is called **NP-hard** if for every $A \in NP$, we have $A \leq_p L$



L has to be at least as hard as every problem in NP, since an algorithm for L can be used to decide all problems in NP


Korea Institute of Energy Technology 2022-05-10

59

59

NP-Completeness






- ullet A language L is called ullet if for every $A \subseteq \mathbb{NP}$, we have $A \leq_p \mathbb{LP}$
- ullet A language in L is called **NP-complete** if L is NP-hard and L \in NP
- The class **NPC** is the set of NP-complete problems

Korea Institute of Energy Technology 2022-05-10

60

NPC





Korea Institute of Energy Technology 2022-05-10


61

61

P=NP




• Theorem: If any NP-Complete language is in P, then P=NP



Korea Institute of Energy Technology 2022-05-10

62



P=NP



• Theorem: If any NP-complete language is in P, then P = NP

o Proof:

- Suppose that L is NP-complete and $L \in P$
- Consider any arbitrary NP problem A
- Since L is NP-complete, $A \leq_p L$
- Since $L \in P$ and $A \leq_p L$, $A \in P$
- Since A was arbitrary chosen, $NP \subseteq P$

\rightarrow P = NP



Korea Institute of Energy Technology 2022-05-10

64

P≠NP



- Theorem: If any NP-complete language is not in P, then P ≠ NP
- Proof:
 - Suppose that \boldsymbol{L} is an NP-complete language not in P
 - Since L is NP-complete, $L \in NP$
 - Therefore, $L \in NP$ and $L \notin P$



Korea Institute of Energy Technology 2022-05-10

65



Question?



OHow do we even know NP-Complete problems exist?

Korea Institute of Energy Technology 2022-05-10

67

Satisfiability



- A propositional logic formula φ is called satisfiable if there is some assignment to its variables that makes it evaluate to true
 - p ∧ q is satisfiable
 - p ∧ ¬p is unsatisfiable
 - $p \rightarrow (q \land \neg q)$ is satisfiable
- ullet An assignment of true and false to the variables of ϕ that makes it evaluate to true is called a satisfying assignment

Korea Institute of Energy Technology 2022-05-10

SAT



- The boolean satisfiability problem (SAT) is the following: Given a propositional logic formula φ , is φ satisfiable?
- Formally: SAT = $\{\langle \varphi \rangle \mid \varphi \text{ is a satisfiable PL formula }\}$

Korea Institute of Energy Technology 2022-05-10

69

$SAT \in NP$



- To show that SAT ∈ NP, need to show that verification takes polynomial time
- Theorem (Cook-Levin): SAT is NP-complete
- Proof Idea:
 - A certificate (T/F assignment of each variable) is given
 - To show that SAT is NP-hard, given a polynomial-time verifier V for an arbitrary NP language L, for any string w you can construct a polynomiallysized formula $\varphi(w)$ that says "there is a certificate c where V accepts $\langle w, c \rangle$."
 - This formula is satisfiable if and only if $w \in L$, so deciding whether the formula is satisfiable decides whether w is in L

Korea Institute of Energy Technology 2022-05-10

SAT



- Resolving P $\stackrel{?}{=}$ NP is equivalent to just figuring out how hard SAT is
- If SAT ∈ P, then P = NP
- o If SAT ∉ P, then P ≠ NP

Korea Institute of Energy Technology 2022-05-10

71

71

NP-Hard Problems



- Computational biology: Given a set of genomes, what is the most probable evolutionary tree that would give rise to those genomes? (Maximum parsimony problem)
- Game theory: Given an arbitrary perfect-information, finite, twoplayer game, who wins? (Generalized geography problem)
- Operations research: Given a set of jobs and workers who can perform those tasks in parallel, can you complete all the jobs within some time bound? (Job scheduling problem)
- Machine learning: Given a set of data, find the simplest way of modeling the statistical patterns in that data (Bayesian network inference problem)
- Medicine: Given a group of people who need kidneys and a group of kidney donors, find the maximum number of people who can end up with kidneys (Cycle cover problem)
- Systems: Given a set of processes and a number of processors, find the optimal way to assign those tasks so that they complete as soon as possible (Processor scheduling problem)

72

Korea Institute of Energy Technology 2022-05-10

NP-Intermediate



- With few exceptions, every problem we've discovered in NP has either
 - definitely been proven to be in P, or
 - definitely been proven to be NP-complete
- A problem that's NP, not in P, but not NP-complete is called NPintermediate
- Theorem (Ladner): There are NP-intermediate problems if and only if $P \neq NP$.

Korea Institute of Energy Technology 2022-05-10

73