Package 'Satisficing'

October 17, 2026

Type Package

Title Tools for Detecting Indicators of Survey Satisficing

Version 0.1.0

Description Provides tools for detecting potential indicators of satisficing in survey responses, including straight-line response patterns and row-wise evaluation of logical conditions.

License GPL (>= 2)

URL https://github.com/soheidon/Satisficing

BugReports https://github.com/soheidon/Satisficing/issues

Encoding UTF-8

Roxygen list(markdown = TRUE)

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Config/roxygen2/version 8.1.1

Contents

matching 1
rawnn 2
stline 3

Index **4**

`matching` *Identify Rows Matching a Logical Condition*

Description

Evaluates a logical condition within the context of a data frame and adds an integer column indicating which rows satisfy the condition.

Usage

```
matching(data, condition, result_col = "match")
```

Arguments

data	A data frame.
condition	An expression to evaluate within data. Must evaluate to a logical vector whose length is exactly nrow(data).
result_col	A non-empty character string specifying the name of the result column. Defaults to "match". Must not conflict with existing columns in data.

Value

The input data frame with an additional integer column indicating whether each row satisfies the condition:

- 1L: The condition evaluated to TRUE.
- 0L: The condition evaluated to FALSE.
- NA_integer_: The condition evaluated to NA.

Examples

```
df <- data.frame(ID = c(1, 2, 3, 4), Value = c(10, 20, 30, 40))
matching(df, Value > 20)
```

---

rawnn *Print Column Names with Indices*

Description

Prints the column names of a data frame along with their respective 1-based indices, formatted as 'index: column_name'.

Usage

```
rawnn(dataframe)
```

Arguments

dataframe	A data frame whose column names are to be printed.

Value

invisible(NULL). Called for its side effect of printing.

Examples

```
rawnn(mtcars)
```

stline *Check for Straight-Line Responses Across Specified Columns*

Description

Evaluates each row across specified columns in a data frame to identify straight-line responses (identical answers across items).

Usage

```
stline(
  data,
  columns,
  result_column_name = "straight_line",
  exclude_values = NULL
)
```

Arguments

data	A data frame. Must not contain duplicate column names.
columns	A non-empty character vector of unique column names existing in data.
result_column_name	A non-empty character string specifying the name of the result column. Defaults to "straight_line". Must not conflict with existing columns in data.
exclude_values	An optional atomic vector of values to exclude from straight-line detection. If identical values match any value in exclude_values, the result is 0. Defaults to NULL.

Value

The input data frame with an additional integer column indicating whether the row is a straight-line response:

- 1L: At least two non-missing values are identical and not excluded.
- 0L: Non-missing values vary across columns, or identical values match exclude_values.
- NA_integer_: The row has 0 or 1 non-missing value.

Examples

```
df <- data.frame(
  q1 = c(1, 1, 1, 2, NA),
  q2 = c(1, 1, 2, 2, NA),
  q3 = c(1, 2, 3, 2, 1)
)
stline(df, c("q1", "q2", "q3"))
```

Index

matching, 1

rawnn, 2

stline, 3