

Microservices vs Monolithic Architecture

This document provides a comparative analysis between **Monolithic Architecture** (specifically *Modular Monoliths*) and **Microservices Architecture**, framed within the context of software engineering and Domain-Driven Design (DDD).

---

1. Overview of Architectural Paradigms





2. Monolithic Architecture

A **Monolith** is an architectural pattern where all software components, business modules, and layers (presentation, business logic, data access) are packaged and deployed together as a **single runnable process / executable unit**.

Modular Monolith (A Clean Approach)

A *modular monolith* structures the internal codebase into well-defined, decoupled domain boundaries (modules/packages) following DDD principles, while maintaining a single deployment artifact and runtime process.

Advantages

- **Simplicity of Development & Debugging:** Running, stepping through code, and testing end-to-end requires no complex distributed networking or multiple containers.
- **Transactional Consistency (ACID):** Cross-module workflows can easily rely on local in-memory calls and single database transactions without needing distributed consensus or saga patterns.
- **Lower Operational Overhead:** Requires minimal infrastructure (single CI/CD pipeline, single server/container, no service mesh or complex distributed tracing).
- **High Performance for Inter-Module Calls:** Communication between domains happens via local function/method calls in memory rather than HTTP/gRPC network overhead.

Disadvantages

- **Tight Coupling Risks:** Without strong discipline, boundaries easily erode into "spaghetti code" or a Big Ball of Mud.
- **Single Point of Failure:** A fatal runtime crash or memory leak in one module can crash the entire application process.
- **Coarse-Grained Scaling:** Scaling requires replicating the entire application, even if only one specific endpoint/module is bottlenecked.
- **Unified Tech Stack:** All modules must conform to the same programming language, runtime, and primary framework.

---

3. Microservices Architecture

A **Microservices Architecture** structures an application as a collection of small, autonomous, loosely coupled services. Each service models a specific **Bounded Context**, maintains its own private data store (*Database-per-Service* pattern), and communicates via network protocols (HTTP REST, gRPC, or asynchronous message brokers).

Advantages

- **Independent Deployability:** Teams can deploy, update, and rollback individual services without coordinating releases across the entire organization.
- **Targeted & Independent Scalability:** High-demand services (e.g., product catalog browsing) can scale out dynamically without allocating extra resources to low-demand services (e.g., checkout/order creation).
- **Fault Isolation:** A failure or performance degradation in an auxiliary service does not bring down the entire system.
- **Technology Diversity:** Teams can choose the optimal programming language, database engine, and runtime suited for each specific bounded context.
- **Organizational Alignment:** Maps naturally to autonomous, cross-functional engineering teams (Conway's Law).

Disadvantages

- **Distributed System Complexity:** Introduces network latency, partial failures, circuit breakers, and network partitioning challenges.
- **Data Consistency Challenges:** Replaces simple ACID transactions with eventual consistency, two-phase commits, or complex Saga orchestration/choreography patterns.
- **Operational & Infrastructure Overhead:** Requires container orchestration (Kubernetes), distributed tracing (OpenTelemetry, Jaeger), centralized logging, service discovery, and complex CI/CD matrices.
- **Complex Testing:** Comprehensive integration and end-to-end testing across asynchronous, network-separated components is significantly harder.

---

4. Key Comparison Summary

Metric / Dimension	Monolithic Architecture (Modular)	Microservices Architecture
Deployment Unit	Single executable / container / process	Multiple independently deployed services
Communication	In-memory function/method calls	Network protocols (HTTP, gRPC, Message Broker)
Data Storage	Shared database or schema-separated DB	Database-per-service (strictly private data stores)
Transaction Model	ACID transactions (immediate consistency)	Eventual consistency (Saga pattern, Outbox pattern)
Scalability	Scale the whole instance vertically/horizontally	Granular, per-service horizontal autoscaling
Operational Complexity	Low (standard deployment, simple logs)	Very high (Kubernetes, distributed tracing, service mesh)
Team Structure	Best for small-to-medium teams (< 15-20 devs)	Best for large organizations with multiple independent teams
Failure Blast Radius	High (process crash affects all features)	Low (isolated per service, degraded modes available)

---

5. Architectural Recommendation for MiniOrder

For the **MiniOrder** educational project: - Starting as a **Modular Monolith** is the optimal design choice. - It enables mastering **Domain-Driven Design (DDD)** concepts, defining domain boundaries, and modeling bounded contexts without incurring distributed systems tax (network unreliability, serialization overhead, and distributed debugging). - Clear internal module boundaries allow transitioning to microservices later when scaling or organizational needs genuinely require it.