

CHRONIOPOST

Interface

Technical specifications

Data flows

Table des matières

1	INTRODUCTION.....	3
1.1	Document purpose.....	3
1.2	Related documents	3
2	FILE FORMAT ORGANISATION	3
2.1	General organization.....	3
2.2	File naming.....	4
3	FUNCTIONAL RULES.....	4
3.1	Pre-alerts	4
3.2	File Structure	5
3.3	Character set.....	6
3.4	Triggering.....	6
4	SPECIFICATIONS	6
4.1	Convention	6
4.1.1	CONSOLIDATION data flow	6
4.1.1.1	Subtype FILE	6
4.1.1.2	Subtype ENCODING	7
4.1.1.3	Subtype VERSION	7
4.1.1.4	Subtype DEFINITION	7
4.1.1.5	Subtype HEADER.....	7
4.1.1.6	Subtype CONSOLIDATION	7
4.1.1.7	Subtype SHIPMENT.....	10
4.1.1.8	Subtype SENDER.....	15
4.1.1.9	Subtype RECEIVER	19
4.1.1.10	Subtype INTER	24
4.1.1.11	Subtype PARCEL.....	32
4.1.1.12	Subtype INTERINVOICELINE	36

1 INTRODUCTION

1.1 Document purpose

This document describes the technical specifications for the IT interface between a Customer and CHRONOPOST INTERNATIONAL, in order to prealert the international parcels over EDI means.

This document is a master document of a set of documents for pre-alerting and labeling parcels and support (see bellow related document) within GEOPOST world.

1.2 Related documents

Id	Name	Reference	Vers.	Date	Owner
R1	Label description	Doc Etiquette ROW-FR-ROE GB_V25.01.pdf + Gestion routage GB-IE-JE-NL-PT .pdf	V15.03	27/01/25	CHR

2 FILE FORMAT ORGANISATION

2.1 General organization

The file is made of a set of different “sub-type” (set of data) organized in a defined hierarchical order.

Each sub-type is built with a set of coherent information which describes a functional point as “sender”, “receiver”, “parcel”,..

The GEODATA file format can carry different functional data flow. The type of data flow is specified into the header sub-type.

This document only describes the Customer Declaration of Shipments Flow.

Please note that this document is a subset of Generic “CONSOLIDATIONPREALERT” (or shortly “CONSO”)

message, applied to Hybrid Injection trafic :

- parcels injected to Chronopost France network for EU Delivery

2.2 File naming

Files are named as follow:

`GEODATA_<DATAFLOW>_<SOURCE>_<DESTINATION>_D<yyyyMMdd>T<HHmmss>_ccccc`

where:

DATAFLOW : CONSO for pre-alerts flow

SOURCE : code of the sender (Chronopost account number). Will be provided by Chronopost Customer Integration Team

DESTINATION : code of the receiver: "CHR"

yyyyMMdd : Year, month, day of the generation of the file

HHmmss : Hour, minute, second of the generation of the file

ccccc : unique number used for file generated in the same Date/time

3 FUNCTIONAL RULES

3.1 Pre-alerts

Pre-alerts flow is formatted according GEOPOST requirements with the classification "CONSOLIDATIONPREALERT" (or shortly "CONSO")

This flow is flat, with a header and several sub-types, fields with variable length, separated by semi-colon.

Mainly files are breakdown as:

- HEADER section
- BODY section
- END section

Each lines of the HEADER section starts by "#" (sharp). HEADER section is made of:

- FILE description
- ENCODING description
- VERSION description
- DEFINITION description

BODY section is spited into subtypes as:

- HEADER
- CONSOLIDATION
- SHIPMENT
- SENDER
- RECEIVER
- INTER
- INTERINVOICELINE
- PARCEL

End BODY section is:

#END

3.2 File Structure

For a pre-alert made by one flight, n expeditions (single piece or multi-pieces of m parcels), there will be:

FILE ¹

ENCODING ¹

VERSION ¹

DEFINITION ¹

HEADER ¹

CONSOLIDATION ¹

SHIPMENT ⁿ

SENDER ¹

RECEIVER ¹

INTER ^{0,1}

INTERINVOICELINE ^{0,99}

PARCEL ^{1,m}

3.3 Character set

ISO 8859-1 is supported.

Nevertheless it is recommended to use ISO 646 (ASCII 7 bits) reduced to (with regular expression syntax):

- [0-9A-Z ,.()@]

Decimal separator is “.” (point).

3.4 Triggering

The flow is synchronized with loading operation.

Usually, one flow is generated for each loading.

4 SPECIFICATIONS

4.1 Convention

In the following:

A is for Alphabetic

N is for Numerical

AN is for Alpha Numerical

Void means empty field

A.5 means from 0 to 5 alphabetical characters. So can be void.

N1.5 means a number of 1 to 5 numerical, void not allowed.

M: mandatory

O: optional

C: condition

4.1.1 CONSOLIDATION data flow

4.1.1.1 Subtype *FILE*

GEODATA fields	Format	Notes
FILE	A..128	Name of the file

4.1.1.2 Subtype *ENCODING*

GEODATA fields	Format	Notes
ENCODING	A..128	Constant « ISO-8859-1 »

4.1.1.3 Subtype *VERSION*

\$GEODATA fields	Format	Notes
VERSION	A..128	Constant « 03.32 »

4.1.1.4 Subtype *DEFINITION*

Can be seen as constant lines. It should drive the decoding of the next lines. See attached file

4.1.1.5 Subtype *HEADER*

One line HEADER per file.

Token	Length	Data type	Optional mandatory	Description
GEODATA:HEADER	6	A	M	Subtype identification (always = "HEADER")
VERSION	5	NN.NN	M	GeoData version : 03.32
CLASSIFICATION	35	A	M	Classification of the data flow (always = "CONSO")

4.1.1.6 Subtype *CONSOLIDATION*

One CONSOLIDATION per file.

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:CONSOLIDATION	13	A	M	Subtype Identification (always = "CONSOLIDATION")
002	NUMORDER	2	N	M	Fixed numerical value (always = 2). Value is provided by the dataflow chosen Defines the

					hierarchical order of the subtype
003	MAWB	12	AN	C	Master-Airwaybill (the first three numbers mark the airline e.g.020-31804625 020 = Lufthansa). Mandatory for air traffic. For non air it must be the swap body/trailer number (number on the back)
004	MAWBDATE	8	N	C	date of MAWB (YYYYMMDD). Mandatory for air traffic.
005	FLIGHTNO	18	AN	C	3 flight numbers MAX. Mandatory for air traffic.
006	FAIR	3	AN	C	from airport, IATA Code. Mandatory for air traffic.
007	TAIR	3	AN	C	to airport, IATA Code. Mandatory for air traffic.
008	LINEHAUL	2	AN	M	AI=Air; RO=Road; SE=Sea
009	DEPDATETIME	14	N	C	Estimated date and time of flight departure (YYYYMMDDhhmmss). Depending of the type of traffic at least for air traffic (not always possible to set).
010	ARRDATETIME	14	N	C	Estimated date and time of flight arrival (YYYYMMDDhhmmss). Depending of the type of traffic at least for air traffic.
011	BAGMAWB	4	N	O	number of bags per MAWB
012	FREIGHTPOSITION	6	N	O	Position on freight list.
013	CGATEWAYEXP	7	AN	M	Constant : "0029999"
014	CGATEWAYIMP	7	AN	C	Constant : "0020456"

015	OPCODE	3	AN	M	Constant "INS"
016	FREIGHTSEQ	12	N	O	Sequential number of the freight list to be put into the MAWB
017	LORRY	20	AN	C	Lorry number (registration number of the truck or trailer) Become mandatory for LINEHAUL=RO
018	CCCREF	25	AN	O	Collective customs clearance (Break Bulk brokerage): consolidation reference number
019	MAWBDEADWEIGHT	8	N	O	Master-Airwaybill total weight in Grams units without decimal delimiter (e.g. 3000 equals 3kg).
020	MAWBVOLUMETRICWEIGHT	9	N	O	Total volumetric weight of the MAWB in gram units without decimal delimiter (e.g. 300000 equals 300kg).
021	SEALNUMBER	128	AN	C	Field to define the seal number of the Linehaul, it becomes mandatory if LINEHAUL field is RO
022	CONSOMRN	18	AN	C	MRN of the electronic export declaration, it becomes mandatory if LINEHAUL field is RO
023	TRANSPORTCOST	15	N.N	O	Custom transport cost Separator is "." (point). The number of decimal will depend of the currency (it could be from 0 to three digit). (documents = 0) Data in this field to be captured based on the rules of each BU
024	TRANSPORTCOSTCUR	3	AN	O	Currency for conversion of transport cost Data in this field to be

					captured based on the rules of each BU
025	SEALOADPORT	5	AN	C	Loading port of the vessel if the linehaul is a boat. Becomes mandatory if LINEHAUL field is SE. Port name is in 5 characters according to the port naming international norm
026	SEADISCPORT	5	AN	C	Discharge port of the vessel if the linehaul is a boat. Becomes mandatory if LINEHAUL field is SE. Port name is in 5 characters according to the port naming international norm
027	SEAVESSELNAME	70	AN	C	Name of the vessel if the linehaul is a boat. Becomes mandatory if LINEHAUL field is SE
028	SEAORIGPORTNAT	70	AN	C	Nationality of the vessel origin port if the linehaul is a boat. Becomes mandatory if LINEHAUL field is SE

4.1.1.7 Subtype SHIPMENT

There are as many SHIPMENT lines as expedition (single or multiple pieces).

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:SHIPMENT	8	A	M	Subtype Identification (always = "SHIPMENT")
002	NUMORDER	2	N	M	Fixed numerical value (always = 3). Value is provided by the dataflow chosen Defines the hierarchical order of the subtype
003	MPSID	14	AN	M	Shipment ID. Optional for CR REQUEST/ANSWER Could be the ID of the first parcel of the list (master ID) or could be

					another ID specially created for that. In all cases, this ID will have to be present on the BIC3 sticker as shipment reference.
004	CUSTOMSREF	25	AN	C	Consignment number for the customs point of view. Not set by customer but mandatory between gateways.
005	MPSIDCCKEY	1	AN	M	Control character key compute from the MPSID Conditional for CR REQUEST/ ANSWER if MPSID is filled
006	MPSCOMP	1	N	O	0=Reserved for the future usage (default) 1= no complete delivery (MPS incomplete) 2= complete delivery (MPS complete). It is mandatory for COD
007	MPSCREF1	35	AN	O	Customer reference number to be printed on the parcel(Label/Sticker) if possible
008	MPSCREF2	35	AN	O	Customer reference number 2
009	MPSCREF3	35	AN	O	Customer reference number 3
010	MPSCREF4	35	AN	O	Customer reference number 4
011	MPSBILLREF	35	AN	O	Customer reference for billing or clearing
012	MPSCOUNT	3	N	M	Number of parcels per shipment
013	MPSVOLUME	9	N	O	3D (3-dimension) of whole shipment (length / width / height) in cm without separators.
014	MPSWEIGHT	8	N	C	Shipment weight in Decagram (10 Grams) units without decimal delimiter (e.g. 300 equals 3kg). Could be used for pallet transportation at least. Mandatory for:

					- PUDO, - Customs, - freight, - Hazardous goods. Rules for weight: Sum of DECLAREDWEIGHTs equal MPSWEIGHT Sum of CGROSSWEIGHTs equal MPSWEIGHT CNETWEIGHT must be less than CGROSSWEIGHT Either CNETWEIGHT or CGROSSWEIGHT should reflect the value on the commercial invoice If CNETWEIGHT is not populated, the broker is responsible for deriving this from CGROSSWEIGHT minus 10% (adjustment for packaging). It is not the responsibility of the Business Units / Customer.
015	SDEPOT	7	N	M	Constant "0029999"
016	CDATE	8	N	M	Creation date, YYYYMMDD format. Will be used in the DPD system to generate a unique ID for the shipment (MPSID+CDATE)
017	CTIME	6	N	M	Creation timestamp of the shipment
018	HARDWARE	1	A	M	Constant "K"
019	RDEPOT	7	N	O	Recipient depot, four alphanumeric places, including leading zero (if necessary), e.g. 0163. The field will be re-calculated at the central EDI-Server if it is empty. When the new GeoRouting will be implemented, this field includes:

					- 3 N (BU Definition) - 4 N (Depot identification) Warning: The 4 digits in the parcel number will not be attached to a depot but to a range associated to a BU or Depot. The old routing format and new routing format is possible on this field This field is also used for the destination depot of a collection request
020	DSORT	5	AN	O	GeoRouting D-SORT. The field will be re-calculated at the central EDI-Server if it is empty.
021	SPTDATE	8	N	M	Date when the shipment is expected to be transferred to the system, YYYYMMDD format Optional for CR REQUEST/ANSWER
022	SPTTIME	6	N	M	Time when the shipment is expected to be transferred to the system, HHMMSS format
023	SPTREALDATE	8	N	O	Date when the shipment has been really transferred to the system, YYYYMMDD format
024	SPTREALTIME	6	N	O	Time when the shipment has been really transferred to the system, HHMMSS format
025	DELMODALLOW	1	N	M	Constant "1"
026	ROUTINGPLANVERSION	8	AN	O	In the old routing the routing plan version counts 1 character. (Value of GeoPost Routing Version (From 1 to 6)) With the new GeoRouting, the field

					must count 8 characters (Date of the GRDB will be used)
027	SPARTNERREF1	35	AN	O	Partner's shipment reference field 1
028	SPARTNERREF2	35	AN	O	Partner's shipment reference field 2
029	SPARTNERCODE	35	AN	O	This field is a generic field describing a partner code
030	OSORT	5	AN	O	GeoRouting D-SORT. The field will be re-calculated at the central EDI-Server if it is empty.
031	SSORT	5	AN	O	GeoRouting S-SORT. This field is defined for the intermediate sortation (Cf. GeoRouting specification)
032	MSORT	5	AN	O	GeoRouting M-SORT, This field provides more information on the D-Sort (GeoRouting)
033	COLREQUESTFLAG	1	N	C	This field defines if the current parcel is coming from a collection request. The default value will be: - 0 => Not a collection request parcel - 1 => Is a collection request parcel This field is mandatory in case of collection request parcel
034	ROUTINGPLACE	9	AN	O	GeoRouting Routing place. This field provides more information on the D-Sort (GeoRouting). For more information, please see the GeoRouting specification
035	ORIGINMPSID	21	AN	C	This field designs the domestic shipment number. It is dedicated to Seur and should be used and only to GeoTrack. This field is mandatory in case of the MPSID is empty
036	OPCODE	3	AN	M	Constant "INS"

037	SYSDEPOT	7	AN	M	Constant "0020456"
038	DATADATETIME	14	Date/Time	M	Date and Time when the shipment is updated, YYYYMMDDhhmmss format.
039	TIMEZONE	5	AN	M	The Timezone field describes the difference with the GMT time ±hhmm (For example : -0545)

4.1.1.8 Subtype SENDER

There are as many SENDER lines as SHIPMENT lines.

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:SENDER	6	A	M	Consignment Subtype Identification (always = "SENDER")
002	NUMORDER	2	N	M	Fixed numerical value (always = 4). Value is provided by the dataflow chosen Defines the hierarchical order of the subtype
003	SCUSTACCNUMBER	20	AN	M	Sending customer ID (Chronopost account number)
004	SCUSTSUBACCNUMBER	5	N	O	Customer number SUBID
005	SCOMPNAME	35	AN	C	Sender Company Name (SCOMPNAME or SNAME1 is mandatory) For historical reason this field can't be set every time but should be used in the future.
006	SUNIQCUSTID	17	AN	O	This is a unique customer ID in the GeoPost group.
007	SNAME1	35	AN	C	Sender name 1
008	SNAME2	35	AN	O	Sender name 2
009	SSTREET	35	AN	M	Sender street
010	SPROPNUM	8	AN	O	House number of the sender (could be included into in the address field and not set). For historical reason this field can't be set every

					time but should be used in the future.
011	SADD2	35	AN	O	Sender address line 2
012	SADD3	35	AN	O	Sender address line 3
013	SFLOOR	35	AN	O	Information on the floor of the sender (e.g. if located in a huge office building) This information could alternatively be included into in one of the address fields.
014	SBUILDING	35	AN	O	Information of the building of the sender (e.g. when located on a big campus). This information could alternatively be included in one of the address fields.
015	SDEPARTMENT	35	AN	O	Information on the department of the sender (e.g. when located in a huge office-building with different departments on the same floor). This information could alternatively be included in one of the address fields.
016	SCOUNTRYCODE	3	AN	M	Sender country (ISO 3166). All three ISO standards will be accepted: - ISO 3166-1: 2 Alpha Numerical Characters - ISO 3166-1: 3 Alpha Numerical Characters - ISO 3166-1: 3 Numerical Characters
017	SSTATE	2	AN	C	State within the Sender country, e.g. CA for California. conditional, according to country code
018	SZIPCODE	9	AN	M	Sender post code, mandatory for country with zip code. If the country does not have the ZIPCODE a default value "000000000" has to be filled. Warning: Only Characters 0-9A-Z are allowed

019	STOWN	35	AN	M	Sender Town
020	SCONTACT	35	AN	O	Sender contact person
021	SPHONE	30	AN	C	Sender telephone number formatted. Has to be encoded in one of the following ways: - XXXXXXXX or - +intcodeXXXXXXXX or - 00intcodeXXXXXXXX where: - XXXXXXXX is numeric and means the phone number - intcode is the numeric country code with a length from 1 to 4. Without international code, the phone number has to be understood as a domestic one. one of the both fields (SPHONE & SEMAIL) is mandatory.
022	SFAX	30	AN	O	Sender fax number
023	SEMAIL	100	AN	C	Sender email address one of the both fields (SPHONE & SEMAIL) is mandatory.
024	SCOMMENT	70	AN	O	Sender comments in the receiver country language or English.
025	SGLN	13	N	O	Sender GLN number (Global location number)
026	SGPSLAT	16	N	O	Geo. Latitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
027	SGPSLONG	16	N	O	Geo. Longitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
028	SACCOUNTOWNER	3	AN	C	Define the owner of the customer account customer. This owner is responsible to bill the parcel.
029	SBUSINESS	1	AN	M	Sender type: "P": PRIVATE OR "B" BUSINESS

030	SENDERWEBSITE	255	AN	C	Selling website, it becomes mandatory if field SBUSINESS is B and the sender is a Ecommercant
031	SEORI	20	AN	C	Sender EORI number, dependency of the custom export regime if SBUSINESS = B this field becomes mandatory (dependency of the custom export regime) and export to UK if SBUSINESS = P this field is empty If any rule of the origin country N/A according to origin country. Ex: UK to SP if SBUSINESS = P this field is empty one of the two fields (SEORI & SVATNO) is mandatory.
032	SVATNO	20	AN	C	Sender VAT number, dependency of the custom export regime. if SBUSINESS = B this field becomes mandatory (dependency of the custom export regime) if SBUSINESS = P this field is empty Ex: UK to SP if SBUSINESS = P one of the two fields (SEORI & SVATNO) is mandatory
033	STAXEIDTYPE	1	AN	C	Sender type of document P: PASSPORT Number C : CNPJ (ou CPF) Number (Brésil) if SBUSINESS = B this field becomes mandatory (dependency of the custom export regime) applicable or not according export custom clearance of origin country

					if SBUSINESS = P this field is empty
034	STAXEIDVALUE	20	AN	O	Sender document information. Data in this field has to be captured based on the rules of each BU

4.1.1.9 Subtype RECEIVER

There are as many RECEIVER lines as SHIPMENT lines.

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:RECEIVER	8	A	M	Subtype Identification (always = "RECEIVER")
002	NUMORDER	2	N	M	Fixed Numerical value ((always =4). Value is provided by the dataflow chosen Define the hierarchical order of the subtype
003	RCUSTID	17	AN	O	GeoPost Customer number of the final consignee
004	RNAME1	35	AN	C	Receiver name 1 This field is linked to RCOMPNAME field. At least, one of the both field has to be provided.
005	RNAME2	35	AN	O	receiver name 2 (in the some case, this information is not managed by BU)
006	RCOMPNAME	35	AN	C	receiver company name. For historical reason this field can't be set every time but should be provided in the future. This field is linked to RNAME1 field. At least, one of the both field has to be provided.
007	RCOMPNAME2	35	AN	O	receiver company name 2 For historical reason this field can't be set every

					time but it has to be set every time it is possible. This field has to be added on all application, files, database and flow where they are updated.
008	RPUDOID	20	AN	C	ID number of PUDO point (parcel shop, post office, customer network point, etc., .) This field must use the GeoPost standard PUDO definition (Mandatory for the Cross Border delivery) e.g: CC12345 with: CC: Country Code compliant with ISO 3166-1: 2 Alpha Numerical Characters 12345: PUDO Number Mandatory in case of SHPNOTPUDO or for a PUDO delivery
009	RSTREET	35	AN	M	Street name of the receiver
010	RPROPNUM	8	AN	O	House number of the receiver For historical reason this field can't be set every time but it has to be set every time it is possible. This field has to be added on all application, files, database and flow where they are updated.
011	RADD2	35	AN	O	Address Line 2 of the receiver
012	RADD3	35	AN	O	Address Line 3 of the receiver
013	RFLOOR	35	AN	O	Information on the floor of the receiver (e.g. if located in a huge office building) This information could alternatively be

					included into in one of the address fields.
014	RBUILDING	35	AN	O	Information on the building of the receiver (e.g. when located on a big campus) This information could alternatively be included in one of the address fields.
015	RDEPARTMENT	35	AN	O	Information on the department of the receiver (e.g. when located in a huge office-building with different departments on the same floor). This information could alternatively be included in one of the address fields.
016	RCOUNTRYCODE	3	AN	M	Receiver country (ISO 3166). All three ISO standards will be accepted - ISO 3166-1: 2 Alpha Numerical Characters - ISO 3166-1: 3 Alpha Numerical Characters - ISO 3166-1: 3 Numerical Characters
017	RSTATE	2	AN	C	State within the receiver country, e.g. CA for California. conditional, according to country code
018	RZIPCODE	9	AN	M	Post code of the receiver If the country does not have the post code a default value "000000000" has to be filled. Warning: Only Characters 0-9A-Z are allowed
019	RTOWN	35	AN	M	Receiver Town
020	RDOORCODE	8	AN	O	A code to open the door of the receiver

021	RCONTACT	35	AN	O	Receiver contact person. He Is not the consignee name.
022	RCONTACTPHO1	30	AN	C	Receiver telephone number formatted. Has to be encoded in one of the following ways: - XXXXXXXX or - +intcodeXXXXXXXX or - 00intcodeXXXXXXXX where: - XXXXXXXX is numeric and means the phone number - intcode is the numeric country code with a length from 1 to 4. Without international code, the phone number has to be understood as a domestic one. One of the both fields (RCONTACTPHO1 & REMAIL) is mandatory.
023	RCONTACTPHO2	30	AN	O	Receiver telephone number formatted. Has to be encoded in one of the following ways: - XXXXXXXX or - +intcodeXXXXXXXX or - 00intcodeXXXXXXXX where: - XXXXXXXX is numeric and means the phone number - intcode is the numeric country code with a length from 1 to 4. Without international code, the phone number has to be understood as a domestic one.
024	RINTERPHONENAME	35	AN	O	Name on the interphone

025	RFAX	30	AN	O	Fax number of the receiver
026	REMAIL	100	AN	C	Email address of the receiver One of the both fields (RCONTACTPHO1 & REMAIL) is mandatory.
027	RCOMMENT	70	AN	O	Additional comments
028	RGPSLAT	16	N	O	Geo. Latitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
029	RGPSLONG	16	N	O	Geo. Longitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
030	RBUSINESS	1	AN	M	Receiver type: "P": PRIVATE OR "B" BUSINESS
031	REORI	20	AN	C	Receiver EORI number if RBUSINESS = B this field becomes mandatory if RBUSINESS = P this field is empty If any rule of the destination country N/A according to destination country. Ex: SP to UK one of the two fields (REORI & RVATNO) is mandatory.
032	RVATNO	20	AN	C	Receiver VAT number if RBUSINESS = B this field becomes mandatory if RBUSINESS = P this field is empty one of the two fields (REORI & RVATNO) is mandatory.
033	RTAXEIDTYPE	1	AN	O	Receiver type of document P: PASSPORT Number

					C : CNPJ (ou CPF) Number (Brésil)
034	RTAXEIDVALUE	20	AN	C	Receiver document information. Linked to the RTAXEIDTYPE. Input the passport number if RTAXEIDTYPE is P
035	RFISCALVATREPRESENTANT	20	AN	O	Fiscal receiver VAT number. This field should be Blank / Empty & ONLY populated with the Fiscal VAT number if applicable / known

4.1.1.10 Subtype INTER

There are in maximum as many INTER lines as SHIPMENT lines.

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:INTER	5	A	M	Identification of the data for international transfer/Custom (always = "INTER")
002	NUMORDER	2	N	M	Fixed Numerical value (always =4). Value is provided by the dataflow chosen Define the hierarchical order of the subtype
003	PARCELTYPE	1	AN	M	Parcel type within the shipment (D=Document, P=Non-Doc). Different parcel types can't be mixed into one shipment. This field is mandatory when the value of the field CLEARANCECLEARED is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECLEARED is "F".
004	CAMOUNT	15	N	M	Declared customs amount in total (documents = 0). Separator is "." (point).

					The number of decimal will depend of the currency (it could be from 0 to three digit). This field is mandatory when the value of the field CLEARANCECleared is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECleared is "F".
005	CURRENCY	3	AN	M	Currency code (ISO 4217 alpha 3) This field is mandatory when the value of the field CLEARANCECleared is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECleared is "F" if exporting to UK
006	CAMOUNTEX	15	N	C	Converted customs amount in total. Separator is "." (point). The number of decimal will depend of the currency (it could be from 0 to three digit). (documents = 0) This field is mandatory when the value of the field CLEARANCECleared is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECleared is "F".
007	CURRENCYEX	3	AN	C	Currency for conversion This field is mandatory when the value of the field CLEARANCECleared is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECleared is "F".

008	CTERMS	2	AN	C	Terms 01 = DAP, not cleared 02 = DDP, delivered duty paid (incl. duties and excl. taxes) 03 = DDP, delivered duty paid (incl. duties and taxes) 05 = ex works (EXW) 06 = DAP 07 = DAP enhanced, Duty and taxes were pre-paid by the receiver This field is mandatory when the value of the field CLEARANCECleared is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECleared is "F". If not provided then the default value applied by DPD UK will be DAP
009	CPAPER	20	AN	O	Accompanying documents without separator, e.g. AGB A = commercial invoice B = pro forma invoice C = export declaration D = EUR1 E = EUR2 F = ATR G = delivery note H = third party billing I = T1 document Separator is " " (a pipe) in case of multiple invoice documents
010	CCOMMENT	70	AN	O	Internal GeoPost comment. Not used by the customer.
011	CLEARANCECleared	1	A	C	(N)o, (F)ree, (E)xport Cleared, (T)ransit cleared,

					(I)mport Cleared, (H)ybrid.
012	HIGHLOWVALUE	1	A	C	(H)igh, (M)id (above 22€ and below 150€), (L)ow. Mandatory in relationship between the import gateway and its broker.
013	PREALERTSTATUS	3	AN	C	Status S03 = Data captured by sending depot S04 = Data are available for export gateway depots S05 = Pre-alert provided (1st linehaul) S06 = Return to sending depot by export gateway S07 = Deactivated S08 =HV import customs cleared S09 = transit via road (T1) S13 = Pre-alert provided (2nd linehaul) S14 = Returned by import gateway (1st linehaul) S15 = LV import customs cleared S16 = Returns to sending country (2nd linehaul) This field is mandatory when the value of the field CLEARANCECLEARED is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECLEARED is "F".
014	CINVOICE	20	AN	C	Invoice number Becomes mandatory according to the threshold value of the destination country Separator is " " (a pipe) in case of multiple invoice numbers
015	CINVOICEDATE	8	N	O	Fixed Numerical value (Cf.Rank in the Subtype Sheet). Value is provided by the dataflow chosen

					Define the hierarchical order of the subtype
016	CNAME1	35	AN	C	Commercial invoice consignee name 1 This field is mandatory when the value of the field CLEARANCECLEARED is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECLEARED is "F".
017	CNAME2	35	AN	O	Commercial invoice consignee name 2
018	CSTREET	35	AN	C	Commercial invoice consignee street This field is mandatory when the value of the field CLEARANCECLEARED is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECLEARED is "F".
019	CPROPNUM	8	AN	M	Commercial invoice consignee Propriety number
020	CCOUNTRYCODE	3	AN	C	Commercial invoice consignee country code (ISO3166). The three ISO standards will be managed: - ISO 3166-1: 2 Alpha Numerical Characters - ISO 3166-1: 3 Alpha Numerical Characters - ISO 3166-1: 3 Numerical Characters This field is mandatory when the value of the field CLEARANCECLEARED is "N", "E", "T" or "I". Furthermore this field is optional when the field value of CLEARANCECLEARED is "F".
021	CSTATE	2	AN	O	State within the commercial invoice

					consignee country, e.g. CA for California. conditional, according to country code
022	CZIPCODE	9	AN	C	Commercial invoice consignee postal code (according GeoPost country list) if the country have one Warning: Only Characters 0-9A-Z are allowed
023	CTOWN	35	AN	O	Commercial invoice consignee Town
024	CGPSLAT	16	N	O	Geo. Latitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
025	CGPSLONG	16	N	O	Geo. Longitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
026	CCONTACT	35	AN	C	Commercial invoice consignee contact, becomes mandatory according to the threshold value of the destination country if no contact copy the recipient contact name.
027	CPHONE	30	AN	C	Commercial invoice telephone number formatted. Has to be encoded in one of the following ways: - XXXXXXXX or - +intcodeXXXXXXXX or - 00intcodeXXXXXXXX where: - XXXXXXXX is numeric and means the phone number - intcode is the numeric country code with a length from 1 to 4. Without international code, the phone number has to be understood as a domestic one. This field is mandatory in

					case of air linehaul Either CPHONE or CEMAIL is mandatory
028	CFAX	30	AN	O	Commercial invoice consignee fax number
029	CEMAIL	100	AN	C	Commercial invoice consignee email address Either CPHONE or CEMAIL is mandatory
030	CGLN	13	N	O	Commercial invoice consignee GLN number (Global location number)
031	CVATNO	20	AN	O	Commercial invoice consignee VAT number
032	CNUMBER	35	AN	O	Customer deferment number with can be used for duty tax collection
033	SHIPMRN	209	AN	O	MRN of the electronic export declaration Remarks: The " " is the separator between two MRN.
034	CEORI	20	AN	O	Commercial invoice consignee VAT/EORI number
035	SINAME1	35	AN	C	Name 1 of the invoice address of the sender At least SINAME1 or SINAME2 is mandatory
036	SINAME2	35	AN	C	Name 2 of the invoice address of the sender At least SINAME1 or SINAME2 is mandatory
037	SISTREET	35	AN	O	Street of the invoice address of the sender
038	SIPROPNUM	8	AN	M	House number of the invoice address of the sender

039	SICOUNTRYCODE	3	AN	O	Country of the invoice address of the sender (ISO 3166). The three ISO standards will be accepted: - ISO 3166-1: 2 Alpha Numerical Characters - ISO 3166-1: 3 Alpha Numerical Characters - ISO 3166-1: 3 Numerical Characters
040	SISTATE	2	AN	O	State of the invoice address of the sender, e.g. CA for California. conditional, according to country code
041	SIZIPCODE	9	AN	O	Postal code of the invoice address of the sender Warning: Only Characters 0-9A-Z are allowed
042	SITOWN	35	AN	O	Town of the invoice address of the sender
043	SIGPSLAT	16	N	O	Geo. Latitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
044	SIGPSLONG	16	N	O	Geo. Longitude coordinate Number (15.11) => Separator is "." (dot) in Geodata . Use of WGS84 standard
045	SICONTACT	35	AN	O	Contact of the invoice address of the sender
046	SIPHONE	30	AN	O	Invoice Phone number of the sender has to be encoded in one of the following ways: - XXXXXXXX or - +intcodeXXXXXXXX or - 00intcodeXXXXXXXX where: - XXXXXXXX is numeric and means the phone number - intcode is the numeric country code with a length from 1 to 4. Without international code, the phone number

					has to be understood as a domestic one.
047	OPCODE	3	AN	M	Constant "INS"
048	NUMBEROFARTICLE	6	N	O	This is the real number of commodities (RCTARIF / SCTARIF). The number of INTERINVOICELINEs must equal the NUMBEROFARTICLE
049	DESTCOUNTRYREG	15	AN	O	Destination country registration information : Registration number (IOSS...) or FDA If destination is DPD UK : Applies to B2B and B2C (Not applicable for C2C) shipments with a goods value under £135 (Excludes shipping cost) and if the Incoterm is not DDP. This is expected to come into force March 19, however no official communication from HMRC yet.
050	SIEORI	20	AN	O	Seller of the good VAT/EORI number
051	REASONFOREXPORT	2	AN	M	Reason for export : 01: sale 02: return/replacement 03: gift If the field is left blank, the default reason for export is 01

There are as many PARCEL lines as parcel really handed over.

There are as many or more PARCEL lines as SHIPMENT lines.

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:PARCEL	6	A	M	Subtype identification (always= "PARCEL")
002	NUMORDER	2	N	M	Fixed Numerical value (always=5). Value is provided by the dataflow chosen Define the hierarchical order of the subtype
003	PARCELNUMBER	14	AN	M	Parcel number. Optional for the collection request
004	PARCELNUMBERCCKEY	1	AN	C	Control character key compute from the parcel number. Optional for the collection request
005	PARCELRANK	3	N	O	Rank of the parcel within a multi-piece shipment. Set to one for the masterpiece of the shipment or for a single piece. Default=Blank
006	SENDPARCELREF1	35	AN	O	Sender parcel reference number 1
007	SENDPARCELREF2	35	AN	O	Sender parcel reference number 2
008	SENDPARCELREF3	35	AN	O	Sender parcel reference number 3
009	SENDPARCELREF4	35	AN	O	Sender parcel reference number 4
010	RECPARCELREF	35	AN	O	Receiver reference number
011	SERVICECODE	3	N	M	Service code / SOCODE in GeoRouting
012	PPARTNERREF1	35	AN	O	partner's own parcel reference field 1
013	PPARTNERREF2	35	AN	O	partner's own parcel reference field 2
014	PPARTNERREF3	35	AN	O	partner's own parcel reference field 3
015	PPARTNERREF4	35	AN	O	partner's own parcel reference field 4
016	DIMENSION	9	N	C	3d dimension of the individual parcel (length /

					width / height) in cm without separators. Mandatory for freight
017	DECLAREDWEIGHT	8	N	C	Weight of each individual parcel as declared by the customer in grams units without decimal delimiter (e.g. 3000 equals 3kg) Mandatory for: - PUDO, - Custom, - Freight - Hazardous good. Rules for weight: Sum of DECLAREDWEIGHTs equal MPSWEIGHT Sum of CGROSSWEIGHTs equal MPSWEIGHT CNETWEIGHT must be less than CGROSSWEIGHT Either CNETWEIGHT or CGROSSWEIGHT should reflect the value on the commercial invoice If CNETWEIGHT is not populated, the broker is responsible for deriving this from CGROSSWEIGHT minus 10% (adjustment for packaging). It is not the responsibility of the Business Units / Customer.
018	MEASUREDWEIGHT	8	N	O	Weight of each individual parcel as measured by each BU in grams units without decimal delimiter (e.g. 3000 equals 3kg) Rules for weight: Sum of DECLAREDWEIGHTs equal MPSWEIGHT Sum of CGROSSWEIGHTs equal MPSWEIGHT CNETWEIGHT must be less than CGROSSWEIGHT

					Either CNETWEIGHT or CGROSSWEIGHT should reflect the value on the commercial invoice If CNETWEIGHT is not populated, the broker is responsible for deriving this from CGROSSWEIGHT minus 10% (adjustment for packaging). It is not the responsibility of the Business Units / Customer.
019	HINSAMOUNT	15	N.N	O	Insurance value for additional insurance if the customer needs an additional insurance. If the value is higher than zero, the increase of insurance value will be applied. Separator is "." (point). The number of decimal will depend of the currency (it could be from 0 to three digit).
020	HINSCURRENCY	3	AN	C	Currency code Mandatory if the field HINSAMOUNT is set
021	HINSCONTENT	35	AN	O	Description of parcel for insurance
022	HAZLQ	1	N	O	Limited quantities of hazardous goods parcel value (1 = yes / 0 =no) Default value is 0.
023	HZDPACKCODE	3	AN	C	Packing code (see PACKINGCODE). Mandatory in case of hazardous parcel
024	OPCODE	3	AN	O	Constant "INS"
025	PCONTENT	200	AN	O	Content (Depending of the destination systems. Could be cut by some system to the first 35 characters) The language recommended in this field is English
026	ORIGINPARCELNUMBER	32	AN	O	This field provides the local parcel number. It is used only for the domestic information without

					PARCELNUMBER information.
027	POWNERBU	3	AN	M	Constant "CHR"
028	PPARTNERCODE	35	AN	O	Describe a generic partner code on the parcel information (i.e. Partner Product code)
029	ASCODE	6	AN	C	Additional Service Code links to the SOCODE Condition: Depends on the SOCODE
030	BAGNO	35	AN	O	bag number
031	CIFCOST	15	N.N	O	Custom transport cost Separator is "." (point). The number of decimal will depend of the currency (it could be from 0 to three digit). (documents = 0)
032	CIFCOSTCUR	3	AN	O	Currency for conversion of transport cost

4.1.1.12 Subtype INTERINVOICELINE

Per shipment, there are as many INTERINVOICELINE lines as NUMBEROFARTICLE into INTER. It is possible to get no INTERINVOICELINE.

ID	Token	Length	Data type	Optional mandatory	Description
001	GEODATA:INTERINVOICELINE	16	A	M	Subtype identification (always = "INTERINVOICELINE")
002	NUMORDER	2	N	M	Fixed Numerical value (always =5). Value is provided by the dataflow chosen Define the hierarchical order of the subtype
003	CINVOICEPOSITION	6	N	O	Line number of the invoice
004	QITEMS	4	N	M	Quantity of items in the shipment even for low/mid/high value or any type of customer
005	CCONTENT	200	AN	M	Content (Depending of the destination system. Could be cut by some system to

					the first 35 characters)
006	CAMOUNTLINE	15	N	M	Value of invoice position Separator is "." (point). The number of decimal will depend of the currency (it could be from 0 to three digits).
007	CCOMMENT	70	AN	O	Internal GeoPost comment. Not use by the customers
008	CORIGIN	3	AN	M	COUNTRYCODE of invoice origin (Manufacturer Country) (ISO 3166). The three ISO standards will be managed: - ISO 3166-1: 2 Alpha Numericals Characters - ISO 3166-1: 3 Alpha Numericals Characters - ISO 3166-1: 3 Numericals Characters
009	CNETWEIGHT	8	N	O	Total weight of the article, excluding packaging, in grams. This is not the unit weight Weight in Grams units without decimal delimiter (e.g. 3000 equals 3kg) Rules for weight: Sum of DECLAREDWEIGHTs equal MPSWEIGHT Sum of CGROSSWEIGHTs equal MPSWEIGHT CNETWEIGHT must be less than CGROSSWEIGHT Either CNETWEIGHT

					or CGROSSWEIGHT should reflect the value on the commercial invoice If CNETWEIGHT is not populated, the broker is responsible for deriving this from CGROSSWEIGHT minus 10% (adjustment for packaging). It is not the responsibility of the Business Units / Customer.
010	CGROSSWEIGHT	8	N	C	Total weight of the article including packaging, in grams. This is not the unit weight Weight in Grams units without decimal delimiter (e.g. 3000 equals 3kg) Rules for weight: Sum of DECLAREDWEIGHTs equal MPSWEIGHT Sum of CGROSSWEIGHTs equal MPSWEIGHT CNETWEIGHT must be less than CGROSSWEIGHT Either CNETWEIGHT or CGROSSWEIGHT should reflect the value on the commercial invoice If CNETWEIGHT is not populated, the broker is responsible for deriving this from CGROSSWEIGHT minus 10% (adjustment for packaging). It is not the responsibility of the Business Units / Customer.

011	CPCODE	255	AN	O	Internal Customer product code
012	CRPRODTYPE	70	AN	O	Short description of the product
013	CFABRICCOMPOSITION	200	AN	O	Description of fabric composition
014	RCTARIF	8	AN	M	Customs tariff number (HSCODE) applicable for the customs clearance Gateway and/or destination country. Ex: origin China different than Europe
015	SCTARIF	10	AN	M	Customs tariff number. Mandatory according to the origin country. If origin custom not done by a BU RCTARIF and SCTARIF can have the same value. Note: in GeoData 3.1 the corresponding field was CTARIF
016	GOODSWEBPAGE	255	AN	O	Goods web page of the seller Emarchant