

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Worksheet 8

Student Name: Sohit Kumar
Branch: CSE
Semester: 5th
Subject Name: ADBMS

UID: 23BCS12492
Section/Group: KRG 3-A
Date of Performance: 09/10/2025
Subject Code: 23CSP-333

1. Aim:

Design a robust PostgreSQL transaction system for the students table where multiple student records are inserted in a single transaction.

- a. If any insert fails due to invalid data, only that insert should be rolled back.
- b. Previous successful inserts should remain intact.
- c. Use savepoints to manage partial rollbacks.
- d. Provide clear messages for successful and failed insertions.

2. Objective:

- Understand Transaction Management in PostgreSQL
- Learn Partial Rollback Using Savepoints
- Handle Errors Gracefully
- Provide Feedback on Database Operations
- **Develop Robust and Fault-tolerant Database Systems**

3. Code:

-- Create table

```
CREATE TABLE students (
    id SERIAL PRIMARY KEY,
    name VARCHAR(50),
    age INT,
    class INT
);
```

-- Insert multiple students in one transaction

```
DO $$  
BEGIN  
    BEGIN  
        INSERT INTO students(name, age, class) VALUES ('Shivanshu',20,12);  
        INSERT INTO students(name, age, class) VALUES ('Tanya',21,12);  
        INSERT INTO students(name, age, class) VALUES ('Devanshu',16,10);  
  
        RAISE NOTICE 'Transaction Successfully Done';  
    EXCEPTION  
        WHEN OTHERS THEN
```

**DEPARTMENT OF
COMPUTER SCIENCE & ENGINEERING**
RAISE NOTICE 'Transaction Failed..! Rolling back all changes.';
RAISE;
END;
END;
\$\$;

SELECT * FROM students;

-- Transaction with Savepoints

BEGIN; -- Start transaction

-- Savepoint 1: Karan
SAVEPOINT sp1;
INSERT INTO students(name, age, class) VALUES ('Karan',19,12);
DO \$\$ BEGIN RAISE NOTICE 'Inserted Karan successfully'; END \$\$;

-- Savepoint 2: Rohit (invalid insert)


SAVEPOINT sp2;
DO \$\$
BEGIN
BEGIN
INSERT INTO students(name, age, class) VALUES ('Rohit','wrong',12);
EXCEPTION WHEN OTHERS THEN
RAISE NOTICE 'Failed to insert Rohit, rolling back to savepoint sp2';
END;
END;
\$\$;

-- Rollback the failed insert in SQL
ROLLBACK TO SAVEPOINT sp2;

-- Savepoint 3: Aditya
SAVEPOINT sp3;
INSERT INTO students(name, age, class) VALUES ('Aditya',17,10);
DO \$\$ BEGIN RAISE NOTICE 'Inserted Aditya successfully'; END \$\$;

-- Commit all successful inserts
COMMIT;

SELECT * FROM students;



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

4. Output:

Output:

```
CREATE TABLE
```

```
DO
```

id	name	age	class
1	Shivanshu	20	12
2	Tanya	21	12
3	Devanshu	16	10

(3 rows)

```
BEGIN
```

```
SAVEPOINT
```

```
INSERT 0 1
```

```
DO
```

```
SAVEPOINT
```

```
DO
```

```
ROLLBACK
```

```
SAVEPOINT
```

```
INSERT 0 1
```

```
DO
```

```
COMMIT
```

id	name	age	class
1	Shivanshu	20	12
2	Tanya	21	12
3	Devanshu	16	10
4	Karan	19	12
5	Aditya	17	10

(5 rows)

```
psql:commands.sql:27: NOTICE: Transaction Successfully Done
```

```
psql:commands.sql:38: NOTICE: Inserted Karan successfully
```

```
psql:commands.sql:50: NOTICE: Failed to insert Rohit, rolling back to savepoint sp2
```

```
psql:commands.sql:57: NOTICE: Inserted Aditya successfully
```

4. Learning Outcomes:

- Master Transaction Control
- Implement Partial Rollbacks with Savepoints
- Error Handling in Database Operations
- Provide Clear Feedback and Maintain Data Consistency