

Module `java.base`

Package `java.lang`

Class `String`

`java.lang.Object`

`java.lang.String`

All Implemented Interfaces:

`Serializable`, `CharSequence`, `Comparable<String>`, `Constable`, `ConstantDesc`

```
public final class String
extends Object
implements Serializable, Comparable<String>, CharSequence, Constable,
ConstantDesc
```

The `String` class represents character strings. All string literals in Java programs, such as `"abc"`, are implemented as instances of this class.

Strings are constant; their values cannot be changed after they are created. String buffers support mutable strings. Because `String` objects are immutable they can be shared. For example:

```
String str = "abc";
```

is equivalent to:

```
char data[] = {'a', 'b', 'c'};
String str = new String(data);
```

Here are some more examples of how strings can be used:

```
System.out.println("abc");
String cde = "cde";
System.out.println("abc" + cde);
String c = "abc".substring(2, 3);
String d = cde.substring(1, 2);
```

The class `String` includes methods for examining individual characters of the sequence, for comparing strings, for searching strings, for extracting substrings, and for creating a copy of a string with all characters translated to uppercase or to lowercase. Case mapping is based on the Unicode Standard version specified by the [Character](#) class.

The Java language provides special support for the string concatenation operator (`+`), and for conversion of other objects to strings. For additional information on string concatenation and conversion, see *The Java Language Specification*.

Unless otherwise noted, passing a `null` argument to a constructor or method in this class will cause a [NullPointerException](#) to be thrown.

A `String` represents a string in the UTF-16 format in which *supplementary characters* are represented by *surrogate pairs* (see the section [Unicode Character Representations](#) in the `Character` class for more information). Index values refer to char code units, so a supplementary character uses two positions in a `String`.

The `String` class provides methods for dealing with Unicode code points (i.e., characters), in addition to those for dealing with Unicode code units (i.e., char values).

Unless otherwise noted, methods for comparing Strings do not take locale into account. The `Collator` class provides methods for finer-grain, locale-sensitive String comparison.

Implementation Note:

The implementation of the string concatenation operator is left to the discretion of a Java compiler, as long as the compiler ultimately conforms to *The Java Language Specification*. For example, the `javac` compiler may implement the operator with `StringBuffer`, `StringBuilder`, or `java.lang.invoke.StringConcatFactory` depending on the JDK version. The implementation of string conversion is typically through the method `toString`, defined by `Object` and inherited by all classes in Java.

See Java Language Specification:

[15.18.1 String Concatenation Operator +](#)

Since:

1.0

See Also:

[Object.toString\(\)](#), [StringBuffer](#), [StringBuilder](#), [Charset](#), [Serialized Form](#)

Field Summary

Fields

Modifier and Type	Field	Description
static final Comparator < String >	CASE_INSENSITIVE_ORDER	A Comparator that orders String objects as by <code>compareToIgnoreCase</code> .

Constructor Summary

Constructors

Constructor	Description
String()	Initializes a newly created String object so that it represents an empty character sequence.
String(byte[] bytes)	Constructs a new String by decoding the specified array of bytes using the default charset .
String(byte[] ascii, int hibyte)	Deprecated.

String(byte[] bytes, int offset, int length)

String(byte[] ascii, int hibyte, int offset, int count)

String(byte[] bytes, int offset, int length, **String** charsetName)

String(byte[] bytes, int offset, int length, **Charset** charset)

String(byte[] bytes, **String** charsetName)

String(byte[] bytes, **Charset** charset)

String(char[] value)

String(char[] value, int offset, int count)

String(int[] codePoints, int offset, int count)

String(**String** original)

String(**StringBuffer** buffer)

String(**StringBuilder** builder)

This method does not properly convert bytes into characters.

Constructs a new **String** by decoding the specified subarray of bytes using the **default charset**.

Deprecated.

This method does not properly convert bytes into characters.

Constructs a new **String** by decoding the specified subarray of bytes using the specified charset.

Constructs a new **String** by decoding the specified subarray of bytes using the specified **charset**.

Constructs a new **String** by decoding the specified array of bytes using the specified **charset**.

Constructs a new **String** by decoding the specified array of bytes using the specified **charset**.

Allocates a new **String** so that it represents the sequence of characters currently contained in the character array argument.

Allocates a new **String** that contains characters from a subarray of the character array argument.

Allocates a new **String** that contains characters from a subarray of the **Unicode code point** array argument.

Initializes a newly created **String** object so that it represents the same sequence of characters as the argument; in other words, the newly created string is a copy of the argument string.

Allocates a new string that contains the sequence of characters currently contained in the string buffer argument.

Allocates a new string that contains the sequence of characters currently contained in the string builder argument.

Method Summary

All Methods

Static Methods

Instance Methods

Concrete Methods

Deprecated Methods

Modifier and Type	Method	Description
char	<code>charAt(int index)</code>	Returns the char value at the specified index.
IntStream	<code>chars()</code>	Returns a stream of int zero-extending the char values from this sequence.
int	<code>codePointAt(int index)</code>	Returns the character (Unicode code point) at the specified index.
int	<code>codePointBefore(int index)</code>	Returns the character (Unicode code point) before the specified index.
int	<code>codePointCount(int beginIndex, int endIndex)</code>	Returns the number of Unicode code points in the specified text range of this String.
IntStream	<code>codePoints()</code>	Returns a stream of code point values from this sequence.
int	<code>compareTo(String anotherString)</code>	Compares two strings lexicographically.
int	<code>compareToIgnoreCase(String str)</code>	Compares two strings lexicographically, ignoring case differences.
String	<code>concat(String str)</code>	Concatenates the specified string to the end of this string.
boolean	<code>contains(CharSequence s)</code>	Returns true if and only if this string contains the specified sequence of char values.
boolean	<code>contentEquals(CharSequence cs)</code>	Compares this string to the specified CharSequence.
boolean	<code>contentEquals(StringBuffer sb)</code>	Compares this string to the specified StringBuffer.
static String	<code>copyValueOf(char[] data)</code>	Equivalent to <code>valueOf(char[])</code> .
static String	<code>copyValueOf(char[] data, int offset, int count)</code>	Equivalent to <code>valueOf(char[], int, int)</code> .

Optional<String>	describeConstable()	Returns an Optional containing the nominal descriptor for this instance, which is the instance itself.
boolean	endsWith(String suffix)	Tests if this string ends with the specified suffix.
boolean	equals(Object anObject)	Compares this string to the specified object.
boolean	equalsIgnoreCase (String anotherString)	Compares this String to another String , ignoring case considerations.
static String	format(String format, Object... args)	Returns a formatted string using the specified format string and arguments.
static String	format(Locale l, String format, Object... args)	Returns a formatted string using the specified locale, format string, and arguments.
String	formatted(Object... args)	Formats using this string as the format string, and the supplied arguments.
byte[]	getBytes()	Encodes this String into a sequence of bytes using the default charset , storing the result into a new byte array.
void	getBytes (int srcBegin, int srcEnd, byte[] dst, int dstBegin)	Deprecated. This method does not properly convert characters into bytes.
byte[]	getBytes(String charsetName)	Encodes this String into a sequence of bytes using the named charset, storing the result into a new byte array.
byte[]	getBytes(Charset charset)	Encodes this String into a sequence of bytes using the given charset , storing the result into a new byte array.
void	getChars (int srcBegin, int srcEnd, char[] dst, int dstBegin)	Copies characters from this string into the destination character array.
int	hashCode()	Returns a hash code for this string.
String	indent (int n)	Adjusts the indentation of each line of this string based on the

value of n, and normalizes line termination characters.

int **indexOf**(int ch)

Returns the index within this string of the first occurrence of the specified character.

int **indexOf**(int ch,
int fromIndex)

Returns the index within this string of the first occurrence of the specified character, starting the search at the specified index.

int **indexOf**(int ch,
int beginIndex,
int endIndex)

Returns the index within this string of the first occurrence of the specified character, starting the search at beginIndex and stopping before endIndex.

int **indexOf**(String str)

Returns the index within this string of the first occurrence of the specified substring.

int **indexOf**(String str,
int fromIndex)

Returns the index within this string of the first occurrence of the specified substring, starting at the specified index.

int **indexOf**(String str,
int beginIndex,
int endIndex)

Returns the index of the first occurrence of the specified substring within the specified index range of this string.

String **intern**()

Returns a canonical representation for the string object.

boolean **isBlank**()

Returns true if the string is empty or contains only [white space](#) codepoints, otherwise false.

boolean **isEmpty**()

Returns true if, and only if, [length\(\)](#) is 0.

static **String** **join**(CharSequence delimiter,
CharSequence... elements)

Returns a new String composed of copies of the CharSequence elements joined together with a copy of the specified delimiter.

static **String** **join**(CharSequence delimiter,
Iterable<? extends
CharSequence> elements)

Returns a new String composed of copies of the CharSequence elements joined

		together with a copy of the specified delimiter.
int	lastIndexOf (int ch)	Returns the index within this string of the last occurrence of the specified character.
int	lastIndexOf (int ch, int fromIndex)	Returns the index within this string of the last occurrence of the specified character, searching backward starting at the specified index.
int	lastIndexOf (String str)	Returns the index within this string of the last occurrence of the specified substring.
int	lastIndexOf (String str, int fromIndex)	Returns the index within this string of the last occurrence of the specified substring, searching backward starting at the specified index.
int	length ()	Returns the length of this string.
Stream<String>	lines ()	Returns a stream of lines extracted from this string, separated by line terminators.
boolean	matches (String regex)	Tells whether or not this string matches the given regular expression .
int	offsetByCodePoints (int index, int codePointOffset)	Returns the index within this String that is offset from the given index by codePointOffset code points.
boolean	regionMatches (boolean ignoreCase, int toffset, String other, int ooffset, int len)	Tests if two string regions are equal.
boolean	regionMatches (int toffset, String other, int ooffset, int len)	Tests if two string regions are equal.
String	repeat (int count)	Returns a string whose value is the concatenation of this string repeated count times.
String	replace (char oldChar, char newChar)	Returns a string resulting from replacing all occurrences of oldChar in this string with newChar.

String	replace(CharSequence target, CharSequence replacement)	Replaces each substring of this string that matches the literal target sequence with the specified literal replacement sequence.
String	replaceAll(String regex, String replacement)	Replaces each substring of this string that matches the given regular expression with the given replacement.
String	replaceFirst(String regex, String replacement)	Replaces the first substring of this string that matches the given regular expression with the given replacement.
String	resolveConstantDesc (MethodHandles.Lookup lookup)	Resolves this instance as a ConstantDesc , the result of which is the instance itself.
		
String[]	split(String regex)	Splits this string around matches of the given regular expression .
String[]	split(String regex, int limit)	Splits this string around matches of the given regular expression .
String[]	splitWithDelimiters (String regex, int limit)	Splits this string around matches of the given regular expression and returns both the strings and the matching delimiters.
boolean	startsWith(String prefix)	Tests if this string starts with the specified prefix.
boolean	startsWith(String prefix, int toffset)	Tests if the substring of this string beginning at the specified index starts with the specified prefix.
String	strip()	Returns a string whose value is this string, with all leading and trailing white space removed.
String	stripIndent()	Returns a string whose value is this string, with incidental white space removed from the beginning and end of every line.
String	stripLeading()	Returns a string whose value is this string, with all leading white space removed.

String	stripTrailing()	Returns a string whose value is this string, with all trailing white space removed.
CharSequence	subSequence (int beginIndex, int endIndex)	Returns a character sequence that is a subsequence of this sequence.
String	substring (int beginIndex)	Returns a string that is a substring of this string.
String	substring (int beginIndex, int endIndex)	Returns a string that is a substring of this string.
char[]	toCharArray()	Converts this string to a new character array.
String	toLowerCase()	Converts all of the characters in this String to lower case using the rules of the default locale.
String	toLowerCase(Locale locale)	Converts all of the characters in this String to lower case using the rules of the given Locale .
String	toString()	This object (which is already a string!)
String	toUpperCase()	Converts all of the characters in this String to upper case using the rules of the default locale.
String	toUpperCase(Locale locale)	Converts all of the characters in this String to upper case using the rules of the given Locale .
<R> R	transform (Function <? super String ,? extends R> f)	This method allows the application of a function to this string.
String	translateEscapes()	Returns a string whose value is this string, with escape sequences translated as if in a string literal.
String	trim()	Returns a string whose value is this string, with all leading and trailing space removed, where space is defined as any character whose codepoint is less than or equal to 'U+0020' (the space character).
static String	valueOf (boolean b)	Returns the string representation of the boolean

<code>static String</code>	<code>valueOf(char c)</code>	argument. Returns the string representation of the char argument.
<code>static String</code>	<code>valueOf(char[] data)</code>	Returns the string representation of the char array argument.
<code>static String</code>	<code>valueOf(char[] data, int offset, int count)</code>	Returns the string representation of a specific subarray of the char array argument.
<code>static String</code>	<code>valueOf(double d)</code>	Returns the string representation of the double argument.
<code>static String</code>	<code>valueOf(float f)</code>	Returns the string representation of the float argument.
<code>static String</code>	<code>valueOf(int i)</code>	Returns the string representation of the int argument.
<code>static String</code>	<code>valueOf(long l)</code>	Returns the string representation of the long argument.
<code>static String</code>	<code>valueOf(Object obj)</code>	Returns the string representation of the Object argument.

Methods declared in class `java.lang.Object`

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Field Details

`CASE_INSENSITIVE_ORDER`

`public static final Comparator<String> CASE_INSENSITIVE_ORDER`

A Comparator that orders String objects as by `compareToIgnoreCase`. This comparator is serializable.

Note that this Comparator does *not* take locale into account, and will result in an unsatisfactory ordering for certain locales. The `Collator` class provides locale-sensitive comparison.

Since:

Constructor Details

String

```
public String()
```

Initializes a newly created `String` object so that it represents an empty character sequence. Note that use of this constructor is unnecessary since `Strings` are immutable.

String

```
public String(String original)
```

Initializes a newly created `String` object so that it represents the same sequence of characters as the argument; in other words, the newly created string is a copy of the argument string. Unless an explicit copy of `original` is needed, use of this constructor is unnecessary since `Strings` are immutable.

Parameters:

`original` - A `String`

String

```
public String(char[] value)
```

Allocates a new `String` so that it represents the sequence of characters currently contained in the character array argument. The contents of the character array are copied; subsequent modification of the character array does not affect the newly created string.

The contents of the string are unspecified if the character array is modified during string construction.

Parameters:

`value` - The initial value of the string

String

```
public String(char[] value,  
             int offset,  
             int count)
```

Allocates a new `String` that contains characters from a subarray of the character array argument. The `offset` argument is the index of the first character of the subarray and the `count` argument specifies the length of the subarray. The contents of the subarray

are copied; subsequent modification of the character array does not affect the newly created string.

The contents of the string are unspecified if the character array is modified during string construction.

Parameters:

value - Array that is the source of characters

offset - The initial offset

count - The length

Throws:

[IndexOutOfBoundsException](#) - If offset is negative, count is negative, or offset is greater than value.length - count

String

```
public String(int[] codePoints,  
             int offset,  
             int count)
```

Allocates a new `String` that contains characters from a subarray of the [Unicode code point](#) array argument. The `offset` argument is the index of the first code point of the subarray and the `count` argument specifies the length of the subarray. The contents of the subarray are converted to chars; subsequent modification of the `int` array does not affect the newly created string.

The contents of the string are unspecified if the codepoints array is modified during string construction.

Parameters:

codePoints - Array that is the source of Unicode code points

offset - The initial offset

count - The length

Throws:

[IllegalArgumentException](#) - If any invalid Unicode code point is found in codePoints

[IndexOutOfBoundsException](#) - If offset is negative, count is negative, or offset is greater than codePoints.length - count

Since:

1.5

String

```
@Deprecated(since="1.1")  
public String(byte[] ascii,  
             int hiByte,  
             int offset,  
             int count)
```

Deprecated.

This method does not properly convert bytes into characters. As of JDK 1.1, the preferred way to do this is via the `String` constructors that take a [Charset](#), charset name, or that use the [default charset](#).

Allocates a new `String` constructed from a subarray of an array of 8-bit integer values.

The `offset` argument is the index of the first byte of the subarray, and the `count` argument specifies the length of the subarray.

Each byte in the subarray is converted to a `char` as specified in the `String(byte[],int)` constructor.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

`ascii` - The bytes to be converted to characters

`hibyte` - The top 8 bits of each 16-bit Unicode code unit

`offset` - The initial offset

`count` - The length

Throws:

`IndexOutOfBoundsException` - If `offset` is negative, `count` is negative, or `offset` is greater than `ascii.length - count`

See Also:

```
String(byte[], int),
String(byte[], int, int, java.lang.String),
String(byte[], int, int, java.nio.charset.Charset),
String(byte[], int, int),
String(byte[], java.lang.String),
String(byte[], java.nio.charset.Charset),
String(byte[])
```

String

```
@Deprecated(since="1.1")
public String(byte[] ascii,
              int hibyte)
```

Deprecated.

This method does not properly convert bytes into characters. As of JDK 1.1, the preferred way to do this is via the `String` constructors that take a [Charset](#), charset name, or that use the [default charset](#).

Allocates a new `String` containing characters constructed from an array of 8-bit integer values. Each character `c` in the resulting string is constructed from the corresponding component `b` in the byte array such that:

```
c == (char)((((hibyte & 0xff) << 8)
            | (b & 0xff)))
```

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

ascii - The bytes to be converted to characters

hibyte - The top 8 bits of each 16-bit Unicode code unit

See Also:

```
String(byte[], int, int, java.lang.String),
String(byte[], int, int, java.nio.charset.Charset),
String(byte[], int, int),
String(byte[], java.lang.String),
String(byte[], java.nio.charset.Charset),
String(byte[])
```

String

```
public String(byte[] bytes,
              int offset,
              int length,
              String charsetName)
    throws UnsupportedEncodingException
```

Constructs a new `String` by decoding the specified subarray of bytes using the specified charset. The length of the new `String` is a function of the charset, and hence may not be equal to the length of the subarray.

The behavior of this constructor when the given bytes are not valid in the given charset is unspecified. The `CharsetDecoder` class should be used when more control over the decoding process is required.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

bytes - The bytes to be decoded into characters

offset - The index of the first byte to decode

length - The number of bytes to decode

charsetName - The name of a supported [charset](#)

Throws:

[UnsupportedEncodingException](#) - If the named charset is not supported

[IndexOutOfBoundsException](#) - If offset is negative, length is negative, or offset is greater than bytes.length - length

Since:

1.1

String

```
public String(byte[] bytes,  
              int offset,  
              int length,  
              Charset charset)
```

Constructs a new `String` by decoding the specified subarray of bytes using the specified `charset`. The length of the new `String` is a function of the charset, and hence may not be equal to the length of the subarray.

This method always replaces malformed-input and unmappable-character sequences with this charset's default replacement string. The `CharsetDecoder` class should be used when more control over the decoding process is required.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

`bytes` - The bytes to be decoded into characters

`offset` - The index of the first byte to decode

`length` - The number of bytes to decode

`charset` - The `charset` to be used to decode the bytes

Throws:

`IndexOutOfBoundsException` - If `offset` is negative, `length` is negative, or `offset` is greater than `bytes.length - length`

Since:

1.6

String

```
public String(byte[] bytes,  
              String charsetName)  
    throws UnsupportedOperationException
```

Constructs a new `String` by decoding the specified array of bytes using the specified `charset`. The length of the new `String` is a function of the charset, and hence may not be equal to the length of the byte array.

The behavior of this constructor when the given bytes are not valid in the given charset is unspecified. The `CharsetDecoder` class should be used when more control over the decoding process is required.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

`bytes` - The bytes to be decoded into characters

`charsetName` - The name of a supported `charset`

Throws:

[UnsupportedEncodingException](#) - If the named charset is not supported

Since:

1.1

String

```
public String(byte[] bytes,  
              Charset charset)
```

Constructs a new `String` by decoding the specified array of bytes using the specified [charset](#). The length of the new `String` is a function of the charset, and hence may not be equal to the length of the byte array.

This method always replaces malformed-input and unmappable-character sequences with this charset's default replacement string. The [CharsetDecoder](#) class should be used when more control over the decoding process is required.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

bytes - The bytes to be decoded into characters

charset - The [charset](#) to be used to decode the bytes

Since:

1.6

String

```
public String(byte[] bytes,  
              int offset,  
              int length)
```

Constructs a new `String` by decoding the specified subarray of bytes using the [default charset](#). The length of the new `String` is a function of the charset, and hence may not be equal to the length of the subarray.

The behavior of this constructor when the given bytes are not valid in the default charset is unspecified. The [CharsetDecoder](#) class should be used when more control over the decoding process is required.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

bytes - The bytes to be decoded into characters

offset - The index of the first byte to decode

length - The number of bytes to decode

Throws:

[IndexOutOfBoundsException](#) - If offset is negative, length is negative, or offset is greater than bytes.length - length

Since:

1.1

String

```
public String(byte[] bytes)
```

Constructs a new `String` by decoding the specified array of bytes using the `default charset`. The length of the new `String` is a function of the charset, and hence may not be equal to the length of the byte array.

The behavior of this constructor when the given bytes are not valid in the default charset is unspecified. The `CharsetDecoder` class should be used when more control over the decoding process is required.

The contents of the string are unspecified if the byte array is modified during string construction.

Parameters:

bytes - The bytes to be decoded into characters

Since:

1.1

String

```
public String(StringBuffer buffer)
```

Allocates a new string that contains the sequence of characters currently contained in the string buffer argument. The contents of the string buffer are copied; subsequent modification of the string buffer does not affect the newly created string.

Parameters:

buffer - A `StringBuffer`

String

```
public String(StringBuilder builder)
```

Allocates a new string that contains the sequence of characters currently contained in the string builder argument. The contents of the string builder are copied; subsequent modification of the string builder does not affect the newly created string.

The contents of the string are unspecified if the `StringBuilder` is modified during string construction.

This constructor is provided to ease migration to `StringBuilder`. Obtaining a string from a string builder via the `toString` method is likely to run faster and is generally preferred.

Parameters:

builder - A `StringBuilder`

Since:

Method Details

length

```
public int length()
```

Returns the length of this string. The length is equal to the number of [Unicode code units](#) in the string.

Specified by:

[length](#) in interface [CharSequence](#)

Returns:

the length of the sequence of characters represented by this object.

isEmpty

```
public boolean isEmpty()
```

Returns true if, and only if, [length\(\)](#) is 0.

Specified by:

[isEmpty](#) in interface [CharSequence](#)

Returns:

true if [length\(\)](#) is 0, otherwise false

Since:

1.6

charAt

```
public char charAt(int index)
```

Returns the char value at the specified index. An index ranges from 0 to [length\(\)](#) - 1. The first char value of the sequence is at index 0, the next at index 1, and so on, as for array indexing.

If the char value specified by the index is a [surrogate](#), the surrogate value is returned.

Specified by:

[charAt](#) in interface [CharSequence](#)

Parameters:

index - the index of the char value.

Returns:

the char value at the specified index of this string. The first char value is at index 0.

Throws:

[IndexOutOfBoundsException](#) - if the index argument is negative or not less than the length of this string.

codePointAt

```
public int codePointAt(int index)
```

Returns the character (Unicode code point) at the specified index. The index refers to char values (Unicode code units) and ranges from 0 to `length()` - 1.

If the char value specified at the given index is in the high-surrogate range, the following index is less than the length of this String, and the char value at the following index is in the low-surrogate range, then the supplementary code point corresponding to this surrogate pair is returned. Otherwise, the char value at the given index is returned.

Parameters:

index - the index to the char values

Returns:

the code point value of the character at the index

Throws:

[IndexOutOfBoundsException](#) - if the index argument is negative or not less than the length of this string.

Since:

1.5

codePointBefore

```
public int codePointBefore(int index)
```

Returns the character (Unicode code point) before the specified index. The index refers to char values (Unicode code units) and ranges from 1 to `length`.

If the char value at (index - 1) is in the low-surrogate range, (index - 2) is not negative, and the char value at (index - 2) is in the high-surrogate range, then the supplementary code point value of the surrogate pair is returned. If the char value at index - 1 is an unpaired low-surrogate or a high-surrogate, the surrogate value is returned.

Parameters:

index - the index following the code point that should be returned

Returns:

the Unicode code point value before the given index.

Throws:

[IndexOutOfBoundsException](#) - if the index argument is less than 1 or greater than the length of this string.

Since:

1.5

codePointCount

```
public int codePointCount(int beginIndex,  
                          int endIndex)
```

Returns the number of Unicode code points in the specified text range of this String. The text range begins at the specified `beginIndex` and extends to the char at index `endIndex - 1`. Thus the length (in chars) of the text range is `endIndex - beginIndex`. Unpaired surrogates within the text range count as one code point each.

Parameters:

`beginIndex` - the index to the first char of the text range.

`endIndex` - the index after the last char of the text range.

Returns:

the number of Unicode code points in the specified text range

Throws:

[IndexOutOfBoundsException](#) - if the `beginIndex` is negative, or `endIndex` is larger than the length of this String, or `beginIndex` is larger than `endIndex`.

Since:

1.5

offsetByCodePoints

```
public int offsetByCodePoints(int index,  
                              int codePointOffset)
```

Returns the index within this String that is offset from the given index by `codePointOffset` code points. Unpaired surrogates within the text range given by `index` and `codePointOffset` count as one code point each.

Parameters:

`index` - the index to be offset

`codePointOffset` - the offset in code points

Returns:

the index within this String

Throws:

[IndexOutOfBoundsException](#) - if `index` is negative or larger than the length of this String, or if `codePointOffset` is positive and the substring starting with `index` has fewer than `codePointOffset` code points, or if `codePointOffset` is negative and the substring before `index` has fewer than the absolute value of `codePointOffset` code points.

Since:

1.5

getChars

```
public void getChars(int srcBegin,
                    int srcEnd,
                    char[] dst,
                    int dstBegin)
```

Copies characters from this string into the destination character array.

The first character to be copied is at index `srcBegin`; the last character to be copied is at index `srcEnd-1` (thus the total number of characters to be copied is `srcEnd-srcBegin`). The characters are copied into the subarray of `dst` starting at index `dstBegin` and ending at index:

$$\text{dstBegin} + (\text{srcEnd} - \text{srcBegin}) - 1$$
Parameters:

`srcBegin` - index of the first character in the string to copy.

`srcEnd` - index after the last character in the string to copy.

`dst` - the destination array.

`dstBegin` - the start offset in the destination array.

Throws:

[IndexOutOfBoundsException](#) - If any of the following is true:

- `srcBegin` is negative.
- `srcBegin` is greater than `srcEnd`
- `srcEnd` is greater than the length of this string
- `dstBegin` is negative
- `dstBegin+(srcEnd-srcBegin)` is larger than `dst.length`

getBytes

```
@Deprecated(since="1.1")
public void getBytes(int srcBegin,
                    int srcEnd,
                    byte[] dst,
                    int dstBegin)
```

Deprecated.

This method does not properly convert characters into bytes. As of JDK 1.1, the preferred way to do this is via the [getBytes\(\)](#) method, which uses the [default charset](#).

Copies characters from this string into the destination byte array. Each byte receives the 8 low-order bits of the corresponding character. The eight high-order bits of each character are not copied and do not participate in the transfer in any way.

The first character to be copied is at index `srcBegin`; the last character to be copied is at index `srcEnd-1`. The total number of characters to be copied is `srcEnd-srcBegin`. The characters, converted to bytes, are copied into the subarray of `dst` starting at index `dstBegin` and ending at index:

`dstBegin + (srcEnd-srcBegin) - 1`

Parameters:

`srcBegin` - Index of the first character in the string to copy

`srcEnd` - Index after the last character in the string to copy

`dst` - The destination array

`dstBegin` - The start offset in the destination array

Throws:

[IndexOutOfBoundsException](#) - If any of the following is true:

- `srcBegin` is negative
- `srcBegin` is greater than `srcEnd`
- `srcEnd` is greater than the length of this `String`
- `dstBegin` is negative
- `dstBegin+(srcEnd-srcBegin)` is larger than `dst.length`

getBytes

```
public byte[] getBytes(String charsetName)  
                throws UnsupportedEncodingException
```

Encodes this `String` into a sequence of bytes using the named charset, storing the result into a new byte array.

The behavior of this method when this string cannot be encoded in the given charset is unspecified. The [CharsetEncoder](#) class should be used when more control over the encoding process is required.

Parameters:

`charsetName` - The name of a supported [charset](#)

Returns:

The resultant byte array

Throws:

[UnsupportedEncodingException](#) - If the named charset is not supported

Since:

1.1

getBytes

```
public byte[] getBytes(Charset charset)
```

Encodes this `String` into a sequence of bytes using the given [charset](#), storing the result into a new byte array.

This method always replaces malformed-input and unmappable-character sequences with this charset's default replacement byte array. The [CharsetEncoder](#) class should be used when more control over the encoding process is required.

Parameters:

charset - The [Charset](#) to be used to encode the String

Returns:

The resultant byte array

Since:

1.6

getBytes

```
public byte[] getBytes()
```

Encodes this String into a sequence of bytes using the [default charset](#), storing the result into a new byte array.

The behavior of this method when this string cannot be encoded in the default charset is unspecified. The [CharsetEncoder](#) class should be used when more control over the encoding process is required.

Returns:

The resultant byte array

Since:

1.1

equals

```
public boolean equals(Object anObject)
```

Compares this string to the specified object. The result is `true` if and only if the argument is not null and is a String object that represents the same sequence of characters as this object.

For finer-grained String comparison, refer to [Collator](#).

Overrides:

[equals](#) in class [Object](#)

Parameters:

`anObject` - The object to compare this String against

Returns:

`true` if the given object represents a String equivalent to this string, `false` otherwise

See Also:

[compareTo\(String\)](#), [equalsIgnoreCase\(String\)](#)

contentEquals

```
public boolean contentEquals(StringBuffer sb)
```

Compares this string to the specified StringBuffer. The result is `true` if and only if this String represents the same sequence of characters as the specified StringBuffer. This method synchronizes on the StringBuffer.

For finer-grained String comparison, refer to [Collator](#).

Parameters:

sb - The StringBuffer to compare this String against

Returns:

true if this String represents the same sequence of characters as the specified StringBuffer, false otherwise

Since:

1.4

contentEquals

```
public boolean contentEquals(CharSequence cs)
```

Compares this string to the specified CharSequence. The result is true if and only if this String represents the same sequence of char values as the specified sequence. Note that if the CharSequence is a StringBuffer then the method synchronizes on it.

For finer-grained String comparison, refer to [Collator](#).

Parameters:

cs - The sequence to compare this String against

Returns:

true if this String represents the same sequence of char values as the specified sequence, false otherwise

Since:

1.5

equalsIgnoreCase

```
public boolean equalsIgnoreCase(String anotherString)
```

Compares this String to another String, ignoring case considerations. Two strings are considered equal ignoring case if they are of the same length and corresponding Unicode code points in the two strings are equal ignoring case.

Two Unicode code points are considered the same ignoring case if at least one of the following is true:

- The two Unicode code points are the same (as compared by the == operator)
- Calling `Character.toLowerCase(Character.toUpperCase(int))` on each Unicode code point produces the same result

Note that this method does *not* take locale into account, and will result in unsatisfactory results for certain locales. The [Collator](#) class provides locale-sensitive comparison.

Parameters:

anotherString - The String to compare this String against

Returns:

true if the argument is not null and it represents an equivalent String ignoring case;
false otherwise

See Also:

[equals\(Object\)](#), [codePoints\(\)](#)

compareTo

```
public int compareTo(String anotherString)
```

Compares two strings lexicographically. The comparison is based on the Unicode value of each character in the strings. The character sequence represented by this String object is compared lexicographically to the character sequence represented by the argument string. The result is a negative integer if this String object lexicographically precedes the argument string. The result is a positive integer if this String object lexicographically follows the argument string. The result is zero if the strings are equal; compareTo returns 0 exactly when the [equals\(Object\)](#) method would return true.

This is the definition of lexicographic ordering. If two strings are different, then either they have different characters at some index that is a valid index for both strings, or their lengths are different, or both. If they have different characters at one or more index positions, let k be the smallest such index; then the string whose character at position k has the smaller value, as determined by using the $<$ operator, lexicographically precedes the other string. In this case, compareTo returns the difference of the two character values at position k in the two string -- that is, the value:

$$\text{this.charAt}(k) - \text{anotherString.charAt}(k)$$

If there is no index position at which they differ, then the shorter string lexicographically precedes the longer string. In this case, compareTo returns the difference of the lengths of the strings -- that is, the value:

$$\text{this.length}() - \text{anotherString.length}()$$

For finer-grained String comparison, refer to [Collator](#).

Specified by:

compareTo in interface [Comparable<String>](#)

Parameters:

anotherString - the String to be compared.

Returns:

the value 0 if the argument string is equal to this string; a value less than 0 if this string is lexicographically less than the string argument; and a value greater than 0 if this string is lexicographically greater than the string argument.

compareToIgnoreCase

```
public int compareToIgnoreCase(String str)
```

Compares two strings lexicographically, ignoring case differences. This method returns an integer whose sign is that of calling `compareTo` with case folded versions of the strings where case differences have been eliminated by calling `Character.toLowerCase(Character.toUpperCase(int))` on each Unicode code point.

Note that this method does *not* take locale into account, and will result in an unsatisfactory ordering for certain locales. The [Collator](#) class provides locale-sensitive comparison.

Parameters:

`str` - the String to be compared.

Returns:

a negative integer, zero, or a positive integer as the specified String is greater than, equal to, or less than this String, ignoring case considerations.

Since:

1.2

See Also:

[Collator](#), [codePoints\(\)](#)

regionMatches

```
public boolean regionMatches(int toffset,  
                             String other,  
                             int ooffset,  
                             int len)
```

Tests if two string regions are equal.

A substring of this String object is compared to a substring of the argument `other`. The result is true if these substrings represent identical character sequences. The substring of this String object to be compared begins at index `toffset` and has length `len`. The substring of `other` to be compared begins at index `ooffset` and has length `len`. The result is false if and only if at least one of the following is true:

- `toffset` is negative.
- `ooffset` is negative.
- `toffset+len` is greater than the length of this String object.
- `ooffset+len` is greater than the length of the other argument.
- There is some nonnegative integer k less than `len` such that:
`this.charAt(toffset + k) != other.charAt(ooffset + k)`

Note that this method does *not* take locale into account. The [Collator](#) class provides locale-sensitive comparison.

Parameters:

`toffset` - the starting offset of the subregion in this string.

`other` - the string argument.

`ooffset` - the starting offset of the subregion in the string argument.

`len` - the number of characters to compare.

Returns:

true if the specified subregion of this string exactly matches the specified subregion of the string argument; false otherwise.

regionMatches

```
public boolean regionMatches(boolean ignoreCase,  
                             int toffset,  
                             String other,  
                             int ooffset,  
                             int len)
```

Tests if two string regions are equal.

A substring of this String object is compared to a substring of the argument other. The result is true if these substrings represent Unicode code point sequences that are the same, ignoring case if and only if ignoreCase is true. The sequences tsequence and osequence are compared, where tsequence is the sequence produced as if by calling this.substring(toffset, toffset + len).codePoints() and osequence is the sequence produced as if by calling other.substring(ooffset, ooffset + len).codePoints(). The result is true if and only if all of the following are true:

- toffset is non-negative.
- ooffset is non-negative.
- toffset+len is less than or equal to the length of this String object.
- ooffset+len is less than or equal to the length of the other argument.
- if ignoreCase is false, all pairs of corresponding Unicode code points are equal integer values; or if ignoreCase is true, `Character.toLowerCase(Character.toUpperCase(int))` on all pairs of Unicode code points results in equal integer values.

Note that this method does *not* take locale into account, and will result in unsatisfactory results for certain locales when ignoreCase is true. The `Collator` class provides locale-sensitive comparison.

Parameters:

ignoreCase - if true, ignore case when comparing characters.

toffset - the starting offset of the subregion in this string.

other - the string argument.

ooffset - the starting offset of the subregion in the string argument.

len - the number of characters (Unicode code units - 16bit char value) to compare.

Returns:

true if the specified subregion of this string matches the specified subregion of the string argument; false otherwise. Whether the matching is exact or case insensitive depends on the ignoreCase argument.

See Also:

`codePoints()`

startsWith

```
public boolean startsWith(String prefix,  
                        int toffset)
```

Tests if the substring of this string beginning at the specified index starts with the specified prefix.

Parameters:

prefix - the prefix.

toffset - where to begin looking in this string.

Returns:

true if the character sequence represented by the argument is a prefix of the substring of this object starting at index toffset; false otherwise. The result is false if toffset is negative or greater than the length of this `String` object; otherwise the result is the same as the result of the expression

```
this.substring(toffset).startsWith(prefix)
```

startsWith

```
public boolean startsWith(String prefix)
```

Tests if this string starts with the specified prefix.

Parameters:

prefix - the prefix.

Returns:

true if the character sequence represented by the argument is a prefix of the character sequence represented by this string; false otherwise. Note also that true will be returned if the argument is an empty string or is equal to this `String` object as determined by the [equals\(Object\)](#) method.

Since:

1.0

endsWith

```
public boolean endsWith(String suffix)
```

Tests if this string ends with the specified suffix.

Parameters:

suffix - the suffix.

Returns:

true if the character sequence represented by the argument is a suffix of the character sequence represented by this object; false otherwise. Note that the result will be true if the argument is the empty string or is equal to this `String` object as determined by the [equals\(Object\)](#) method.

hashCode

```
public int hashCode()
```

Returns a hash code for this string. The hash code for a `String` object is computed as

$$s[0]*31^{(n-1)} + s[1]*31^{(n-2)} + \dots + s[n-1]$$

using `int` arithmetic, where `s[i]` is the *i*th character of the string, *n* is the length of the string, and [^] indicates exponentiation. (The hash value of the empty string is zero.)

Overrides:

`hashCode` in class `Object`

Returns:

a hash code value for this object.

See Also:

`Object.equals(java.lang.Object)`,

`System.identityHashCode(java.lang.Object)`

indexOf

```
public int indexOf(int ch)
```

Returns the index within this string of the first occurrence of the specified character. If a character with value `ch` occurs in the character sequence represented by this `String` object, then the index (in Unicode code units) of the first such occurrence is returned. For values of `ch` in the range from 0 to 0xFFFF (inclusive), this is the smallest value *k* such that:

```
this.charAt(k) == ch
```

is true. For other values of `ch`, it is the smallest value *k* such that:

```
this.codePointAt(k) == ch
```

is true. In either case, if no such character occurs in this string, then -1 is returned.

Parameters:

`ch` - a character (Unicode code point).

Returns:

the index of the first occurrence of the character in the character sequence represented by this object, or -1 if the character does not occur.

indexOf

```
public int indexOf(int ch,  
                  int fromIndex)
```

Returns the index within this string of the first occurrence of the specified character, starting the search at the specified index.

If a character with value `ch` occurs in the character sequence represented by this `String` object at an index no smaller than `fromIndex`, then the index of the first such occurrence is returned. For values of `ch` in the range from 0 to 0xFFFF (inclusive), this is the smallest value k such that:

```
(this.charAt(k) == ch) && (k >= fromIndex)
```

is true. For other values of `ch`, it is the smallest value k such that:

```
(this.codePointAt(k) == ch) && (k >= fromIndex)
```

is true. In either case, if no such character occurs in this string at or after position `fromIndex`, then `-1` is returned.

There is no restriction on the value of `fromIndex`. If it is negative, it has the same effect as if it were zero: this entire string may be searched. If it is greater than the length of this string, it has the same effect as if it were equal to the length of this string: `-1` is returned.

All indices are specified in char values (Unicode code units).

API Note:

Unlike `substring(int)`, for example, this method does not throw an exception when `fromIndex` is outside the valid range. Rather, it returns `-1` when `fromIndex` is larger than the length of the string. This result is, by itself, indistinguishable from a genuine absence of `ch` in the string. If stricter behavior is needed, `indexOf(int, int, int)` should be considered instead. On a `String s`, for example, `s.indexOf(ch, fromIndex, s.length())` would throw if `fromIndex` were larger than the string length, or were negative.

Parameters:

`ch` - a character (Unicode code point).

`fromIndex` - the index to start the search from.

Returns:

the index of the first occurrence of the character in the character sequence represented by this object that is greater than or equal to `fromIndex`, or `-1` if the character does not occur.

indexOf

```
public int indexOf(int ch,  
                  int beginIndex,  
                  int endIndex)
```

Returns the index within this string of the first occurrence of the specified character, starting the search at `beginIndex` and stopping before `endIndex`.

If a character with value `ch` occurs in the character sequence represented by this `String` object at an index no smaller than `beginIndex` but smaller than `endIndex`, then

the index of the first such occurrence is returned. For values of `ch` in the range from 0 to 0xFFFF (inclusive), this is the smallest value k such that:

```
(this.charAt(k) == ch) && (beginIndex <= k < endIndex)
```

is true. For other values of `ch`, it is the smallest value k such that:

```
(this.codePointAt(k) == ch) && (beginIndex <= k < endIndex)
```

is true. In either case, if no such character occurs in this string at or after position `beginIndex` and before position `endIndex`, then -1 is returned.

All indices are specified in char values (Unicode code units).

Parameters:

`ch` - a character (Unicode code point).

`beginIndex` - the index to start the search from (included).

`endIndex` - the index to stop the search at (excluded).

Returns:

the index of the first occurrence of the character in the character sequence represented by this object that is greater than or equal to `beginIndex` and less than `endIndex`, or -1 if the character does not occur.

Throws:

[StringIndexOutOfBoundsException](#) - if `beginIndex` is negative, or `endIndex` is larger than the length of this String object, or `beginIndex` is larger than `endIndex`.

Since:

21

lastIndexOf

```
public int lastIndexOf(int ch)
```

Returns the index within this string of the last occurrence of the specified character. For values of `ch` in the range from 0 to 0xFFFF (inclusive), the index (in Unicode code units) returned is the largest value k such that:

```
this.charAt(k) == ch
```

is true. For other values of `ch`, it is the largest value k such that:

```
this.codePointAt(k) == ch
```

is true. In either case, if no such character occurs in this string, then -1 is returned. The String is searched backwards starting at the last character.

Parameters:

`ch` - a character (Unicode code point).

Returns:

the index of the last occurrence of the character in the character sequence represented by this object, or -1 if the character does not occur.

lastIndexOf

```
public int lastIndexOf(int ch,  
                      int fromIndex)
```

Returns the index within this string of the last occurrence of the specified character, searching backward starting at the specified index. For values of `ch` in the range from 0 to 0xFFFF (inclusive), the index returned is the largest value k such that:

$$(this.charAt(k) == ch) \ \&\& \ (k \leq fromIndex)$$

is true. For other values of `ch`, it is the largest value k such that:

$$(this.codePointAt(k) == ch) \ \&\& \ (k \leq fromIndex)$$

is true. In either case, if no such character occurs in this string at or before position `fromIndex`, then -1 is returned.

All indices are specified in char values (Unicode code units).

Parameters:

`ch` - a character (Unicode code point).

`fromIndex` - the index to start the search from. There is no restriction on the value of `fromIndex`. If it is greater than or equal to the length of this string, it has the same effect as if it were equal to one less than the length of this string: this entire string may be searched. If it is negative, it has the same effect as if it were -1: -1 is returned.

Returns:

the index of the last occurrence of the character in the character sequence represented by this object that is less than or equal to `fromIndex`, or -1 if the character does not occur before that point.

indexOf

```
public int indexOf(String str)
```

Returns the index within this string of the first occurrence of the specified substring.

The returned index is the smallest value k for which:

$$this.startsWith(str, k)$$

If no such value of k exists, then -1 is returned.

Parameters:

`str` - the substring to search for.

Returns:

the index of the first occurrence of the specified substring, or -1 if there is no such occurrence.

indexOf

```
public int indexOf(String str,  
                  int fromIndex)
```

Returns the index within this string of the first occurrence of the specified substring, starting at the specified index.

The returned index is the smallest value *k* for which:

```
k >= Math.min(fromIndex, this.length()) &&  
this.startsWith(str, k)
```

If no such value of *k* exists, then -1 is returned.

API Note:

Unlike `substring(int)`, for example, this method does not throw an exception when `fromIndex` is outside the valid range. Rather, it returns -1 when `fromIndex` is larger than the length of the string. This result is, by itself, indistinguishable from a genuine absence of `str` in the string. If stricter behavior is needed, `indexOf(String, int, int)` should be considered instead. On `String` *s* and a non-empty `str`, for example, `s.indexOf(str, fromIndex, s.length())` would throw if `fromIndex` were larger than the string length, or were negative.

Parameters:

`str` - the substring to search for.

`fromIndex` - the index from which to start the search.

Returns:

the index of the first occurrence of the specified substring, starting at the specified index, or -1 if there is no such occurrence.

indexOf

```
public int indexOf(String str,  
                  int beginIndex,  
                  int endIndex)
```

Returns the index of the first occurrence of the specified substring within the specified index range of this string.

This method returns the same result as the one of the invocation

```
s.substring(beginIndex, endIndex).indexOf(str) + beginIndex
```

if the index returned by `indexOf(String)` is non-negative, and returns -1 otherwise. (No substring is instantiated, though.)

Parameters:

str - the substring to search for.

beginIndex - the index to start the search from (included).

endIndex - the index to stop the search at (excluded).

Returns:

the index of the first occurrence of the specified substring within the specified index range, or -1 if there is no such occurrence.

Throws:

[StringIndexOutOfBoundsException](#) - if beginIndex is negative, or endIndex is larger than the length of this String object, or beginIndex is larger than endIndex.

Since:

21

lastIndexOf

```
public int lastIndexOf(String str)
```

Returns the index within this string of the last occurrence of the specified substring. The last occurrence of the empty string "" is considered to occur at the index value `this.length()`.

The returned index is the largest value k for which:

```
this.startsWith(str, k)
```

If no such value of k exists, then -1 is returned.

Parameters:

str - the substring to search for.

Returns:

the index of the last occurrence of the specified substring, or -1 if there is no such occurrence.

lastIndexOf

```
public int lastIndexOf(String str,  
                        int fromIndex)
```

Returns the index within this string of the last occurrence of the specified substring, searching backward starting at the specified index.

The returned index is the largest value k for which:

```
k <= Math.min(fromIndex, this.length()) &&  
this.startsWith(str, k)
```

If no such value of `k` exists, then `-1` is returned.

Parameters:

`str` - the substring to search for.

`fromIndex` - the index to start the search from.

Returns:

the index of the last occurrence of the specified substring, searching backward from the specified index, or `-1` if there is no such occurrence.

substring

```
public String substring(int beginIndex)
```

Returns a string that is a substring of this string. The substring begins with the character at the specified index and extends to the end of this string.

Examples:

```
"unhappy".substring(2) returns "happy"
"Harbison".substring(3) returns "bison"
"emptiness".substring(9) returns "" (an empty string)
```

Parameters:

`beginIndex` - the beginning index, inclusive.

Returns:

the specified substring.

Throws:

[IndexOutOfBoundsException](#) - if `beginIndex` is negative or larger than the length of this `String` object.

substring

```
public String substring(int beginIndex,
                        int endIndex)
```

Returns a string that is a substring of this string. The substring begins at the specified `beginIndex` and extends to the character at index `endIndex - 1`. Thus the length of the substring is `endIndex - beginIndex`.

Examples:

```
"hamburger".substring(4, 8) returns "urge"
"smiles".substring(1, 5) returns "mile"
```

Parameters:

`beginIndex` - the beginning index, inclusive.

`endIndex` - the ending index, exclusive.

Returns:

the specified substring.

Throws:

[IndexOutOfBoundsException](#) - if the `beginIndex` is negative, or `endIndex` is larger than the length of this `String` object, or `beginIndex` is larger than `endIndex`.

subSequence

```
public CharSequence subSequence(int beginIndex,  
                                int endIndex)
```

Returns a character sequence that is a subsequence of this sequence.

An invocation of this method of the form

```
    str.subSequence(begin, end)
```

behaves in exactly the same way as the invocation

```
    str.substring(begin, end)
```

Specified by:

`subSequence` in interface [CharSequence](#)

API Note:

This method is defined so that the `String` class can implement the [CharSequence](#) interface.

Parameters:

`beginIndex` - the begin index, inclusive.

`endIndex` - the end index, exclusive.

Returns:

the specified subsequence.

Throws:

[IndexOutOfBoundsException](#) - if `beginIndex` or `endIndex` is negative, if `endIndex` is greater than `length()`, or if `beginIndex` is greater than `endIndex`

Since:

1.4

concat

```
public String concat(String str)
```

Concatenates the specified string to the end of this string.

If the length of the argument string is 0, then this `String` object is returned. Otherwise, a `String` object is returned that represents a character sequence that is the concatenation of the character sequence represented by this `String` object and the character sequence represented by the argument string.

Examples:

```
"cares".concat("s") returns "caress"
```

```
"to".concat("get").concat("her") returns "together"
```

Parameters:

str - the String that is concatenated to the end of this String.

Returns:

a string that represents the concatenation of this object's characters followed by the string argument's characters.

replace

```
public String replace(char oldChar,  
                      char newChar)
```

Returns a string resulting from replacing all occurrences of oldChar in this string with newChar.

If the character oldChar does not occur in the character sequence represented by this String object, then a reference to this String object is returned. Otherwise, a String object is returned that represents a character sequence identical to the character sequence represented by this String object, except that every occurrence of oldChar is replaced by an occurrence of newChar.

Examples:

```
"mesquite in your cellar".replace('e', 'o')  
returns "mosquito in your collar"
```

```
"the war of baronets".replace('r', 'y')  
returns "the way of bayonets"
```

```
"sparring with a purple porpoise".replace('p', 't')  
returns "starring with a turtle tortoise"
```

```
"JonL".replace('q', 'x') returns "JonL" (no change)
```

Parameters:

oldChar - the old character.

newChar - the new character.

Returns:

a string derived from this string by replacing every occurrence of oldChar with newChar.

matches

```
public boolean matches(String regex)
```

Tells whether or not this string matches the given [regular expression](#).

An invocation of this method of the form `str.matches(regex)` yields exactly the same result as the expression

`Pattern.matches(regex, str)`

Parameters:

regex - the regular expression to which this string is to be matched

Returns:

true if, and only if, this string matches the given regular expression

Throws:

`PatternSyntaxException` - if the regular expression's syntax is invalid

Since:

1.4

See Also:

`Pattern`

contains

`public boolean contains(CharSequence s)`

Returns true if and only if this string contains the specified sequence of char values.

Parameters:

s - the sequence to search for

Returns:

true if this string contains s, false otherwise

Since:

1.5

replaceFirst

`public String replaceFirst(String regex,
 String replacement)`

Replaces the first substring of this string that matches the given `regular expression` with the given replacement.

An invocation of this method of the form `str.replaceFirst(regex, repl)` yields exactly the same result as the expression

`Pattern.compile(regex).matcher(str).replaceFirst(repl)`

Note that backslashes (\) and dollar signs (\$) in the replacement string may cause the results to be different than if it were being treated as a literal replacement string; see `Matcher.replaceFirst(java.lang.String)`. Use `Matcher.quoteReplacement(java.lang.String)` to suppress the special meaning of these characters, if desired.

Parameters:

regex - the regular expression to which this string is to be matched

replacement - the string to be substituted for the first match

Returns:

The resulting String

Throws:

[PatternSyntaxException](#) - if the regular expression's syntax is invalid

Since:

1.4

See Also:

[Pattern](#)

replaceAll

```
public String replaceAll(String regex,  
                        String replacement)
```

Replaces each substring of this string that matches the given [regular expression](#) with the given replacement.

An invocation of this method of the form *str.replaceAll(regex, repl)* yields exactly the same result as the expression

```
Pattern.compile(regex).matcher(str).replaceAll(repl)
```

Note that backslashes (\) and dollar signs (\$) in the replacement string may cause the results to be different than if it were being treated as a literal replacement string; see [Matcher.replaceAll](#). Use [Matcher.quoteReplacement\(java.lang.String\)](#) to suppress the special meaning of these characters, if desired.

Parameters:

regex - the regular expression to which this string is to be matched

replacement - the string to be substituted for each match

Returns:

The resulting String

Throws:

[PatternSyntaxException](#) - if the regular expression's syntax is invalid

Since:

1.4

See Also:

[Pattern](#)

replace

```
public String replace(CharSequence target,  
                    CharSequence replacement)
```

Replaces each substring of this string that matches the literal target sequence with the specified literal replacement sequence. The replacement proceeds from the beginning of the string to the end, for example, replacing "aa" with "b" in the string "aaa" will result in "ba" rather than "ab".

Parameters:

target - The sequence of char values to be replaced

replacement - The replacement sequence of char values

Returns:

The resulting string

Since:

1.5

split

```
public String[] split(String regex,  
                      int limit)
```

Splits this string around matches of the given [regular expression](#).

The array returned by this method contains each substring of this string that is terminated by another substring that matches the given expression or is terminated by the end of the string. The substrings in the array are in the order in which they occur in this string. If the expression does not match any part of the input then the resulting array has just one element, namely this string.

When there is a positive-width match at the beginning of this string then an empty leading substring is included at the beginning of the resulting array. A zero-width match at the beginning however never produces such empty leading substring.

The `limit` parameter controls the number of times the pattern is applied and therefore affects the length of the resulting array.

- If the *limit* is positive then the pattern will be applied at most *limit* - 1 times, the array's length will be no greater than *limit*, and the array's last entry will contain all input beyond the last matched delimiter.
- If the *limit* is zero then the pattern will be applied as many times as possible, the array can have any length, and trailing empty strings will be discarded.
- If the *limit* is negative then the pattern will be applied as many times as possible and the array can have any length.

The string "boo:and:foo", for example, yields the following results with these parameters:

Regex	Limit	Result
:	2	{ "boo", "and:foo" }
	5	{ "boo", "and", "foo" }
	-2	{ "boo", "and", "foo" }
o	5	{ "b", "", ":and:f", "", "" }
	-2	{ "b", "", ":and:f", "", "" }
	0	{ "b", "", ":and:f" }

An invocation of this method of the form `str.split(regex, n)` yields the same result as the expression


```
Pattern.compile(regex).split(str, n)
```

Parameters:

regex - the delimiting regular expression

limit - the result threshold, as described above

Returns:

the array of strings computed by splitting this string around matches of the given regular expression

Throws:

[PatternSyntaxException](#) - if the regular expression's syntax is invalid

Since:

1.4

See Also:

[Pattern](#)

splitWithDelimiters

```
public String[] splitWithDelimiters(String regex,  
                                   int limit)
```

Splits this string around matches of the given regular expression and returns both the strings and the matching delimiters.

The array returned by this method contains each substring of this string that is terminated by another substring that matches the given expression or is terminated by the end of the string. Each substring is immediately followed by the subsequence (the delimiter) that matches the given expression, *except* for the last substring, which is not followed by anything. The substrings in the array and the delimiters are in the order in which they occur in the input. If the expression does not match any part of the input then the resulting array has just one element, namely this string.

When there is a positive-width match at the beginning of this string then an empty leading substring is included at the beginning of the resulting array. A zero-width match at the beginning however never produces such empty leading substring nor the empty delimiter.

The `limit` parameter controls the number of times the pattern is applied and therefore affects the length of the resulting array.

- If the *limit* is positive then the pattern will be applied at most *limit* - 1 times, the array's length will be no greater than $2 \times \text{limit} - 1$, and the array's last entry will contain all input beyond the last matched delimiter.
- If the *limit* is zero then the pattern will be applied as many times as possible, the array can have any length, and trailing empty strings will be discarded.
- If the *limit* is negative then the pattern will be applied as many times as possible and the array can have any length.

The input "boo:::and:::foo", for example, yields the following results with these parameters:

Regex	Limit	Result
:+	2	{ "boo", "::::", "and::foo" }
	5	{ "boo", "::::", "and", ":", "foo" }
	-1	{ "boo", "::::", "and", ":", "foo" }
o	5	{ "b", "o", "", "o", "::::and::f", "o", "", "o", "" }
	-1	{ "b", "o", "", "o", "::::and::f", "o", "", "o", "" }
	0	{ "b", "o", "", "o", "::::and::f", "o", "", "o" }

API Note:

An invocation of this method of the form `str.splitWithDelimiters(regex, n)` yields the same result as the expression

```
Pattern.compile(regex).splitWithDelimiters(str, n)
```

Parameters:

regex - the delimiting regular expression

limit - the result threshold, as described above

Returns:

the array of strings computed by splitting this string around matches of the given regular expression, alternating substrings and matching delimiters

Since:

21

split

```
public String[] split(String regex)
```

Splits this string around matches of the given [regular expression](#).

This method works as if by invoking the two-argument [split](#) method with the given expression and a limit argument of zero. Trailing empty strings are therefore not included in the resulting array.

The string "boo:and:foo", for example, yields the following results with these expressions:

Regex	Result
:	{ "boo", "and", "foo" }
o	{ "b", "", ":and:f" }

Parameters:

regex - the delimiting regular expression

Returns:

the array of strings computed by splitting this string around matches of the given regular expression

Throws:

[PatternSyntaxException](#) - if the regular expression's syntax is invalid

Since:

1.4

See Also:

[Pattern](#)

join

```
public static String join(CharSequence delimiter,  
                           CharSequence... elements)
```

Returns a new String composed of copies of the CharSequence elements joined together with a copy of the specified delimiter.

For example,

```
String message = String.join("-", "Java", "is", "cool");  
// message returned is: "Java-is-cool"
```

Note that if an element is null, then "null" is added.

Parameters:

delimiter - the delimiter that separates each element

elements - the elements to join together.

Returns:

a new String that is composed of the elements separated by the delimiter

Throws:

[NullPointerException](#) - If delimiter or elements is null

Since:

1.8

See Also:

[StringJoiner](#)

join

```
public static String join(CharSequence delimiter,  
                           Iterable<? extends CharSequence> elements)
```

Returns a new String composed of copies of the CharSequence elements joined together with a copy of the specified delimiter.

For example,

```
List<String> strings = List.of("Java", "is", "cool");  
String message = String.join(" ", strings);  
// message returned is: "Java is cool"  
  
Set<String> strings =  
    new LinkedHashSet<>(List.of("Java", "is", "very", "cool"));
```

```
String message = String.join("-", strings);
// message returned is: "Java-is-very-cool"
```

Note that if an individual element is null, then "null" is added.

Parameters:

delimiter - a sequence of characters that is used to separate each of the elements in the resulting String

elements - an Iterable that will have its elements joined together.

Returns:

a new String that is composed from the elements argument

Throws:

[NullPointerException](#) - If delimiter or elements is null

Since:

1.8

See Also:

[join\(CharSequence,CharSequence...\)](#),
[StringJoiner](#)

toLowerCase

```
public String toLowerCase(Locale locale)
```

Converts all of the characters in this String to lower case using the rules of the given Locale. Case mapping is based on the Unicode Standard version specified by the [Character](#) class. Since case mappings are not always 1:1 char mappings, the resulting String and this String may differ in length.

Examples of lowercase mappings are in the following table:

Language Code of Locale	Upper Case	Lower Case	Description
tr (Turkish)	\u0130	\u0069	capital letter I with dot above -> small letter i
tr (Turkish)	\u0049	\u0131	capital letter I -> small letter dotless i
(all)	French Fries	french fries	lowercased all chars in String
(all)	ΙΧΘΥΣ	ιχθυσ	lowercased all chars in String

Parameters:

locale - use the case transformation rules for this locale

Returns:

the String, converted to lowercase.

Since:

1.1

See Also:

`toLowerCase()`, `toUpperCase()`, `toUpperCase(Locale)`

toLowerCase

```
public String toLowerCase()
```

Converts all of the characters in this `String` to lower case using the rules of the default locale. This method is equivalent to `toLowerCase(Locale.getDefault())`.

API Note:

This method is locale sensitive, and may produce unexpected results if used for strings that are intended to be interpreted locale independently. Examples are programming language identifiers, protocol keys, and HTML tags. For instance, `"TITLE".toLowerCase()` in a Turkish locale returns `"t\u0131tle"`, where `'\u0131'` is the LATIN SMALL LETTER DOTLESS I character. To obtain correct results for locale insensitive strings, use `toLowerCase(Locale.ROOT)`.

Returns:

the `String`, converted to lowercase.

See Also:

`toLowerCase(Locale)`

toUpperCase

```
public String toUpperCase(Locale locale)
```

Converts all of the characters in this `String` to upper case using the rules of the given `Locale`. Case mapping is based on the Unicode Standard version specified by the `Character` class. Since case mappings are not always 1:1 char mappings, the resulting `String` and this `String` may differ in length.

Examples of locale-sensitive and 1:M case mappings are in the following table:

Language Code of Locale	Lower Case	Upper Case	Description
tr (Turkish)	\u0069	\u0130	small letter i -> capital letter I with dot above
tr (Turkish)	\u0131	\u0049	small letter dotless i -> capital letter I
(all)	\u00df	\u0053 \u0053	small letter sharp s -> two letters: SS
(all)	Fahrvergnügen	FAHRVERGNÜGEN	

Parameters:

`locale` - use the case transformation rules for this locale

Returns:

the `String`, converted to uppercase.

Since:

1.1

See Also:

`toUpperCase()`, `toLowerCase()`, `toLowerCase(Locale)`

toUpperCase

```
public String toUpperCase()
```

Converts all of the characters in this `String` to upper case using the rules of the default locale. This method is equivalent to `toUpperCase(Locale.getDefault())`.

API Note:

This method is locale sensitive, and may produce unexpected results if used for strings that are intended to be interpreted locale independently. Examples are programming language identifiers, protocol keys, and HTML tags. For instance, `"title".toUpperCase()` in a Turkish locale returns `"T\u0130TLE"`, where `'\u0130'` is the LATIN CAPITAL LETTER I WITH DOT ABOVE character. To obtain correct results for locale insensitive strings, use `toUpperCase(Locale.ROOT)`.

Returns:

the `String`, converted to uppercase.

See Also:

`toUpperCase(Locale)`

trim

```
public String trim()
```

Returns a string whose value is this string, with all leading and trailing space removed, where space is defined as any character whose codepoint is less than or equal to `'U+0020'` (the space character).

If this `String` object represents an empty character sequence, or the first and last characters of character sequence represented by this `String` object both have codes that are not space (as defined above), then a reference to this `String` object is returned.

Otherwise, if all characters in this string are space (as defined above), then a `String` object representing an empty string is returned.

Otherwise, let k be the index of the first character in the string whose code is not a space (as defined above) and let m be the index of the last character in the string whose code is not a space (as defined above). A `String` object is returned, representing the substring of this string that begins with the character at index k and ends with the character at index m -that is, the result of `this.substring(k, m + 1)`.

This method may be used to trim space (as defined above) from the beginning and end of a string.

Returns:

a string whose value is this string, with all leading and trailing space removed, or this string if it has no leading or trailing space.

strip

```
public String strip()
```

Returns a string whose value is this string, with all leading and trailing [white space](#) removed.

If this `String` object represents an empty string, or if all code points in this string are [white space](#), then an empty string is returned.

Otherwise, returns a substring of this string beginning with the first code point that is not a [white space](#) up to and including the last code point that is not a [white space](#).

This method may be used to strip [white space](#) from the beginning and end of a string.

Returns:

a string whose value is this string, with all leading and trailing white space removed

Since:

11

See Also:

[Character.isWhitespace\(int\)](#)

stripLeading

```
public String stripLeading()
```

Returns a string whose value is this string, with all leading [white space](#) removed.

If this `String` object represents an empty string, or if all code points in this string are [white space](#), then an empty string is returned.

Otherwise, returns a substring of this string beginning with the first code point that is not a [white space](#) up to and including the last code point of this string.

This method may be used to trim [white space](#) from the beginning of a string.

Returns:

a string whose value is this string, with all leading white space removed

Since:

11

See Also:

[Character.isWhitespace\(int\)](#)

stripTrailing

```
public String stripTrailing()
```

Returns a string whose value is this string, with all trailing [white space](#) removed.

If this `String` object represents an empty string, or if all characters in this string are [white space](#), then an empty string is returned.

Otherwise, returns a substring of this string beginning with the first code point of this string up to and including the last code point that is not a [white space](#).

This method may be used to trim [white space](#) from the end of a string.

Returns:

a string whose value is this string, with all trailing white space removed

Since:

11

See Also:

[Character.isWhitespace\(int\)](#)

isBlank

```
public boolean isBlank()
```

Returns true if the string is empty or contains only [white space](#) codepoints, otherwise false.

Returns:

true if the string is empty or contains only [white space](#) codepoints, otherwise false

Since:

11

See Also:

[Character.isWhitespace\(int\)](#)

lines

```
public Stream<String> lines()
```

Returns a stream of lines extracted from this string, separated by line terminators.

A *line terminator* is one of the following: a line feed character `"\n"` (U+000A), a carriage return character `"\r"` (U+000D), or a carriage return followed immediately by a line feed `"\r\n"` (U+000D U+000A).

A *line* is either a sequence of zero or more characters followed by a line terminator, or it is a sequence of one or more characters followed by the end of the string. A line does not include the line terminator.

The stream returned by this method contains the lines from this string in the order in which they occur.

API Note:

This definition of *line* implies that an empty string has zero lines and that there is no empty line following a line terminator at the end of a string.

Implementation Note:

This method provides better performance than `split("\R")` by supplying elements lazily and by faster search of new line terminators.

Returns:

the stream of lines extracted from this string

Since:

11

indent

```
public String indent(int n)
```

Adjusts the indentation of each line of this string based on the value of `n`, and normalizes line termination characters.

This string is conceptually separated into lines using `lines()`. Each line is then adjusted as described below and then suffixed with a line feed `"\n"` (U+000A). The resulting lines are then concatenated and returned.

If `n > 0` then `n` spaces (U+0020) are inserted at the beginning of each line.

If `n < 0` then up to `n` [white space characters](#) are removed from the beginning of each line. If a given line does not contain sufficient white space then all leading [white space characters](#) are removed. Each white space character is treated as a single character. In particular, the tab character `"\t"` (U+0009) is considered a single character; it is not expanded.

If `n == 0` then the line remains unchanged. However, line terminators are still normalized.

Parameters:

`n` - number of leading [white space characters](#) to add or remove

Returns:

string with indentation adjusted and line endings normalized

Since:

12

See Also:

`lines()`, `isBlank()`, `Character.isWhitespace(int)`

stripIndent

```
public String stripIndent()
```

Returns a string whose value is this string, with incidental [white space](#) removed from the beginning and end of every line.

Incidental [white space](#) is often present in a text block to align the content with the opening delimiter. For example, in the following code, dots represent incidental [white space](#):

```
String html = ""
.....<html>
.....    <body>
.....        <p>Hello, world</p>
.....    </body>
```

```
.....</html>
.....""";
```

This method treats the incidental [white space](#) as indentation to be stripped, producing a string that preserves the relative indentation of the content. Using | to visualize the start of each line of the string:

```
|<html>
|   <body>
|       <p>Hello, world</p>
|   </body>
|</html>
```

First, the individual lines of this string are extracted. A *line* is a sequence of zero or more characters followed by either a line terminator or the end of the string. If the string has at least one line terminator, the last line consists of the characters between the last terminator and the end of the string. Otherwise, if the string has no terminators, the last line is the start of the string to the end of the string, in other words, the entire string. A line does not include the line terminator.

Then, the *minimum indentation* (*min*) is determined as follows:

- For each non-blank line (as defined by `isBlank()`), the leading [white space](#) characters are counted.
- The leading [white space](#) characters on the last line are also counted even if [blank](#).

The *min* value is the smallest of these counts.

For each [non-blank](#) line, *min* leading [white space](#) characters are removed, and any trailing [white space](#) characters are removed. [Blank](#) lines are replaced with the empty string.

Finally, the lines are joined into a new string, using the LF character `"\n"` (U+000A) to separate lines.

API Note:

This method's primary purpose is to shift a block of lines as far as possible to the left, while preserving relative indentation. Lines that were indented the least will thus have no leading [white space](#). The result will have the same number of line terminators as this string. If this string ends with a line terminator then the result will end with a line terminator.

Implementation Requirements:

This method treats all [white space](#) characters as having equal width. As long as the indentation on every line is consistently composed of the same character sequences, then the result will be as described above.

Returns:

string with incidental indentation removed and line terminators normalized

Since:

15

See Also:

`lines(), isBlank(), indent(int), Character.isWhitespace(int)`

translateEscapes

```
public String translateEscapes()
```

Returns a string whose value is this string, with escape sequences translated as if in a string literal.

Escape sequences are translated as follows;

Escape	Name	Translation
<code>\b</code>	backspace	U+0008
<code>\t</code>	horizontal tab	U+0009
<code>\n</code>	line feed	U+000A
<code>\f</code>	form feed	U+000C
<code>\r</code>	carriage return	U+000D
<code>\s</code>	space	U+0020
<code>\"</code>	double quote	U+0022
<code>\'</code>	single quote	U+0027
<code>\\</code>	backslash	U+005C
<code>\0 - \377</code>	octal escape	code point equivalents
<code>\<line-terminator></code>	continuation	discard

Implementation Note:

This method does *not* translate Unicode escapes such as `"\u2022"`. Unicode escapes are translated by the Java compiler when reading input characters and are not part of the string literal specification.

Returns:

String with escape sequences translated.

Throws:

[IllegalArgumentException](#) - when an escape sequence is malformed.

See Java Language Specification:

[3.10.7 Escape Sequences](#)

Since:

15

transform

```
public <R> R transform(Function<? super String,? extends R> f)
```

This method allows the application of a function to this string. The function should expect a single String argument and produce an R result.

Any exception thrown by `f.apply()` will be propagated to the caller.

Type Parameters:

R - the type of the result

Parameters:

f - a function to apply

Returns:

the result of applying the function to this string

Since:

12

See Also:

[Function](#)

toString

```
public String toString()
```

This object (which is already a string!) is itself returned.

Specified by:

[toString](#) in interface [CharSequence](#)

Overrides:

[toString](#) in class [Object](#)

Returns:

the string itself.

chars

```
public IntStream chars()
```

Returns a stream of int zero-extending the char values from this sequence. Any char which maps to a [surrogate code point](#) is passed through uninterpreted.

Specified by:

[chars](#) in interface [CharSequence](#)

Returns:

an IntStream of char values from this sequence

Since:

9

codePoints

```
public IntStream codePoints()
```

Returns a stream of code point values from this sequence. Any surrogate pairs encountered in the sequence are combined as if by [Character.toCodePoint](#) and the result is passed to the stream. Any other code units, including ordinary BMP characters, unpaired surrogates, and undefined code units, are zero-extended to int values which are then passed to the stream.

Specified by:

`codePoints` in interface `CharSequence`

Returns:

an `IntStream` of Unicode code points from this sequence

Since:

9

toCharArray

```
public char[] toCharArray()
```

Converts this string to a new character array.

Returns:

a newly allocated character array whose length is the length of this string and whose contents are initialized to contain the character sequence represented by this string.

format

```
public static String format(String format,  
                             Object... args)
```

Returns a formatted string using the specified format string and arguments.

The locale always used is the one returned by `Locale.getDefault(Locale.Category)` with `FORMAT` category specified.

Parameters:

`format` - A [format string](#)

`args` - Arguments referenced by the format specifiers in the format string. If there are more arguments than format specifiers, the extra arguments are ignored. The number of arguments is variable and may be zero. The maximum number of arguments is limited by the maximum dimension of a Java array as defined by *The Java Virtual Machine Specification*. The behaviour on a null argument depends on the [conversion](#).

Returns:

A formatted string

Throws:

[IllegalFormatException](#) - If a format string contains an illegal syntax, a format specifier that is incompatible with the given arguments, insufficient arguments given the format string, or other illegal conditions. For specification of all possible formatting errors, see the [Details](#) section of the formatter class specification.

Since:

1.5

See Also:

[Formatter](#)

format

```
public static String format(Locale l,  
                             String format,  
                             Object... args)
```

Returns a formatted string using the specified locale, format string, and arguments.

Parameters:

`l` - The [locale](#) to apply during formatting. If `l` is `null` then no localization is applied.

`format` - A [format string](#)

`args` - Arguments referenced by the format specifiers in the format string. If there are more arguments than format specifiers, the extra arguments are ignored. The number of arguments is variable and may be zero. The maximum number of arguments is limited by the maximum dimension of a Java array as defined by *The Java Virtual Machine Specification*. The behaviour on a `null` argument depends on the [conversion](#).

Returns:

A formatted string

Throws:

[IllegalFormatException](#) - If a format string contains an illegal syntax, a format specifier that is incompatible with the given arguments, insufficient arguments given the format string, or other illegal conditions. For specification of all possible formatting errors, see the [Details](#) section of the formatter class specification

Since:

1.5

See Also:

[Formatter](#)

formatted

```
public String formatted(Object... args)
```

Formats using this string as the format string, and the supplied arguments.

Implementation Requirements:

This method is equivalent to `String.format(this, args)`.

Parameters:

`args` - Arguments referenced by the format specifiers in this string.

Returns:

A formatted string

Since:

15

See Also:

[format\(String, Object...\)](#),

[Formatter](#)

valueOf

```
public static String valueOf(Object obj)
```

Returns the string representation of the Object argument.

Parameters:

obj - an Object.

Returns:

if the argument is null, then a string equal to "null"; otherwise, the value of obj.toString() is returned.

See Also:

Object.toString()

valueOf

```
public static String valueOf(char[] data)
```

Returns the string representation of the char array argument. The contents of the character array are copied; subsequent modification of the character array does not affect the returned string.

The contents of the string are unspecified if the character array is modified during string construction.

Parameters:

data - the character array.

Returns:

a String that contains the characters of the character array.

valueOf

```
public static String valueOf(char[] data,  
                             int offset,  
                             int count)
```

Returns the string representation of a specific subarray of the char array argument.

The offset argument is the index of the first character of the subarray. The count argument specifies the length of the subarray. The contents of the subarray are copied; subsequent modification of the character array does not affect the returned string.

The contents of the string are unspecified if the character array is modified during string construction.

Parameters:

data - the character array.

offset - initial offset of the subarray.

count - length of the subarray.

Returns:

a String that contains the characters of the specified subarray of the character array.

Throws:

[IndexOutOfBoundsException](#) - if offset is negative, or count is negative, or offset+count is larger than data.length.

copyValueOf

```
public static String copyValueOf(char[] data,  
                                int offset,  
                                int count)
```

Equivalent to `valueOf(char[], int, int)`.

Parameters:

data - the character array.

offset - initial offset of the subarray.

count - length of the subarray.

Returns:

a String that contains the characters of the specified subarray of the character array.

Throws:

[IndexOutOfBoundsException](#) - if offset is negative, or count is negative, or offset+count is larger than data.length.

copyValueOf

```
public static String copyValueOf(char[] data)
```

Equivalent to `valueOf(char[])`.

Parameters:

data - the character array.

Returns:

a String that contains the characters of the character array.

valueOf

```
public static String valueOf(boolean b)
```

Returns the string representation of the boolean argument.

Parameters:

b - a boolean.

Returns:

if the argument is true, a string equal to "true" is returned; otherwise, a string equal to "false" is returned.

valueOf


```
public static String valueOf(char c)
```

Returns the string representation of the char argument.

Parameters:

c - a char.

Returns:

a string of length 1 containing as its single character the argument c.

valueOf

```
public static String valueOf(int i)
```

Returns the string representation of the int argument.

The representation is exactly the one returned by the `Integer.toString` method of one argument.

Parameters:

i - an int.

Returns:

a string representation of the int argument.

See Also:

`Integer.toString(int, int)`

valueOf

```
public static String valueOf(long l)
```

Returns the string representation of the long argument.

The representation is exactly the one returned by the `Long.toString` method of one argument.

Parameters:

l - a long.

Returns:

a string representation of the long argument.

See Also:

`Long.toString(long)`

valueOf

```
public static String valueOf(float f)
```

Returns the string representation of the float argument.

The representation is exactly the one returned by the `Float.toString` method of one argument.

Parameters:

f - a float.

Returns:

a string representation of the float argument.

See Also:

[Float.toString\(float\)](#)

valueOf

```
public static String valueOf(double d)
```

Returns the string representation of the double argument.

The representation is exactly the one returned by the `Double.toString` method of one argument.

Parameters:

d - a double.

Returns:

a string representation of the double argument.

See Also:

[Double.toString\(double\)](#)

intern

```
public String intern()
```

Returns a canonical representation for the string object.

A pool of strings, initially empty, is maintained privately by the class `String`.

When the `intern` method is invoked, if the pool already contains a string equal to this `String` object as determined by the `equals(Object)` method, then the string from the pool is returned. Otherwise, this `String` object is added to the pool and a reference to this `String` object is returned.

It follows that for any two strings `s` and `t`, `s.intern() == t.intern()` is true if and only if `s.equals(t)` is true.

All literal strings and string-valued constant expressions are interned. String literals are defined in section 3.10.5 of the *The Java Language Specification*.

Returns:

a string that has the same contents as this string, but is guaranteed to be from a pool of unique strings.

repeat

```
public String repeat(int count)
```

Returns a string whose value is the concatenation of this string repeated count times.

If this string is empty or count is zero then the empty string is returned.

Parameters:

count - number of times to repeat

Returns:

A string composed of this string repeated count times or the empty string if this string is empty or count is zero

Throws:

[IllegalArgumentException](#) - if the count is negative.

Since:

11

describeConstable

```
public Optional<String> describeConstable()
```

Returns an [Optional](#) containing the nominal descriptor for this instance, which is the instance itself.

Specified by:

[describeConstable](#) in interface [Constable](#)

Returns:

an [Optional](#) describing the [String](#) instance

Since:

12

resolveConstantDesc

```
public String resolveConstantDesc(MethodHandles.Lookup lookup)
```

Resolves this instance as a [ConstantDesc](#), the result of which is the instance itself.

Specified by:

[resolveConstantDesc](#) in interface [ConstantDesc](#)

Parameters:

lookup - ignored

Returns:

the [String](#) instance

Since:

12

examples. [Other versions](#).

Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.

Copyright © 1993, 2024, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.

All rights reserved. Use is subject to [license terms](#) and the [documentation redistribution policy](#). [Modify Cookie Preferences](#). [Modify Ad Choices](#).