

# PL/SQL - COLLECTIONS

A collection is an ordered group of elements having the same data type. Each element is identified by a unique subscript that represents its position in the collection.

PL/SQL provides three collection types:

- Index-by tables or Associative array
- Nested table
- Variable-size array or Varray

Oracle documentation provides the following characteristics for each type of collections:

| Collection Type                       | Number of Elements | Subscript Type    | Dense or Sparse                 | Where Created                             | Can Be Object Type Attribute |
|---------------------------------------|--------------------|-------------------|---------------------------------|---|------------------------------|
| Associative array (or index-by table) | Unbounded          | String or integer | Either                          | Only in PL/SQL block                      | No                           |
| Nested table                          | Unbounded          | Integer           | Starts dense, can become sparse | Either in PL/SQL block or at schema level | Yes                          |
| Variable-size array (Varray)          | Bounded            | Integer           | Always dense                    | Either in PL/SQL block or at schema level | Yes                          |

We have already discussed varray in the chapter 'PL/SQL arrays'. In this chapter, we will discuss PL/SQL tables.

Both types of PL/SQL tables i.e., index-by tables and nested tables have the same structure and their rows are accessed using the subscript notation. However, these two types of tables differ in one aspect; the nested tables can be stored in a database column and the index-by tables cannot.

## Index-By Table

An **index-by** table (also called an associative array) is a set of **key-value** pairs. Each key is unique, and is used to locate the corresponding value. The key can be either an integer or a string.

An index-by table is created using the following syntax. Here we are creating an index-by table named **table\_name** whose keys will be of *subscript\_type* and associated values will be of *element\_type*

```
TYPE type_name IS TABLE OF element_type [NOT NULL] INDEX BY subscript_type;  
  
table_name type_name;
```

## Example:

Following example how to create a table to store integer values along with names and later it prints the same list of names.

```

DECLARE
    TYPE salary IS TABLE OF NUMBER INDEX BY VARCHAR2(20);
    salary_list salary;
    name    VARCHAR2(20);
BEGIN
    -- adding elements to the table
    salary_list('Rajnish') := 62000;
    salary_list('Minakshi') := 75000;
    salary_list('Martin') := 100000;
    salary_list('James') := 78000;

    -- printing the table
    name := salary_list.FIRST;
    WHILE name IS NOT null LOOP
        dbms_output.put_line
            ('Salary of ' || name || ' is ' || TO_CHAR(salary_list(name)));
        name := salary_list.NEXT(name);
    END LOOP;
END;
/

```

When the above code is executed at SQL prompt, it produces following result:

```

Salary of Rajnish is 62000
Salary of Minakshi is 75000
Salary of Martin is 100000
Salary of James is 78000

PL/SQL procedure successfully completed.

```

## Example:

Elements of an index-by table could also be a %ROWTYPE of any database table or %TYPE of any database table field. The following example illustrates the concept. We will use the CUSTOMERS table stored in our database as:

```
Select * from customers;
```

| ID | NAME     | AGE | ADDRESS   | SALARY  |
|----|----------|-----|-----------|---------|
| 1  | Ramesh   | 32  | Ahmedabad | 2000.00 |
| 2  | Khilan   | 25  | Delhi     | 1500.00 |
| 3  | kaushik  | 23  | Kota      | 2000.00 |
| 4  | Chaitali | 25  | Mumbai    | 6500.00 |
| 5  | Hardik   | 27  | Bhopal    | 8500.00 |
| 6  | Komal    | 22  | MP        | 4500.00 |

```

DECLARE
    CURSOR c_customers is
        select name from customers;

    TYPE c_list IS TABLE of customers.name%type INDEX BY binary_integer;
    name_list c_list;
    counter integer :=0;
BEGIN
    FOR n IN c_customers LOOP
        counter := counter +1;
        name_list(counter) := n.name;
        dbms_output.put_line('Customer('||counter|| '):'||name_list(counter));
    END LOOP;
END;
/

```

When the above code is executed at SQL prompt, it produces following result:

```
Customer(1): Ramesh
```

```
Customer(2): Khilan
Customer(3): kaushik
Customer(4): Chaitali
Customer(5): Hardik
Customer(6): Komal

PL/SQL procedure successfully completed
```

## Nested Tables

A **nested table** is like a one-dimensional array with an arbitrary number of elements. However, a nested table differs from an array in the following aspects:

- An array has a declared number of elements, but a nested table does not. The size of a nested table can increase dynamically.
- An array is always dense i.e., it always has consecutive subscripts. A nested array is dense initially, but it can become sparse when elements are deleted from it.

An **nested table** is created using the following syntax:

```
TYPE type_name IS TABLE OF element_type [NOT NULL];

table_name type_name;
```

This declaration is similar to declaration of an **index-by** table, but there is no INDEX BY clause.

A nested table can be stored in a database column and so it could be used for simplifying SQL operations where you join a single-column table with a larger table. An associative array cannot be stored in the database.

## Example:

The following examples illustrate the use of nested table:

```
DECLARE
    TYPE names_table IS TABLE OF VARCHAR2(10);
    TYPE grades IS TABLE OF INTEGER;

    names names_table;
    marks grades;
    total integer;
BEGIN
    names := names_table('Kavita', 'Pritam', 'Ayan', 'Rishav', 'Aziz');
    marks := grades(98, 97, 78, 87, 92);
    total := names.count;
    dbms_output.put_line('Total ' || total || ' Students');
    FOR i IN 1 .. total LOOP
        dbms_output.put_line('Student: ' || names(i) || ', Marks: ' || marks(i));
    end loop;
END;
/
```

When the above code is executed at SQL prompt, it produces following result:

```
Total 5 Students
Student:Kavita, Marks:98
Student:Pritam, Marks:97
Student:Ayan, Marks:78
Student:Rishav, Marks:87
Student:Aziz, Marks:92

PL/SQL procedure successfully completed.
```

Example:

Elements of an **nested table** could also be a %ROWTYPE of any database table or %TYPE of any database table field. The following example illustrates the concept. We will use the CUSTOMERS table stored in our database as:

```
Select * from customers;
```

| ID | NAME     | AGE | ADDRESS   | SALARY  |
|----|----------|-----|-----------|---------|
| 1  | Ramesh   | 32  | Ahmedabad | 2000.00 |
| 2  | Khilan   | 25  | Delhi     | 1500.00 |
| 3  | kaushik  | 23  | Kota      | 2000.00 |
| 4  | Chaitali | 25  | Mumbai    | 6500.00 |
| 5  | Hardik   | 27  | Bhopal    | 8500.00 |
| 6  | Komal    | 22  | MP        | 4500.00 |

```
DECLARE
  CURSOR c_customers is
    SELECT name FROM customers;

  TYPE c_list IS TABLE of customers.name%type;
  name_list c_list := c_list();
  counter integer :=0;
BEGIN
  FOR n IN c_customers LOOP
    counter := counter +1;
    name_list.extend;
    name_list(counter) := n.name;
    dbms_output.put_line('Customer'||counter||':'||name_list(counter));
  END LOOP;
END;
```

When the above code is executed at SQL prompt, it produces following result:

```
Customer(1): Ramesh
Customer(2): Khilan
Customer(3): kaushik
Customer(4): Chaitali
Customer(5): Hardik
Customer(6): Komal

PL/SQL procedure successfully completed.
```

Collection Methods

PL/SQL provides the built-in collection methods that make collections easier to use. The following table lists the methods and their purpose:

| S.N. | Method Name & Purpose  |
|------|--|
| 1    | <b>EXISTS(n)</b><br>Returns TRUE if the nth element in a collection exists; otherwise returns FALSE. |
| 2    | <b>COUNT</b><br>Returns the number of elements that a collection currently contains.                 |
| 3    | <b>LIMIT</b><br>Checks the Maximum Size of a Collection.   |

|    |   |
|----|---|
| 4  | <b>FIRST</b><br>Returns the first (smallest) index numbers in a collection that uses integer subscripts.  |
| 5  | <b>LAST</b><br>Returns the last (largest) index numbers in a collection that uses integer subscripts.   |
| 6  | <b>PRIOR(n)</b><br>Returns the index number that precedes index n in a collection.  |
| 7  | <b>NEXT(n)</b><br>Returns the index number that succeeds index n.   |
| 8  | <b>EXTEND</b><br>Appends one null element to a collection.  |
| 9  | <b>EXTEND(n)</b><br>Appends n null elements to a collection.  |
| 10 | <b>EXTEND(n,i)</b><br>Appends n copies of the ith element to a collection.  |
| 11 | <b>TRIM</b><br>Removes one element from the end of a collection.  |
| 12 | <b>TRIM(n)</b><br>Removes n elements from the end of a collection.  |
| 13 | <b>DELETE</b><br>Removes all elements from a collection, setting COUNT to 0.  |
| 14 | <b>DELETE(n)</b><br>Removes the nth element from an associative array with a numeric key or a nested table. If the associative array has a string key, the element corresponding to the key value is deleted. If n is null, DELETE(n) does nothing. |
| 15 | <b>DELETE(m,n)</b><br>Removes all elements in the range m..n from an associative array or nested table. If m is larger than n or if m or n is null, DELETE(m,n) does nothing.   |

## Collection Exceptions

The following table provides the collection exceptions and when they are raised:

| Collection Exception    | Raised in Situations  |
|-------------------------|---|
| COLLECTION_IS_NULL      | You try to operate on an atomically null collection.  |
| NO_DATA_FOUND           | A subscript designates an element that was deleted, or a nonexistent element of an associative array. |
| SUBSCRIPT_BEYOND_COUNT  | A subscript exceeds the number of elements in a collection.   |
| SUBSCRIPT_OUTSIDE_LIMIT | A subscript is outside the allowed range.   |

VALUE\_ERROR

A subscript is null or not convertible to the key type. This exception might occur if the key is defined as a PLS\_INTEGER range, and the subscript is outside this range.