

SQL - CHECK CONSTRAINT

The CHECK Constraint enables a condition to check the value being entered into a record. If the condition evaluates to false, the record violates the constraint and isn't entered into the table.

Example:

For example, the following SQL creates a new table called CUSTOMERS and adds five columns. Here we add a CHECK with AGE column, so that you can not have any CUSTOMER below 18 years:

```
CREATE TABLE CUSTOMERS (  
    ID INT NOT NULL,  
    NAME VARCHAR (20) NOT NULL,  
    AGE INT NOT NULL CHECK (AGE >= 18),  
    ADDRESS CHAR (25) ,  
    SALARY DECIMAL (18, 2),  
    PRIMARY KEY (ID)  
);
```

If CUSTOMERS table has already been created, then to add a CHECK constraint to AGE column, you would write a statement similar to the following:

```
ALTER TABLE CUSTOMERS  
    MODIFY AGE INT NOT NULL CHECK (AGE >= 18 );
```

You can also use following syntax, which supports naming the constraint and multiple columns as well:

```
ALTER TABLE CUSTOMERS  
    ADD CONSTRAINT myCheckConstraint CHECK (AGE >= 18);
```

DROP a CHECK Constraint:

To drop a CHECK constraint, use the following SQL. This syntax does not work with MySQL:

```
ALTER TABLE CUSTOMERS  
    DROP CONSTRAINT myCheckConstraint;
```