



A326

FILL A GAP CLASSIC MULTI-PURPOSE ACRYLIC GAP SEALANT AND FILLER

TECHNICAL DATA SHEET

KEY FEATURES

- Excellent sealing and adhesion properties
- Skins within 15 minutes
- Can be over-painted with acrylic paint
- High bond strength
- Once cured excellent water resistance
- Slump resistant

PRODUCT DESCRIPTION

Bostik A326 FILL A GAP CLASSIC is a general purpose one-part water based, paintable acrylic gap filler. This easy to use, economical sealant provides excellent adhesion for gaps and low movement joints.

RECOMMENDED USE

- Sealing cracks in plasterboard
- Sealing window and door frames
- Sealing around ceramic tiles
- Sealing low movement joints
- Cracks filing prior to painting
- Sealing cracks in brickwork and concrete
- Sealing between light partition walls
- Sealing skirting and architraves

APPLICATIONS

1. Hold caulking gun at a 45° angle and squeeze trigger at even pressure
2. While the caulk is being dispensed, move the caulking gun along the crack or gap at an even speed
3. Smooth off with wet finger or scrape off lightly with a wet putty knife or damp cloth
4. Becomes touch dry within 30 minutes under normal conditions

PRECAUTION

NOT recommended for:

- Use underwater
- Use where abrasion or physical abuse can be expected
- Use for sealing submerged joints
- Application on damp substrates
- Joint subject to movements over 10 Use in external applications where rain is imminent within 4 hours



TECHNICAL DATA (approx.)

Typical properties after cured at 25°C & 50% RH	
Appearance	Smooth paste like consistency
Colour	White
Chemical Type	Water based acrylic
Specific Gravity	Approx. 1.6
Service Temperature	-20°C to +75°C
Application Temperature	5°C to 50°C
Tool Working Time	15 minutes at 20°C
Tack Free Time (Skin Time)	15 minutes
Full Cure	2 to 3 days (depending on temperature)
Max. Joint Movement	+/- 5%
Max. Joint Width	Up to 25mm in localised areas
Flammability	Non Flammable

PAINTABILITY

Bostik A326 FILL A GAP CLASSIC can be painted after full cured. Coatings containing high solvent contents such as gloss enamels or high oil based undercoats may cause the surface of the sealant to react creating a tacky surface to develop. A field test is recommended to ensure compatibility. To obtain best appearance and performance the paint must approximate the elongation capabilities of the sealant. High build coatings with some elastomeric ability such as quality acrylic emulsions have the capability to absorb low movement without significant distortion of the paint film.

PACKAGING

- 275 ml Cartridge, 25 per box

COVERAGE

The coverage below is approximate and is dependent on substrate conditions

Meters per 450g cartridge

Joint Depth (mm)	Joint Width (mm)			
	5	10	20	25
5	12.8	6.4	4.2	3.2
10	-	3.2	2.1	1.6
15	-	-	1.4	1.1

CLEAN UP

Water or damp cloth when still wet.

SHELF LIFE AND STORAGE

Store all materials in a cool dry place, keep out of direct sunlight. Store away from oxidising agents and acids. The shelf life of this product is 24 months from date of manufacturing if store properly in original unopened packaging.

HEALTH & SAFETY

This product is considered non-hazardous and non-toxic. However, good hygiene practices should be observed at all times. For more details, refer Safety Data Sheet.

The information and recommendations relating to the application and end-use of the product are given in good faith and based on tests which we believe to be reliable. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. However, no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship, whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. No guarantee of their accuracy can be made because of the great range of field conditions and variation encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with limited warranty only, and on condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik be liable to anyone except for replacement of the products or refund of the purchase price.

Bostik

Bostik Findley (Malaysia) Sdn Bhd
Lot 112 & 113, Kawasan Perindustrian Senawang, 70450 Seremban
Negeri Sembilan D.K. Malaysia www.bostik.com

BOSTIK SMART SUPPORT

Smart help digital
bostik.com/

Smart help
+606 678 9788

