Sky-Guard Radar R5000

5 km Low-Altitude UAV Detection Radar

Overview

The Sky-Guard Radar R5000 is a compact, fully coherent Ku-band pulse-Doppler radar purpose-built for detecting and tracking low-altitude unmanned aerial vehicles. The system comprises a radar unit, a motorised turntable, and display-and-control terminal software. It outputs real-time 3D target data — range, azimuth, altitude, speed, longitude, and latitude — and provides precise cueing to co-located electro-optical or counter-UAS effectors. Maximum detection range is 5 km against small consumer-class UAVs (DJI Phantom 3/4, Pd = 85%).

Operating Mode

360° Full-Domain Low-Altitude Surveillance — the radar continuously sweeps 360° in azimuth while electronically scanning 0°–30° in elevation, automatically initiating track, maintaining target association, and reporting results to the display console.

Applications

- Standalone tripod-mounted deployment for independent UAV detection and tracking
- Integration with EO identification, jamming, or spoofing sub-systems for detect-track-neutralise chains
- Vehicle-mounted (mobile) or rooftop-mounted (fixed) monitoring station configurations

Key Technology

- Fully coherent pulse-Doppler processing
- Sum-and-difference monopulse angle measurement
- MTD coherent integration
- CFAR (Constant False-Alarm Rate) detection

Specifications

Frequency Band	Ku, 16 GHz ± 100 MHz
Azimuth Scan	360° mechanical
Elevation Scan (electronic)	≥ 30°
Beam Width (Az / El)	≤ 3° / ≤ 6°
Peak Transmit Power	≤ 100 W
Max Detection Range	≥ 5 km (DJI Phantom 3/4, Pd = 85%)
Min Detection Range	≤ 250 m
Min Detectable Speed	≤ 2.5 m/s
Range Accuracy (RMS)	≤ 10 m
Azimuth Accuracy (RMS)	≤ 0.5°
Elevation Accuracy (RMS)	≤ 0.5°
Data Refresh Rate	3 s (full 360° sweep)
Radar Unit Dimensions	≤ 650 × 400 × 100 mm
Radar + Turntable Dimensions	≤ 650 × 650 × 250 mm
Power Supply	+28 V DC
Power Consumption	≤ 200 W (incl. turntable)
System Weight	≤ 35 kg (radar + turntable + tripod)
Interface	Gigabit Ethernet

Display & Control Software

The accompanying terminal software handles radar operation control, parameter configuration, data parsing, target display, and experimental data logging. It converts native protocols to customer-specified formats for seamless integration with third-party C2 systems.

Packing List

#	Item	Qty	Remark

1	Radar Unit	1	
2	Motorised Turntable	1	
3	Tripod	1	
4	GNSS/INS Antenna	2	
5	Cable Set	1	Power + data, 10 m
6	Fastener Kit	1	

MetaBee Technology Limited

Unit 836, 8/F, Building 8, Hong Kong-Shenzhen Innovation and Technology Park
Email: metabeelimited@gmail.com | Web: www.metabee.com.hk

Date Code: March 2026

Disclaimer

DISCLAIMER — The information contained in this document is provided for reference purposes only. All specifications are subject to change without prior notice. MetaBee Technology Limited makes no warranties, express or implied, regarding the accuracy or completeness of the information herein. Actual product performance may vary depending on the operating environment, configuration, and deployment conditions. This document does not constitute a binding offer or contract. Final deployment performance depends on operating environment and configuration. For the most up-to-date specifications, please contact MetaBee Technology Limited directly.