

Sky-Guard SG-6000F AoA Drone Signal Detection System

Passive 360° RF sensing for unattended site protection



Overview

A fixed-mounted passive drone detection system based on SDR architecture and spectrum identification technology. It performs 360° reconnaissance, identification, direction finding, and tracking for multiple UAV types, supporting long-range detection and integration with external systems.

Key Capabilities

- Passive RF detection with no active emissions.
- Customisable detection bands from 20 MHz to 6 GHz with 200 MHz instantaneous bandwidth.
- 24/7 unattended wake-up, alerting, historical query, and trajectory playback.
- Spectrum recognition, protocol parsing, Remote ID, O4 decoding, and 600+ model recognition.

Technical Specifications

Model	SG-6000F
Detection Mode	Radio-frequency passive detection
Coverage Band	20 MHz to 6000 MHz
Instantaneous Bandwidth	200 MHz
Detection Direction	360° omnidirectional
Detection Range	5–8 km open areas; 1–3 km urban areas
Simultaneous Targets	≥ 100 aircraft
Protection / Temperature	IP66; -30°C to +65°C
Size / Weight	Approx. Φ450 × H400 mm; approx. 13 kg

MetaBee Technology Limited

Hong Kong-Shenzhen Innovation and Technology Park, Hong Kong
Email: info@metabee.com.hk | Web: www.metabee.com.hk
Date Code: September 2026

The information contained in this document is provided for reference purposes only. Specifications are subject to change without prior notice.
Actual performance may vary depending on operating environment, deployment configuration, and integration conditions.