


Sky-Guard EO Tracking System

Visible-light and thermal imaging for target confirmation



Overview

An electro-optical tracking subsystem combining visible-light imaging, infrared thermal imaging, multi-spectral fusion, and servo tracking. It delivers day/night target detection, tracking, identification, and intelligent warning for low, slow, and small aerial targets.

Key Capabilities

- Visible-light + thermal imaging channels with multi-spectral data fusion.
- 48× optical continuous zoom with automatic focus and optical defogging.
- Horizontal 360° continuous rotation and -90° to +90° pitch coverage.
- Radar guidance, spectrum-positioning guidance, GPS, environmental data, and power-management access.

Technical Specifications

Visible Camera	1920 × 1080 @ 25/30 fps
Optical Lens	F6.5–312 mm, 48× continuous zoom
Thermal Imaging	Uncooled 640 × 512; 75 mm fixed lens
Day UAV Detection	≥ 2.5 km detection; ≥ 2 km tracking
Night UAV Detection	≥ 1.2 km detection; ≥ 1 km tracking
Gimbal	360° pan; -90° to +90° tilt; ±0.01° preset accuracy
Power / Weight	≤ 30 W steady-state; ≤ 8 kg
Protection	IP66

MetaBee Technology Limited

Hong Kong-Shenzhen Innovation and Technology Park, Hong Kong
Email: info@metabee.com.hk | Web: www.metabee.com.hk
Date Code: September 2026

The information contained in this document is provided for reference purposes only. Specifications are subject to change without prior notice. Actual performance may vary depending on operating environment, deployment configuration, and integration conditions.